

Palazzoli

Garanti: 12 ay
Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Palazzoli Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Palazzoli Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
P477417	Art.-Nr.: 0370000000000P477417 CEE STRAIGHT PLUG 63A 3P+E 380-415V 50-60HZ 6H IP67 Frequency 50-60Hz - Protection degree IP67 Poles 3P+ // Clock Position 6 Standard plug-socket EN60309-2 Nominal Operating Voltage 400V Insulating Voltage 500V Manufacturing Material Thermoplastic Nominal current 63A // Execution MOBILE Shape Straigh (t8536 6990 IT)
MIGNON-EX Selector Switch Teile-Nr. P202275EX	
RED 800061	24VDC
GREEN 800062	24vdc
TRASPARENT 800063	24VDC
YELLOW 800064	24VDC
TRASPARENT 831072	24VDC
	P202275EX MIGNON-EX SELECTOR SWITCH 1X16A 3D 3G Technical data Dimensions 136X62X51 mm Hole type M20

03700000000P202275EX	Number of entries in enclosure 1 Rated current/voltage 16A 250V~10A 400V~ Frequency 50/60Hz Protection degree IP66 Poles 1P Rated operating voltage 250V~/400V~ Manufacturing material RESIN THERMOSETTING ANTISTAT DEVICE FUNCTION Selector switches Width 62 mm Rated current 16/10A Execution WALL MOUNTING Atex ATEX application zone Zona/Zone 2 and 22 Atex Dust Nominal Current - Atex Gas Nominal Current - Atex Dust Marking Ex tc IIIC T70°C Dc Atex Gas Marking Ex nR IIC T6 Gc GAS Dissipable Power - DUST Dissipable Power - Min. Amb. Temp. -20°C Max. Amb. Temp. +40°C Group & Cat. ATEX GAS II 3G Group & Cat. ATEX DUST II 3D
P831072	RINO OVAL LIGHTING FIXTURE IN ALUMINIUM 60W 1 LAMPHOLDER E27 INLET M20 CAGE
272178	
532005	
Distribution Box Al Ip55	
538610	
Ip 44 - , No	
630051	
292102	
476416	
14.12.0491	
P151881	
511512	
472446	
Alternator	
Pala531440	
477516	
710236	
356338	
Pala538210	
202282	
Tais Series With 5 Socket-Outlets 16a 2p + E 220v Ac	
472518	
630011	

4701204	
515512	
464330ex	
515111	
511217	
P532242ex	TAIS-EX BOXES IN THERMOSETTING (GRP) FOR COMPOSITION OF SOCKET BOARDS 250X185X125 Dimensions 250X185 mm Cover height 50 mm Protection degree IP66 Manufacturing Material Thermosetting halogen free Height Box 75mm Execution WALL MOUNTING Cover Type Blind Outfit WITHOUT PLATE Insulation Class II Atex ATEX application zone Zona/Zone 2, 21 and 22 Notified body (CE) 0051 Atex Dust Marking Ex tb IIIC Db Atex Gas Marking Ex nR IIC Gc Certificate Number ATEX TÜV IT 13 ATEX 050 U GAS Dissipable Power 8 DUST Dissipable Power 22 Min. Amb. Temp. -40°C
471204	
346350	
491233.	
Tais Series With 5 Socket-Outlets 32a 3p + E 380v Ac	
3p+e 63a 440-460v 11h Ip67	
14.18.0057	
477302	
819056	
D001051620	
473103	
D1830700301	
477303ex	
477105	
900463	
472233	
477602	
Equipment, Including Equipment Connection By Fg7(O)m1 0,6/1 Kv Cable	
511210	

07.37.0012
201151
400247
433052
477002
Krio.Lx.Sa.250 Ip657
P/N:431 237,Poles:2p+e
800061ex
710336
511212
D192036
D001054142
532117ex
472731
472731ex
08.31.0009
477303
477423ex
476426
18663
831072
P472453
477206
Tais Series With 5 Socket-Outlets 16a 3p + E 380v Ac
467126ex Protection 2p+t 16a 230v 50- 60hz Ip66/Ip67 For Atex Zones 2d 3g
671532716
249550
464430ex
D7380710201

[471-304-D220-250v-16a-6k-2p+t](#)
[347001](#)[471105](#)[515323](#)[19.02.0027](#)[511632](#)[477103](#)[463136ex](#)[472732](#)[532035ex](#)[630002](#)[01.01.0384](#)[Motor Starter](#)[101031](#)[08.37.0009](#)[511324](#)[740 001](#)[477677](#)[D1110403004](#)[800062ex](#)[473413](#)[472768](#)[S10r819](#)[720244](#)[151880 Socket With Stop Switch 63a](#)
[3p+e 690v](#)[14.02.0028](#)[D1110403103](#)[730346](#)[151891](#)[900643](#)

Ter Series With 3 Outlets 16 A-2p 150va	
472333	
710246	
D005452335	
471812	
D1110402902	
477305	
P900473	P900473 Sirens in aluminium alloy, with vibrating membrane 50-60Hz IP66 Hole type M20 Sound level at 1 mt. 107/105dB Frequency 50/60Hz Protection level IP66 Poles 2P+ Acoustic Signal Type D Operational working temp -40 T 40 Nominal Operating Voltage 230V Manufacturing Material Aluminium alloy Nominal current 0.3A Zolltarif-Nr.: 8536 6990 Ursprungsland: Italien
272303	
14.12.0215	
D002053599ring	
477203	
D19jm00100	
270323	
540033	
472844	
472447	
540091	
471304d	
P101221	
511452	
800062	
400126	
540090	
151881 Socket With Stop Switch 125a	
3p+e 690v	
477416	
472781	

315.6346
Moil Point For Hydro Hammer
477456
D11107001601
05.41.0009
549550
511110
D1110701503
400336
159030
472547
Fm90z1 450/750v
D1120761102
479463
471362
37-1304daufschnappbar 35 Mm
472466
540035
579400
471254
473203
515453
700126
473105
272142ex
PaI900473
477417
P471414
472428
800061
473605

511320
276702
472456
D7380710401
2p 16a 24v Tais Ip44
08.37.0010
464732ex
D13011241
463146ex
Pal 515632
472730
Sp231391
579500
720224ul
14.14.0080
346338
Nt-Rtd-393 T/R Pt100ohm-Classe B- Ambiente
2.5 Mm2 ,4.8 X 0.8 Mm
650426 , Raplacement 630002 And 630051
471354
900473
16a 2p 24v 50/60 Hz Ip44
249538
Pala531021
477 426
720126
D001050807
437152
261431

D001050691
831095
477716
511 632
472443
464731ex
473317
540034
471-354+101221-220-250v-16a-6k-2p+t
431237 (Ex.431027)
532006
W11: Industrial Dust Proof Integral Controlgear, Wellglass Luminaire, Suitable For 70w Hpsv Lamp
471873
431237
515200
472732ex
831172
477412
630050
477676
08.33.0014
32a-500v-3f+t-IP65
14.14.0081
Pal 515637
26420469
473303
19.01.0385