

Pepperl Fuchs

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Pepperl Fuchs Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Pepperl Fuchs Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Nbn4 - 12gm40 - 20 - V1	
Kfd2-Cd-Ex1.32	P&F isolating converter 1-channel. 0-20mA / 0-20mA special item 104204
Kfd2-Stc4-Ex1-Y1	P&F transmitter feed 283680
Kfd2-Stc4-Ex1-Y ## Successor Type ##	
Nx360d-F99-U2e2-V15	Tilt sensor INX360D-F99-U2E2-V15 Measuring range: 0 ... 360 °, operating voltage: 10 ... 30 V DC, output type: 2 switching outputs pnp, normally open, reverse polarity protected, short-circuit proof, output type: 1 voltage output 0 ... 5 V, connection type: connector M12 x 1, 5-pin
P&F Reflexionsli OBT350-R100-2EP-IO-V31	267075-0058
NJ5-18GM-N-V1	PTB00 ATEX 2048X
NBN4-12GM40-Z0-V1	Induktiver Sensor
KFD2-STC4-EX1	
KFD2-STC4-EX2	
KFD2-STV4-EX1-2	

KFD2-SH-EX1	Voltage repeater - 1-channel isolated barrier - 24 V DC supply (Power Rail) - Voltage input 0 V ... -20 V - Vibration sensor input - Field supply with voltage / current - Voltage output 0 V ... -20 V - Up to SIL 2 according to IEC 61508
KFD2-VR4-EX1.26	
UB2000-F42S-E5-V15	133994
NCB1,5-8GM40-N0-V1-Y97264	180206
KFU8-UFC-EX1.D	231197 P&F Frequency converter KFU8-UFC-EX1.D
NCN8-18GM40-N0-V1	Proximity initiator Switching distance: 8 mm, installation: non-flush, switching function: break contact (NC), output type: NAMUR, nominal voltage: 8.2 V (Ri approx. 1 k?)
NBN3-F69-E2-V1	
RLK28-55-Z/31/116	
OBT500-18GM60-E5	Photoelectric proximity switch Scanning distance: 500mm, adjustable, IRED 880nm Cylindrical design M18, 80mm long, brass housing vern. Operating voltage: 10 ... 30VDC Output: 1 pnp, light / dark switching electronically switchable Connection: fixed cable 2 m
NJ5-18GK-N-150	Inductive sensor cylindrical, switching distance: 5mm, flush Temperature range: -40 ... 150 ° C Electrical version: NAMUR with 2m AIHF cable
KFD2-SCD2-EX2.LK	Smart output driver - 2-channel isolated barrier - 24 V DC supply (Power Rail) - Current output up to 650 Ü burden - HART I / P and positioner - Line fault monitoring - accuracy 0.1% - SIL 2 (SC 3) according to IEC / EN 61508
KFD0-TR-Ex1	- 1-channel isolated barrier - 24 V DC supply (loop powered) - 2- or 3-wire Pt100 RTD input - Output 4 mA ... 20 mA, temperature linearization selectable - Setting of the ranges via DIP switches - Sensor break monitoring
SL3010-X1/GS130-133	
KFD0-CS-EX1-5IP	
KCD2-E2L	
UB300-18GM40A-U-V1	
NBB15-30GM50-A2-V1	326161-0148 Induktiver Sensor
PROXİMİTY SWITCH NBN10-F10-E2-V1	
3SMT PT1000 MB	
3S WDI	4-20mA
MODEL:A250 PSP-5/	TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB1
MODEL:A250 PSP-5/	TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB2
MODEL:A250 PSXP1	SENSOR TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB1
MODEL:A250 PSXP1	SENSOR TİPİ:NBB3-V3-Z4 \ BRAKET TİP:MB2
KFU8-UFC-EX1.D	Frequency converter KFU8-UFC-EX1.D
KFU8-UFC-1.D	
Z728.F	
Nj3 0 U1 E2	

552354	
3005300110 Visolux Sensor	
Nbb20-L2-E2-V1	PART NO: 187481
3rg7057-3cc00-Pf	
06.00712	
87764	
Nj5-18gm-N	
Kfd2-Stc4-Ex1	BARRIER
Nj-2-11ng	
254606	
Klr-C02-2,2-2,0-K70	
RIk28-8-H-2000-Ir	
Kfu8-Ufc-Ex1.D	P + F item no .: 231197 Series KF ... Construction housing 40mm Input frequency 0.001Hz ... 5kHz Analog output 0/4 ... 20 mA Measuring range freely parameterizable 2 relay outputs 1 electronic outputs, potential-free each output individually parameterizable up suppression Reclosing lockout Line break and Short circuit monitoring bounce filter Parameterization via control panel 1-channel SIL2 acc.to IEC 61508
11.02340	
85567	
541996	
Nj5-18gk-Sn	
087764	
Nmb15-30gm65-E2-V1	
Kfu8- Ufc- Ex1d Frequency Current Converter	
If5826	
Nj5-18gk-N-150	
01.00778	
104093	
If-0/66	
Dk10-Las/9s20	
106437	
481197	
3rg4013-0kb00-Pf	Art nr. 552300 Induktiver Sensor
Kfd2-Ut2-Ex2	
256494	
254631	
Mlv12-8-H-350-Rt/47/65b/124	

[Nbb2-12gm50-E2-V1](#)