

Pic

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Pic Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Pic Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Pic	
Pic	
Pic	
Pic	
Pic	
MS-328-3-1-0500	
MSM-328	Magnet order nr: 30G4729 Accessories for sensors, MSM-328, PIC GmbH Technical specifications Magnetic material: N30H Remanence Br: 1105 mT Coercivity HcB: 836 kA/m Coercivity HcJ: 1274 kA/m
THREAD REED SENSOR M8 PIC MS-228-3	
Ms 328 4 1 0500	4515
Ta043	OSCILLOSCOPE PROBE, 100 MHZ, DIFFERENTIAL, 700 V, 10:1, 100:1, ALL MAKES MODELS OF OSCILLOSCOPES, ROHS

	COMPLIANT: YES
Pp850	OSCILLOSCOPE, PC, 4CH, 200MHZ, 1GSPS, SERIES:PICOSCOPE 8000, SCOPE TYPE:HAND HELD, SCOPE CHANNELS:4 ANALOGUE, BANDWIDTH:200MHZ, SAMPLING RATE:1GSPS, I
Pp748	OSCILLOSCOPE, 4-CHAN, 500MHZ, 5GSPS, SCOPE TYPE:PC BASED, SCOPE CHANNELS:4, BANDWIDTH:500MHZ, SAMPLING RATE:5GSPS, INPUT IMPEDANCE:1MOHM, RISE TIME:70
Tc08usbcald	DATA LOGGER, TEMPERATURE, SVHC:NO SVHC (20-JUN-2011)
Pp711	OSCILLOSCOPE, PC BASED, 2 CH, 100MHZ, 500MSPS, SCOPE TYPE:PC BASED, SCOPE CHANNELS:2, BANDWIDTH:100MHZ, SAMPLING RATE:500MSPS, INPUT IMPEDANCE:1MOHM
Picoscope4224kit	20MHZ OSCILLOSCOPE, PRODUCT RANGE:PICOSCOPE 4000 SERIES, SCOPE CHANNELS:4 DIGITAL, BANDWIDTH:20MHZ, SAMPLING RATE:80MSPS, DISPLAY MEMORY DEPTH:32 MPTS
Ta044	OSCILLOSCOPE PROBE, 70 MHZ, HIGH-VOLTAGE DIFFERENTIAL PROBE, 7 KV, 100:1, 1000:1, ROHS COMPLIANT: YES
Pp839	OSCILLOSCOPE, PC-BASED, 4CH, 250MHZ, 1.25GSPS, SCOPE TYPE:USB MODULAR, SCOPE CHANNELS:4 ANALOGUE, BANDWIDTH:250MHZ, SAMPLING RATE:1.25GSPS, INPUT IMPE
Tc08usbcald	TC08 USB CALIBRATED
Rsf54v100mc	
Picoscope2208	OSCILLOSCOPE, PC, 200MHZ, 2CH, AWG, SCOPE TYPE:PC BASED, SCOPE CHANNELS:2, BANDWIDTH:200MHZ, SAMPLING RATE:1GSPS, RISE TIME:1.75NS, EXTERNAL HEIGHT:40
Ta046	ACTIVE DIFFERENTIAL PROBE 30V, 800MHZ, X1/10, CAT I
Tc08usbcald	DATA LOGGER, TEMPERATURE, SVHC:NO SVHC (20-JUN-2011)
Picoscope4424kit	20MHZ OSCILLOSCOPE, PRODUCT RANGE:PICOSCOPE 4000 SERIES, SCOPE CHANNELS:4 ANALOGUE, BANDWIDTH:20MHZ, SAMPLING RATE:80MSPS, DISPLAY MEMORY DEPTH:32 MPT
Pp851	OSCILLOSCOPE, PC, 4CH, 200MHZ, 1GSPS, SERIES:PICOSCOPE 8000, SCOPE TYPE:HAND HELD, SCOPE CHANNELS:4 ANALOGUE, BANDWIDTH:200MHZ, SAMPLING RATE:1GSPS, I
Pp631	OSCILLOSCOPE, 4-CHAN, 350MHZ, 5GSPS, SCOPE TYPE:PC BASED, SCOPE CHANNELS:4 DIGITAL, BANDWIDTH:350MHZ, SAMPLING RATE:5GSPS, INPUT IMPEDANCE:1MOHM, RISE
Pp312	HIGH PRECISION DATA LOGGERS, KIT CONTENTS:ADC-24 HIGH RESOLUTION DATA LOGGER, 24 BIT WITH TERMINAL

	BOARD AND SOFTWARE, ROHS COMPLIANT: NA
Ta042	OSCILLOSCOPE PROBE, 100 MHZ, DIFFERENTIAL, 1.4 KV, 100:1, 1000:1, ROHS COMPLIANT: YES
Picoscope4424caldu	CALIBRATED W/DATA UNCERTAINTIES CHILD SKU # 68R4303
Pp749	OSCILLOSCOPE, 4-CHAN, 500MHZ, 5GSPS, SCOPE TYPE:PC BASED, SCOPE CHANNELS:4, BANDWIDTH:500MHZ, SAMPLING RATE:5GSPS, INPUT IMPEDANCE:1MOHM, RISE TIME:70
Pp478	20MHZ OSCILLOSCOPE, SCOPE TYPE:PC BASED, SCOPE CHANNELS:4 DIGITAL, BANDWIDTH:20MHZ, SAMPLING RATE:80MSPS, INPUT IMPEDANCE:1MOHM, RISE TIME:17.5NS, INP
Pp454	OSCILLOSCOPE, PC BASED, 4 CH, 5MHZ, 5MSPS, SCOPE TYPE:PC BASED, SCOPE CHANNELS:4, BANDWIDTH:5MHZ, SAMPLING RATE:5MSPS, INPUT IMPEDANCE:10.1MOHM, SUPPL
Picoscope3425	OSCILLOSCOPE, PC BASED, 4 CHANNEL, 5MHZ, 5MSPS, PRODUCT RANGE:PICOSCOPE 3000 SERIES, SCOPE CHANNELS:4 ANALOGUE, BANDWIDTH:5MHZ, SAMPLING RATE:5MSPS, D
Picoscope6403cal	SCOPE KIT, WITH PROBES, 1GS MEMORY, SCOPE TYPE:ANALOGUE, SCOPE CHANNELS:4, BANDWIDTH:350MHZ, SAMPLING RATE:5GSPS, INPUT IMPEDANCE:50OHM
Picoscope4224	20MHZ OSCILLOSCOPE, PRODUCT RANGE:PICOSCOPE 4000 SERIES, SCOPE CHANNELS:2 ANALOGUE, BANDWIDTH:20MHZ, SAMPLING RATE:80MSPS, DISPLAY MEMORY DEPTH:32 MPT
Picoscope4424	20MHZ OSCILLOSCOPE, PRODUCT RANGE:PICOSCOPE 4000 SERIES, SCOPE CHANNELS:4 ANALOGUE, BANDWIDTH:20MHZ, SAMPLING RATE:80MSPS, DISPLAY MEMORY DEPTH:32 MPT
U4/7	
Pp630	OSCILLOSCOPE, 4-CHAN, 350MHZ, 5GSPS, SCOPE TYPE:PC BASED, SCOPE CHANNELS:4 DIGITAL, BANDWIDTH:350MHZ, SAMPLING RATE:5GSPS, INPUT IMPEDANCE:1MOHM, RISE
Picoscope2207	OSCILLOSCOPE, PC, 100MHZ, 2CH, AWG, SCOPE TYPE:PC BASED, SCOPE CHANNELS:2, BANDWIDTH:100MHZ, SAMPLING RATE:1GSPS, RISE TIME:3.5NS, EXTERNAL HEIGHT:40M
Picoscope3205	PC-BASED OSCILLOSCOPE , SCOPE BANDWIDTH:100 MHZ, SCOPE CHANNELS:2 SCOPE, SERIES:PICOSCOPE 3000, FEATURES:DEEP MEMORY BUFFERS, ADVANCED TRIGGER MODES R
Picoscope6407	OSCILLOSCOPE, PC BASE, 4CH, 1GHZ, 5GSPS, PRODUCT RANGE:-, SCOPE CHANNELS:4 ANALOGUE,

	BANDWIDTH:1GHZ, SAMPLING RATE:5GSPS, DISPLAY MEMORY DEPTH:1 GPTS
Ms-328-3-1-0500	Standard MS-328-3-1-0500 Reed sensor according to enclosed data sheet
4226 Case Bundle	OSCILLOSCOPE KIT HI-RES 50 MHZ, SCOPE TYPE:PC BASED, SCOPE CHANNELS:2, BANDWIDTH:50MHZ, SAMPLING RATE:125MSPS, INPUT IMPEDANCE:1MOHM, RISE TIME:7NS, I
Picoscope3205caldu	OSCILLOSCOPE, 100MHZ, 2 CHANNEL, 100MSPS, SCOPE TYPE:PC BASED, SCOPE CHANNELS:2
Pp671	OSCILLOSCOPE, 50MHZ, 2 CHANNEL, 125MSPS, SCOPE TYPE:PC BASED, SCOPE CHANNELS:2 DIGITAL, BANDWIDTH:50MHZ, SAMPLING RATE:125MSPS, INPUT IMPEDANCE:1MOHM
Pp712	OSCILLOSCOPE, PC BASED, 2 CH, 200MHZ, 500MSPS, SCOPE TYPE:PC BASED, SCOPE CHANNELS:2, BANDWIDTH:200MHZ, SAMPLING RATE:500MSPS, INPUT IMPEDANCE:1MOHM
Pp629	OSCILLOSCOPE, 4-CHAN, 350MHZ, 5GSPS, SCOPE TYPE:PC BASED, SCOPE CHANNELS:4 DIGITAL, BANDWIDTH:350MHZ, SAMPLING RATE:5GSPS, INPUT IMPEDANCE:1MOHM, RISE
Ms-328-3	FLACHGEH. REEDSENSOR PIC MS-328-3