

Procentec



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Procentec Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Procentec Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Profihub A5	16010 RS485 5-fach Repeater IP65 für PROFIBUS DP / MPI & PROFISAVE galvanically isolated output channels; EMC filter through BIT regeneration; Integrated switchable Terminating resistors; Bus status display per channel; Automatic baud rate detection 9.6 Kbps - 12Mbps; 31 devices per channel; Protection class IP65; UL listed
PA003135	CONNECTOR PROFIBUS DP DIAGNOSTIC FC PG (90°) RS485 IN IP 20 ENVIRONMENTS WITH DIAGNOSTIC INDICATORS
101-00211A	
1720R	
17210R	
17420	
37020	
37021 (PROFIBUS)	
B5-17010	
GC-PB-CB-1CH-SC	
ProfiBUS-Hub B5 5	
17030X	ProfiSwitch X5 RS485 5-channel repeater with variable baud rate per channel for PROFIBUS DP / MPI & PROFISAVE 5 galvanically isolated output channels; Multiple connection options (screw connections, SUB-D, universal clamps); Redundant power supply with 2x 24V connection; EMI filter by BIT regeneration and robust operation mode (optional); switchable redundancy mode; Integrated switchable terminating resistors; bus status display per channel;

	configurable baud rate per channel; 31 devices per channel; protection class IP20; UL (E365044-A1-UL), DNV (A-13659), FCC & CE certifications
ProfiHub B5+R	17020R RS485 5-channel repeater with diagnostic function for PROFIBUS DP / MPI & PROFISAVE 5 galvanically isolated output channels; Multiple connection options (screw connections, SUB-D, universal clamps); Redundant power supply with 2x 24V connection; EMI filter by BIT regeneration and robust operation mode (optional); switchable redundancy mode; Integrated switchable terminating resistors; bus status display per channel; Automatic baud rate detection 9.6 Kbps – 12Mbps; 31 devices per channel; Capable of diagnostics as a PROFIBUS slave via PLC connection or with Procentec COMBricks; protection class IP20; Certifications according to UL (E365044-A1-UL), DNV (A-13659), FCC & CE
101-2000127	ComBricks Fixed Backplane HS + 6 Sub
101-20011C	ComBricks Head Station Type 1C
SA3060	Anybus Premium Fee
101-201101	ComBricks 1 Channel Repeater
101-200qc4s	
101-201610	
110-00013a	
101-201102	
37021 Profitrace 2	
101-201101	
Profihub B5+rd	
Kompakter Repeater B1	
100-201610	
101-201530	
Profihub-A5	
101-20011b	
101-210210k	
16010	PROFIBUS HUB 5 CHANNEL DP REPEATER 10-32VDC 4.1W
38022	
14020	
L45467-G16-C355	
101-200qbs	

101-00201a	
Gc-Pb-Profihub-B	
101-20011c	
B5-17010 Obsolete/Replacement 17020r	
Pa003135.	
17020r	
17020rd	
39020	
17030x	
16011	
Profitrace 2	
101-200	
513-00011a	
101-00211a T1 Terminator	
101-20011ck	
Profihub-B5	
101-200012	
514-00011a	
Profihub A5 (16010)	
Dp Hub 16010	
Ab7000-C	
Profihub B5+r	17020R B5 + R is the successor product of the B5, which is not more we offered
37021	
17010	
Erdungsschiene Fuer Profihub A5 (16011)	
Gc-Detect-Pb-Kit2-Upro	
101-201210	ComBricks 1 Channel SCOPE Repeater