

Profibus

Garanti: 12 ay
 Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Profibus Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Profibus Trkiye Distribtr veya temsilcisi deėildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Crevis_Na-9122	
Profibus-Tester Pb-Q One	Incl.case, CD, manual guide, adapter, USB cable * Assessment of physical and logical transmission quality * fully automatic detection of PROFIBUS topology under running Production conditions with indication of Repeaters and cable lengths * suitable for acceptance and Commissioning, maintenance and service as well Troubleshooting in PROFIBUS networks Stat.-commodity code: 90303370 Country of origin: Federal Republic of Germany Net weight: 1.50 kg
Pa Adapter Fr Pb-Q One	Nomenclature number: 90303370 Country of origin: Federal Republic Germany
Pbmb Ii Profibus Assembly Module	(blue housing) Input: 24 V DC (20 - 28V, reverse polarity protected) Output: 5V DC / 200mA short-circuit proof PIN 5 (GND) 6 (+ 5V) * Connection via screw terminal * Type of fastening: snap on DIN rail according to EN 50022 Net weight: 0.033 kg Static product no .: 85423190 UL No .: E218520 Country of origin: European Community (EEC Germany) No cumulation applied with preference
M12 Terminating Resistor Socket B-Coded Ip67	Screw thread (M12 x 1 mm) recommended Tightening torque 0.6 Nm, self-locking Degree of protection: IP67 when plugged in and screwed on (EN 60529) Material (locking): zinc Die-cast, matt nickel-plated country of origin: Germany Stat. Product number: 85331000
Adapter Set For M12 Connection Technology	with M12 connection technology, including terminating resistor Nomenclature number: 85075000
Anybus AB7000-C	Device to Fieldbus Converter

110010050	
17020R	
226534	
38022	
DDL-NN-006012	
PA003135	
DDA-NN-006014	PROFIBUS testers 5 sets To check the cabling, the bus physics and the Communication in PROFIBUS-DP networks. Including PROFIBUS Tester 5 main unit (DDA-NN-006015), portable oscilloscope, PC software PROFIBUS diagnostic suite, manuals, power pack (100..240V/50..60Hz), mains cable (EU+USA) and adapter cable in carrying case. -- For deliveries within the EU: -- According to EU regulation 1907/2006 (REACH) Article 33 we hereby inform you that this product has the following Substance(s) from ECHA's extended candidate list for special contains Substances of Very High Concern (SVHC) above the Limit of 0.1 percent by weight is/is: - 1,2-dimethoxyethane,ethylene glycol dimethyl ether (EGDME) (CAS No. 110-71-4 1)
DDA-NN-006014	PROFIBUS testers 5 sets To check the cabling, the bus physics and the Communication in PROFIBUS-DP networks. Including PROFIBUS Tester 5 main unit (DDA-NN-006015), portable oscilloscope, power supply (100..240V/50..60Hz), mains cable (EU+USA) and adapter cable in carrying case.
DUCKER/ELK/10168487/PROFIBUS GATEWAY/BIHL WIEDEMAN	BWU2545
CNC/PLC SST PCU3L-A	
PROFIBUS Troubleshooting Toolkit Ultra PRO	38022
VCI 1P CA	DP INTERFACE
2862398	
Pbif1ms	PC BOARD
Bluambas® Pb Comfort - Funkmaster	Protection class IP 65 PROFIBUS over radio " - Connection of up to 4 PROFIBUS nodes at max. 1.5 Mbps - Connection of 1 radio master with max. 4 radio slaves - Bluetooth wireless technology 2.4 GHz, 100 mW - Range: up to 100 m (Antenna-dependent) - Power supply: 24 V DC Stat. Lot number: 85176200 Net weight: country of origin: Germany
700-972-6aa02	
Encoder.Crd58-8192 R 4096 C2z01 Profibus	
Fast Corner Pg 6es7972-0ba50-0xa0	
Mlc9002-Bm240pb Bus Control Module	
6137591	
Profibus Diagnostic Case Iii	for service and commissioning Diagnostic tools for continuous and temporary network analysis in PROFIBUS for commissioning and service * PB-Q One - PROFIBUS Tester * PROFtest II XL without DP master function - Line tester * PB INSPEKTOR® NT - Distributed Data Collector * APKA II - Active programming cable * Plug-in power supply 24V / 1.25A * EMCheck LSMZ I - Leakage measuring clamp * Transport case Customs tariff number: 90308930 Country of origin: Federal Republic of Germany
Kpi1000	

Rpba-01	
9350-9 Diag Conn 90	
2170212 Unitronik Bus Fdp L2/Fip 1x2x0,64 Laap	
Bc-Pbmb-Pb-S	
Bc-600-Pb-Cb-M12	
Profibus-Dp	
Awg22s	
2718688 Pho01720	
Pb-B V3.3	
I-7550-B Cr	
Mms6350/Dp	
Tra-Pb-Ts	
Bc-M12dp-Pb	
Bwu1703	
700-972-6aa00	
Ocd-Dpc1b-1212-C100-H3p	
Cev-65m-01460	
Ab7821-F(Bwu1703)	
Patest	* Segment check with "OK / BAD" display * Recording the number of devices in the segment * Live List Display * Registration and cancellation of participants * Telegram errors and repetitions * Segment voltage display * Display of signal levels of all devices * Short-circuit detection between signal wires and cable shield * Measurement of interference mean and - peak value Goods tariff number: 90303310 Equipment: * PAtest with MBP and USB interface * Connection cable with measuring adapter * USB cable
Dp / V1	
700-972-0bb12 Profibus-Stecker, 90;	
Bm4-O-Pro-01-00-00	
Bluambas® Pb Comfort - Radio Slave	Protection class IP 65 PROFIBUS over radio " - Connection of up to 4 PROFIBUS nodes at max. 1.5 Mbps - Connection of 1 radio master with max. 4 radio slaves - Bluetooth wireless technology 2.4 GHz, 100 mW - Range: up to 100 m (depending on antenna) - Power supply: 24 V DC Stat. Lot number: 85176200 Net weight: country of origin: Germany - Power supply: 24 V DC Stat. Lot number: 85176200 Net weight: country of origin: Germany
4.071	
S202-F4/06/0r-001/0b-K0	
Bk3120.	
0.050	
Bc-502-Pb	
Gcdetectpbkit2pl	ANALYZER

Pb-Lsz-Chb3	
Bidp-170	
Gcdetectpbtr2hws	ANALYZER
Dp-Encoder	
Gccif104pb	MODULE
Rif 1769?Dpm	
700-972-0ba12 Profibus-Stecker, 90;	
Gcdetectpbkit2up	ANALYZER
Mlc9002-An11100 Mlcsoftware, User Manual And Cabel	
Bc-600-Pb-Cb-Dsub1	
700-884-Mpi21	NETLink® PRO Compact, PROFIBUS Ethernet gateway - PROFIBUS - ETHERNET/IP