

Protego

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz. **Protego** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Protego Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün

Açıklama

[PROTEGO® ER-V-LP-600](#)

A20104151-3106601100041 Set pressure: + 7.5 mbar Volume flow at design pressure: 17750.0 m³ / h Design pressure: + 8.25 mbar Pressure relief valve PROTEGO® ER-V-LP-600 Flange connection: 24 " drilled according to ASME B16.5 CL 150 R.F. US Patent No. 9,383,021 Housing pressure PN 1 Conformity according to: 2006/42 / EG Housing assembly Housing: 316L / 1.4571 Valve seat: 316 SS / 1.4571 Lead screw: 316 SS / 1.4571 Screw / nut: A4 Pressure relief valve disc Valve head cover: 316 SS / 1.4571 Valve head: 316 SS / 1.4571 Sealing: metallic Pipe guides: 316 SS / 1.4571 Locking screw: 316 SS / 1.4571 Spring clip: A4 Lock washer: 1.4404 Nuts: A4 Weight: 316 SS / 1.4571 Item number: Country of origin: 84814010 Germany Unit weight approx. 149 KG

C600004F05020	Inspection certificate 3.1 according to DIN EN 10204 issued by BRAUNSCHWEIGER FLAMMENFILTER GmbH with tests according to PROTEGO® standard, e.g. Function check and set pressure (for valves) as well as showing the materials used - but without material analysis - per position, net
C600058F05020	Material certificate 3.1 according to DIN EN 10204 issued by the sub-supplier for pressurized parts per position, net
SPARE PARTS FOR BREATHER VALVE AND	VACUUM BREAKER BREATHER VALVE TYPE VD/SV-FF-50 SIZE 2",150#RF DESIGN PRESSURE +110MBAR SET PRESSURE +100MBAR SET VACUUM -90MBAR PRESSURE VENTING RATE 660M 3/N VACUUM RELIEF RATE 366M 3/N VALVE SEATS MATERIAL 316SS/1.4571 VALVE PALLET MATERIAL 316SS/1.4571 GUIDE AND RINGS MATERIAL 316SS/1.4571
VALVE SET POS.006,1.4571/31655	
VALVE DISC POS.017,1.4571/31655	
VALVE DISC POS.018 ,1.4571/31655	
SPRING POS.020 MAT. 1.4310	
SPRING POS.027 MAT. 1.4310	
BALL POS.040 MAT. 1.4310	
BREATHER VALVES	TYPE VD/SV50 , SIZE:2" 150#RF DESIGN PRESSURE + 25 mbar SET PRESSURE +22.5 mbar SET VACUUM -4.5 mbar PRESSURE VENTING RATE 480 M3/H VACUUM RELIEF VALVE 162 M3/H VALVE SEATS MATERIAL :316 SS/1.4571 VALVE PALLET MATERIAL :316 SS/1.4571 GUIDE AND RINGS MATERIAL :316 SS/1.4571
VALVE SEAT POS.070, MAT.1.4571/316SS	
VALVE PAIET-METALLIC	POS.110, MAT 1.4571/316SS
VALVE PAIET-FEP	POS.120, MAT. 1.4571/316SS
A21100237-3703101220022	Volume flow at design pressure: 843.0 m ³ / h Design pressure: + 55.0 mbar Pressure relief valve PROTEGO® DZ / T-100 Flange connections: DN 100 drilled according to DIN EN 1092-1, PN 16 Form B1 the direction of flow is on the housing marked by an arrow designed for: ventilation function Conformity according to: 2006/42 / EG Housing assembly Housing: 1.4408 Valve seat: 316 SS / 1.4571 Cover: 1.4408 Bolts / nuts: A4 Seal: PTFE Valve disc Valve head cover: 316 SS / 1.4571 Valve head: 316 SS / 1.4571 Sealing: metallic Spindle guide: 316 SS / 1.4571 Hex nut: A4 Weight: 316 SS / 1.4571 Item number: Country of origin: 84814010 Germany 49KG
C600004F06003	Acceptance test certificate 3.1 according to DIN EN 10204 issued by BRAUNSCHWEIGER FLAMMENFILTER GmbH with tests according to PROTEGO® standard, e.g. function check and set pressure (for valves) as well as showing the materials used - but without material analysis - per position,

	net
C600056F06003	Material certificate 3.1 according to DIN EN 10204 issued by the sub-supplier for pressurized parts per position, net
A21102016-452120024	A21102016-010 A21102016452120024 FLAMEFILTER® set 1.4310 for PROTEGO® DA-E-300-IIA-P1,2 S / N: 015102477-050-001 / 004 FLAMEFILTER® set for PROTEGO® fittings When installing the FLAMEFILTER® is absolutely our operating manual to be observed. FLAMEFILTER® set FLAMEFILTER® set - 7-fold: 1.4310 FLAMEFILTER® gap width: 0.7 mm Liner: 1.4571 Product number: 84799070 DE
A21102016-432100039	A21102016-020 A21102016432100039 FLAMEFILTER® set 1.4571 for PROTEGO® DA-SB-H-400/150-IIB3-P1,6-X3 S / N: 015102477-020-001 / 002 FLAMEFILTER® set for PROTEGO® fittings When installing the FLAMEFILTER® it is essential to observe our operating instructions. FLAMEFILTER® set FLAMEFILTER® set - 8-fold: 1.4571 FLAMEFILTER® gap width: 0.5 mm Interlayers: 1.4571
A21102016-332100099	for PROTEGO® DA-SB-300/50-IIB3-P1,6-X3 S / N: 015102477-040-001 / 002 A21102016-030 A21102016332100099 FLAMEFILTER® set: 1.4571 for PROTEGO® DA-SB-H-300/50-IIB3-P1,6-X3 S / N: 015102477-010-001 / 002 S / N: 015102477-030-001 / 004 FLAMEFILTER® set for PROTEGO® fittings When installing the FLAMEFILTER® is absolutely our operating manual to be observed. FLAMEFILTER® set FLAMEFILTER® set - 8-fold: 1.4571 FLAMEFILTER® gap width: 0.5 mm Liner: 1.4571
Flammensperre DN 150 nasse Umgebung: JP-5	Durchflussmenge: 120 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Flammensperre DN 150 Trockene Umgebung zu	verwenden: JP-5 Durchflussmenge: 120 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Flammensperre DN 250 Nassbereich: F-76	Durchflussmenge: 320 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Flammensperre DN 250 Trockene Umgebung zu	verwenden: F-76 Durchflussmenge: 320 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Flammensperre DN 50 Nassbereich: F-76/JP-5	Durchflussmenge: 10 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Flammendurchschlagsicherung DN 50 trocken Typ	Zu verwendende Medien: F-76/JP-5 Durchflussmenge: 10 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Flammensperre DN 100 trocken Typ	Zu verwendende Medien: F-76/JP-5 Durchflussmenge: 50 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Flammendurchschlagsicherung DN 100 Nassausführung	Zu verwendende Medien: F-76/JP-5 Durchflussmenge: 50 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C

Rohrtyp Flammensperre DN50 Zu verwendende	Umgebung: F-76/JP-5 Durchflussmenge: 10 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Rohrförmige Flammensperre DN150 Zu verwendende	Umgebung: JP-5 Durchflussmenge: 120 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Rohrtyp Flammensperre DN250	Zu verwendende Umgebung: F-76 Durchflussmenge: 320 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Flammensperre auf Entlüftungsrohr DN250	Zu verwendende Umgebung: F-76 Durchflussmenge: 320 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Flammensperre auf Entlüftungsrohr DN150	Zu verwendende Medien: JP-5 Durchflussmenge: 120 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Flammensperre DN 200 trockener Typ Umgebung: F-76	Durchflussmenge: 320 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Belüftungskappe	(BELÜFTUNGSDECKEL) PROTEGO EH/O Zu verwendende Medien: F-76/JP-5 Durchflussmenge: 320 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
Belüftungskappe	(BELÜFTUNGSDECKEL) PROTEGO EH/O Zu verwendende Medien: F-76/JP-5 Durchflussmenge: 120 m3/h Auslegungsdruck: 16 bar (PN16) Auslegungstemperatur: 20-25 C
info	Für trockene Flammendurchschlagsicherungen: PROTEGO DR / ES □ Für Nassflammendurchschlagsicherungen: PROTEGO LDA-F □ Rohrförmige Flammensperre: PROTEGO FA-CN □ Flammensperre am Lufterrohr: PROTEGO D-SVL-EB F-76 fuel tank; It is vertically located underground with a diameter of 22 m and a height of 7.5 m. JP-5 fuel tank; It is vertically positioned underground with a diameter of 9.5 m and a height of 4.5 m.
VD/TS-50-IIB3	
1767-1	
8550181	
A17100539-3303051220016	
A17100539-4003081220268	
A18103102-010 122100002	
A18103102-020 132220005	
A21100138-4153051210003	
DA-G- ?"-IIA-P1,1	

DR/U-15 42100004
PV / EBR-80-IIB3
PV Flap DN 250 PN16
St 2101101100001
VD/TS-100-IIB3 (4003101210078)
VD/TS-300-IIB3 (4006301210005)
Listen amanhang
PROTEGO® ER-V-LP-600 modeli,4" + 6"
VD/SV-PA
Fa-E
Ef/V-Ii ? 50
551251220002
Vd/Ts-100-Iib3 (4003101210078)
Artikel-Nr. 8550181 Dichtung: Ptfe Fur ® Da-Ub-300/150-Iib3-P1,3-X3
Scu007
7140003
101251220004
Sv / E-80-Iib3
Pv / Ebr-80-Iib3
Artikel-Nr. 112120006 Flammenfilterã174; Satz - 3fach
Ef/V-50-Iib3
2101251220006 (Protegoã174; Da-G-1 Quot;-Iib3-P1,1)
Dr / Es-V-50-Iib3-P1
192100012
Artikel-Nr. 8550181 Dichtung: Ptfe Fur Protegoã174; Da-Ub-300/150-Iib3-P1,3- X3
102220002
3100010
551251220001

22100056	
Dr/Es-T-150-Iia-P1,6	
92100004	
Vd/Ts-300-Ii B3 /Dn300 Pn10	
Vd/Ts-100-Iib3 4003101210123	
Artikel-Nr. 8610367 O-Ring-Dichtung: Fpm Fur Protegoã174; Dr/Eu-40-Iia-P1,6	
Artikel-Nr. 332120015 Flammenfilterã174; Satz - 7fach	
282100049	
2071151210001	
2101251220006 (@ Da-G-1 "-Iib3-P1,1)	
Vd/Ts-250-Ii B3 /Dn250 Pn10/	
A17104948-010	Art Nr. 8610289 8610289 Membran FPM für PROTEGO® UB/SF-0-150 Werk-Nr.: 90/0.715-01 Tariff number: 40169300 Country of origin: Germany
Artikel-Nr. 112120006 Flammenfilter@ Satz - 3fach	
7140001	
Artikel-Nr. 332120015 Flammenfilter@ Satz - 7fach	
A13103915-4003081220280	
322220023	
Scu009	
Vd/Ts-300-Iib3 (4006301210005)	
Artikel-Nr. 8610367 O-Ring-Dichtung: Fpm Fur ® Dr/Eu-40-Iia-P1,6	
Scu007 (Werksabnahmezeugnis Waz)	
2073051220014	
Be/Hk 50-11a	
Scu009 (Materialabnahmezeugnis Maz)	
Be/Hk-50-Iia	