

Raco

Garanti: 12 ay
Bu őrüne ait Tőrkiye ići kapı teslim fiyat ve teslim sőresi ićeren teklifimizi almak ićin **info@yursat.com.tr** e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi ićin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Raco Markası, tedarik sőresi ićin lőrften bizimle iletiřime gećiniz.

Firmamız Raco Tőrkiye Distribőrőrü veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen őrünlerde sadece Orjinal ve yeni őrün teklifi sunmaktadır. Bu sitede gősterilen őrzel marka adları ve ticari markalar ilgili sahiplerinin mőrliyetindedir, talep durumunda kaldırılmaktadır.



őrün	Aćıklama
ELEKTRISCH ON / OFF SITE GESTEUERT	actuator 4.000 Nm Supply voltage 380-400 VAC For control type and control unit, taking into account the attached drawing; 4...20mA reference information will be sent from PLC 4...20Ma position information will be sent to PLC PLC will receive on-off, torque error on opening, torque error on closing, general error, local and remote information.
ELEKTRISCH ON / OFF SITE GESTEUERT	actuator 8.000 Nm Supply voltage 380-400 VAC For control type and control unit, taking into account the attached drawing; 4...20mA reference information will be sent from PLC 4...20Ma position information will be sent to PLC PLC will receive on-off, torque error on opening, torque error on closing, general error, local and remote information.
ELECTRIC PROPORTIONAL- ON SITE CONTROLLED	actuator 1.500 Nm Supply voltage 380-400 VAC For control type and control unit, taking into account the attached drawing; 4...20mA reference information will be sent from PLC 4...20Ma position information will be sent to PLC PLC will receive on-off, torque error on opening, torque error on closing, general error, local and remote information.
	actuator 2.000 Nm Supply voltage 380-400 VAC For control

ELECTRIC PROPORTIONAL- ON SITE CONTROLLED	type and control unit, taking into account the attached drawing; 4...20mA reference information will be sent from PLC 4...20Ma position information will be sent to PLC PLC will receive on-off, torque error on opening, torque error on closing, general error, local and remote information.
ELECTRIC PROPORTIONAL	actuator 10.000 Nm Supply voltage 380-400 VAC For control type and control unit, taking into account the attached drawing; 4...20mA reference information will be sent from PLC 4...20Ma position information will be sent to PLC PLC will receive on-off, torque error on opening, torque error on closing, general error, local and remote information.
ELECTRIC ON-OFF	actuator 10.000 Nm Supply voltage 380-400 VAC For control type and control unit, taking into account the attached drawing; 4...20mA reference information will be sent from PLC 4...20Ma position information will be sent to PLC PLC will receive on-off, torque error on opening, torque error on closing, general error, local and remote information.
Liste am anhang	
T6N4-23744 (166-746-7)	RACO COMPACT T6N4 with trapezoidal screw drive 0 C = motor voltage.....3x400 V, 50 Hz, P = 0.17 kW 1 A = engine speed.....3000 rpm 2 Q = adjustment speed.....20 mm/sec 3 T6N4= type/adjusting force.....3 kN 4 F = adjustment range.....200 mm 5 E = linear feed/revolution.....4 mm 6 J = eye attachment 7 A = motor IP 54, ISO F + thermal contact 8 J = 2 proximity switches outside (10-30V DC opener) 9 I = - 10 D = 1st joint head on the thrust tube (a3 dimension increases by 40 mm) 2. Motor with holding brake type "L" (with voltage venting), 230V AC, to be wired separately 3. All connection cables 1.5 m long, open cable ends (1 x motor cable 5 x 0.75 mm ² marking U,V,W,N,PE) (1 x brake cable including thermal contact 4 x 0.50 mm ² marking 31,32,35,36) Lacquering: none, bare aluminum Main dimension according to drawing: 166-707-6 and 3D model
Replacement for: T6N4-23745 (166-746-7)	166-746-7 RACO COMPACT T6N4 with trapezoidal screw drive 0 C = Motor voltage.....3x400 V, 50 Hz, P = 0.17 kW 1 A = Motor speed.....3000 min-1 2 Q = Adjustment speed.....20 mm/sec 3 T6N4= Type/adjustment force.....3 kN 4 F = Adjustment path.....200 mm 5 E = Linear feed/revolution.....4 mm 6 J = Eye fastening 7 A = Motor IP 54, ISO F + thermal contact 8 J = 2 external proximity switches (10-30V DC opener) 9 I = - 10 D = 1. Joint head on the push tube (a3 dimension extends by 40 mm) 2. Motor with holding brake type "L" (released with voltage), 230V AC, to be wired separately 3. All connection cables 1.5 m long, open cable ends (1 x motor cable 5 x 0.75 mm ² Marking U,V,W,N,PE) (1 x brake cable including thermal contact 4 x 0.50 mm ² marking 31,32,35,36) Painting: none, bare aluminum Main dimensions according to drawing 166-707-6 and 3D model
518	

[3805rac](#)[1379](#)[5173-7](#)[1153](#)[2915us](#)[1668](#)[3203-8](#)[888-009-1](#)[1244](#)[248](#)[1112](#)[5829-10](#)[2661](#)[5173-2](#)[2511](#)[205rac](#)[4802-8](#)[50169001929](#)[2246-2](#)[2233](#)[3303](#)[2125us](#)[601q](#)[2960us](#)[3201](#)[2822](#)[167ts](#)[154-257-5](#)[6288](#)[3203db](#)

54551-3/4-1	
54151-Msb	
898	
2664rac	
5818-5	
T/Mb, 2100w, 230v	
355	
5147-0	
2912-8	
208030	
8773	
Nmssc	
2142	
7050	
906	
2720aj	
50169007532	
1264	
6425	
2924	
3566	
1211	
2905us	
2144us	RGD/EMT SET SCREW CONN 3-1/2 IN STL USA
5606-5	
3543-8	
4724-8	
5389-0	
3544	
137-913-5 Dmu 2	
5157-0	

266	
7835rac	
5186-1	
2404	
2639	
8206rac	
881rac	
5026-0	
3802rac	
1156	
5180-5	
5400-0	
5091-0	
2834	
2166us	RGD/EMT SET SCREW CONN 4 INSUL STEEL USA
3kf45a	
2918us	
3564-3	
2763	
3702-3	
3422-8	
2454-8	
Ah1886.4623	
2964us	
5028-5	
1455	
7922rac	
2632	
5361-7	
1206	

2442
3403-8
3008
6237
1046
6415
5638-5
T1m7
3202
5183-0
D-34034-5
2126
Vde6pc Rt35/696
4723-8
3566-3
693
T/Mb, 1600w, 230v
6264
1262
154-999-5
294
3793-2
4804-4
2622
1002
3703-1
2823
5103-6
50169-00660
967-2

270rac	
3703-5	
2160	
5820-8	
5343-0	
7090	
3702-2	
5121-0	
7320	
8777-0	
685	
5625-5	
4804-0	
T1a2 Motor Unit	
4703-4	
Rcv2-Dr	
3405	
5045-0	
224-Val	
8650	
2164us	RGD/EMT SET SCREW CONN 3-1/2 INS STL USA
1806	
2709-9	
838	
4734-8	
692	
50169-00865	
2940rt	
6353	
C10-1-020-1450	CATALYST AUTODIALER 5MB 120VAC 96/CHANNEL 4/UI

3513rac
571
6239ss
1198
3305db
8722-5
2124-8
5876-6
7051
2024-8
768r
2928
136-326-3
4714
2924-8
3552
2960rt
5320-6
2124us
2842
Cs1rac
3562-3
3792-3
5511
2406
3304-8
3703-4
842
5166-0
959
6355

911-4
4803-8
T/Mb, 2500w, 230v
1808
5002-0
7119rac
Vq295
839
7075
257hs
Repair Parts(Shaft , Bushes And Linkages) For Dn-300
1012
3424-8
2328
2902rt
7919rac
2853
8355
5323-0
14rcn
48011
7848rac
2940
2026us
1135
1372
1197
665
K1 Y5/6578 - Obsolete, Replacement - 154-257-5

[1971](#)[2416](#)[791](#)[5839-9](#)[Sp1rac](#)[8087k27](#)[902](#)[6372](#)[5624-6](#)[807c](#)[666](#)[3428](#)[2903-8](#)[873](#)[5345-0](#)[4804-1](#)[2606](#)[7302](#)[K55p5851](#)[5390-0](#)[2923-8](#)[3prac](#)[2195rac](#)[90013020-1](#)[50169008409](#)[3511-3](#)[2701-8](#)[2166](#)[805c](#)[816c](#)[418](#)

4722-8	
5101-0	
3303-8	
698	
3448	
232a	
3793-4	
7321	
5883-5	
2102-8	
2128us	
Verbatim	ALARM DIALING REMOTE MONITOR W/4 ALARM OUTPUTS
5829-9	
5337-1	
2162us	
7122rac	
722-Each	
3514-8	
5883-6	
4703-3	
189f	
3423-8	
2912	
5340-0	
257f	
3546	
7053	
937	
8125	
7120-1	

109-481-5
5146-5
2164
5269-1
2905rt
5189-7
3524-3
3561-3
2006us
Tir6
4751
2140
2923rt
2923
5694-0
5155-0
5103-0
2956
3pcs.65 85/94 12 721 Vgfu01
5346-0
50169002322
5874-5
701fd
3703-2
3792-2
4804-5
5269-0
Dhrac
4743
5033-0

5138-0
5173-5-Each
2913rt
2838
8326
2638
832
6275
1434-8
48010
2008us
296
3792-6
5155-5
2800
4700-5
5101-1
694
2712r
2922-8
3401-8
2082
781r
208
2950us
5189-5
786
681
2241
526

2454
3314db
663
5795-0
Dn-300
T1a2 Sn:35256
1391
5606-7
4745
3793-1
8767
257m
1186
5175-5
125each
683
841
3446
3051le1v
2507
2538
2944us
1803
911-1
213hwp
6244
2054
8752-5
2750bulk
7070
970sbs

3204db
6436
5321-1
2833
2204-8
7823rac
5121-1
4742
911-3
5186-7
4803-9
2952us
2916us
2712-9r
806c
5652-1
4pcrac
2003rac
5034-0
6258
2008-Fbar
1665
5146-1
7717rac
154-257-5 K1y5
6313
3512-3
5155-6
957
7054

[1963](#)[2913-8](#)[3514-3](#)[2444](#)[8977-5](#)[5141-5](#)[2025us](#)[5102-0](#)[58c1](#)[276](#)[1267](#)[2108](#)[2905](#)[701rd](#)[2140us](#)[3542-8](#)[3548-3](#)[4702-4](#)[2192](#)[519](#)[2942](#)[2123us](#)[857](#)[2915rt](#)[813c](#)[6289](#)[5334-0](#)[2122-8](#)[890](#)[232-Os](#)

6427
2281
8240
958
1387
709
8293
8983-1
320vplc-4c-32
545
2835
887
815c
4702-6
5621-6
4648
206rac
833
2904rt
1433
6401
6441
7645rac
4563
262-Mod
2914rt
1256
2925rt
2273
7318rac

9014
864
2922
956
3524
5189-6
1232rac
8233
8257
5333-0
5185-0
2918
5363-0
273-L
6293
3512-8
5103-7
5124-0
2628
5378rac
M-832
51450
5193-2
2908us
5160-0
294-1
1674
5405-0
5186-5
4752
5374-0

4804-3
14465
5166-5
2162rac
2056
3204-8
2662
8504
5137-0
3408
6448rac
5180-2
Rsc080804rc
5753-0
2703
5361-2
2624
5180-6
3426-8
8768
2966
1268
8771
2126us
5167-0
T1a2
5101-2
2150
708
50169907528

567	
6357	
3305	
T1m4	
2914us	
300vss-4c	ALARM DIALING REMOTE MONITOR W/4 ALARM OUTPUTS
1972	
3514rac	
19418	
847	
1371	
2235	
8196	
3441	
7846rac	
5361-6	
2240	
5613-1	
235	
7081	
1185	
3563	
010-2194-000	
5269-2	
769r	
686	
3793-6	
2913	
5175-1	
2962rt	
2023us	

[5412-0](#)

[5177-0](#)

[2926us](#)

[2713](#)

[878](#)

[2203-8](#)