

RECO

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
RECO Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız RECO Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
RECO Membrane MB-DN 25	RECO diaphragm MB-DN 25 CleaningLine membrane Material TPE-E Purge / raw gas temperature -20 ... + 100 ° C Medium quality class 2 compressed air (ISO 8573) Country of origin: Germany Manufacturer: RECO GmbH
RM-216 C.10.01	RECO filter control RM-216C.10.01 Loop-Bus System EasyLine IN 110/ 230V~, 26-28 V= OUT 24V= NormLine 28.08, 250x160x90 mm Protection IP-66, NEMA 5 Gland 1x M16, 3x M25 Plug 1x M16, 1x M20, 1x M25 dp- Connector N6/4 Range OUT 4-20mA=0-5000Pa RM-216C.10.01
017410615002	
10502741	
10600001	
10600013	
10600075	
10600258	

10600717
10600750
10601330
10602301
10602304
10602400
10603055
10603060
10603206
10603227
10603228
10603271
10603291
10603292 RM-BV 12 DP 10V ATEX
10603944
10697145
16000014
16000300
16000300 (RM-216 C.10.01)
16000302
16000310
16000340
16000351
16000380
16000395
16000500
16000532
2/2 N4,5-8P-24VDC
2/2 NG4,0-6P-24VD
2/2 NG4,0-6P-24VDC
2/2 NG4,5-8P-24VDC

21115936
53010001
60250293
61700000
61700002
61700004
61700096
61700099
61700123
70100002
70100026
70100046
70100049
70100056
70100057
70100074
70500279
DHL
H07RN-F 5x1,5mm? 0,2m
H07RN-F 5x1,5mm? 10m
H07RN-F 5x1,5mm? 2m
MB-DN 25
P/N 353119-01
PCB
pn10600001
RM-200C
RM-208 CB 13 UL 0V
RM-216 CB.10
RM-216 CB.10 ATEX
RM-216C

RM-300_C	
RM-BV 12 DP	
RM-BV 12 DP 3V ATEX	
RM-BV4	
RM-BV8	
RM-BV8.10.04 (10600329)	
RM-DPC	
RM-LV 6 / 5V	
RM-N 4,5	
VD-DN25;E343908 SET	
VPE5 10600013	
RM-BV4 Micro DP 2V ATEX	RECO filter control RM-BV4 Micro DP 2V ATEX Basic Line IN 230V~ OUT 24V= BluLine S 321/2.02 IP-66, NEMA 4 Certificate ATEX Zone 22 Cat 3 D 2 mounted RM-Valve NG 4P6R-90° 1xM16+BP, 1x M20+BP DP-Connector 6/4
NG 4	
2/2 NG4,0-6P-24VDC	RECO Magnetventil, solenoid valve Components 2/2 magnetic valve input supply voltage 24V DC power 22 W ED 10% with seal and gland M25 - black RECO
RM-200C	RECO filter control RM-200C Plug and Play ATEX with connection cable RECO filter control RM-200C plug and play ATEX EasyLine loop bus 10m IN 100-240VAC OUT loop bus DP sensor 0-5000 Pa +/-1% Certificates CE, ATEX 3D housing PC; IP 66, NEMA 4 NormLine 057Z-001; 250x160x90mm B,H,T Connections 1xM25, 2xM20, 1xM16 DP connector TPC push-4/6mm 1x connector M25-5 pole 1.5 mm² Hardware RM-200C xx.xx 1x connection cable_H07RN-F 5x1.5mm²- Male-socket-M25-10m(6025 0261)
RM-LV 6 / 5V	RECO valve module RM-LV 6 / 5V RECO valve module RM-LV 6 / 5V EasyLine loop bus IN loop bus OUT loop bus Valve outputs 5, 24V= Solenoid valve RM-N 4.5 Certificates CE, ATEX 3GD housing AI; IP-66 AI box ST_AI valve box 5V anod.; L 299, W 156, H 91mm Connections 2x plug connector M25-5 pin 1.5mm²
Connection cable_H07RN-F 5x1.5mm²	10m Connection cable_H07RN-F 5x1.5mm²- Male-female M25
RM-216 C.10	Loop-Bus System EasyLine IN 110/ 230V~, 26-28 V= OUT 24V= NormLine 28.08, 250x160x90 mm Protection IP-66, NEMA 5 Gland 1x M16, 3x M25 Plug 1x M16, 1x M20, 1x M25 dp- Connector N6/4 Range OUT 4-20mA=0-5000Pa RM-216C.10.01
RM-LV 4/2V	