

Römheld

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Römheld Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Römheld Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
2174160	Swivel clamping element double acting with manual override, overload protection and position monitoring Clamping force: 60 kN at 400 bar Swing stroke: 13 mm Clamping and lowering stroke: 5 mm max volume flow: 10 cm ³ / s for clamping edge: 18 mm max.operating pressure: 400 bar with pipe connection G1 / 4 according to data sheet WZ 4.2170 Net single weight: 4.13kg
Artikel-Nr. 0460729	Coupling nipple NW5 long built-in version for Ø20 H7 mm max.flow 12 l / min can only be coupled without pressure max. 300 bar, as per data sheet F9.428 Net single weight: 0.0483kg
1896608VMH36	Swing clamps with reinforced swing mechanism Flange below with O-ring connection, double-acting Pivoting angle 90° left Piston Ø 50 mm, rod Ø 40 mm Clamping stroke 20 mm, swing stroke 16 mm with shift rod, without metal scraper max. 500 bar, according to data sheet B1.8811 Net single weight: 4.524kg
	Swing clamps with reinforced swing mechanism Flange below with O-ring connection, double-acting Pivoting angle 90° left

1895608VMH35	Piston Ø 40 mm, rod Ø 32 mm Clamping stroke 22 mm, swing stroke 13 mm with shift rod, without metal scraper max. 500 bar, according to data sheet B1.8811
1543516	Block cylinder, double-acting with aluminum housing Piston Ø 25 mm, stroke 50 mm Connection pipe thread G1/4, seals NBR 2 transverse and 4 longitudinal bores max. 350 bar, according to data sheet B1.554 Net single weight: 0.902kg
Article No. 1801230a	RGR: V Compact clamp size 1 2.5 kN, flange below with long cocking lever (blank) with pneumatic relaxation control Max. 250 bar, according to data sheet B1.828
1843 A090 R23	
0460-659	
1475011	
Artikel-Nr. 1462100	Screw-in cylinder, ew Ø20 x 15 mm stroke 500 bar, according to sheet B1.461
0460-776	
Article No. 1942900	RGR: R Screw-in support element M26 x 1.5 mm, single-acting, Metal wiper edge, bolt Ø 16 mm, bolt stroke 6.5 mm, Max. Loading force 4 kN, type of function: oil pressure with spring force, Max. 350 bar, according to data sheet B1.9405.
Piston Hidrolik Ø12-10 1460001 - 12dx 10 Hub 500 Bar	
0460-682	
Artikel-Nr. 1802131	RGR: V Compact clamp size 2 4.0 kN, without cover with long cocking lever (blank) with pneumatic tension control Max. 250 bar, according to data sheet B1.827
1843 A090 L23	