

Rototherm

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Rototherm Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Rototherm Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
12" Mechanical Chart Recorders	Model: Clearscan (Pressure & Temperature) 1 pen Temperature & 1 pen Pressure CPT Mounting Portable / Rear connection Chart Drive 24 h. & 7 day Mechanical Dual Rotation Pressure System 0 to 160 bar or 0 to 200 bar Process Connection 1/2" NPT
Am180	
Sentinel Recorder Controller - Single Pen (Sen10)	
Fw4505 (Blue)	
Bh345-A-8.0mm-500mm-0 To 100-C-X-1	
Rp010/5/C/2/1/D/0-6000kpa	
61a12-B-2c	
12/D/60/X	
Pt100 ?3mmã215;14mmã215;3000mm	

Sem310 (Hart Protocol)	Temperature Configurator Transmitter Certification EExia Certified Calibration Type RTD RTD Type PT100 Wire Configuration 3 Wire Burnout Protection Type Upscale Calibration Type Programmed Transmitter Clips Not Required Transmitter Range 0 to 400 C
724.Pz.5141.27.1101	
78bt-B1141-27 -12/50 Npt By 78b.T.3141.12/050/Npt	
Fw4505 (Red)	
Heat Wheel	
Frequency Inverter For Motor (Speed Control)	
Csp100-6ssmk-2s051a	
61a12-B-4c	
Rp010/5/C/2/1/D/0-10,000kpa	
Wesg-03600	
18309-Sp0031,1260mm Lg,5	
Y98228.1261	
9/D/132/X	
23988/11	
No Direct Dg1 Tx Vn	
Cstp200-6wsqi-Nojc0c1/3/1/O150f- 2c061d	
Rtpo200-6w0ei-Nooc5c1/10/4/I305f- 2s562d	
Cstpp300-6wsmi-Xojc0c1/3/1/O36f- 2s091d-2s091e	
V-Belt Pulley	
Ind Press 810-500-8345 K5974 504/5	
V-Belt	
9/W/137/X	
Obsolete C105 Replaced By Rpo100	
Mx-5141n	
Documentation Package For Csp100- 6ssmk-2s051a	

[Pt100 ?3mmã215;32mmã215;3000mm](#)

[Sentinel Recorder Controller - Two Pen
\(Sen20\)](#)

[Model:Dg1 Tx Vn 0-10bar 11 Range: 0
To 10 Bar Absolute S/N:668022-8-4](#)

[Bh345 + T/Well](#)