

Schaaf

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Schaaf Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Schaaf Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Schaaf	
03490NBR	O-Ring d=1,78 D1=53,7 D2=57,26 NBR 90°Shore A API034 40169300 DE
Air hydraulic pump HDL 3000	A37200023 0 - 3000 bar according to SCHAAF drawing A3720 with 2 useful connections M16x1.5 IT 60°DK 2 outlets with quick-release coupling sleeve SVK30 M16x1.5 AG 58° DK - external precision pressure relief valve (adjustment range 50 bar - 3000 bar) - 1 pressure gauge 0 - 3000 bar, Ø 100 mm, quality class 1.0 glycerin filled Short name: 022A3720300/10X/S3/2/XX/XDB Drawing number A3720 Index a
	Screw tensioning device SSV M64x6 Article no. B41430000 Technical data: Clamping force 1980 kN at 2922 bar hydraulic pressure Stroke 6mm max. outside diameter 166 mm Height 209mm Support diameter inside 110 mm External support diameter 141 mm consisting of: ----- Cylinder, support sleeve Pistons High pressure seal kit Hexagon socket SW 95 for tightening the main nut using an adjusting rod Ø 12 mm Adjusting rod Ø 12 mm Manual piston

B41430000	return stroke device via return elements Stroke signal band with max.stroke - max.stroke indications Venting Support sleeve attachment integrated into the cylinder (support sleeve remains rotatable) Quick-release coupling nipple type SVN30 Eyebolt ----- The surfaces of the individual parts are burnished. The SSV is fully assembled and functionally tested. Price includes 1x detailed technical documentation in German. Drawing number B4143 Index a
A06470004	High pressure hose, 4.0 m long with quick-release coupling sleeve and nipple type SVK30 / SVN30 Max. operating pressure: 3000 bar
B41170000	Screw tensioning device SSV M72x6 Technical data: ----- ----- Clamping force 2400 kN at 2875 bar hydraulic pressure Stroke 6mm max. outside diameter 185 mm Height 190mm Internal support diameter 122 mm External support diameter 155 mm consisting of: ----- Cylinder, support sleeve Pistons High pressure seal kit Adjusting rod Ø 12 mm Manual piston return stroke device via return elements Stroke signal band with max.stroke - max.stroke indications Venting Support sleeve attachment integrated into the cylinder (support sleeve remains rotatable) Rotatable angle connection with quick-release coupling nipple type SVN30 ----- The surfaces of the individual parts are burnished. The SSV is fully assembled and functionally tested. Price includes 1x detailed technical documentation in German. Drawing number B4117 Index a
B41810000	Screw tensioning device SSV M80x6 Article no. B41810000 Technical data: Clamping force 3000 kN at 2987 bar hydraulic pressure Stroke 10mm max. outside diameter 200 mm Height 202.6mm Internal support diameter 134 mm External support diameter 175 mm consisting of: ----- Cylinder, support sleeve Pistons High pressure seal kit Hexagon socket SW 115 for tightening the main nut using an adjusting rod Ø 12 mm Adjusting rod Ø 12 mm Manual piston return stroke device via return elements Stroke signal band with max.stroke - max.stroke indications Venting Support sleeve attachment integrated into the cylinder (support sleeve remains rotatable) Rotatable angle connection with quick-release coupling nipple type SVN30 Eyebolt ----- ----- The surfaces of the individual parts are burnished. The SSV is fully assembled and functionally tested. Price includes 1x detailed technical documentation in German. Drawing number B4181 Index a
A0500vs00	Set of wearing parts to the HP 1600 consisting of; 1stk U-Ring NA300 10 / 20x8 94AU925 1stk wiper AS10 / 20x5x8 88NBR 5pcs nylon ring Dia12 / Dia18x3 1stk U-Ring NI300 Dia 16 / Dia 8 x 5.5 94AU925 1stk copper sealing ring according to DIN7603A 12 / 06x1, 5 Cu 1stk seal 110x110x1
D65d10-A3173-22/307	
A52430000	
	High pressure hose 3,0m long with quick-release coupling

A06540003	sleeve and nipple Ty CVK 25-2 / CVN 25-2 customs tariff 39173100 DE
A66805200	
A06810003	High pressure hose 3,0m long with quick-release coupling sleeve and nipple Ty CVK 16 / CVN 16 customs tariff 39173100 DE
A05680003	High pressure hose 3,0m long with quick-release coupling sleeve and nipple Ty CVK 15 / CVN 15 customs tariff 39173100 DE
A42820000	
Zu0010508	
A66805300	
M36-A3874-22/307	
A66805400	