


Schaltbau

Garanti: 12 ay
 Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin info@yursat.com.tr e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.
Schaltbau Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Schaltbau Trkiye Distribtr veya temsilcisi deėildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.



rn	Aıklama
Zh437 E150	fuse includes the following SVHC: BLEI / CADMIUM, 231-100-4 / 231-152-8, 7439-92-1 / 7440-43-9 Net weight: 0.070 KG Nomenclature number: 85351000 Country of origin: DE
1-1440-201918	AWZ-B removal tool RoHS compliant includes the following SVHC: BLEI, 231-100-4, 7439-92-1 Net weight: 0.036 KG Nomenclature number: 85389099 Country of origin: DE
S870	W3L1 r 024 snap switch W 1-1570-125551 RoHS compliant Net weight: 0.760 KG Nomenclature number: 85365007 Country of origin: DE
1-1649-542435	Description C157 G40-S-220DX-X10 - Contactor 4pole
S800e 1-1520-243444	
C195 W /110ev	
Z3	
AFS817 24C 24V 150A	
1 6224 441069	70A 3kV Endverbleib Trkei
C193 A/ 24EV-U1 - Schtz S	1-1693-845881 RoHS compliant Contains the following SVHC: BLEI / PFBS, 231-100-4 / 249-616-3, 7439-92-1 / 29420-49-3 Net weight: 24.232 KG Commodity code: 85364900 Country of origin: DE AL: N ECCN: N Execution closer Rated insulation Ui (V) 1200 Nominal operating voltage Un (V) 1000 Number of poles 1 Type of voltage DC (unidirectional) Rated control supply voltage Us (V) 24 Continuous

thermal current Ith (A) 50
LIMIT SWITCH S870 W3B1T VAL0301597
BS-A-V10-FILLER PLUG
M33 SQUARE FLANGE RECEPTACLE
222K142-15 SHRINK BOOT 90
- M3E-12P+PE – KOD: 1-1402-908108
M36 ZB – KOD: 1-1402-981523
M3 E-12S+PE – KOD: 1-1402-908095
M3 KS – KOD: 1-1402-981589
T28-13/16 – KOD: 1-2411-319962
1-1494-857237
1-1522-104022
11522530965
1-1522-799733
1-1570-128016
1-1570-261909
1-1570-263518
1-1620-168651
1-1620-432383
1-1620-537933
1-1735-304561
1-1756-211505
1-1756-213023
1-2756-208510
1-2756-301762
1-2756-339203
1-2756-340613
1-3756-337097
1751221
1751231
1751335
7609539
7609827
7623342
7623343
8150300

8172602
8173511
8173534
9300324
BAC-1.00-Ag
C193 A/ 24EV
C193 A/ 72EVU1
C193A/ 24EV-UI
C195 A/ 24EV
C310 A/300 24I-V1
C310A/150 24I-V1
C310A/500 24I-V1
C310S/500 24I-V1
CL 1315/02X110ET-U2
CT1115/08 H 24ET-00
CT1115/08 V 110ET-00
CT1115/08 V 24ET-00 Schütz 1-polig
CT1115/08V-24ET-00
CT1115/11 N 24ECM-00
CT1215/04 V 24ET-00
CT1215/08 V 24ECM-00
EKS 127c
F-SO 2/2 E Kippschalter
LV160/320
LV320/400-N-P70-0-0-LO-HQ
LV320/400-N-S70-0-0-LO-HQ
M1 DS
M1 E-6P-PE
M1 E-6S-PE
M1 KS
M16Z
M18
MB-H S2
S800 a 10/40
S800 B

S826 a	
S826 AS	
S826 b 20	
S826e10	
S840 r 20	
S847 W1A2 b	
S847W2A8b	
S847W3B2e	
s870 w1f1a 044	
S870 W3B1	
SAC-1.00-Ag	
T1-6/8	
T1-8/10	
CT1115/08 V 110 ET-00	
C310 A/300 24I-V1 and C310 A/500 24I-V1	
C193 A/ 24EV-U1 - contactor S	RoHS compliant Contains the following SVHC: LEAD / PFBS, 231-100-4 / 249-616-3, 7439-92-1 / 29420-49-3 Net Weight: 11.184KG Statistical Commodity No.: 85364900 Country of origin: DE AL:N ECCN:N Version normally open rated isolation Ui(V) 1200 Rated operating voltage Un (V) 1000 Number of poles 1 Type of voltage DC (unidirectional) Rated control supply voltage Us(V) 24 Thermal continuous current Ith (A) 50
CT1115/08	V 24ET-00 contactor 1-pole RoHS compliant Contains the following SVHC: PFBS / PB / D6, 249-616-3/231-100-4/208-762-8, 29420-49-3/7439-92-1/540-97-6 Net Weight: 462KG Statistical Commodity No.: 85353010 Country of origin: DE AL:N ECCN:N Version normally open rated isolation Ui(V) 3000 Rated operating voltage Un (V) 1500 Number of poles 1 Type of voltage AC, DC (bidirectional) Rated control supply voltage Us(V) 24 Thermal continuous current Ith (A) 800
CT1115/08 V 24ET-00	
CT1115/08 V 24ET-00 contactor 1-pole	1-1756-302205 RoHS compliant Contains the following SVHC: PFBS / PB / D6, 249-616-3/231-100-4/208-762-8, 29420-49-3/7439-92-1/540-97-6 Version normally open rated isolation Ui(V) 3000 Rated operating voltage Un (V) 1500 Number of poles 1 Type of voltage AC, DC (bidirectional) Rated control supply voltage Us(V) 24 Thermal continuous current Ith (A) 800
S850 O6A8a	1-1550-195618
S800 a snap switch W	1-1520-209546 RoHS compliant Contains the following SVHC: LEAD / PFBS, 231-100-4 / 249-616-3, 7439-92-1 / 29420-49-3 Type of connection screws / clamping washer Version changer Actuation type roller lever contacts silver rated isolation Ui(V) 400 Thermal continuous current Ith (A) 10 snap with forced opening Yes
CT1115/08 V 24ET-00 contactor 1-pole	1-1756-302205 RoHS compliant Contains the following SVHC: PFBS / PB / D6, 249-616-3/231-100-4/208-762-8, 29420-49-3/7439-92-1/540-97-6 Version normally open rated isolation Ui(V) 3000 Rated operating voltage Un (V) 1500 Number of poles 1 Type of voltage AC, DC (bidirectional) Rated control supply voltage Us(V) 24 Thermal continuous current Ith (A) 800
	S826 a snap switch W RoHS compliant Contains the following SVHC: PFBS, 249-616-3, 29420-49-3 Type of connection screws / clamping

1-1522-530965	washer Version changer Actuation type roller lever contacts silver rated isolation Ui(V) 400 Thermal continuous current Ith (A) 10 snap with forced opening Yes
S847W3B8E	
1-1523-272169 S804 b	RoHS konform Enthält folgende SVHC: BLEI / PFBS, 231-100-4 / 249-616-3, 7439-92-1 / 29420-49-3 Type of connection screws / clamping washer Version changer Type of actuation push button contacts silver rated isolation Ui(V) 400 Thermal continuous current Ith (A) 10 snap with forced opening Yes Old material designation S804 B SNAP SWITCH
C164 C/72EV apr.1-1622-469341	
1-1620-925169	C163 C/ 72EV - Contactor S Contains the following SVHC: LEAD, 231-100-4, Version normally open rated isolation Ui(V) 150 Rated operating voltage Un (V) 120 Number of poles 1 Type of voltage DC (unidirectional) Rated control supply voltage Us(V) 72 Continuous thermal current Ith (A) 80
C137 C/ 72EV - Contactor S	1-1618-314241 Contains the following SVHC: LEAD, 231-100-4, 7439-92-1 Version normally open rated isolation Ui(V) 150 Rated operating voltage Un (V) 120 Number of poles 1 Type of voltage DC (unidirectional) Rated control supply voltage Us(V) 72 Continuous thermal current Ith (A) 40
S870 W1F1 a 044	1-1570-838214 Contains the following SVHC: PFBS, 249-616-3, 29420-49-3 Connection type circuit board pins Version changer Type of actuation push button contacts silver rated isolation Ui(V) 250 Thermal continuous current Ith (A) 10 snap with forced opening Yes
S870 W1D1 a 012	1-1570-276558 Contains the following SVHC: PFBS, 249-616-3, 29420-49-3
JA222D	Electronic buzzer not RoHS compliant Contains the following SVHC: LEAD, 231-100-4, 7439-92-1 Net Weight: 35,200KG Statistical Commodity No.: 85123090 Country of origin: DE AL:N ECCN:N 1-1726-207799
CH1130/02	
1-1550-195618	S850 O6A8 a Snap switch Ö. RoHS compliant Contains the following SVHC: LEAD / PFBS, 231-100-4 / 249-616-3, 7439-92-1 / 29420-49-3
C193 A/ 24EV-U1 - Contactor S	RoHS compliant Contains the following SVHC: LEAD / PFBS, 231-100-4 / 249-616-3, 7439-92-1 / 29420-49-3
1-1522-258709	S826 a 24 snap switch W RoHS compliant Contains the following SVHC: PFBS, 249-616-3, 29420-49-3 Connection type flat plug Version changer Roller lever actuation type Silver contacts Rated insulation voltage Ui(V) 400 Thermal continuous current Ith (A) 10 Snap. with forced opening Yes Old material name S826 A24 SNAP SWITCH
1-5974-201542	Lock cylinder IKON Tuvasas Rotem RoHS konform
1-5974-278985	Lock cylinder IKON 160-5-321 RoHS konform
1-1614-350734 C310A/500 24I-V1	Contains the following SVHC: LEAD / PFBS, 231-100-4 / 249-616-3, 7439-92-1 / 29420-49-3 Closer version Rated insulation voltage Ui(V) 1500 Rated operating voltage Un (V) 1000 Number of poles 1 Voltage type AC, DC (bidirectional) Rated tax feed sp.Us(V) 24 Thermal continuous current Ith (A) 500
1-3614-351856	C310A separator plate pluggable
S926 e24	
1-1494-120080	
	RoHS compliant includes the following SVHC: LEAD, 231-100-4, 7439-92-

K-Tknkt H Cc Sk Kippsch	1 Net weight: 1.260 KG Statistical Lot No .: 85365080 Country of origin: DE AL: N ECCN: N
Ct1115/08 V 24et-00	
C195 A/24ev	
G28-Dd	
1-1520-209557	
1-1401-594061	
C137 C 24ev-V1	
1-1402-908095 M3 E-12s+pe	
1-1622-469330	
Ga Df 1pl (Ex Ga Df 1pl M40)	
C294a/24ev-U1	
K-Ttnst U Cc Sw Kippsch.	Net weight: 0.140 g Statistical Product No .:
1-1735-748746 Indusi - Befehl	
1-1736-545014 P-S 1/1/1 Switch..	
1-1570-128016 Unsere Art.-Nr.: 7608314schnappschalter Wechsler Ip671-1570-128016s870w3l1rschaltbau	
1-1534-195186	
1 1455 120171	
S134-1-Z1-H00-M10-L1 Notabschalter	RoHS compliant Net weight: 5 KG Statistical Lot No .: 85363090 Country of origin: DE Old material name S134-1SCH / V EMERGENCY STOP SWITCH AL: N ECCN: N
S826/A 10/20	
S847 W1a2 B Schnappschalter W	
Schaltbau Snap Action Switch	Type: S847
Bbc-4.00ag	
S826e10 S826e10 (1-1522-103109)	
S800 A ** Contact	
1-6727-975722	
1-1490.801847	
S008 P5 41kw08	
S800 E	
S83415340195186	
K-Tsnst-4-Cc-Sk	
1sbb525012p1101	
K-Ssnss Ff Cc Kippsch	Nettogewicht: 0,070 G Statistische Warennr.:
M1 E -6p+pesw	

Bcc-6.00-Ag Uic541-5 Plug Piná;	
C163 C/24ev-R1	
??1115/08 V 110 Et-00	
Ct1115/08	
1-2756-339203 Kontakt Kontakt-Set	
K-Tknkt-4-Cc-Sh	
S840r20	
1-1494-118521	
1-1401-119648	
K-Tknkt S Cc Sky	Nettogewicht: 0,070 G Statistische Warennr.
S870w2d1a	
1-1043 235488	
S826 B 20 1-1522-532518 S826 B 20	
1-1734-214992 / 43w08 Switch Toggle.. Commutateur De Sablage Manuel40139367	
1-1429-102822	
C195 A/ 34es-Y2 1-1695-303 686	
Ct1115/08v24et-00	
1-1520-209546	
1-1440-981170 Bac-2.50-Ag	
S870w3l1	
61119940356	
Hfw1201k45	
1-1440-472723 Bs-A 1,50	
S818as	
Bac-1.00-Ag-67	
1-1401-119604 M1 E-4s+pe	
C195 S/24bd-U1- =10pcs.	
S826a	
1-1520-243444 (S800 E)	
C200/250 24 Fv-V1	
Lv320-N-P95-2-2-Lo-Hw1-Wo	
S826as Schnappschalter	
1-1440-316 894	
S132-100	
1-1440-474592, Bac-0,50-Ag	

1-1455-120171	
C137 C/110ev-V1	RoHS compliant includes the following SVHC: LEAD, 231-100-4, 7439-92-1 Net weight: 2,800 KG Statistical Lot No .: 85364900 Country of origin: DE AL: N ECCN: N Min sip miktarı 10 adettir
Bcc-6,00-Ag	
C164	
1-1440-844333 Awz-A	
1-2756-340613 1-2756-340613 Kontakteinheit	
Sk200 Sk200 (1-1050-415526)	
CI 1015/02 P 24 Et-U2-1pol	
1-1401-593944	
C295	
1-1620-432383 Rohs Konformalte Materialbezeichnung: Hilfskontaktgruppe F. S163	
1-1735-748746 Switch.. 2 Position - 25 Ampere - Frei	
S847w3b2e Endschalter	
1-1523-272169	
1-3756-337097 Keramikeinlage	
S579 T Sifa-Handtaster	includes the following SVHC: LEAD, 231-100-4, 7439-92-1 Net weight: 3.675 KG Statistical Lot No .: 85365080 Country of origin: DE Old material name SIFA-HANDBAR (TABLE) AL: N ECCN: N
C294 A/110ev-U1	
Bac-1.50-Ag 1-1440-474570	
C195 S 250v 250a	
Cma 5y14	
Cwz-120	
1-1401-119615, M1e-6s+pe	
C163	
1-1401-593977 M16sw	
S826e	
S800as	
C193 A/ 24ev-U1	
1-1756-213501	CT1115/04 V 24ET-00 CONTACTOR
Lv320-N-S95-2-2-Lo-Hw1-Wo	
C137 C/24ev	
S840 R20	
	cable connector 1-1435-585261 includes the following SVHC: BLEI, 231-100-4, 7439-92-1 Net weight: 0.260 KG Nomenclature number:

Nf10 A2l0a7	85366990 Country of origin: DE Old material designation PLUG NF10A2L0A7 AL: N ECCN: N
S870w2f1r	
S870 W2d1 I	
Lv160-N-S50-2-2-Lo-Hw1-Wo	
1-1440-303729	
C165	
1-1402-908108 M3 E-12p+pe	
1-1693-845881	
S800e	
C294 A/24ev	
S880	
K-Tknkt H Cc Kippsch.	1-1733-336425 RoHS compliant includes the following SVHC: LEAD, 231-100-4, 7439-92-1 Net weight: 1.260 KG Statistical Lot No .: 85365080 Country of origin: DE AL: N ECCN: N
1-1735-748746 Switch.. 2 Position - 25 Ampere -Wachsam	
1-1527-319199	
1-1440-981169 Sac-2,50-Ag	
C130/250 24rt-V2-004	
1620-432383	
Cl 1315/02?110??-U2	
Bhc-2,50-Au-30 Uic541-5 Plug Piná;	
C195a/72ev-U2	
1-1540-193306	
1-1520-243444 S800 E Schnappschalter W	
1-1440-474581	
S870w1d1a012	1-1570-276558
1-1435 161912	
1 1440 474581	
C193 A/24ev	
C137h/48ev	
Afs799/24b	art nr. 1603-328762 AFS799/24B 250a SPST 24V CO ENC BO 1
S826a10	
Bcc-2,50-Ag Socket	
G28e-2s+pe/L	
S804b	
S826as	

C137c/24rx 11s137c24	
1-1490-801596	
1-1490-801541	
1-1735-117517 Switch... 3 Position - 25 Amp	
Indusi - Wachsam40144506	
Nf10 – A3I0a23 steckverbinder	
1-1570-261909 Schnappschalter	
Ct1115/08 H 24et-00 Contactor	
C195a-24ev-U2	
1-1528-302161	S819 b 40 Taster Ö. RoHS konform Nettogewicht: 0,480 KG Statistische Warennr.: 85365007 Herkunftsland: DE
Ja222d Indusi Sounder.. Panel (Not Shown)	
1-1522-104022 Schalter S826 A 10	
1-1736-425421 P-S 0/1 Switch..	
1-1520-243444 (Ex.1-1520-270641)	
C294	
Cu1215/06	
Bhc-1.00-Au-30 Uic541-5 Plug Piná;	
S826 A 10(Ex S810)	
S870 W1f1a 044 Sprungschalter	
7501619	
1-1437 371346	
1-1440-303 725	
K-Tknkt Hhh Cc Kippsch	Net weight: 0.070 G Statistical Product No .:
C165 C/24ev	
Bac-1.50-Ag	
7501207	
1-1735-117517 Switch... 3 Position - 25 Ampere	
-Befehl	
Ch815	
Sk200	
C164 C/ 24ev	
S847 W2a2 B L Schnappschalter W	1-1547-339943 RoHS compliant Net weight: 0.740 KG Statistical Lot No .: 85365007 Country of origin: DE
C163 C/110EV-R1 - Contactor S	RoHS compliant Contains the following SVHC: LEAD / PFBS, 231-100-4 / 249-616-3, 7439-92-1 / 29420-49-3 Net Weight: 304KG Statistical Commodity No.: 85364900 Country of origin: DE AL:N ECCN:N Version normally open rated isolation Ui(V) 150 Rated operating voltage Un (V) 120 Number of poles 1 Type of voltage DC (unidirectional) Rated control

supply voltage Us(V) 110-Continuous thermal current Ith (A) 80	
1-1735-117517 Indusi - Frei	
1-1401-594016 M1 Ks	
S800 A10 Controller.. Brake - Position 4	
S800b	
Ct1130/04 H 110et-00	
S870 W1f1a Microschalter	
1-1401-119604	
Nf07c1l0	
1-1401-594950, M13	
1-1494-209-230	
1-1440-474570 Bac-1,50-Ag	
Ct1215/04	
1-1736-425578 P-S 7/9 Switch.	
Bpc-10.0-Ag Uic541-5 Plug Piná;Á;Á;Á;Á;	
E8002620	
Lv320 S10/95 1-1448-175261	
1-1773-473000 Db	
Ch829/110ev	
C164 C/24ev	
S800 E Snap-Action Switch W	RoHS konform Nettogewicht: 0,720 KG Statistische Warennr.: 85365007 Herkunftsland: DE A_L_:N _ E_C_C_N_:_N
Pt06-En-16-2/8p	
1-1440-303729, Sac-1,50-Ag	
1-1520-209568	
Cs115/10-22-110et	
1-2756-340613 Kamera Kontakteinheit Ct1015/04 V Ohne Festkon Rohs Konform	