



Schiebel

Garanti: 12 ay

Bu rne ait Trkiye ii kapı teslim fiyat ve teslim sresi ieren teklifimizi almak iin **info@yursat.com.tr** e-posta adresine bařvuru yapabilir ya da ayrıntılı bilgi iin +90 224 240 03 04 numaralı telefonumuzdan bizlere ulařabilirsiniz.

Schiebel Markası, tedarik sresi iin ltfen bizimle iletiřime geiniz.

Firmamız Schiebel Trkiye Distribtr veya temsilcisi deęildir. Firmamız sipariř durumunda, belirtilen rnlerde sadece Orjinal ve yeni rn teklifi sunmaktadır. Bu sitede gsterilen zel marka adları ve ticari markalar ilgili sahiplerinin mlkiyetindedir, talep durumunda kaldırılmaktadır.

rn	Aıklama
07836672	
95803933	
C300	
P/N 8z1	
RAB3 E 10 30NM	
RAB5 E 30 40NM	
AB3 E 80 CSC.V1.2mW4 H K2+E550 G	
rCM03.V1.2 E ER SR+E550G	
150	
C405	
7z0	
C3z2	
P/Ná;:Á;Opf004-2ap	
Type Ab5a5, No: 95803933	
Hna30aa001,Model: Ab8e80,Sn:88824543,	
Lca20aa001, Model:Ab18b40,	
603	
Ab200	
1201	
161	

375ma C 302a Vpe	
P/Ná;8z1á;Á;	
152z2ta	
P/Ná;7z1á;	
Mbr20aa051,Model:R Ab18e40zh,	
713	
0067 2175	
Hna30aa51-52,Model:Hna30aa51-52,Sn:88801999,	
Type Ab18b30, No: 07836672	
12z1	
C2z1	
500ma C 302b Vpe	
0567 2177	
Type Ab18e80, No: 95834090	
Mt 5004 00 001	
Pn:Á;11z1	
3z1	
Han24e Casing, Ab5b20,Sn:89804401	
Rab18 X 120 Csc.V1.2 Csz1fu Er Sr Fu-FC280-4,0-400 Hk2 + L220.18	exchange operator - for drive with Fab. No .: 0883 6896 - from comm. no .: 080633 (mechanically in the same version but with our current Smartcon FU control) rAB18 X 120 CSC.V1.2 CSZ1FU ER SR FU-FC280-4.0-400 HK2 + L220.18 Max. Regulating force 39.55 kN set force: 60 kN Drive is not self-locking 10 s positioning time (fast) for 117 mm stroke (variable Operating time) Dimensional drawing without control: M83_5E26_6m Motor: 400/230 V, 50 Hz, with brake (brake voltage 230 VAC) Power: 3.0 kW Inenn: 5.9 A Ia: 32.9 A Motor changes reserved with temperature switch SMARTCON V1.2 Drive control with Bluetooth interface - FU-FC280-4.0-400: frequency converter 4.0 kW - Input voltage: 3x380-480 VAC - 8 binary outputs (24 VDC) - freely configurable - 5 binary inputs (24 VDC) - freely configurable - CSZ1FU: Control Cassette Type for wall mounting - ER: 0 / 4-20 mA position feedback - SR: Positioner for input signal: 0 / 4-20 mA - Heating 5 watts 24 V - Electrical connection
Pná;14z1á;	
Pn:1201	
Mt5004/00/001	

153
Csc C 301 Type B
Type Ab5b30, No: 95803703
Ab18
4x1