

Seim

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Seim Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Seim Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Bvpa031/2g	Zolltarifnummer: 84136031
02004-0981 (MD032	
032 ARO 00 E07 E02	
0554072000 SERIAL: 12010130	
10757SP	
KPCXV	
KPDA	
KPE	
KPWQ	
KPPC	
P DAO 40	
P00328ar00800122000259643	
PA055	
PA072	
PA072	

PCX032	
PDA-029-2AL1-D05-D01-90	
PE032	
PFX040	
PW0025	
PW0025	
PW0025	
PW0032	
PW0055	
PX032	
PX040	
PX040	
PXC040	
PXC040	
PXC040	
PXC040	
PXC045	
PXC055	
PXF040	
PXF060	
PXF060	
PXF060	
PXF060	
PXF072	
PXF102	
PXF126	
PXFE083	
PXFE083	
PZ072	
VMPI	
PWOF032#6BRWF3WF400	Screw Pump - Series PWOF for hydraulic applications Housing: aluminum Spindles: steel nitrided Weight: approx. 15.00 kg
1213L/M 5BAR PPE-PEA083-23070	
SSP.3 / PXF040#4BR0A000C13X0200	Screw pump weight: 15.0 kg Housing material: EN-GJL-250 Mechanical seal: J.Crane axial suction side without integrated safety valve ◆◆◆ "C13" - improved mechanical seal
PXF083#3AR0A000C13X3200	Screw pump weight: 110.0 kg Housing material: EN-GJL-250 Mechanical seal: J.Crane axial suction side with chamfered spindle entry
	Screw pump weight: 180.0 kg inline design Body: EN-GJS-400 Spindle:

PZ102#3AC0Z15CV045Z3200	hardened steel
PW0055#6AR008W0400	Screw pump for coolant/lubricant Weight: approx. 67 kg Case: GG25 - hardened Spindles: steel - hardened with mechanical seal for dry installation
083-3-170-0000 0.164406.D	
PXF055#4CR0A0HUC13X0200	Screw spindle pump weight: 25.0 kg Housing material: EN-GJL-250 Mechanical seal: J.Crane axial suction side with integrated safety valve ◆◆◆ "C13" - improved mechanical seal ◆◆◆
PW0055#6AR008W0400	Screw spindle pump for coolant/lubricant Weight: approx. 67 kg Housing: GG25 - hardened Spindles: Steel - hardened with mechanical seal for dry installation
PA40AS	
PXF032#4BR0R000C13X0200	Screw spindle pump weight: 13.0 kg Housing material: EN-GJL-250 Mechanical seal: J.Crane T2100 radial suction side without integrated safety valve ◆◆◆ "C13" - improved mechanical seal ◆◆◆
PXF072#4CR0A0HUC13X3200	Screw spindle pump weight: 60.0 kg Housing material: EN-GJL-250 Mechanical seal: J.Crane T2100 axial suction side with integrated safety valve with chamfered spindle entry ◆◆◆ "C13" - improved mechanical seal ◆◆◆
Pz032ã3ar0z03cv063z0100	
Kupplung	
Px0055	
Pcxv102c-Com15 10-Rpo 36244010e	
Pcxa055c-Com017/17	
Satellite Spindle Pos.8 For Pcx060a	
E83314000	
E0554086s000á; Poz:15	
Pga072#4br0	
Vmp-042-Av-0400	
Px-060-4a-R0-R2-00-X01-X02-00 Pumpe	
Seim-32	
Pa055ã4a0ma01r019	
Svd 65x50 Scm4 200ad 455 C1-13028	
Pxf055	
Vmpi	
Pa072ã4b0ma10r000	
Pof032ã6brof3of100	
Pxf072ã4c R0a0hux01x0200	
Po040-6c	
Px040ã4ar0a0hbx18x3200	
Pe045#4a.R.0.Ha	

Kpx040 Ã 4a
Pz072ã3ar0z13cv051z0100
Pga0404ar0 (Ex.Pfga040ar000)
Kpxf
Kpeã04040e02e07r
Pe045ã4a.R.0.Ha
Px040ã4ar0a0hbx01x0200
0554072000 Serial: 12010130
Px055-4b-R0-R2-00-X01-X02-00 Pumpe
Px040ã4 - Obsolete
Vm100sca-C-Hw
Pxf032ã4br0a000x01x0200
Spider Insert For Pump Pe 032 Aro 00 E07 E02
Pa055 4c - Om
Px025
Pa072ã4b0ta01r000
Driving Spindle Pos.7 For Pcx060a
Pxf032
Vmp-030-B
Pea 072=3cr000e07e2900
Pa040
Pz102ãc3r0z01cv046z010
Repair Kit For Pump Pcx032ã4alx01cx000000
Pxf045
Pxf032ã4br0a0hux01x0200
Kpcx
Px83-3a-R0-R200-X01-X0-300 Pumpe
Px 040 Ã 4
Px060
Pe032ã4ar000e07e02e7
Pxf032ã4br0r0hax01x0200
Pxf055ã4ar0a0hux01x0200
Vms80sca-C
Pcx055
Pxf 060
Pu102ã3bru05u07000024r002500

Pda040ã2a00d05d0100
Pda0322b01d05d0100
P Dao 40ã2c01d05d0100
Pga072ã4br0
Pa 072 4-A
Pcxv102, Wie Unter Com15/10 Geliefert
Pz060-3f00p-Dn80
Pga045
Px045ã4br0r2hbx01x32
Pa 083 4-A
Px040ã4cr0r0hux01x0200