



Sensopart

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Sensopart Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Sensopart Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
740-21021 Ft 18-2 Rm-Ps-L4	Diffuse sensor, 400mm, metal housing, red light, PNP, metal connector M12 4-pin.
FT 50 RLH-PAL4	Laser photoelectric proximity switch with background suppression, SN 30-150 mm, PNP antiv., 2.5 kHz, IP67, connector M12 4-pin Net weight of the item: 0.043 KG Country of origin: DE Stat. Lot number: 85365019
L4-2m-G-PUR	Accessories, M12 connection cable, 2 m, straight PUR, 4 pole
MS F 50	Accessories, bracket, fastening set (Bracket and screws) for F50
UT 20-240-PSM4	Ultrasonic button PNP, 240 mm, connector M8 4-pin, teach-in
V10-OB-S1-W6	VISOR V10 object sensor, standard, max. 8 jobs with 32 detectors each, position tracking, 5 Detector types, focal length 6mm, white LEDs, 8 IO Channels, Ethernet, EtherNet / IP, Profinet Net weight of the item: 0.688 KG (per unit: 0.344 KG) Country of origin: DE Stat. Lot number: 85365019
FT 92 IL-PSL4	Laserdistanzsensor Reichweite 6 m, 1 x PNP -MSP F 90 Bracket Fx90 (V2A / 1.4301 -L4-2m-G-PUR Accessories, M12 connection cable, 2 m, straight PUR, 4 pole INCLUDED
	Reflective light scanner energetic, 800 mm, red light, LED,

FT 25-R-PNSL-M4	auto-detect, teach-in, connector M8 4-pin, IP 67 & IP 69, IO-Link
FR 25-R-PS-M4	606-11000 Reflection light barrier, 6m, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 606-11042 FR 25-R-PNSL-M4 This offers additional functions via IO-Link.
FT 25-RA-170-PSU-M4M	604-41002 Measuring range 30 ... 200mm, resolution 50µm red light, analog 1 ... 10 V, teach-in, PNP, N.O./N.C, metal plug M8x1, 4-pole For this product there is a new variant 604-41009 FT 25-RA-170- PNSUL-M4M This offers additional functions via IO-Link.
FT 25-RA-170-PNSUL-M4M	"Measuring range 30 ... 200mm, resolution 50µm Red light, analog 1 ... 10 V, teach-in, Auto-Detect, N.O./N.C, metal plug M8x1, 4-pin, IO-Link *****SUCCESSORS WITH IO-LINK
UT 20-700-AIM4	Ultrasonic sensor with analog output, Working range 120-700 mm, Scanning range limit 1000 mm, 4-20 mA, M8 connector, 4-pin, teach-in
FT 25-RLH-PS-M4	Diffuse reflection sensor with background suppression, 120mm, Laser, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 609-11015 FT 25-RLH-PNSL-M4 This offers additional functions via IO-Link.
FT 25-RLH-PNSL-M4	Diffuse reflection sensor with background suppression, 150 mm, laser, Automobile- Detect, teach-in, connector M8 4-pin, IP 67 & IP 69, IO-Link
MS F20	Fastening set for F 20, (Bracket and screws)
K4-2m-G-PUR	Connection cable M8 connection cable - 4-pin 2m - straight - PUR
FT 25-C1-GS-M4M	RGB color sensor, 12 +/- 3mm, 10 kHz, push-pull, Teach-in, metal connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 607-21040 FT 25-C1-GSL-M4M
FT 25-C1-GSL-M4M	RGB color sensor, 12 +/- 3mm, 10 kHz, push-pull, teach-in, Metal connector M8 4-pin, IP 67 & IP 69, IO-Link
V20-OB-A2-R12	VISOR V20 object sensor, Advanced, 255 jobs with 255 detectors each, position tracking, 6 detector types, Focal length 12mm, red LEDs, 10 IO channels, Encoder input, interface to IO-Box, RS422, RS232, Ethernet, EtherNet / IP, Profinet
FT 50 RLA-100-PL5	Distance sensor, 70 ... 170 mm, resolution 0.1% MBE 1 x PNP, N.C./N.O. 4 ... 20 mA, connector M12 5-pin
MS F 50	Accessories, bracket, fastening set (Bracket and screws) for F50
L5-2m-G-PUR	L5-2m-G-PUR, M12, F 5pol. 2000 Straight PUR Connection cable, 2m, M 12, straight, PUR, 5-pin f. F 40, Fx 92
	Laser photoelectric proximity switch with Background suppression, red light, Laser class 1, SN = 10..70mm, PNP,

FT 10-RLH-PS-KM4	1000Hz, IP67, molded plug (Pigtail) M8 4-pin, 200mm cable, Teach-in There is a new variant for this product: 600-11165 FT 10-RLH-PNSL-KM4 This offers additional functions via IO-Link
FT 10-RLH-PNSL-KM4 (Alternative)	FT 10-RLH-PNSL-KM4 180.50 EUR 1,805.00 EUR "Laser diffuse reflection sensor with Background suppression, red light, Laser class 1, SN = 10 # 70 mm, Auto-Detect, 1000 Hz, IP 67, Cable tail 200 mm with connector M8 4-pin, Teach-in, IO-Link "
MS F 10	Fastening set (bracket and screws) for F10
MFT 12 PP4	Mains and switching devices, SmartPlug, timer, PNP in / PNP out, plug M12x1 100ms, drop-out delay Net weight of the item: 0.026 KG Country of origin: DE Stat. Lot number: 85365019
30 RZ 12/1000-MSL LS	Fiber optic button Glass fibers for FMS sensors, light switches with metal helix, 100mm, radial Light emission, button
FR 25-RGO-PS-M4M	Reflective light barrier with autocollimation principle for Detection of transparent objects, 2m, red light, LED, PNP, Teach-in, metal plug M8 4-pin, IP67 & IP69K There is a new variant for this product: 606-11052 FR 25-RGO-PNSL-M4M This offers additional functions via IO-Link.
041-01303	
506-11000	
518-51505	
533-11037	
540-51622	
543-11023	
543-11043	
551-11000	
551-11010	
558-41000	
572-51008	
572-51062	
573-52007 FE 50 I-PAL4	
579-50010	
580-51406	
600-11002	
600-11003	

600-11036
604-41008
606-11012
606-11016
607-21010
607-21018 + 902-50805 + 558-41000
607-21025
608-11000
608-11019
608-11044
609-11005
609-11009
609-11017
609-31001
623-11000
623-11031
623-11038
631-91080
690-51541
690-51561
690-51562
706-11000
741-11014
742-51000
823-11010
832-11008
832-11010
832-11012
902-5080
902-51612

902-51799	
974-51281	
978-06547	
978-06548	
979-06242	
979-06274	
979-51628	
996-51467	
FE 20 R-PSM4	
FR 25-RL-PS-M4M	Reflection light barrier, 13m, laser, PNP, Teach-in, metal connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 609-31018 FR 25-RL-PNSL-M4M This offers additional functions via IO-Link.
FS 20 R-M4	
FT 55-RH-PS-L4	
FT 25-RH-PS-M3M	608-11012 Diffuse mode sensor with background suppression, 200mm, red light, LED, PNP, teach-in, metal connector M8 3-pin, IP67 & IP69K There is a new variant 608-11055 FT for this product 25-RH-PNSLM3M This offers additional functions via IO-Link
FT 25-RH-PNSL-M3M (alternative for pos1)	608-11055 Diffuse mode sensor with background suppression, 200mm, red light, LED, auto-detect, teach-in, metal connector M8 3-pin, IP67 & IP69K, IO-Link
FT 50 RH-PAL4	572-51004 Diffuse mode sensor with background suppression, SN 30-300 mm, PNP antiv., 1 kHz, IP67, connector M12 4-pin, F 50 Item net weight: 0.129KG (per unit: 0.043KG)
FSE 18-2 IM-PS-L4	One-way light barrier, 10m, S+E, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin Item net weight: 0.112KG
FT 18-2 IDM-PS-L4	Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin Item net weight: 0.825KG (per unit: 0.075KG) Country of Origin: TW Stat. Commodity number: 85365019
FT 25-RHD-PS-M4	Diffuse mode sensor with background suppression, 400mm, Red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant 608-11042 FT for this product 25-RHD-PNSLM4 This offers additional functions via IO-Link
FT 25-RHD-PNSL-M3M	Diffuse mode sensor with background suppression, 400mm, Red light, LED, auto-detect, teach-in, metal connector M8 3-pin, IP67 & IP69K, IO-Link

K4-2m-G-PUR	connection cable M8 connection cable - 4-pin 2m - Straight - PUR
MS F20	Fastening set for F 20, (brackets and screws)
FT 25-RH-PNSL-M4	Diffuse mode sensor with background suppression, 200mm, red light, LED, auto-detect, teach-in, connector M8 4-pin, IP67 & IP69K, IO link
979-06184 18/30 RZ 2/500-PVC LS=10	
FR 25-R-PNSL-M4M	606-11046
FR 25 RG0	
FT 50 RH-PAL4	572-51004 Diffuse mode sensor with background suppression, SN 30-300 mm, PNP antiv., 1 kHz, IP67, connector M12 4-pin, F 50
FT 50 RH-PAL4	Diffuse mode sensor with background suppression, SN 30-300 mm, PNP antiv., 1 kHz, IP67, connector M12 4-pin, F 50
MS F 50	579-50000 Accessories, bracket, fastening set (brackets and screws) for F50
L4-2m-G-PUR	902-50805 Accessory, M12 connection cable, 2 m, straight PUR, 4 pin
L5-2m-G-PUR	902-51652 L5-2m-G-PUR, M12,F 5pol. 2000 Straight PUR Connection cable, 2m, M 12, straight, PUR, 5-pin f. F 40, Fx 92
LL 18 R-24-L4	525-51156 Digital TTL control (trigger) up to 500 kHz Opening angle 45° Easy hand focusing M18 male thread for easy and versatile attachment LED power indicator M12 connector ensures optimal connection Electrically insulated housing
K4-2m-G-PUR	902-50801 connection cable M8 connection cable - 4-pin 2m - Straight - PUR
MS F20	558-41000 Fastening set for F 20, (brackets and screws)
FT 25-RLH-PNSL-M4	609-11015 Background suppression sensor, 150 mm, laser, Automobile- Detect, teach-in, 4-pin M8 connector, IP 67 & IP 69, IO-Link
FT 25-RH-PNSL-M4	"Reflection sensor with background suppression, 200mm, red light, LED, auto-detect, teach-in, connector M8 4-pin, IP67 & IP69K, IO link"
K4-2m-G-PUR	558-41000 connection cable M8 connection cable - 4-pin 2m - Straight - PUR
MS F20	902-50801 Fastening set for F 20, (brackets and screws)
FGL 30-RK-30-PS-M4	832-11002 fork light barrier, plastic, Fork width 30 mm, fork depth 34 mm, Red light, teach-in, 2000 Hz, PNP, Connector M8 4-pin

FGL 50-RK-50-PS-M4	832-11006 fork light barrier, plastic, Fork width 50 mm, fork depth 54 mm, Red light, teach-in, 2000 Hz, PNP, Connector M8 4-pin
Nr. 606-11043 - FR 25-R-PNSL-K4.	
IT 12 NBM-PSL4	996-51481 Inductive sensor made of stainless steel/ full metal with increased switching distance 10mm, M12 non-flush, PNP N.O., Connector M12 4-pin
MA 12	041-01305
L4-2m-G-PUR	902-50805 Accessory, M12 connection cable, 2 m, straight PUR, 4 pin
FT 18-2 IDM-PS-L4	Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin
FT 25-R-NS-M4M	607-21007 Diffuse mode sensor energetic, 800mm, red light, LED, NPN, teach-in, metal connector M8 4-pin, IP67 & IP69K
FMS 18-34 U	510-51587 Photo sensor Universal Light barrier for light guide adaptation, M18, Infrared, 1000Hz, PNP N.O./N.C., Cable Item net weight: 0.247KG Country of origin: DE Stat. Commodity number: 85365019
740-21029 Ft 18-2 Idm-Ps-L4	
MA 18	041-01304
FT 18-2 IDM-PS-L4	Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin Item net weight: 0.375KG (per unit: 0.075KG)
606-11012 FR 25-RF-PS-M4	Retro-reflective sensor, 3m, red light, LED, PNP, fixed setting, connector M8 4-pin, IP67 & IP69K
607-21000 FT 25-R-PS-M4	Diffuse mode sensor energetic, 800mm, red light, LED, PNP, teach-in, connector M8 4-pin, IP67 & IP69K There is a new variant for this product: 607-21027 FT 25-R-PNSL-M4
FT 18-2 IDM-PS-L4	740-21029 Reflex light barrier, 800mm, metal threaded sleeve, Infrared, PNP, metal connector M12 4-pin
FR 25 R PS M4	
FMS 30-35 U INFRARED 10	
30 RZ 12/1000-MCS	
30 RZ 12/1000-MSC LS=16	979-06318 30 RZ 12/1000-MSC LS=16 fiber optic button glass fibers for FMS sensors, light scanner with metal coil, 100mm, radial Light exit, button
ft 18-2 idmps-l4	
FT 10-RLH-PNSL-KM4	Laser diffuse reflection sensor with background suppression, red light, Laser class 1, SN = 10 # 70 mm, Auto-Detect, 1000 Hz, IP 67, Cable tail 200 mm with M8 4-pin connector, teach-

	in, IO-Link
FT 10-BF3-PS-KM3	2...50mm, blue light, HGA, fixed focus, PNP, cable tail 200mm with M8 3-pin connector
FSE 18-2 IM-PS-L4	Through-beam light barrier, 10m, S+E, metal threaded sleeve, infrared, PNP, Metal connector M12 4-pin
FMS 30-35 U	544-51323 Light barrier for fiber optic adaptation, infrared, 100Hz, PNP N.O., VMA, cable
30 RZ 12/1000-MSC LS=16	30 RZ 12/1000-MSC LS=16 fiber optic button glass fibers for FMS sensors, light scanner with metal coil, 100mm, radial Light exit, button
820-41001	
608-11004 Schalter Sensopart Ft 25-Rh-Ps-M4	
545-01000	IP68 OVERHOUSING, STAINLESS STEEL DOES NOT INCLUDE FA45
609-11005 Ft 25-RIh-Ps-M4	
Fgl5-Ik-50-Ps-K4	
Fr55-Rlap-70-2pnsi-L8	
Lb86rd-24-Kfl5	
580-51406, Fls 18-L4fls 18-L4	
532-51035	(LR 100 WD-24-KFL5) RINGLIGHT, DIFFUSE, 100 MM, WHITE
Mg3a	
574-41014	
580-51398, Fs 18 RI-L4fs 18 RI-L4	
552-11007, Fe 23 R-Ps-M4fe 23 R-Ps-M4	
609-11002	
580-51416, Fle 18 Wfle 18 W	
604-41003	
600-11012	
18/30r04/1000-Si	
P/N: 621-11004 Type: Fr 55-R-Ns-K4	
537-91011	
P/N: 535-91006 Type: V10-Ob-A1-I6	
697-01052	

697-01037	
Ft50rlhd-Nak4	
Ft90ila-S2-Q12	
Ft25-RIh-Ps-M3	
620-11002	
605-21013, Fe 25-R-Ns-M4mfe 25-R-Ns-M4m	
Fms18-34u-60	
591-91003	(FT 91 ILA-S2-Q12) DIFFUSE 0.5M-6M, 5MM RES., LASER, ANALOG, 2XPNP, 4-20MA / SERIAL, PLUG M16 12 PINS
996-50325	
Fr55-RI-Ns-K4	
Idt6-2b-Ps-K3	
536-91042	
Art.No. 608-11000, Type: Ft 25-Rhd-Ps-M4	
042-12825 / Ma 18 A	
Vision V10-A Model	
96905910 (Vk5575ube91970)	
978-08577	
18/30 Lz 1/500-Si Ls=10	
It12-8n-Ns-K3	
532-51071	
Llk1rm3pe-1m	
540-51319	
522-91088	EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, LIGHT VER., 6MM LENS, ETHERNET / RSXXX
552-11009, Fe 23 R-Ns-M4fe 23 R-Ns-M4	
041-01304	
525-51156, LI 18 R-24-L4II 18 R-24-L4	
Ut18-270-Ail4	
690-51541 Ultraschallsensor Um 18-60-250-Cd-Hp	

580-51408	
525-51137	
Lr56r-24-Kfl5	
750-11005	
620-21000, Fe 55-R-Ps-L4fe 55-R-Ps-L4	
690-51566	
18/30rz2/1000-Sils=10	
Ft10-Bf2-Ns-Km3	
532-51005	(LR 70 R-24-KFL5) RINGLIGHT, 70 MM, RED
606-11015	
K3-2m-G-Pur	
V10c-All-A2-W 25	
553-11013	
902-51664	
622-21007	
Fr20rlo-Psk4	
600-11132	
605-21014, Fe 25-RI-Ps-M4mfe 25-RI-Ps-M4m	
979-06254	
902-51794	
Fms30-34b	
V10c-Eye-A2-W 6	
996-50274	
V10-Cr-A1-R6	
Fms184u	
532-51034	(LR 70 WD-24-KFL5) RINGLIGHT, DIFFUSE, 70 MM, WHITE
543-11002	
Mspf50	
742-51004, Fse 18-2 Im-Ps-L4fse 18-2 Im-Ps-L4	

Lb625rk24a353I5	
978-06405	
Mft12pp4	
532-51009	(LR 132 WW-24-KFL5) RINGLIGHT, ANGLE, 132 MM, WHITE
Ft10-Bf2-Ns-K4	
Lr70rid-24-KfI5	
623-11007	
Ft10-Rf1-Ns-Km4	
902-51632	
552-11004, Fs 23 R-M4fs 23 R-M4	
996-09444	
Fs55-RI-L4	
Fm18500-4x	
532-51069	
551-11011	
690-51541 / Um18-60/250-Cd-Hp	
Llk2slr10pe-2m	
902-51792	
535-91022	
Llk2lv6pe-1m	
30Iz42000silS	
718-51400	
623-11022	
600-11146	
601-61005, Fs 10-RI-Km3fs 10-RI-Km3	
Fgl120-Ik-50-Ps-M3	
535-91073	(V10C-CO-A2-W6) V10 COLOR ADVANCED OBJECT SENSOR, 736X480, 6MM WHITE, RS422/RS232, ETHERNET/ETHERNET/IP
535-91104	
Fms200-01	

974-09617 Lichtleiter 30 Ql 0,2x10/1000-Si	
Lb44wd-24-Kf15	
551-11025	
979-06656	
978-08195	
Mbd-F-10	
Ft20-R-Psm4	
Ft10-Rf2-Ps-Km3	
604-41000	
978-06488	
Cusb-Rs485-0.7m	
927-81003	INFRARED, MEASURING FIELD 150MM, RANGE 2100MM, RESOLUTION 7 MM, 0-10 V
978-06453	
536-91011	
522-91095	EYESIGHT, VGA, WHITE LIGHT, CCD-COLOR, ADVANCED VER., 6MM LENS, ETHERNET / RSXXX
522-91080	EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, LIGHT VER., 6MM LENS, ETHERNET / RSXXX
527-51139	
Ft18-2id-Ps-K4	
526-51516, Lo C 25lo C 25	
522-91053	VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 12MM LENS, HIGH END, ETHERNET/RS422
979-08345	
Ft20rh-Psm4	
741-11015	
532-51004	
Fs 20 R-M4 / By Fs 25-R-M4m	
V10-Tcbox-101	
18/30I2/500-Msc	
Fms3024ul460	

996-51486	
Ft25-Rlh-Ps-M3m / 609-11007	
543-11010	
978-06382	
718-51403	
Fr25-Rlo2-Ps-K4	
It12bm-Psl4	
Ft 25-R-Ps-M4m	
902-51844	
571-50005	
693-11012	
902-51773	
580-51411, Fle 18-L4-15fle 18-L4-15	
Fgl80r-Psm3	
532-51014	
690-10102	
V10-Cr-A1-I25	
979-08342	
572-51004 Sensor Ft 50 Rh-Pal4	
518-51505 Optischer Sensorfmh 18-L4 , Reflexions-Lichttaster Mit Hga, M12- Stecker 4-Polig, Bis 120mm	
522-91084	EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, ADVANCED VER., 12MM LENS, ETHERNET / RSXXX
978-06428	
591-91008	
Cusb-Rs232	
978-06459	
978-06383	
574-41030	80 . 300MM, 0.215MM, LASER, ANALOG, 1 X NPN, NC/NO , 4 TO 20MA, PLUG M12 5 PINS
978-06412	

Imt18-8b-Ns-L4	
831-81000	(FG40 I-PSM3) 40 X 80MM, PNP N.O., PLUG M8 3 PINS
902-51610	
Ft-10-RIh-Ps-Km4	
551-11022	
591-91011	
696-51478	
Ft91-Ila-S2-Q12	(591-91003) DIFFUSE 0.5M-6M, 5MM RES., LASER, ANALOG, 2XPNP, 4-20MA / SERIAL, PLUG M16 12 PINS
579-50000	
522-91085	EYESIGHT, VGA, CCD-MONO, ADVANCED VER., C-MOUNT LENS, ETHERNET / RSXXX
R1	
Lms10-S22	
611-51002, Fs/Fe 10-RI-Ps-K4fs/Fe 10-RI-Ps-K4	
K4-2m-W-Pur	
611-51005, Fs/Fe 10-RI-Ns-Km4fs/Fe 10-RI-Ns-Km4	
600-11104	
Fr51rl-Pal4	
551-71000	
606-11000 Fr 25 R-Ps-M4	
532-51021	
Fr91ila-S2-Q12	
607-21011	
917-16000	
532-51030	(LR 70 WID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 70 MM, WHITE
532-51015	(LR 130 WI-24-KFL5) RINGLIGHT, INDIRECT, 130 MM, WHITE
Fr 23 R-Psm4	
558-41001	
996-09972	

97908045 (R1/500pvc)	
Lb1000irk24a353l5	
532-51018	(LF 36 WD-24-KFL5) AREALIGHT, DIFFUSE, 36 MM, WHITE
Fs25-R-M4m	
522-91128	VGA, CCD-MONO, CODEREADER, C-CS MOUNT LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422
605-21017, Fe 25-Rf-Ns-M4fe 25-Rf-Ns-M4	
611-51006, Fs/Fe 10-RI-Ps-Km3fs/Fe 10-RI-Ps-Km3	
979-08337	
526-51531, Lof-Pf-30,5x0,5lof-Pf-30,5x0,5	
Ft25-W1-Gs-M4m	
572-51062 Sensor Ft 50 RIhd-Pal4	
601-61004, Fs 10-RI-Km4fs 10-RI-Km4	
978-08551	
572-51051	
573-52002, Fs 50 I-K4fs 50 I-K4	
572-51011	
It8-1b5-Ps-K3	
Cl12fg-S-5m-Pur	
741-11022	
996-09973	
978-06437	
978-06364	
902-50690	
Fs10-RI-Km4	
Ft10-RIhr-Ps-Km4	
978-51649 / 18/30 Lzx 1/400-260 Si Ls=11	
742-51000 Sensopart Fse 18-1 I-Ps-L4einweglichtschranke, M18,Sn=8000	

Mm, Pnp, Stecker M12-4pol	
CI8-Fg-S-10m-Pur	
543-11011	
532-51037	(LR 100 RD-24-KFL5) RINGLIGHT, DIFFUSE, 100 MM, RED
573-52005, Fe 50 I-Psvk4fe 50 I-Psvk4	
536-91026	
607-21010 Ft 25-Rgb1-Gs-KI4	
Ci L4mg/Rj45g-Gs-5m-Pur	
Lr50ww-24-Kfl5	
904-51564	
609-21003	
Fr25-Rgo-Ns-M4	
Is46-12	
525-51150	
Fe25-R-Ns-K4	
575-11000	
832-11009	
620-11000, Fs 55-R-L4fs 55-R-L4	
535-91027	
Fr25-R-Ps-K4	
Fr 25-R-Ps-M4	Reflection light barrier, 6m, red light, LED, PNP, teach-in, M8 4-pin connector, IP67 & IP69K There is a new version for this product: 606-11042 FR 25-R-PNSL-M4 This offers additional functions via IO-Link. Product information can be found at www.sensopart.de Net weight of the item: 0.022 KG Country of origin: DE Stat. Product number: 85365019I
978-06527	
Lf100ard-24-Kfl5	
591-91000	(FT 90 ILA-S2-Q12) DIFFUSE 0.5M-12M, 4MM RES., LASER, ANALOG, 2XPNP, 4-20MA / SERIAL, PLUG M16 12 PINS
979-06185	
532-51020	(LF 100 WD-24-KFL5) AREALIGHT, DIFFUSE, 100 MM, WHITE
620-11003, Fs 55-RI-K4fs 55-RI-K4	
526-51514	

697-01058	
902-51735	CONVERTER, RS422 / PROFIBUS
V10-Ob-A1-I12	
18/30lz3/1500-Pvcls=14	
Fe55-RI-Ns-L4	
681-50956	
602-71005, Fe 10-RI-Ns-Km4fe 10-RI-Ns-Km4	
510-51589	
996-50641	
Cl12/3fw-S-20m-Pur	
620-21003, Fe 55-R-Ps-K4fe 55-R-Ps-K4	
Imt30-15n-Ns-K3	
Ut 20-150-Aim4	
580-51410, Fle 18-L4fle 18-L4	
K4-2m-G-Pur (902-50801)	cable M8 connection cable - 4-pin 2m - straight - PUR Net weight of item: 0.280 KG (per unit: 0.070 KG) Country of origin: CZ Stat. Product number: 85444290
527-51136, Lpt S5lpt S5	
927-81001	INFRARED, MEASURING FIELD 100MM, RANGE 2100MM, RESOLUTION 7 MM, 0-10 V
621-11026	
Ft25-R-Ps-Km4	
690-51567	
V20-Eye-A2-W12	
Ft10-B-RIf2-Ns-K4	
540-51605, Fms 30-34 U-54fms 30-34 U-54	
Lpt45cml5l	
Fr25-Rgo-Ps-M4	
Kd12b-Psl4	
532-51008	(LR 90 WW-24-KFL5) RINGLIGHT, ANGLE, 90 MM, WHITE
Ft18-2 Rwmpsl4	

623-11006	
18/30r15/500-Si	
620-11002, Fs 55-RI-L4fs 55-RI-L4	
99609905	
979-08051	
580-51406 Fls 18-L4 Laser- Einweglichtschranke, M12,Sender, Stecker M 12 4-Pol	
608-11039	
30rz4/250-Sils=16	
979-06184	
567-71003	
V10c-Eye-A2-W 12	
522-91055	VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 6MM LENS, HIGH END, ETHERN./RS422
697-01006	
18/30lz1/750-Sils=10	
571-50004	
8340f410p1f7a2h142-2a	
Ft50-C-1-Ps1-L8	
Fr25-Rgo2-Ns-K4	
720-50766	
688-51090	
532-51012	(LR 90 RW-24-KFL5) RINGLIGHT, ANGLE, 90 MM, RED
R5 (Refl.51x61),Standard	Accessories, reflector 51 x 61mm; 2 mounting holes
609-11005 Schalter Sensopart Ft 25-RIh- Ps-M4	
740-21016	
604-41002	
903-05142	
902-51736	
FMS 30-35 U	544-51323 Light barrier for light guide adaptation, Infrared, 100Hz, PNP N.O., VMA, Kab

RI250
Ft55-Rh-Ps-L4
Ft50rla-100-PI5
606-11016 Optischer Sensorfr 25-Rgo-Ps-M4m
535-91050
Ft10-B-RI1-Ps-Km4
K4-10m-G-Pur
996-09397
Aerp 150 B90 Ae 2,5mt
P/N: 551-11010 Type: Ft 20 Ih-Psm4
1830rx21000si X
V10-Cr-A1-W12
Fe10-RI-Ps-K4
Fle18w-L4-15
697-01005
571-50001
979-08415
Art.No. 575-11000, Type: Ft 50 C-1-PsI8
558-41006
902-51835
535-91041
Ft55b-Rh-Ps-L4
904-51533
V10-All-A2-R25
535-91096
611-51001, Fs/Fe 10-RI-Ns-E4fs/Fe 10-RI-Ns-E4
038-12401
902-50683
532-51007
(LR 74 WW-24-KFL5) RINGLIGHT, ANGLE, 74 MM, WHITE

605-21004, Fe 25-RI-Ns-K4fe 25-RI-Ns-K4	
Fr18-2iw-Ps-L4	
902-50808	
979-50544	
Ft50rlh-Nak4	
840-11002	
580-51415, Fle 18 W-L4-15fle 18 W-L4-15	
605-21012, Fe 25-R-Ps-M4mfe 25-R-Ps-M4m	
V20-So-A2-C	
P/N: 830-11007 Type: Fgl 180 R-Psm3	
605-11002, Fs 25-RI-K4fs 25-RI-K4	
927-81001 , Type Fcp 100-I7-2100-Psu-L	
Ft10-Rh-Ns-E4	
Ft88r-Ga-L4	
904-51565	
602-71003, Fe 10-RI-Ns-K4fe 10-RI-Ns-K4	
927-81000	INFRARED, MEASURING FIELD 100MM, RANGE 2100MM, RESOLUTION 5 MM, 0-10 V
979-51457	
Mbst2	
902-51813	
580-51400	
609-31010	
540-51622 Fm 30-800-3 X Sp-L4-X01 (Ndt)fotosensor Mit L4-Stecker	
L4-10m-G-Pur	
750-11004	
579-50010 Ms F 55 Befestigungswinkel	

Set (L-Form, V2a/1.4301)	
996-51481	
Ft20r-Nsm3	
918-10001	
Mfc12pp4	
Fe25-RI-Ns-M4m	
97951295	
553-11000	
902-51716	
30I4/500-Si	
532-51011	(LR 74 RW-24-KFL5) RINGLIGHT, ANGLE, 74 MM, RED
Aerp 150 B90	
978-06439	
532-51036	(LR 70 RD-24-KFL5) RINGLIGHT, DIFFUSE, 70 MM, RED
693-11007	
600-11030	
Kd08b-Pom3	
535-91023	
97806798 (L12/500msc)	
KI06nb-Nom3	
978-06949	
996-09394	
608-11004	
978-06797	
902-51688	
18/30r31000s1	
V10-AII-A2-I12	
750-11001	
902-51641	
522-91067	VGA, RED LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END, ETHERN./RS422

Fr 20 Rlo-Psm4	
V10-Ob-A1-W6	
R3-2Ik1	
979-08081	
605-11001, Fs 25-R-K4fs 25-R-K4	
553-51004	
605-21017	
K3-5m-G-Pur	
97908050	
18/30r1/500si	
Fe10-RI-Ns-Km4	
522-91083	EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, ADVANCED VER., 6MM LENS, ETHERNET / RSXXX
53051589 (Fms30-44ug-60)	
527-51135	
904-51588	
18/30r2/500-Si	
604-41010	
979-08049	
741-11011	
Fr 20 RI -Psm 4 Sensor	
Fr 25-RI-Ps-M4m	Reflection light barrier, 13m, laser, PNP, Teach-in, metal connector M8 4-pin, IP67 & IP69K There is a new version for this product: 609-31018 FR 25-RL-PNSL-M4M This offers additional functions via IO-Link. Product information can be found at www.sensopart.de Net weight of the item: 0.050 KG (per unit: 0.025 KG) Country of origin: DE Stat. Product number: 85365019
Fms18-34u	
Art.No. 968-11000, Type Mft 12 Pp4	
522-91097	EYESIGHT, VGA, CCD-COLOR, ADVANCED VER., C-MOUNT LENS, ETHERNET / RSXXX
697-01047	
K2ade	

609-31013	
537-91015	
567-71001	
K4-5m-W-Pur	
904-51543	
602-71002, Fe 10-RI-Ps-K4fe 10-RI-Ps-K4	
532-51013	(LR 132 RW-24-KFL5) RINGLIGHT, ANGLE, 132 MM, RED
544-51323	
Ut20-240-Nsm4	
Fms30-34ut	
042-12820	
571-50009	
Lms13-S22	
697-01010	
Fs/Fe10-RI-Ns-E4	
Fse18-2im-Ps-L4	
Rf775x500mm	
902-51654	
902-51797	
623-11012	
821-11013	
Ft12r-Psk3	
Lb1000rk24a353I5	
551-21018	
Ft92ila-PsI5	
904-51590	
609-21004	
994-51132	
Ma45I	
18/30I1/750-Si	

902-51604	
580-51446	
551-11023	
575-11016	
532-51076	
K3-10m-G-Pur	
591-91001	(FR 90 ILA-S2-Q12) RETRO 0.5M-250M, 2MM RES., LASER, ANALOG, 2XPNP, SSI / SERIAL, PLUG M16 12 PINS
522-91052	VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 6MM LENS, HIGH END, ETHERNET/RS422
Fr20rl-Nsk4	
720-50767	
Ft55-RI2h-Ps-L4	
526-51515, Lo C 16lo C 16	
FI20r-Psm3	
522-91093	EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, ADVANCED VER., 6MM LENS, ETHERNET / RSXXX
681-50917	
Fgl30-Ik-30-Ns-M4	
30rz12/1000-Sils= 16	
Ft25-RIh-Ps-KI4	
902-50805	
600-11010	
Ft20rh-Psm3	
536-91012	
Imt8-2b-Ps-M3	
903-50314	
555-31000	
532-51024	(LF 200 WD-24-KFL5) AREALIGHT, DIFFUSE, 200 MM, WHITE
FI70ra-Nsd-K5	
543-11030, Lr 0,5lr 0,5	
Mfw12nn4	

741-11008	
832-11024	
533-01027, Pv-Aw1010.4tx_Depv-Aw1010.4tx_De	
Soda Caustica	
904-51532	
Fms-30-44ul-4-60	
974-09617	
602-71008, Fe 10-RI-Ns-Km3fe 10-RI-Ns-Km3	
Ft25-Rhd-Ns-M4	
681-50942	
543-11021	
522-91065	VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END, ETHERN./RS422
Is518-02	
690-51542	
18/30 Lz 1/1000-Si Ls=10	
Vk-5575u-05	
623-11035	
Ft25-RI-Ps-Km4	
532-51017	(LR 130 RI-24-KFL5) RINGLIGHT, INDIRECT, 130 MM, RED
Fr55-R-Ps-L4	
Ms F 20	558-41000 Fastening set for F 20 , (Bracket and screws)
996-51449	
Fms30-44ug-56	
Fr20rg-Nsm3	
FI70r-Ns-K4	
902-51694	
571-50006	
742-51007, Fse 18-2 Im-Ns-K4fse 18-2 Im-Ns-K4	

532-51078, Lb 1000 Irk 24 A35 3I5Ib	
1000 Irk 24 A35 3I5	
951-50008	
951-50001	
Fr-18-1 I-PsI4	
978-06545	
V20c-Eye-A2-C	
Is48-12t	
V10-Cr-S2-I25	
830-11005	
693-11006	
Ft20rl-Psk4	
526-51353, Ex2cex2c	
823-11010 Lichtschranke Fr 88-R-Pav-L5	
Llk1rvv6pe-1m	
902-51657	
Ft10-Rf3-Ps-Km3	
30Iz4/500-Mscls=16	
978-06543	
Cil8mgk/L4mgk-S-02m-Pvc	
528-51106	LINE SENSOR, ANALOGUE OUTPUT 4 . 20MA
952-50001	
580-51408, Fls 18 W-L4fls 18 W-L4	
978-08215	
697-01033	
609-11012	
Imt30-15n-Ps-L4	
K3-10m-W-PI-Pur	
18/30r3/500-Si	
18/30rz1/500-Mscls=10	
978-06406	

621-11023	
742-51005, Fse 18-2 Im-Ns-L4fse 18-2 Im-Ns-L4	
Rd4	
527-51139, Lpf S1lpf S1	
551-11003	
Cl12/3fg-S-5m-Pur	
30I4/2000-Msc	
532-51059	
Fr20r-Nsm3	
Art.No.740-21029 Ft 18-2 Idm-Ps-L4	
681-50957	
525-51126	LUMINARY, USABLE AEREA 420MM, IP 67
600-11103	
532-51025	(LF 200 RD-24-KFL5) AREALIGHT, DIFFUSE, 200 MM, RED
978-08236	
Ft 25-Rh-Ps-M4m (608-11014)	Diffuse reflection sensor with background suppression, 200 mm, red light, LED, PNP, metal plug M8, 4-pin, IP67 & IP69K For this product there is a new variant 608-11053 FT 25-RH PNSLM4M This offers additional functions via IO-Link. Further Product information can be found at www.sensopart.de Net weight of item: 0.084 KG (per unit: 0.021 KG) Country of origin: DE Stat. Product number: 85365019
R50bc	
Is-530-04-S	
Ft 20 R-Psm4	
Fr10-RI-Ns-K4	
K4-2m-G-Pur	902-50801 Connection cable, M8 connection cable - 4-pin 2m - straight - PUR
591-91012	
580-51405, Fe 12 RI-NsI4fe 12 RI-NsI4	
532-51006	
Mg 2 A	
580-51407, Fls 18fls 18	
Ft18-2id-Ps-L4	

902-51840
18/30I3/750-Msc
978-06478
902-51681
600-11134
041-01304 Ma 18 (Montagewinkel Fm 18)
572-51004
608-11034
Is34-52
Ft12 R-Psl4
580-51412, Fle 18fle 18
Fmsa668232
690-51167
611-51003, Fs/Fe 10-RI-Ns-K4fs/Fe 10-RI-Ns-K4
Fr18-2rm-Ns-L4
Ut18-270-Psl4
Fe25-RI-Ns-K4
18/30rz3/250sils=14
Fr25-RI-Ps-M3m
681-50955
552-11007
697-01036
Ft10-RIhr-Ns-Km3
832-11018
902-50801 K4-2m-G-Pur(M8-Kabel F 4p2000 Gerade Pu
979-06274 Fiber Optic Cable18/30 Rz 2/500-Pvc-2v2a
609-21012
620-21000

605-11006, Fs 25-R-M4mfs 25-R-M4m	
Ft 25-Rlh-Ps-M4	
Ft10-Rf1-Ns-Km3	
Fr50rl-Psvk4	
V10-Ob-A1-I6	
608-11000 Ft 25-Rhd-Ps-M4	
Fe50i-Pal4	
525-51143	
Lf36wd-24-KfI5	
821-11013 Lichtschränke Ft 88-Ih-Pa-L5	
Ms F 20 (Fixing Set F 20	Fixing set for F 20, (Bracket and screws)
978-06407	
902-51817	
533-01010, Lof-Lp-Ir850-30,5x0,5lof-Lp-Ir850-30,5x0,5	
821-11010	
Imt8-2n-Ps-K3	
750-11006	
Ut20-150-Aum4	
902-51830	
Ft55-Rh-Ps-K4	
978-06653	
978-51688	
Fs10-RI-K4	
97908058	
574-41032	
608-11004 Ft25-Rh-Ps-M4	
620-21001, Fe 55-R-Ns-L4fe 55-R-Ns-L4	
99509516	
996-09399	
Fr25-RI-Ps-K4	

571-50003	
Fr20-R-Psm4	
551-21007	
697-01019	
R5-8/L	
Mft12pp4t:...	
Lvlf6-M3	
902-51715	
741-11025	
526-51519, Lot-Tec-M55lot-Tec-M55	
979-06147	
611-51006	
Ft50c-1-Psl8	
580-51409, Fls 18 Wfls 18 W	
30rz4/1000-MscIs=16	
522-91126	VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422
979-06647	
904-51641	
Ft25-Rh-Ns-M3m	
535-91102	
18/30-R-3/250-Si	
555-31006	
Llk2lz	
Ut12-370-Ail4	
Ut	
Is48-01	
601-61002, Fs 10-RI-K4fs 10-RI-K4	
830-11010	
Ft18-2rw-Ns-K4	
Fse18-2im-Ps-K4	

607-21025 Sensorft 25-Rgb1-Gs-M4m-X07	
522-91054	VGA, CCD-MONO, OBJECT DETECTION, C-CS MOUNT LENS, HIGH END, ETHERNET/RS422
573-52004, Fe 50 I-Psvl4fe 50 I-Psvl4	
Imt18-8b-Ns-K3	
979-08414	
742-51006, Fse 18-2 Im-Ps-K4fse 18-2 Im-Ps-K4	
522-91129	VGA, RED LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422
Fl70ra-Psd-K5	
Ms F20 (558-41000)	(Bracket and screws) Net weight of item: 0.052 KG (per unit: 0.013 KG) Country of origin: DE Stat. Lot number: 76041090
605-21016, Fe 25-Rf-Ps-M4fe 25-Rf-Ps-M4	
832-11019	
602-71006	
832-11000	
600-11105	
Is34-51	
697-01038	
Fms30/34-U	
522-91089	EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, LIGHT VER., 12MM LENS, ETHERNET / RSXXX
740-21034	
Ft55-Bh-Ns-L4	
33lvl22w	
Rf-50kl	
623-11000 Sensopart Ft55-Rh-Ps-L4	
553-11010	
575-11014	
902-51821	
974-09617 30 Ql 0,2x10/1000 Si,	

Querschnittswandler, 1000mm, Silikon, 10mm Lichtaustritt 605-21001	
979-06320	
903-05142 / Mb 10 (Z-Halterung)	
611-51004, Fs/Fe 10-RI-Ps-Km4fs/Fe 10- RI-Ps-Km4	
Cil4fgk/L8fgk-S-02m-Pvc	
Is58-13s	
Fav 30-01	
551-11005	
522-91035	VGA, WHITELIGHT, CCD-COLOR, COLOR, 12MM LENS, HIGH END, ETHERNET/RS422
Ft10-B-RIf2-Ps-Km3	
Mft12nn4t:...	
553-11000 Sensor Fr 20 Rpsm4	
Ft88rh-Pa-L5	
740-21026	
552-21000	
623-11014	
P/N: 742-51004 Type: Fse 18-2 Im-Ps- L4	
606-11030	
30rx2/310-Si	
522-91081	EYESIGHT, VGA, WHITE LIGHT, CCD-MONO, LIGHT VER., 12MM LENS, ETHERNET / RSXXX
605-21003, Fe 25-R-Ns-K4fe 25-R-Ns-K4	
Lr132rw-24-KfI5	
Fr20rg1-Nsm4	
V20-Ob-A2-C	
996-09421	
Sal-12-Rk12-5/A3 Conec	
Fr50rl-Nsvk4	

572-51002	
P/N: 606-11000 Type: Fr 25-R-Ps-M4	
Ft25-Rvd-Pns-M4m	
Ft50ih-Pak4	
690-51569	
522-91056	VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 12MM LENS, HIGH END, ETHERN./RS422
567-71002	
Fe 20 R-Psm4 / By Fe 25-R-Ps-M4m	
605-21015, Fe 25-RI-Ns-M4mfe 25-RI-Ns-M4m	
Lr130wi-24-KfI5	
18/30r3/750-Msc	
606-11023	
522-91058	VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 6 MM LENS, LIGHT, ETHERNET
Umt30-6000-2psd-L5	
Ft10-RIh-Ps-K4	
690-51164	
580-51417	
608-11040	
532-51077, Lb 625 Irk 24 A35 3I5Ib 625 Irk 24 A35 3I5	
Is56-11t	
Is530-44-S	
Ft25-Bf2-Ns-K4	
572-51029	
591-91000 Ft 90 Ila-S2-Q12	
Is530-41	
Fr10-RI-Ps-E4	
740-21022	
L8f-10m-W-Pur	

978-08231	
902-51695	
904-51644	
902-51831	
Ut20-240-Aum4	
996-09396	
V20-All-A2-R12	
831-81002	(FG 120 I-PSM3) 120 X 80MM, PNP N.O., PLUG M8 3 PINS
532-51019	(LF 51 WD-24-KFL5) AREALIGHT, DIFFUSE,51 MM, WHITE
C L12fg-S-5m-Pur	
Imt18-8b-Ps-L4	
602-71006, Fe 10-RI-Ps-Km3fe 10-RI-Ps-Km3	
Cl12/3fw-S-5m-Pur	
580-51413	
Imt18-5b-Ns-L4	
97908491	
18/30rz2/250sils=10	
750-11002	
Ft50rh-Nal4	
Ft10-RIh-Ps-Km3-X07	
903-05141	
978-08234	
522-91082	EYESIGHT, VGA, CCD-MONO, LIGHT VER., C-MOUNT LENS, ETHERNET / RSXXX
Fms30-44ul-4-60	
Ft50rh-Psvl4	
951-50009	
978-06426	
Fr25-RI-Ns-Km4	
621-11001	
979-06199	

902-50679	
532-51038	(LD 50 WD-24-KFL5) RINGLIGHT, DOME, DIFFUSE, 50 MM, WHITE
527-51140, Lpf S2lpf S2	
607-21004	
575-11018	
527-51134, Lpt 45 Cml 5llpt 45 Cml 5l	
Lb180rd-24-Kfl5	
978-06420	
Ft55-R-Ps-L4	
979-06196	
606-11005	
522-91127	VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422
Q12-3m-W-Pvc	
048-12932	
Fs25-RI-M4m	
Sg12t-02	
527-51138, Lpt 45llpt 45l	
527-51143, Etsets	
R100bc	
P/N: 536-91012 Type: V20-Ob-A2-R12	
660-01000	
532-51032	(LR 70 RID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 70 MM, RED
Fgl30-Rk-30-Ns-M4	
543-11031, Lr 1lr 1	
Mbd-S94	
904-51570	(RL700) REFLECTOR
Fa-46-305-Wcc-Obo12es6	VISION SENSOR AND LEADS WHITE LIGHT GUI 2
FT 50 RLA 220 PL5	574-41029 Distance sensor, 80...300mm, resolution 0.1% MBE, 1 x PNP, N.C./N.O. 4...20 mA, plug M12 5-pin

573-52007, Fe 50 I-Pal4fe 50 I-Pal4	
620-11001, Fs 55-R-K4fs 55-R-K4	
591-91009	
V10-All-A2-R12	
Fe10-RI-Ps-Km3	
Lb180wd-24-Kfl5	
Sal-45s-S8.36-12d-Rs4.2-5/Gaf/025	
18/30rz1/1000-MscIs=10	
742-51004	
532-51039	(LD 50 RD-24-KFL5) RINGLIGHT, DOME, DIFFUSE, 50 MM, RED
Ft50rlh-Psvk4	
33l1/500msc	
Imt8-2n-Ns-K3	
978-08549	
902-51652	
608-11015	
528-51105	LINE SENSOR, ANALOGUE OUTPUT 0 . 10 V
904-51562	
978-06370	
Ft-10-B-RIf2-Ps-Km4	
574-41034	
Fr25-R-Ps-M3m	
580-51440, Fle 18wm-L4-X01fle 18wm-L4-X01	
522-91062	VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 12MM LENS, LIGHT, ETHERNET
522-91094	EYESIGHT, VGA, RED LIGHT, RED NOTCH FILTER, CCD-MONO, ADVANCED VER., 12MM LENS, ETHERNET / RSXXX
Ft20r-Nsm4	
605-11008, Fs 25-Rf-M4fs 25-Rf-M4	
Mspf20-11	
697-01045	

522-91034	VGA, WHITELIGHT, CCD-COLOR, COLOR, 6MM LENS, HIGH END, ETHERNET/RS422
Imt30-15b-Ns-K3	
V10-Cr-A1-C	
Ft50-RIh-PaI4	
681-50945	
Fr-25-RI-Ns-M4m	
V20-Ob-A2-W12	
904-51585	
Ft50 RIa-40sl4s* 574-41003	
Ft50ria-70-L8	
K2r-25	
740-21030	
580-51399, Fe 18 RI-Ns-L4fe 18 RI-Ns-L4	
543-11032, Lr 10lr 10	
742-51006	
522-91036	VGA, CCD-COLOR, COLOR, C-CS MOUNT LENS, HIGH END, ETHERNET/RS422
551-21001	
Fs10-RI-Km3	
510-51590 Fms 18-34 UI4-60m18infrarot, 5000hz, Pnp/Npn N.O., Stecker M12 4-Poliglichtleitersensoren	
974-51281 30 Qlx 1,0x15/750-Si, X = 12.01.06	
555-31007	
Ms-F-10	
979-08063	
535-91094	
551-21004	
608-11030	
522-91130	VGA, RED LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END., QUALITY PARAMETERS, ETHERN./RS422

555-31004	
602-71008	
Is-512-44-S	
705-21001	
978-08202	
601-61000, Fs 10-RI-E4fs 10-RI-E4	
Ft 55-RI2h-Ps-L4 Sensor	Laser reflection light scanner with background suppression, Red light, PNP, IP67, connector M12, laser class 1 Item net weight: 0.171 KG (per unit: 0.057 KG) Country of origin: DE Stat. Product number: 85365019
580-51401, Fs 12 RI-L4fs 12 RI-L4	
996-51454	
P/N: 605-11006 Type: Fs 25-R-M4m	
Ft10-Rf3-Ns-Km4	
622-21009	
704-21001	
978-06379	
Lpfs2	
P/N: 571-50009 Type: Fr 50 RI-Pa14	
536-91005	
978-06444	
573-52003, Fe 50 I-Pak4fe 50 I-Pak4	
572-51026	
681-50895	
580-51414, Fle 18 W-L4fle 18 W-L4	
532-51023	(LF 100 RD-24-KFL5) AREALIGHT, DIFFUSE, 100 MM, RED
L8fs-2m-G-Pur	
580-51446, Fls 18wm-L4-X02fls 18wm-L4-X02	
Is56-12	
602-71001, Fe 10-RI-Ns-E4fe 10-RI-Ns-E4	
606-11009	

P/N: 540-51321 Type: Fms 30-34-Un	
522-91059	VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, 12 MM LENS, LIGHT, ETHERNET
978-06462	
978-08239	
Ft-160-Rh-Pal4	
Art.No. 571-50009 [fr 50 RI-Pal4]	
Ld50wd-24-Kfl5	
Ft12rf-Psl4	
525-51144	
968-21000	
Fl70r-Ns-M4	
Fls18	
Is518-03	
535-91089	
510-51587 (Fms1834u)	
536-91001	
Ft 18-2-Rwmps-L4 740-21025	
741-11006	
527-51137, Lpt 45lpt 45	
18/30rz2/250mscls=14	
V20-Eye-A2-C	
580-51402, Fe 12 RI-Psl4fe 12 RI-Psl4	
99609429	
P/N: 605-21012 Type: Fe 25-R-Ps-M4m	
18/30r15/1000-Si	
Fr18-2iw-Ps-K4	
Fe88r-Nav-L5	
979-06236	
P/N: 572-51008 Type: Ft 50 RIh-Pal4	

607-21012	
571-50012	
571-50033	
607-21005	
902-51624	
580-51447, Fle 18wm-L4-X02fle 18wm-L4-X02	
740-21025	
Fr88r-Pav-L5	
518-51505 Sensopart Fmh 18-L4 , Reflexions-Lichtttaster Mit Hga, M12-Stecker 4-Polig, Bis 120mm	
962-50577	
Ft 18-2 Rm-Ps-L4	
510-51590	
Ft50rlh-NaI4	
Fls18wm-L4-X02	
978-06402	
Ft18-2rwm-Ps-L4	
621-11010	
522-91096	EYESIGHT, VGA, WHITE LIGHT, CCD-COLOR, ADVANCED VER., 12MM LENS, ETHERNET / RSXXX
97808207	
978-06550	
Idt4-0b8-Ps-K3	
996-09428	
605-11007, Fs 25-RI-M4mfs 25-RI-M4m	
697-01030	
996-09438	
979-06162	
Fr10-RI-Ns-Km3	
522-91061	VGA, RED LIGHT, CCD-MONO, OBJECT DETECTION, 6MM LENS, LIGHT, ETHERNET

575-11009	
18/30rz3/2000-MscIs=10	
917-16003	
543-11015	
42-10034	
718-51404	
Ft55-R-Ns-L4	
Lf51wd-24-KfI5	
605-21007, Fe 25-RI-Ps-K4fe 25-RI-Ps-K4	
978-06404	
18/30r1/500-Si	
97908062	
693-11004	
30r12/2000-Si	
543-11033, Lr 20lr 20	
Ft25-C1-Gs-M4m	
532-51022	(LF 51 RD-24-KFL5) AREALIGHT, DIFFUSE, 51 MM, RED
974-09623	
526-51513, Lo C 8lo C 8	
620-21004, Fe 55-R-Ns-K4fe 55-R-Ns-K4	
Ft10-B-RIh2-Ns-E4	
P/N: 623-11006 Type: Ft 55-RIh2-Ps-L4	
620-21006, Fe 55-RI-Ps-L4fe 55-RI-Ps-L4	
Fr23r-Ps-M4	
606-11032	
978-06440	
527-51132, Lpt 45 Cml 5lpt 45 Cml 5	
V20-AII-P2-W12	
927-81004	INFRARED, MEASURING FIELD 300MM, RANGE 2100MM, RESOLUTION 7 MM, 0-10 V

30I12/2000-Msc	
Fms3024ug60	
741-11005	
903-50313	
Ft20rh-Psk4	
Idt6-2b-Ns-M3	
Ft 25-Rhd-Ps-M4m (608-11016)	Diffuse reflection sensor with background suppression, 400mm, Red light, LED, PNP, teach-in, metal connector M8 4-pole, IP67 & IP69K For this product there is a new variant 608-11044 FT 25-RHD PNSLM4M
978-08567	
Loc50	
21000pvcIrl	
532-51031	(LR 100 WID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 100 MM, WHITE
741-11024	
608-11008	
V10-Ob-A1-R6	
Fgl120-Rk-50-Ps-M3	
525-51127	
Ft25-Ra-60-Nsu-M4m	
543-11011, Lr 5lr 5	
525-51152	
740-21033	
Fr23r-Psk4	
Ft92il-Ps-KI4	
902-51843	
Ft12rh-Psl4	
522-91064	VGA, WHITE LIGHT, CCD-MONO, CODEREADER, 6MM LENS, HIGH END, ETHERN./RS422
902-50693	
533-01028, Pv-Aw1010.4tx_Enpv-Aw1010.4tx_En	
Fr12r-Psl4	

18/30lz2/2000-MscIs=14
979-06655
968-11009
18/30rz3/500-Pvcls=14
703-11003
741-11026
57251004
536-91006
048-02144
572-51007
974-09617 Sensopart 30 QI 0,2x10/1000 Si, Querschnittswandler, 1000mm, Silikon, 10mmlichtaustritt
600-11145
620-21007
553-51006
Fr20rg-Psm4
99509515
Is530-42
902-51800
902-51647
Mspf20-2
902-50689
535-91052
Fr20rg1psm4
705-11000
Is512-42
810-50007
It30nbm-Psl4
602-71000, Fe 10-RI-Ps-E4fe 10-RI-Ps-E4
611-51007, Fs/Fe 10-RI-Ns-Km3fs/Fe

10-RI-Ns-Km3	
526-51514, Lo C 12lo C 12	
740-21042	
591-91002	(FR 91 ILA-S2-Q12) RETRO 0.5M-50M, 4MM RES., LASER, ANALOG, 2XPNP, SSI / SERIAL, PLUG M16 12 PINS
30rz4/250-Mscls=16	
978-06455	
544-51324 / Fms 30-35 UI5	
533-01013, Mp Ppc 10,4mp Ppc 10,4	
506-11000 Lichttasterft12rh-Psl4	
581601	
622-21018	
740-21015	
Ft10-Rf2-Ns-K4	
Imt18-8n-Ps-K3	
573-52006, Fs 50 I-L4fs 50 I-L4	
P/N: 600-11002 Type: Ft 10-Rh-Ps-Km4	
Lr32r-24-Kfl5	
Ma18a	
831-81001	(FG80 I-PSM3) 80 X 80MM, PNP N.O., PLUG M8 3 PINS
580-51410	
532-51002	(LR 70 W-24-KFL5) RINGLIGHT, 70 MM, WHITE
979-06197	
608-11041	
696-51473	
927-81002	INFRARED, MEASURING FIELD 150MM, RANGE 2100MM, RESOLUTION 5 MM, 0-10 V
Fe20r-Psk4	
517-51396	
574-41003	
Fgl30-Rk-30-Ns-M3	
526-51515	

606-11011	
L4-2m-G-Pur	
996-09488	
Fr50r-Nak4	
535-91021	
522-91068	VGA, RED LIGHT, CCD-MONO, CODEREADER, 12MM LENS, HIGH END, ETHERN./RS422
522-91060	VGA, WHITE LIGHT, CCD-MONO, OBJECT DETECTION, C-CS MOUNT LENS, LIGHT, ETHERNET
Ft50rlh-Nsvl4	
L4s-2m-G-Pvc, M12	
574-41028	30 . 100MM, 68.36 MM, LASER, ANALOG, 1 X NPN, NC/NO , 4 TO 20MA, PLUG M12 5 PINS
718-51398	
551-11017	
580-51400, Fe 18 RI-Ps-L4fe 18 RI-Ps-L4	
Imt30-10b-Ps-L4	
Ft 55b-Rh-Ps-L4 Schalter Lichtschränke	
902-51796	
Fr10-R-Ps-Km4	
902-51628	
681-50880	
Fgl220-R-Psm3	
978-06541 / 30 Lz 12/1000-Si Ls=16	
543-11024 - Mg 3a	
522-91066	VGA, CCD-MONO, CODEREADER, C-CS MOUNT LENS, HIGH END, ETHERN./RS422
979-06250	
526-51116, Lo C 75lo C 75	
697-01020	
Umt30-350-A-Iud-L5	
902-51757	

526-51525, Lo C 35lo C 35	
602-71004, Fe 10-RI-Ps-Km4fe 10-RI-Ps-Km4	
696-51470	
Ft10-RIh-Ns-Km3	
30rz12/500-Mscls=20	
Pf30-T	
525-51122	
Ft10-Bf3-Ns-Km4	
18/30rp2/1000-Si	
611-51000, Fs/Fe 10-RI-Ps-E4fs/Fe 10-RI-Ps-E4	
18/30lz2/500-Sils=10	
996-51455	
551-21021	
697-01009	
Fgl80-Rk-50-Ns-M4	
526-51519	INFINITY.
697-01017	
978-06652	
551-71002	
555-31002	
P/N: 608-11000 Type: Ft 25-Rhd-Ps-M4	
Ft	
Lk25r-24-Kfl5	
R3-2lk	
533-01015, Lof-Bp-R635-30,5x0,5lof-Bp-R635-30,5x0,5	
902-50801	
V10-Eye-A1-R12	
527-51135, Lpt W 50lpt W 50	
P/N: 571-50000 Type: Fr 50 R-Pak4	

832-11021	
Fr25-Rgo-Ps-M4m	
608-11024	
Fr25-R-Ps-M3	
979-06150	
It10-4n-Ps-K3	
978-51680	
525-51121	LUMINARY, USABLE AEREA 98MM, IP 54
978-06460	
605-21001, Fe 25-R-Ps-K4fe 25-R-Ps-K4	
18/30r3/1500-Msc	
600-11009	
526-51113, Lo C 50lo C 50	
K2I-202	
580-51403, Fe 12 RI-Po-L4fe 12 RI-Po-L4	
722-01003	
57251000	
978-08216	
580-51439, Fls 18wm-L4-X01fls 18wm-L4-X01	
740-21028	
18/30rz3/250mscls=10	
532-51033	(LR 100 RID-24-KFL5) RINGLIGHT, INDIRECT, DIFFUSE, 100 MM, RED
510-51602	
Ft25-Ra-170-Nsu-M4m	
Fgl50-R-Psm3	
979-06648	
Ft50c-3-Psl8	
623-11037	

[038-12399](tel:038-12399)

[681-50903](tel:681-50903)

[Fms18-34ul4-54](tel:Fms18-34ul4-54)

[901-05096](tel:901-05096)