



Servomech

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Servomech Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Servomech Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Elektrischer Antrieb	ATL80 RV2 C500 TS FCP SP RH VERS.5 IEC112 B5 U B + AC 3 PHASE MOTOR 4KW 4 POLES 400V 50HZ 230/400V 50HZ IEC112 B5 (WITH SEP. WIRED BRAKE) 31.000 N 70 mm/s 400 V, AC, 50 Hz 4 kW
MA BS Mod A Ball Screw Jack	
MA 100 BS	
MA 150 BS	
MA 200 BS	
ACT.BSA30 BS20X10RV2 C800 H-RH	
ATL30 RN C50ROE FS	HOOK RELEASE MOTOR (Electric Motor + Actuator) Actuator: Acme screw actuator Rod end, Ratio: 1:16, Stroke: 61 mm Motor: 3 phase, 400V, 0,25 kW, 2.800 rpm IP65, Ex II 2GD EEx d
02.030/6867 rev.0	BSA 30 BS20x10 RV2 C800 FO FI RPT90 Vers.4 IEC63B14 H LH prep. to receive encoder SICK AFM60E-BDLA004096 ac 3 ph motor 0,37kW 4pole 415V 50HZ Flange and shaft reduced Special thermal protection Tropicalized IP55 F ***** Remarks: Encoder not included in our contractor
20.0684.05498	
BSA 40 RL C100 FCE FO B	R:1/25 C:100 mm V:5,5 mm/s
	Your items 1 + 2 screw jacks SJ05 MOD.A RH1 VERS.2 U C420 NF B

05.025/5379	CA+G/TG T FCM(NC) Prod. Code 05.025/5379 Rev.1 Customs tariff number: 84834051 Country of origin: Italy
SJ 05 Mod. A RH1 C420 NF T+FCM(NF) Vers.2 U D1=69	SJ05 mod.A RH1 C420 vers.2 FCM(NF) NF B CA+G/TG U D1=69 SERVOMECH mechanical cylinder with translation screw capacity = 5kN stroke = 420mm closed length = D1=69 mm ratio = 4/1 screw TR Ø18x4 vers.2 = 2x solid input shaft Ø 9 mm screw end "NF" = male thread M12x1.75 with standard protection tube "T" with protective nylon/PVC "B" bellows with guide and connecting piece protection tube in BRONZE "CA+G/TG" with set of adjustable magnetic limit switches FCM (2xNC) casing with threaded mounting holes (FF) U HR execution according to plan SERVOMECH 5379 rev.1 identical to serial number 16.1119.06731- 06732
Protection Sensor AZ9099 LME01 SERVOMECH	
SJ100 MOD.A RL1 VERS.2 FP H C107,50 P T	Lc= 91 mm La= 198,50 mm screw jacks
SJ300 MOD.A RL1 VERS.2 FP D C230 P T AR	Prod Code 05.110/3759 screw jacks
SJ 200 Mod.A RL1 C140 P T VERS.2 D FP	with special threaded cover Prod Code 3865
Actuator for Clamshell flap +Location Connection	Strok : C800 mm LINEAR SPEED [mm/s] : 70 DYNAMIC LOAD [kN] : 31 RATIO : RV2 MOTOR: POWER [kW] — N° of POLES SPEED [rpm] : 4 kW 4-pole 1400 SELF-LOCKING COEFFICIENT : 0.34 LIMIT-SWITCH
Actuator for trouser flap +Ground Connection	Strok : C500 mm LINEAR SPEED [mm/s] : 70 DYNAMIC LOAD [kN] : 31d RATIO : RV2 MOTOR: POWER [kW] — N° of POLES SPEED [rpm] : 4 kW 4-pole 1400 SELF-LOCKING COEFFICIENT : 0.34 Pantolon klape için aktüatör Strok: C400 mm LINEAR SPEED [mm/s] : 70 DYNAMIC LOAD [kN] : 31 RATIO : RV2 MOTOR: POWER [kW] — N° of POLES SPEED [rpm] : 4 kW 4-pole 1400 SELF-LOCKING COEFFICIENT : 0.34 LIMIT- SWITCH
02.040/3861	
Atl 40 Rn1 C100 Fo Fce Sp	
Sj50 A Rn Vers.1 C9	
Vs. Art. 52is118	
Atl-20-RI1-C400-Ba-Vers.3	
Sj25-Mod.B-RI1-Vers1-Rh/U-Fp-C300-N-Sbc	
Bg110 - R1 - S - M1 -Ausf. 30-C-Ho	
Prod. Code: 02.040/4920 Rev. 0	
Poz1 Linear Actuators (Right)	
Sj5 A25 1	
Lmr01-RI1-C200-Rf-Fc2	
Bsa40 Rn1 C400 Ts Sp Fcm B Vers.3 (Just Drive Motor)	
Tf71 B/4 14, Nr:A05000015 Special Design / Possible Replacment Bsa40 Rn1 C400 Ts Sp Fcm B Vers.3 (Just Drive Motor)	
Tn63a7414 ()	
02 040 1000/3017	
1:4 Blind Holes Screwjack For Tr18 1:4	
00.1711.08011	

Atl10 ? RI2 ? C100 ? Roe ? Ac 1 Phase 0,09kw; 2p; 230v; 50 Hz
Bsa0300014
02.100/5719
Atl30 Rv C500(Eff.468) Ts Fcm(No)
01.030/3971 U-Lh
Ma 80a4 No:L 114043980058001
06.2322.10332
Atl0400086
Atl20m1 C200 Ba Fcm Nc
Sj05 A Rn1 63b5 V6
02.040.700/2413.2
Clb40 Rxl1 C100 F0 Fcp
Atl30 RI1 C500 Roe Fce Sp
Atl40 RI2 C400ts Fcmnc
Atl40 Rn1 C400 Roe Fcm/Nc
Ma50 - Mod.A - RI1 - Vers.5
Clb30-Rxl1-C120-Fo-B-Fc-Por5k
Sj25-Mod.B-RI1-Vers2-Rh/U-Fp-C300-N-Sbc
Atl40 Rv1 C400 Fo Fcm Iec71b14 Sp Rh B
Atl100 Rv1 C500 Tf B Fc Vers.6(Iec132 B5) Msa(For Push Load) Lh
Bsa0200003
Lmr-01-RI1-C300-Rf-Fc2-24v
02.100/5558
Atl-20-Rxl1-C200-Ba
21.025/5946
Atl30-Rv2-C995-Ts+sp-Fcp- Vers.3-Rh-Sp-Ar-Ms
Atl50 ? Rv1 ? C600 ? Tf ? Fcp ? Vers. 5 ? 230/400v; 1,5kw; 4-Polig; Mit Bremse
02.080/5560
N63b/4 Tr-S
Serial No. : A00710937 Prot.IP 55
Atl05rl1c100roefcm(Cs)
Bsa40 Rv1 C800 Roe Fcm(No) Vers.3 Iec 71b14 Rh
Redüktör 01.050/3843 R.1/6 C. L362 Mm
Atl 20
Chl0871

Bsa40 ? Rv1 ? C400 ? Ts ? Fcm(Nc) ? Sp	
Atl50 Rv2 C600ts Fcp	
Sj50 A Rn Vers.4 C900	
Atl63 RI1 C60 Ba Ar Fcp(2)	
Lmr01-RI1-C300-Rf-Fc2	
Atl10 - Rn1 - C200 - Fo - Fs	
Type. M50I2	
Sj05	
Atl20-RI2-C300-Ts-Fcm-V3-Dx-Ca3f	
Bsa 40 Rv1 C800 Roe Fcmno	
Atl 25 RI1 C400 Roe Fce Sp	
Atl-10-Rv1-C600-Roe	
Uba3-RI1-C230-Ts-Sp	
Clb40 Rx11 C100 Fo Fcp	
Uba2c120bafcmnc 9 (.)	
Bsa 50 Rv1c800-Ba-Sp	
Bsa 030 Rv1 C500 Ba Sp Vers3 R	
M50I2	
Lmr01-RI2-C200-Fr-Fc2	
Atl-20-RI-C250-Fs-Sp-Fo	
Actuator No : Vs.Art.49.Nc193 Seri:14.1010.05700	
Atl20 Tr13.5x3 Rx11 C100 Roe Fce Sp Fs Rpt90; Vers.4 Iec56 B14 Wechselstrommotor 0.09 Kw 4 Polig 11	
S/N: 12.0050.02212 (.)	
L112123280011001	
0426453	
Atl100 – Rv1 – C500 – Tf – B – Fc – Vers.6/ Iec132b5 – Msa(Push) – Rh Bzw. Lh	Technical specifications: stat. Load (push / pull): 200kN / 200kN effective stroke length: 500mm (C500) Spindle: trapezoidal thread spindle TR70x12; catchy Reduction: i = 1: 8 (RV) Front attachment: rod end (TF) Limit switch: two; Microswitch; inside, via cam, opener (FC) ** Motor bell IEC132B5 incl. Clutch and additional output shaft (vers.6) ** internal safety nut for pressure load (MSA) ** bellows (B) ** Motor bell right or left (RH or LH) ** Max. Duty cycle 30% per 10 minutes ** Drive statically self-locking ** Tariff number: 8483 4051 Country of origin: Italy
Ma25 - Mod.A - Tr30x6 - Rv1	Screw jack + motor MA25 - Mod.A - TR30x6 - RV1 - NF (M22x1.5) / NF (M10x20) - TS (Ø30) - CA + G / CA + G - SC - B - Vers.5 (IEC80 B14) - U / LH Three-phase motor with brake ** 1,1kW; 4-pin; 230 / 400V; 50Hz (277 / 480V; 60Hz) ** brake 230V; Hand release; second wave Version as supplied with S.N. 04.2315.08702

Prod. Code: 02.040/4919 Rev. 0	
32x8	
Bsa40 ? Rv1 ? C800 ? Ts ? Fcm(Nc) ? Sp	
Atl 25-Rh-C400	
Poz6 Linear Actuators (Left)	
3662100	
02.080/5559	
Vs.Art.52is117	Date : 50/12 Serial No. : 12.3080.13993
25 A C300	
Atl30 Rn2 C230 Roe	
Carr 32x300x1/D24c Skf MaterialNr.:9734806	
M56b4	
Atl 50 Rh Vers3 Rv1 Tf C600 Fcp	