

Sick

Garanti: 12 ay
Bu rne ait Trkiye
ii kapı teslim fiyat
ve teslim sresi
ieren teklifimizi
almak iin
info@yursat.com.tr
e-posta adresine
bařvuru yapabilir ya
da ayrıntılı bilgi iin
+90 224 240 03 04
numaralı
telefonumuzdan
bizlere
ulařabilirsiniz.
Sick Markası,
tedarik sresi iin
ltfen bizimle
iletiřime geiniz.

*Firmamız Sick Trkiye
Distribtr veya temsilcisi
değildir. Firmamız sipariř
durumunda, belirtilen
rnlerde sadece Orjinal ve
yeni rn teklifi
sunmaktadır. Bu sitede
gsterilen zel marka adları
ve ticari markalar ilgili
sahiplerinin
mlkiyetindedir, talep
durumunda
kaldırılmaktadır.*



rn	Aıklama
	Type: installation Execution: Absolute multiturn Communication interface: HIPERFACE® Sine / cosine periods per revolution:

Srs/Srm50, Srm50-Hfa0-K21	1,024 Safety-related system: no Mechanical interface: cone shaft, spring plate support, 9 mm Connection type: connector, 8-pin, radial Technology: optical
Mat. Nr.:1026820	Safety laser scanner S300 Standard, S30B-2011BA Protective field range: 2 m Scan angle: 270 ° Number of fields: 3
1040965	Inductive proximity sensors IME, IME18-08BPSZC0K Housing design: short design Switching distance Sn: 8 mm Installation in metal: flush Electrical version: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 connector, 4-pin Country of origin: HU; Stat. Product number: 85365019
1065887	Small light barriers G10, GL10-P4212 Switching distance max.: 0.08 m ... 15 m, 0.08 m ... 12 m Sensor principle: reflection light barrier Detection principle: double lens Switching output: PNP Switching mode: light / dark switching Connection type: M12 connector, 4-pin Light transmitter: PinPoint-LED Setting: potentiometer Included in delivery: BEF-G10DC01 mounting bracket, P250 reflector Country of origin: MY; Stat. Product number: 85365019 EC dual use / export list number: non;
1047361	Mid-range distance sensors Dx50, DL50-P1123 Measuring range: 200 mm ... 50,000 mm, on reflective tape #Diamond Grade " Minimum response time: 15 ms Analog output type: current output Digital output: 1 x PNP Light transmitter: laser, red Laser class: 1 (IEC 60825-1: 2014, EN 60825-1: 2014) Multi-function input (MF): 1 x
Afm60b-S1kz000s06 Absolute Encoder	1075531 004096 steps x 4096 rev., 4.5 ... 32V, SSI / Gray, Sin / Cos 1024 periods, Cable 12-wire, universal, 1m with struck M23,17-pol. plug with customer-specific pin assignment
Absolute Encoder Baumer Eal580-Bnc.5wpt.	.18130.A PROFIN.
S300 FRONT SCREEN 2039248	
LFV200-XATGACPV	6036381 Level sensors LFV200, Process connection: G 1 A PN 64 Output signal: contactless switch Probe length: 67 mm Materials in contact with media: stainless steel 1.4404 Housing material: stainless steel 1.4404, PEI Connection type: valve plug DIN 43650 Process temperature: -40 ° C ... +150 ° C Approvals: WHG
IME12-02BPSZC0S	Inductive proximity sensors 1040732 Housing design: standard Switching distance Sn: 2 mm Installation in metal: flush Electrical version: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin
IME12-04BPSZC0S	Inductive proximity sensors 1040764 Housing design: standard Switching distance Sn: 4 mm Installation in metal: flush Electrical version: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin
PL80A	1003865 Reflectors Angular, PL80A Description: Rectangular, screwable Dimensions: 80 mm 80 mm Ambient temperature, operation: -20 ° C ... +65 ° C
Range -10 +10 mbar,output 4-20 mA,	

24vdc	
VFS 60 - 2048	Encoder VFS 60 - 2048 - TTL 4.5- 32V fully programmed and assembled with connector
1040970	IME, IME18-08BPOZC0S
T40-E0121K	Contactless safety switches T4000 Direct, T40-E0121K System part: sensor Coding: Uniquely coded Connection type detail: connector, M12, 8-pin LED: yes
AFS/AFM60	1059034 Absolut-Encoder AFS / AFM60 PROFINET, AFM60A-BENB018x12 Singleturn or multiturn design: multiturn Resolution max.: 18 bit x 12 bit (262,144 x 4,096) Mechanical design: blind hollow shaft Shaft diameter: 12 mm Communication interface: PROFINET Connection type: plug, 1x, M12, 4-pin, axial, socket, 2x, M12, 4-pin, axial Programming interface: Via PLC engineering tool
IQ20-07BPSDU2S	6045180 Inductive proximity sensors IQV, IQ20-07BPSDU2S Switching distance Sn: 7 mm Installation in metal: flush Cuboid shape (W x H x D): 20 mm x 32 mm x 8 mm Electrical version: DC 3-wire Switching output: PNP Switching function: normally open Connection type: cable, 3-core, 2 m
P250F	5308843 Reflectors Fine triple reflectors, P250F Description: Feintripel, screw-on, suitable for laser sensors Dimensions: 52 mm 62 mm Ambient temperature, operation: -30 ° C ... +65 ° C
LMS1xx, LMS141-15100 Security Prime	1070409 2D LiDAR sensors Working range: 0.5 m ... 40 m Opening angle: 270 ° Degree of protection: IP67 Color: Gray (RAL 7032) Integrated application: Field evaluation with flexible fields, security-specific parameterization, Easy Teach lite and pro Connection type: 1 x M12 round connector Scanning frequency: 25 Hz, 50 Hz
MZT7-03VPS-KWB	
W12-3, WTB12-3P2431	1041411 Small light barriers Switching distance max.: 20 mm ... 350 mm Sensor principle: photoelectric proximity switch Switching output: PNP Switching type: light / dark switching Connection type: M12 connector, 4-pin Light transmitter: LED Type of light: Visible red light Setting: potentiometer, 5 turns Included in delivery: 2 x clamp holders BEF-KH-W12, including screws
MZT7-03VPS-KWP	
IME12-04BPOZCOK-1040767 END/KAP	
S30A-6011DA	Safety laser scanner 1019600 S3000 Professional, S30A-6011DA Protective field range: 5.5 m Scan angle: 190 ° Number of fields: 24
VFS60A-BHPZ0-S01	
SLA-ML4V5 3W8 1001019	
1064607	Miniature photoelectric switches W2S-2, WTB2S-2P3160 Switching distance max.: 1 mm ... 66 mm Sensor principle: photoelectric proximity switch Detection principle: background suppression Switching output: PNP Switching type: light

	switching Connection type: Cable with connector M8, 3-pin, 200 mm Light transmitter: PinPoint-LED Setting: none Communication interface: -
G6, GSE6-P1212	Miniature photoelectric switches Switching distance max.: 0 m ... 15 m Sensor principle: one-way light barrier Switching output: PNP Switching type: light / dark switching Connection type: cable, 3-core, 2 m Light transmitter: PinPoint-LED Type of light: Visible red light Housing material: ABS / PC Setting: potentiometer Included in delivery: Stainless steel mounting bracket (1.4301 / 304) BEF-W100-A
2054.1041114	2D LiDAR sensors LMS1xx, LMS111-10100 Working range: 0.5 m ... 20 m Opening angle: 270 ° Degree of protection: IP67 Color: Gray (RAL 7032) Integrated application: field evaluation with flexible fields Connection type: 1 x M12 round connector Scanning frequency: 25 Hz, 50 Hz
6035499	Round light barriers V18V, VS / VE18-4P3140V Switching distance max.: 0 m ... 20 m Sensor principle: one-way light barrier Switching output: PNP Switching type: light / dark switching Connection type: M12 plug, 4-pin Light transmitter: LED Setting: none
LUT1B-31325	
Move mechanics stainless %15 steel for DHSP-T	2043925 (Move mechanics SS for DHSP-T)
SRM50S-HFZ0-S22	
TiM3xx, TIM320-1131000	2D LiDAR sensors 1062219 Area of application: indoors Integrated application: field evaluation with flexible fields Measuring principle: HDDM+ Working range: 0.05 m ... 4 m Angular resolution: 1° Number of field sets: 16 Digital outputs: 3 (PNP, additional 1 x "Device Ready") Connection type: 1 x 12-pin M12 device connector (0.8 m)
LMS511-22100 Heavy Duty	+ laser scanner power cable
STE-1204-GE01	
DT50-2B215552	
YF2A15-100VB5XLEAX	
IMB 18-12 NPSVCOS (PNP) 1070173	
DOS-1204-GX 6026528	
6052361	miniature light barriers W100-2, WL100-2P3439 Switching distance max.: 0.01 m ... 7.2 m Sensor principle: Reflection light barrier Detection principle: double lens Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 3-pin Light emitter: LED Adjustment: potentiometer Included in delivery: mounting bracket BEF-W100-A, reflector P250
1002314	reflectors Square, PL30A Description: Rectangular, screwable Dimensions: 30mm 82mm Ambient operating temperature: -20 °C ... +65 °C

5M3-BEH-K04-096	1038155 incremental encoder DFS60, DFS60B-BHEK04096 Mechanical design: blind hollow shaft 15 mm Communication interface: 10 V ... 32 V, HTL, push-pull Connection type: cable, 8-wire, universal, 1.5 m Pulses per revolution: 4,096 Country of origin: DE; Stat. Commodity number: 90314990 EU dual use / export list number: non; US ECCN: non
MBA810ZIN2-N00650-N-XXXXX	Digital rotary paddle switch - Parameters adjustable - maintenance free - wear-free - insensitive to vibrations. MBA810ZIN2-N00650-N-XXXXX MBA810 supply voltage: 115V to 230V 50Hz Z with certificate for dust Ex Zone 20/21 I process connection: Flange DN 125 PN 6, stainless steel N Pressure in the container: - 0.5 ... + 3 bar 2 Temperature in the container: up to 200 °C N Angle bracket for horizontal assembly, reinforced, stainless steel Diving depth: 650 mm N toggle wing Ø 12 x 100 mm 2 Process temperature up to 200°C N Shaft with 90° angle, reinforced, stainless steel Immersion depth: 600 mm N Toggle paddle, stainless steel MBA200
DFS60B-BHEK04096	INCREMENTAL ENCODER DFS60, DFS60B-BHEK04096 Mechanical design: blind hollow shaft 15 mm Communication interface: 10 V ... 32 V, HTL, push-pull Connection type: cable, 8-wire, universal, 1.5 m Pulses per revolution: 4,096
FX3-CPU000000 FLEXISOFT CONTROLLER	1043783 Security systems for AGVs and AMRs Safe EFI-pro system, FX3-CPU000000 Module: main module Configuration and diagnostic interface: RS-232 Type of connection: tension spring terminals Protective varnish for increased environmental requirements: no Scope of delivery: Main module without system plug, safety instructions, operating instructions to download
FX3-MPL000001 FLEXISOFT MEMORY PLUG	1043700 connectors and cables Miscellaneous connectors and cables, FX3-MPL000001 Description: System plug: Power supply for the Flexi Soft system and Saving the system configuration (without EFI-enabled devices) Connection technology: screw terminals
FX3-XTIO84002 FLEXISOFT 8IN/4OUT	1044125 Security systems for AGVs and AMRs Safe EFI-pro system, FX3-XTIO84002 Module: I/O module Secure inputs: 8 Safe exits: 4 Flexi Loop compatible: yes Type of connection: tension spring terminals Protective varnish for increased environmental requirements: no
i110RP313	
WTB27X-3P1811	
WLL190T-2P434	FIBER GAIN Article number: 6032553 fiber optic sensors WLL190T-2, WLL190T-2P434 Switching distance max.: 2 ... 4 m Switching type: light/dark switching Connection type: M8 plug, 4-pin Degree of protection: IP66 Setting: menu-driven, teach-in button, line
LL3-TH08-3	LIGHT GUIDE HEAT RESIST. Article number: 5328051 light guide LL3, LL3-TH08-3 For fiber optic sensor: GLL170(T), WLL180T Functional principle detail: Consisting of a transmitter and a receiver Material, fiber: glass Material, jacket: stainless steel Material, light guide head: brass Thread diameter (housing): M4 Light guide length: 3,000 mm

MRA-F130-110D2 CABLE MECHANISM	Cable mechanism, MRA-F130-110D2 Description: HighLine cable mechanism for servo flange with 6 mm shaft, Measuring range 0 m ... 10 m Scope of delivery: without encoder
A3M60B-S4PB013X13 ABSOLUTE ENCODER	1038826 Absolute encoder A3M60 PROFIBUS, A3M60B-S4PB013x13 Singleturn or multiturn version: multiturn Max. resolution: 13 bits x 13 bits (8192 x 8192) Mechanical design: solid shaft clamping flange 10 mm x 19 mm Communication interface: PROFIBUS DP, DPV0, programmable Connection type: plug, 2x, M12, 5-pin, axial, socket, 1x, M12, 5-pin, axial Programming interface: Via PLC engineering tool
SICK END.SEN. IME18-08BPSZC08(1040966)	Inductive proximity sensors IME, IME18-08BPSZC0S Housing design: Standard Sensing distance Sn: 8 mm Installation in metal: Flush Electrical design: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin
IME18-08BPSZC0S 1040966	Inductive proximity sensors IME, IME18-08BPSZC0S Housing design: Standard Sensing distance Sn: 8 mm Installation in metal: Flush Electrical design: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin
IQ40-40NPPKC0K 1071552	Inductive proximity sensors IQG, IQ40-40NPPKC0K Sensing distance Sn: 40 mm Installation in metal: non-flush Block shape (W x H x D): 40 mm x 40 mm x 66 mm Electrical design: DC 4-wire Switching output: PNP Switching function: complementary Connection type: M12 plug, 4-pin
IME18-08BPSZC0K -1040965	Inductive proximity sensors IME, IME18-08BPSZC0K Housing design: Short design Sensing distance Sn: 8 mm Installation in metal: Flush Electrical design: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin
YF2A15-050VB5XLEAX PVC/5*0,34/GR/US	2096240 connectors and cables Connecting leads, YF2A15-050VB5XLEAX Connection type head A: socket, M12, 5-pin, straight, A-coded Type of connection Head B: Open cable end Approvals: CE, UL Signal type: sensor/actuator line Cable: 5 m, 5-core, PVC Description: Sensor/actuator cable, unshielded Area of application: chemical area
IP67 1063132	Photoelectric sensor RT-P2233 sensor/detection principle: sensor with reflection from the object, background suppression response distance: 60 ... 900mm type of radiation: infrared light Operating voltage: 10 ... 30V DC switching output: PNP Switching type: dark Connection type: cable with M12 connector, 4-pin, 300mm Degree of protection: IP67 1063132 SICK
Transmitter M20S-02150A122 24-28	,8V DC 10-55Hz 3,7W 0 - 55° C 0 - 25m 48 x 40mm 1018186 SICK
LFP2500-G1NMB	level sensors 1065361 LFP Inox, LFP2500-G1NMB Process connection: G ¾ A Probe length: 2,500 mm Application type/design: Standard Output signal: 1 x PNP + 1 x PNP/NPN + 4 mA ... 20 mA / 0 V ... 10 V Connection type: circular connector M12 x 1, 5-pin Process temperature: -20 °C ... +150 °C Materials in contact with media: 1.4404 (Ra ≤ 0.8 µm), PEEK Housing design: With viewing window made of PMMA (acrylic glass)

1019229 - WT34-B410	Compact light barriers 1019229 W34, WT34-B410 Sensor principle: diffuse reflection sensor Detection principle: background suppression Switching output: NPN, PNP Switching type: light switching, dark switching Connection type: M12 plug, 4-pin Light emitter: LED Adjustment: potentiometer Communication interface: -
Control Panel for MCU of dusthunter art No:	2061514-0000
WL100L-F2231 REFLEXIONS-LS	6030710 miniature light barriers W100 Laser, WL100L-F2231 Switching distance max.: 0.08 m ... 12 m Sensor principle: Reflection light barrier Detection principle: double lens Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 4-pin Light emitter: laser Adjustment: potentiometer Laser class: 1 Included in delivery: stainless steel mounting bracket (1.4301/304) BEF-W100-A, reflector P250F
IME18-08BPSZC08(1040966)	
IME18-08BPSZC08(1040966)	
IQ40-40NPP-KC0K 6037073	
IME18-08BPSZCOK 1040965	
DOL-1205-G05M (6009868)	
IME08-02BPSZW2K	Inductive proximity sensors IME, IME08-02BPSZW2K Housing design: Short design Sensing distance Sn: 2 mm Installation in metal: Flush Electrical design: DC 3-wire Switching output: PNP Switching function: normally open Connection type: cable, 3-wire, 2 m
IME18-08BPSZW2S	Inductor. Article number: 1040968 Inductive approximation sensors Ime, ime18-08bpszw2s Housing form: standard design Switch distance SN: 8 mm Installation in metal: flush Electrical version: DC 3 ladder Switch output: PNP Switch function: closer Connection type: line, 3-caded, 2 m
DME4000-211	DISTANCE MEASUREMENT UNIT Artikelnummer: 1029790 Long range distance sensors DME4000, DME4000-211 Measuring range: 0.15 m ... 130 m, on "Diamond Grade" reflective foil Repeatability: 2mm Accuracy: ±5mm Output Time: 1ms Communication interface: SSI Connection type: plug, M16, 8-pin Current consumption: At 24 V DC < 250 mA
DBS36E-BBAK01000 INCREMENTAL ENCODER	Article number: 1060528 incremental encoder DBS36/50, DBS36E-BBAK01000 Mechanical design: blind hollow shaft 8 mm Communication interface: 4.5V ... 5.5V, TTL, RS-422 Connection type: cable, 8-wire, universal, 1.5 m Pulses per revolution: 1,000
1001019	
DFS60B-S4EA05000	Part Nr: 1037275 INCREMENTAL ENCODER DFS60, DFS60B-S4EA05000 Mechanical design: solid shaft clamping flange 10 mm x 19 mm Communication interface: 10 V ... 32 V, HTL, push-pull Connection type: plug, M23, 12-pin, radial Pulses per revolution: 5,000

A3M60B-BEP	Absolut-Encoder Article number: 1052509 Scope of delivery: 1 x A3M60B-BEPB013X13 (1038825), 1 x STE-1205-WQ (6041428), 1 x DOS-1205-W (6009720), 1 x DOS-1205-WQ (6041429) Special feature: sales set
IME18-08BPSZW2S	1040968 Inductive proximity sensors IME, IME18-08BPSZW2S Housing design: Standard design Sensing distance Sn: 8 mm Installation in metal: Flush Electrical design: DC 3-wire Switching output: PNP Switching function: normally open Connection type: cable, 3-wire, 2 m
DT500-A111 DISTANCE SENSOR BUTTON	1026515 Long range distance sensors Dx500, DT500-A111 Measuring range: 0.2 m ... 30 m, 90% remission 0.8 m ... 15 m, 6% remission Repeatability: 1mm Accuracy: ±3mm Type of analog output: current output Power Consumption: Typ. 3w Heating: no
AFM60A-S1NB018X12 ABSOLUTE ENCODER	Absolute encoder AFS/AFM60 Ethernet, AFM60A-S1NB018x12 Singleturn or multiturn version: multiturn Max. resolution: 18 bits x 12 bits (262,144 x 4,096) Mechanical design: solid shaft servo flange 6 mm x 10 mm Communication interface: PROFINET, programmable Connection type: Plug, 1x, M12, 4-pin, axial Socket, 2x, M12, 4-pin, axial Programming interface: Via PLC engineering tool
WL100-2P4439	REFLEXIONS-LS miniature light barriers W100-2, WL100-2P4439 Functional principle: Reflection light barrier Functional principle detail: double lens Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 4-pin Light emitter: LED Adjustment: potentiometer Communication interface: - Included in delivery: mounting bracket BEF-W100-A, reflector P250
GL6-P4212	REFLEXIONS-LICHTSCH. miniature light barriers G6, GL6-P4212 Switching distance max.: ≤ 6 m Functional principle: Reflection light barrier Functional principle detail: double lens Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 4-pin Light emitter: PinPoint LED Type of light: Visible red light Housing material: ABS/PC Adjustment: potentiometer Included in delivery: P250 reflector, stainless steel mounting bracket (1.4301/304) BEF-W100-A
WL9M4-3P2232	REFLEXIONS-LICHTSCH. Small light barriers W9, WL9M4-3P2232 Functional principle: Reflection light barrier Functional principle detail: autocollimation Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 4-pin Light emitter: PinPoint LED Setting: teach-in button Communication interface: -
SKS36-HFA0-K02SKS36-HFA0-K02	1034095 MOTORFEEDBACK HIPERFACE® rotary motor feedback systems SKS/SKM36, SKS36-HFA0-K02 Communication interface: HIPERFACE® Execution: absolute single turn Type: built-in Sine/cosine periods per revolution: 128 Safety-related system: no Mechanical design: conical shaft, spring plate support Type of connection: plug, 8-pin, radial Technology: Optical Operating temperature range: -20 °C ... +110 °C
WE260-S270	
WSE280-2H4331 THROUGH-BEAM SENS.	

EKS36-0KF0108A	
GRTE18S-P2317	
WTB26P-24861120A00Z2ZZZZZZZZ1	1115766 Compact light barriers W26, WTB26P-24861120A00 Switching distance min. / max.: 30 mm / 1,600 mm Functional principle: reflection light scanner Functional principle detail: background suppression Switching output: PNP Connection type: M12 plug, 4-pin Light transmitter: PinPoint LED Light type: Visible red light Housing material: VISTAL® Setting: Teach-in button, cable, potentiometer, push-turn element Communication interface: IO-Link V1.1 Smart Sensor: Enhanced Sensing, Efficient Communication, Smart Task Smart Task Name: Basic Logic
2049526	Printed-circuit board assembly
E10-P123	e10-p123-25 For rational and permanent labeling of all types of products made of metal, plastic, wood, etc. The marking system is characterized above all by its robust and industrial-grade design according to the following specification: Marking head Hand-held device with pistol-shaped handle X-axis with linear guide and ball-bearing slide, drive via Rack, Y-axis swivel drive via rack Rubberized front panel for position fixation with V recess and Quick adjustment for workpiece distance Labeling area 120 x 25 mm, LED lighting Electromagnetic needle drive with needle guide and 60 mm embossing needle made of carbide Embossing up to 62 HRC material hardness possible max. 5 mm height compensation, depending on the embossing force Noise development 76 dB (measured at medium embossing force and speed on sheet steel) 7.5 m control cable to the control unit with cable bending protection Weight 3.7 kg Control unit Integrated membrane keyboard, high-resolution color display (480x272 pixels) USB interface, special USB driver is required
C4C-SA18030A10000 LIGHTCURTAIN	Safety light curtains deTec, C4C-SA18030A10000 deTec variant: deTec4 Core System part: transmitter Area of application: standard industrial environment Safety level: Type 4, PL e, SIL3 Resolution: 30mm Range: 15m Protective field height: 1,800 mm Connection type: M12 plug, 5-pin Protection class: IP65, IP67 Scope of delivery: transmitter
C4C-EA18030A10000 LIGHTCURTAIN	Safety light curtains deTec, C4C-EA18030A10000 deTec variant: deTec4 Core System part: receiver Area of application: standard industrial environment Safety level: Type 4, PL e, SIL3 Resolution: 30mm Range: 15m Protective field height: 1,800 mm Connection type: M12 plug, 5-pin Protection class: IP65, IP67 Scope of delivery: receiver, test rod with a diameter corresponding to the resolution of the Safety light curtain, safety instructions, assembly instructions, operating instructions for download
C4C-SA09010A10000 LIGHTCURTAIN	Safety light curtains deTec, C4C-SA09010A10000 deTec variant: deTec4 Core System part: transmitter Area of application: standard industrial environment Safety level: Type 4, PL e, SIL3 Resolution: 14mm Range: 10m Protective field height: 900 mm Connection type: M12 plug, 5-pin Protection class: IP65, IP67 Scope of delivery: transmitter
	Safety light curtains deTec, C4C-EA09010A10000 deTec variant: deTec4 Core System part: receiver Area of application: standard

C4C-EA09010A10000 LIGHTCURTAIN	industrial environment Safety level: Type 4, PL e, SIL3 Resolution: 14mm Range: 10m Protective field height: 900 mm Connection type: M12 plug, 5-pin Protection class: IP65, IP67 Scope of delivery: receiver, test rod with a diameter corresponding to the resolution of the Safety light curtain, safety instructions, assembly instructions, operating instructions for download
YF2A15-100UB5M2A15 PUR/5*0,34/BK/US	Connectors and cables Connecting cables, YF2A15-100UB5M2A15 Connection type head A: Socket, M12, 5-pin, straight, A-coded Connection type head B: plug, M12, 5-pin, straight, A-coded Approvals: CE, UL Signal type: sensor/actuator cable Cable: 10 m, 5-wire, PUR, halogen-free Description: Sensor/actuator cable, unshielded Area of application: oil/lubricant area, drag chain operation, robots
YF2A15-050UB5M2A15 PUR/5*0,34/BK/US	Connectors and cables Connecting cables, YF2A15-050UB5M2A15 Connection type head A: Socket, M12, 5-pin, straight, A-coded Connection type head B: plug, M12, 5-pin, straight, A-coded Approvals: CE, UL Signal type: sensor/actuator cable Cable: 5 m, 5-wire, PUR, halogen-free Description: Sensor/actuator cable, unshielded Area of application: oil/lubricant area, drag chain operation, robots
DSC-1205T000025KM0 T-VERBINDER M12* 5	Distributor T-distributor, DSC-1205T000025KM0 Connection type head A: Socket, M12, 5-pin, A-coded Connection type head B: plug, M12, 5-pin, A-coded Connection type head C: M12 socket A-coded Description: T-splitter for simultaneous connection to transmitter and receiver, divides the line coming from the control cabinet between the transmitter and receiver Note: 5-pin
S30A-7111CP S3000 PN	Security laser scanner S3000 PROFINET IO Advanced, S30A-7111CP Version: Sensor without system plug Protective field range: 7 m Scan angle: 190° Number of fields: 8 Transmission medium for PROFINET IO: copper cable
S3000 MOUNTING KIT HEAVY DUTY	Mounting brackets and plates Mounting bracket, heavy duty mounting kit Description: Mounting bracket, heavy duty, with protective cover Floor installation, adjustment around the longitudinal and transverse axes using an alignment plate, Height adjustment possible. Tilt angle $\pm 5^\circ$. There are no additional brackets necessary. Material: steel Details: Steel, painted (RAL 1021) Color: RAL 1021 (rapeseed yellow) Packaging unit: 1 piece
SX1A-A0000L S3000 PN SYS-PLUG	Connectors and cables Other connectors and cables, SX1A-A0000L Connection type head A: system plug Description: Without cable, for S3000 PROFINET IO Advanced and Professional, Not for use with incremental encoders, integrated configuration memory
LEITUNG,STEC/BUC 0M30 RJ45PP/M12	Connectors and cables Other connectors and cables, RJ45PP/M12 adapter cable Cable: 0.3 m Description: Shielded, for connecting the RJ-45 port on Safety laser scanner with M12 standard connectors
DSL-8U04G02M025KM1 VERBINDUN.LTG M 8* 4	Connectors and cables Connection cables, DSL-8U04G02M025KM1 Connection type head A: plug, M8, 4-pin, straight Connection type head B: male, USB-A, straight Cable: 2 m, 4-wire, PVC Description: Unshielded, configuration cable

	with integrated RS-232 converter to USB to connect a sensor configuration connector (M8, 4-pin) to the USB interface of a PC
REF-IRF-56 REFL.FOLIE 50.0* 60.0	5314244 Reflectors Reflective film, REF-IRF-56 Accessory group: reflectors Accessory family: reflective film Description: Self-adhesive Dimensions: 50mm 60mm Operating ambient temperature: -20 °C ... +60 °C
AFM60A-S4PM262144	1037512 Absolute encoder AFS/AFM60 SSI, AFM60A-S4PM262144 Singleturn or multiturn version: Multiturn Resolution max.: 18 bit x 12 bit (262,144 x 4,096) Mechanical design: solid shaft clamping flange 10 mm x 19 mm Communication interface: SSI, programmable Connection type: cable, 8-wire, universal, 5 m Programming interface: Via handheld programming tool, via SOPAS
PGT-08-S PROGRAMMING TOOL	1036616 Programming and configuration tools, PGT-08-S Description: USB programming device, for programmable SICK encoders AFS60, AFM60, DFS60, VFS60, DFF60 and cable pull encoders with programmable encodersv
AFM60B-S4AM004096 ABSOLUTE ENCODER	1058001 Absolute encoder AFS/AFM60 SSI, AFM60B-S4AM004096 Singleturn or multiturn version: Multiturn Resolution max.: 13 bit x 12 bit (4,096 x 4,096) Mechanical design: solid shaft clamping flange 10 mm x 19 mm Communication interface: SSI, non-programmable Connection type: cable, 8-wire, universal, 5 m
IME18-08BPSZC0S	1040966 Inductive proximity sensors IME, IME18-08BPSZC0S Housing design: standard design Sensing distance Sn: 8 mm Installation in metal: Flush Electrical version: DC 3-wire Switching output: PNP Switching function: normally open Connection type: M12 plug, 4-pin
GTB10-P4211	Small light barriers G10, GTB10-P4211 Functional principle: reflection light scanner Functional principle detail: background suppression Switching output: PNP Switching type: light/dark switching Connection type: M12 plug, 4-pin Light transmitter: PinPoint LED Setting: potentiometer Communication interface:-
WL280-2P1131	Compact light barriers W280-2, WL280-2P1131 Functional principle: retro-reflective light barrier Functional principle detail: double lens Switching output: PNP Switching type: light/dark switching Connection type: cable, 3-wire, 2 m Light transmitter: LED Setting: potentiometer Communication interface:- Included in delivery: BEF-W280 mounting bracket, P250 reflector
WT34-B410	Compact light barriers W34, WT34-B410 Functional principle: reflection light scanner Functional principle detail: background suppression Switching output: NPN, PNP Switching type: light switching, dark switching Connection type: M12 plug, 4-pin Light transmitter: LED Setting: potentiometer Communication interface:-
WL100-2P3439	Miniature photoelectric sensors W100-2, WL100-2P3439 Functional principle: retro-reflective light barrier Functional principle detail: double lens Switching output: PNP Switching type: light/dark switching Connection type: M8 plug, 3-pin Light transmitter: LED Setting: potentiometer Communication interface:- Included in delivery: mounting bracket BEF-W100-A, reflector P250

VL180-2P42433	Round light barriers V180-2, VL180-2P42433 Functional principle: retro-reflective light barrier Functional principle detail: double lens Switching output: PNP Switching type: light/dark switching Connection type: M12 plug, 4-pin Light transmitter: LED Setting: potentiometer Communication interface:- Included in delivery: reflector P250
WL100-2P3439	
VL180-2P42433	
YG2A14-020VB3XLEAX PVC/4*0,34/GR/US	2095895 Connectors and cables Connection cables, YG2A14-020VB3XLEAX Connection type head A: Socket, M12, 4-pin, angled, A-coded Connection type head B: Open cable end Approvals: CE, UL Signal type: sensor/actuator cable Cable: 2 m, 4-wire, PVC Description: Sensor/actuator cable, unshielded Area of application: chemical sector
KTM-WP11172P	Contrast sensors KTM Prime, KTM-WP11172P Light transmitter: LED, RGB Communication interface:- Detecting distance: 12.5 mm Switching output: PNP Light spot size: 1.6mm x 9.5mm Light spot position: longitudinal Light emission: Long side of the device Connection type detail: Cable with M12 plug, 4-pin Setting: Teach-in button Teach-in procedure: 2-point teach-in static/dynamic + mark proximity, ET: Teach in static Housing material: plastic
RZT7-03ZWS-KWB	1070872 MASTER CYLINDER SENSOR Sensors for T-slot cylinders RZT7, RZT7-03ZWS-KWB Connection type: cable, 2-wire Switching output: Reed Switching function: normally open Typical travel distance: 10 mm Protection class: IP65, IP67 Supply voltage: 5 V AC/DC ... 230 V AC/DC Electrical version: AC/DC 2-wire
VT18-204470 REFLEXIONS-LT	Round light barriers V18, VT18-204470 Functional principle: reflection light scanner Functional principle detail: background suppression Switching output: NPN, PNP Switching type: light/dark switching Connection type: M12 plug, 4-pin Light transmitter: LED Setting: None Communication interface:-
KT5W-2P1113	
AHM36A-SCPK014X12 ABSOLUTE ENCODER	1079920 Absolute encoder AHS/AHM36, AHM36A-SCPK014x12 Singleturn or multiturn version: Multiturn Resolution max.: 14 bit x 12 bit (16,384 x 4,096) Mechanical design: solid shaft clamping flange 10 mm x 24 mm Communication interface: SSI, programmable Connection type: cable, 8-wire, universal, 1.5 m Programming interface: Via handheld programming tool, via SOPAS
KTX-WS91142242ZZZZZZZZZZZZZZZZZZ1	1078166 KTX, KTX-WS91142242ZZZZZZZZZZZZZZZZZZ1 Light transmitter: LED, RGB Communication interface:- Device type: Standard Detecting distance: 13 mm Switching output: PNP, NPN Light spot size: 0.9mm x 3.8mm Light spot position: longitudinal Light exit: Short device side Connection type detail: M12 plug, 4-pin Teach-in procedure: 1-point teach-in, 2-point teach-in, dynamic teach-in, Auto mode Delivery status: 2-point teach-in Housing material: plastic
	Programming and configuration tools, PGT-08-S Accessory group: programming and configuration tools Description: USB

PGT-08-S PROGRAMMING TOOL	programming device, for programmable SICK encoders AFS60, AFM60, DFS60, VFS60, DFV60 and pulley encoders with programmable encoders
DSL-3D08-G0M5AC2 LTG,ST/DS 0M5 M23/SUB-D	Connectors and cables Connection cables, DSL-3D08-G0M5AC2 Connection type head A: Socket, M23, 12-pin, straight Connection type head B: plug, D-Sub, 9-pin, straight Signal type: SSI Cable: 0.5 m, 8-core, PUR, halogen-free Description: SSI, shielded, programming cable for programming tool PGT-08-S and PGT-10-S Note: Suitable for use with SSI interface, not for use with Interface SSI + Incremental or SSI + Sin/Cos suitable., Programming adapter cable for programming tool PGT-10-Pro and PGT-08-S
STE-2312-G LTG.STE. M23 12P.GE	Connectors and cables Assembleable connectors, STE-2312-G Connection type head A: plug, M23, 12-pin, straight Signal type: HIPERFACE®, SSI, incremental, RS-422 Description: HIPERFACE®, shielded, M23 connectorSSIIncrementalRS-422 Connection technology: solder connection
BEF-FA-020-036 FLANSCHADAPTER	flanges Mounting flange, BEF-FA-020-036 Description: Flange adapter centering collar D20 to D36 Scope of delivery: flange adapter, screws for encoder mounting (3 pieces M3 x 14 cylinder head)
SKS36-HFA0-S05	Motor feedback systems rotary HIPERFACE® SKS/SKM36, SKS36-HFA0-S05 Communication interface: HIPERFACE® Version: Absolute single turn Type: built-in Sine/cosine periods per revolution: 128 Safety-related system: no Mechanical design: conical shaft, spring plate support Connection type: plug, 8-pin, radial Technology: Optical Operating temperature range: -20 °C ... +110 °C Special feature: Without side fastening screws, delivered in Revolving packaging (020-240-000-710), operating instructions 8013452 not included Scope of delivery,
DME5000-117 DISTANCE MEASURING UNIT	Long-range distance sensors DME5000, DME5000-117 Measuring range: 0.15 m ... 70 m, on "Diamond Grade" reflective film Repeatability: 0.5mm Accuracy: ±2mm Output time: 2 ms Communication interface: HIPERFACE® Connection type: connector, 1 x M12, 4-pin, 1 x M12, 8-pin Current consumption: At 24 V DC < 250 mA
DS50-P1122 DISTANCE SENSOR	Mid-range distance sensors Dx50, DS50-P1122 Measuring range: 200 mm ... 10,000 mm, 90% reflectance200 mm ... 6,000 mm, 18 % reflectance200 mm ... 4,000 mm, 6% reflectance Minimum response time: 20 ms Digital output: 2 x PNP Light transmitter: laser, red Laser class: 1 Multifunctional input (MF): 1 x
RT-P3231	1063131
WL18-3P430	1025911
DME5000-117 Distance Measuring	
DS50-P1122	
PGT-08-S	
AD-ATM60-KA3PR	Bus-Adapter KR3, 3 x PG IP67
VTE18-3F4740	

LMS111-10100S09	
6026473 Sick Induktiver Sensor Iq80-50bpp-Kco	
Eks36-0kf0b018a	Motor feedback systems rotary HIPERFACE DSL® EKS / EKM36, EKS36-0KF0B018A Type: installation Communication interface: HIPERFACE DSL® Mechanical interface: torque arm Connection type: Plug 4-pin Safety-related system: no Resolution per revolution: 18 bit Country of origin: DE; Stat. Product number: 90314990 EC dual use / export list number: non;
6052379	
7029163	
Iq40-20bppk0s	
1040696 Wt4-3p3441s38	
6008900 Stecker Mit Kabel 2 Meter (Eckig)	
2073484	
1019248	
7122797	
1028936	
1064461 Scanner	
1036028	
1026538 Sensorkt5w-2p1116d	
1063923	
6044999	
2064574	
WI12-3p2431	
1209148	
1026834	
WI45-P260	
1019253 Lichtschränke Ws/We34-V230	
1016629	
Wt14-2p432so8	
2076544	
Dt50-N1113 Abstandssensor	
Re27-Sa05l	

Dos-1204-W
Dbv50e-22eka2000
1052595
Wlf18-3v930
6047606 Thts-1aat11006mz
2105497 Kabel
Wl11-2p2430
Srs50-Hza0-S36 Encoder Motor Feedback
2071778 Dos-2312-Ready-To-Gs02montage Steck -Steckverbinder
6054714 Ultraschall-Sensor
5311210 Pl10f Reflektor
Al20e-Pm331s01
P/N: 7102162, Type: Dol-Ms10-G05mma3
1052866
7101656 Dgs35-1h408192inkrementelles Wegmess
6055955
6036082 Wl8g-P2231s01 Lichtschranke
Bef-W280 Montagewinkel K. V. Optischen
2045739
6010543
6022774
6024788 Ws/We140-2p132 Sensordie Bestimmungen Optoelektronnyj
Wl12l-2b530s03
1018975
Clv620-2000s01 Scanner
Ds35-?15221 Abstandssensor
1046894 Inductive Sensor Ime 18-08-Nppzc0s (No/Nc)
5310602
Dme4000-321

P/N: 1057792, Type: Ttk50-Hxi0k02
Wtb4t-3n1264
6041752
6022083 Ste-1205-G Stecker Gerade(Papst)
Ws/We100I-F223
Dme4000-211s06
1068866
6022012
1043006 Kt5w-Sensor 2b1116kontrastierenden Markierungen
Dfs60b-Bhak01024
6024791 Ws/We140-2p430 Through-Beam Sens.Sensorbestimmungen
P/N: 1063567, Type: Ttk70-Hxi0-K02
6009719 Anschluss Typ Dos-1205-G, M12, 5-Polig
Dt35-B15551 Sensor
1040984 Stellungsgeber
Im18-08n-N-Zwo
6013533
1025326
6063340 Sensor Lichtschränke. Typ: GII170t-B432
6013254 Sensor
1059031 Encoder Absolute Afm60a- Bhnb018x12
2025238
6030715
S30b-2011da Agv Sensor -
1062542
6036841 Wfl120-95b416 Geschlitztsensoren
6010192
1052700

6049678 Ufn3-70b413
6007988 Dos-1612-W Steckdose (Ready-To -Montage)
Dt500-A211
I12-Sb213
6032451
1026244 Kt3l-P3216
1040747 Ime12-Induktiver 04npszc0ksensor
6034414 Ssl-2j04-G02meanschlussskabel Mitstecker Und Stecker
1036354 Encoder Dfs60e-Beek01024
6022083
1016910 Magnetischer Zylindersensortyp: Mzt 1-03 Vps-Kp 0al: N Ecen:
6025907 Dol-1205-G05mcstarthilfekabel Mitweiblicher Teil
Im12-04nps-Zqd Induktiver Stellungsgeber
5321625
5304812 Leichter Reflektor
1037729
Wll170-2p162
1028669
6022083 Connector M12 Sick Ste-1205-G
1026538
1071843 Iq40-15bpp-Kko
6048407
1036074
1037909
Dol-1204-G02m
1027770 Wl27-2f440
2085763 (Ex.2077728)
1207969

Srm50-Hwa0-K21
6052362
Dos-1204-Gz Stecker
2045890 Spring Terminal Set
6011971
Pl40a Reflektor 41 X 60
1036077
1053411
6058497
1040736 Induktiver Sensor Ime12-02bpoz0s
1030001
Wtb9-3n1161
M40e-034000rr0
1016934
6009932 Ste-1204-G Stecker M12 4-Pin., Luftlinie, "papa"
1041290 Barcodescanner, Clv650-0000
1099335
1036081
Icr620s-T11503 Barcodeleser
1085373
1026515
1207795 Sensor
1040856
5308445 Bef-W n-M30 Befestigungssystem
Bef-Ha-M18r
1053167
1072273
4026324
1059925
6044736 Optischer Sensor

P/N: 7102161, Type: Dol- Ms10-G03mma3
1057655
1030009
Wtb12-3p1111
1019251
1062420
T4000-1kba
1053126 Dfs60b-
Bdea01000inkrementelles Wegmess
Dt20-N130b0960 Optischer Sensor
We12-2p430
Uc4-11341
1026820
2029245
Dmt10-2-1213
1053168
1062110
1070720
Im30-22bps-Zc1
2025264
1070814
Dme 4000-111 Long-Range-
Distanzsensoren
6022084 Ste-1204-W Stecker M12, 4-Pin -
Ecke (Papa)
Wt12l-2b550-T01
1065661
Kt3w-P1116
1016592
Lm31l/450
1029951
6024916
1022603
1053131

C4c-Ea12030a10000	
M40z-043000tr0	
6030710 Sensor	
1040966 Sensor Ime18-08bpszc0s	
6048061 Photoelectric Sensor	
1028097 Sensor Wtb4-3p3161	
Vfs60a-Bh pz0-S01	Encoder
Ime18-08nnszw2s	
??-3583? 100 ??? 16 ???	
Wl36-R230	
Bef-Dsdt	
1044369 Optischer Sensor	
Drehgeber Dgs35-1h408192, Lines - 8192, 5vdc	
5327812 Sensor	
1033490	
We12l2p430	
Bef-W170	
6041818 Optic Sensor Vl180 - 2p41131	
1037981 Encoderdfs60bbdcc01024	
1051889 Wtb9m4-3p2261	
58072117	
C20e-045304	
6039094 Wl180t-N432fiberoptikoptoelektronische Sensoren	
P/N: 1053558	
2068147	
1041986 Barcodeleser Clv631-6000	
1016806 Reflektor Pl560dg665 Mm X 665 Mm	
Dfs60b-S4pk10000 Drehgeber	
5313885 Bef-W280 Wannensicherungswinkel	

1033548	
1012720 Reflektor PI40a	
Srm50-Hfa0-K21	previous material number: 6CF-KR0-202-000 Motor feedback systems rotary HIPERFACE® SRS / SRM50, SRM50-HFA0-K21 Type: installation Communication interface: HIPERFACE® Mechanical interface: Spring plate support Spring plate support Connection type: Plug 8-pin radial Safety-related system: no Resolution per revolution: 4,096 Country of origin: HU; Stat. Product number: 90318020 EC dual use / export list number: non; US ECCN: non
P/N: 7102165, Type: Dol-MS10-G30mma3	
Ars60-A4b00360	
7900099	
4035439	
Dos-1612-G Stecker	
1003865 Reflektorpl80a	
P/N: 1053007	
Btf08-A1am	
1033532 L230-Linear P580c2s00000endlosregler	
2013942 Montageplatte	
1036087	
1082138 Kontrastsensoren , Ktm- Wp11172p	
Kt10w-2p1115 Contrast Sensor Sick	
6025911	
S30a-4011da S3000s	
210802 Ultraschallsensortyp: Um 18- 51111artikel-Nr.: 6028965	
Atm60-A4a0-K06	
6 009 867 Kabel Dol-1204-W05m	
1059555	
Lms511-11100	
Mm12-60aps-Zck ? Dos-1204-Wx Sensor	
1025245	
20227180	
VI184p3240 (Ex.VI180p430)	

Msle02-25011 Satz
1034263
1040853 Induktiver Sensor
1070871rzt7-03zws-Kw0
1036924 Endlosregler Df60b-Tepk1000
Ps95w-24v
1019280
6011048 Wt150-P162reflexions- Lichttaster Mit Hintergrundausblendung
Strl-Xas Opto Sensor
We27-2d430 Dc10
1041263
Foto-Elektrischer Sensor Wtf12-3p2431
Ds50-P1112
6037481 Sensick V180-2 Vte180-2n41147 (Npn)
1036193
1036456
Dol-2312-G03mma3
Dol-1204-W 10mrn
1069860
WI260-P230
1036455
2075254
1036100
1017910 PI240dg Reflektierendeplatte
6028626
6044701
Iq80-50bpp-Kc0
1018250 Sensor Lichtschränke Sick Wt12l- 2b530
1052438
6022083 Ste-1205-G Ready-To -Montage

Steck -Steckverbinder
1051529
1047314 Sensor Dt50-P2113
.Srm50-Hwz0-S35.
P/N: 1053765
Iq40-20bppkcok
1041385 Sensor
Dme4000-211
Atm60-A1a-12x12 4096
6034576
6052615
P/N: 7102160, Type: Dol-MS10-G1m5ma3
Wtb12-Sensor 3p2441optoelektronnyj
1060534 Inkrementaler Drehgeber Dbs36e-Bbek01024
2096215 Kabel Patch Yg2a15- 020vb5xleax
1037697 Endlosregler
2096239
Im18-08nps-Zwb
C40e-S113
Ste-1205-Wq
1200126
6038659
1060294
1088196 Encoder Dfs60a-S1pk10000
1036014
1053258 Kt5w-2p1156s41
1019254 Sensor Ws/We-B430.
1 040 950
Mb320-0008
2095888 Yf8u14-020va3xleax
5308050 LI3-Tb01

1041411 Sensor Lichtschränke Wtb12-3p2431
Wl100l-F2231
1071200
Lp10 -01000444
6041802
Wl14-2p431
1036992 Vfs60a-Thpz0-S01motorfeedback-Sensorposition Pulse
6032638
1063375
1066198
6024920
1040838 Induktiver Sensorime081b5psztos
6021353
1206482
I17-Sa213 Elektromechanischer Schalter
Ars60-F4a00360
2062450
Im12-08nps-Zc1
6036831 Wfl30-60b416 Fork Sensor
6029507
6058483
Gtb10-P4411s01
?4?-??03030?10000 Sender
2095888
1029200
Bef-Wn-Dx50
P/N: 1069972, Type: Vfs60e-Bjck01000
P/N: 1059513, Type: Vfs60b-Bhaj02048
1003865 Reflektor PI80a
6009867

10410763	
Bef-W n-W45 (2011480)	
C4mt-03634abb03de0	
6027511	
Srs50-Hza0-S21	
1041376 Sensor	
6036923	
2023797	
C41e-0301ag300	
1052684 DI100-Sensor 21aa2101entfernung Ssi	
1041390 Sensor 4m Palletizer WI11g- 2b2531	
Am164-81a000000037	
1040976	
???-301-???4 ???1 0,25/0,6/0,6	
2013353 Dol-1612-5m-2 Ltg,Rd.Dose/Aeh 5m0 12a	
6013117 Sensor Vte18-4p8212	
1023547	
5308050 Lwl-Kabel	
We24-2b230	2021160 Receiver, PNP / NPN, H / D
1203241 M40e-63a503rb0 Multiple Beam System Mehrstrahl-Sicherheitssystem	
WI9-2p121	
6058495	
6058505	
4019634	
1046763 Spl-S280pps1w04	
6009868	
1079051 Dbs60e-S4ec00100 Incremental Encoder	
Dks40-E5I00200 Endlosregler	

[6020688 Optischer Sensor WI150-P420
Wlg4s-3p2232 Sensor](#)[DI100-22aa2101 Sensor Distanz](#)[1018253](#)[6052374 Wt100-Sensor 2p4439optisch](#)[5312981](#)[Ime12-04bpszcok](#)[Srs50-Hwa0-K21](#)[1041404](#)[Fx3-Xtio84002](#)[6058476](#)[VI18-3p3140 Photoelectric Sensor
6013527](#)[6034414](#)[Dol-1608-G10ma](#)[5326523 PI30f Reflektor](#)[Kabel Zum Sensor](#)[1072836](#)[1041132 Sensor Wse4-3f2131,Reflex](#)[1052446](#)[1041456 Sensor WI12g-3b2531](#)[6011992 Induktiver Sensor](#)[1042046](#)[Ime18-08bpszc0s Induktiver Schalter](#)[2019649](#)[1019237 Lasersensorwt34-B440](#)[Mps-032tstp0](#)[WI100-P3330](#)[2045643](#)[1066556](#)[1036108](#)[Ih03-0b6ns-Vu1](#)[1046399](#)

1071746
Dt20-P214b
Dsl-0612g01m075km0
1036759 Dfs60b-S1pm10000inkrementelles Wegmess
Mhl15-P3236 Optischer Sensor
Vs/Ve 18-4p3240
Dfs60b-S4pc10000 Endlosregler
1067186 2d-Lidar-Sensortyp: Ld-Lrs3611
1044124 Fx3-Xtdi80002 Controllersicherheit
1045104
6048393
6024907
5313025
6052386 Sensorminiatur-Lichtschraken, WI100-2p4429
1081712 Sensorcfs50-Aaz00s13
6011047 Optischer Sensor Wt150-460
2029227
Tsp-1qag10606mzs
6022082 Stecker Ste-1205-W Sick
6007302 Dos-1204-G Stecker M12 4pin
WI11-B560
Im020bm45vb8
1060232
6009974
??-3583? 63 ??? 16 ???
Gtb6-N4211
6028454 Sensor Wf50-40b416
1065640
6043823
Wt12l-2b530 P/N 1018250

1082456
1040895 Sensoren Sick
1036490
1051434 Vfs60a-Thpz0-S03 Programmierbare Encoder
6025910
Obs-W45
1048117
6021125
1062094
Ws/We45-R260
Dos-0803-G
1027763
M40s-025010ar0
1037235
1064593
6010185 Optischer Sensor
6054708 Uc4-13346 Ultraschallsensor
1000131
1027858
1012719 PI20a Reflektoren
Kt5w-2p1126
2014457
6044736 Wl280-2p2431lichtschränke
1058622
6024878 Sicherheitsrelais Ue42-2hd2d2
2095963
Iq08-04npskw2s
Wsg-Dsdt
Wtb4sc-3p2232 Pnp Sensor
S30a-6011ba
1003865 PI80a

[1036787 Inkremental-Encoder, Dfs60b-Bhpk10000](#)[Dme4000-115](#)[1076983 Lichtschränke Gr18-P2452](#)[1043784 Fx3-Cpu130002
Controllersicherheit](#)[Wtz72r610](#)[1204147](#)[6034574](#)[Dt50-2b215252](#)[1018665](#)[1025912](#)[1027775](#)[1041390 Sensor 4m Wl11g-2b2531](#)[Od1-B035c15a14](#)[6029832](#)[1036090](#)[Dme4000-227](#)[6048401](#)[Wtb27-3p1111](#)[1026538 Kontrastreicher Fotosensor
Kt5w-2p1116d](#)[6024915 Ue48-2os2d2 Sicherheitsrelais](#)[6022774 Sensor](#)[100 1019](#)[1039017](#)[6025907](#)[C40s-1503ca010](#)[1040749](#)[6022742 Sensor](#)[Mhl15-P3236](#)[1048152](#)[2079314](#)

1051072
P/N: 1053168
1043006 Sensor Kt5w-2b1116
WI24-2b333
6028359 Ste-1204-Gn Stecker (Fertigezur Montage)
6022369
WI100-N4439
6028422 Dos-1208-G Socket Pg9 M12-8p M12-Stecker
1052427
6048420 Um18-218161101ultraschall-Sensoren
6027931
6020478
1031556 Winkel-Sensor Ars60-F4a00360 (1031556) Verbindet Sich Von Der Spielmarke
2031079 Werkzeug
1078126
Drs60-D4a01024
2024896
Wtb250-2p2451 Optischer Sensor
Ie12-F1
1016019
6033211 Sensorwtb8-P1111
1029791 Dme4000-212
6026473
1027770
Olm200-1002
1026052 Sensor Lichtschränke Wt14-2p422 Dc10 30v Class2 500mm
1003122
6036923 Um30-213118 Stellungsgeberultraschall

1017405	
6009932	
C4c-Ea04510a10000	
WI34- R240	
1202667 Transmitter - M40s-025003ea0	
WI280-2p2431	
Kt5w-2n2116d	
1019237	
1019249	
Clv430-6010	
Dfs60e-S4ea00360	
Im30-15bps-Zc1	
6011050 Optischer Sensor	
2096357 Anschlusskabel	
1036354 Dfs60e-Beek01024 Inkrementaler Drehgeber	
Srm50-Hxa0-K22	
Wtr2-P511	
6022880 E100-B2a22s10a Steuerungsblock	
6032861	
Dfs60a-S4pa65536	
6032676 Modul Relaisausgang Ue410-4ro4	
1016932	
6027577	
1035242	
1043783 Fx3-Modul Cpu000000flexisoft	
Ekm36-0kf0b018a	Motor feedback systems rotary HIPERFACE DSL® EKS / EKM36, EKM36-0KF0B018A Type: installation Communication interface: HIPERFACE DSL® Mechanical interface: torque arm Connection type: Plug 4-pin Safety-related system: no Resolution per revolution: 18 bit Country of origin: DE; Stat. Product number: 90318020 EC dual use / export list number: non;
Wtr2-P521s09	

6048416 Uc12-12231 Stellungsgeber Ultraschall
6009382
Pbs-Rb250sg1ssnamaoz
6009873
?2?-Ea09030a10000
1025896
Yf8u13-C60ua1m2a13 Verbindungskabel Mit Steckern
Wl9-3p1130
2022544
1200129
1030013
Skm36-Hfa0-K02
6036917 Sensor
1035239
1061396
Wt18-3p610
6 009 869 Kabel Dol-1205-W05m
1018044
6020312 Im12-02bds-Zc1
Wf80-60b410
2034324
Ar60 1015741 Befestigung
1031556 Ars60-Absolute F4a00360wegmess
1018587 Sensor Typ: Kt5w-2p1126
1325354
7028790 Netzteil Und Netzkabel
1015993 Sensor
Um30-213112
6037782
6058156

1010994 Einweg-Lichtschränketyp: Ws/We 45-R 250
6012640
6010542
6028431 Sensor
WI24-2b230s02 Sensor
1036121
2045891
1002314 Reflektor PI30a
Dt35-B15552
2055634
1041725 Scanner Lms400-2000
6041423
Dme4000-214
C40s 0603ca010
1037395 Srs50-Hza0-S21 Systemfeedback
1046135
P31267
Drs60-Eam01000
1058182 Wse9l-3p2237 Photoelectric Switch Lichtschränke
WI9g-3n1234s02
1040870
2042516
1045096 Sensor
6049679 Schlitzsensor
1053183
WII160-F122
6020598
1057643 Kt5w-2p2156s42
1046449 WIg4s-3p3432vlichtschränke
P/N: 6037423, Type: Mvm-04m-2mc-Mklb

6052613 Kabel
Wt24-2r210
1063542 Dfs60e-S1ec01000incremental
Encoder
1070847 Rzt7-03zrs-Kp0-Sensorposition
Magnetisch
1038186 Endlosregler
1059455
2055427 Bef-Slg-Set1
Cdb620-001
6012820
Wtb9l3p2261
1017857
6009383 Dol-1204-W02mstarthilfekabel
Mitweiblicher Teil
1060544 Dbs36e-S3ek01000
Inkrementaler Drehgeber
6009869
5333571 Madenschraube
Ktm Wp11181p
1059039 Absolut-Encoder, Afm60a-
S4nb018x12
1019311
F8u13-C60ua1m2a1
1050768
Bef-Wg-W12
6036918 Ultraschallsensor
1044458
Ime08-02bpszt0k Sensor
6036644
5313019
Gr18sg-E233z 1061927 Optischer Sensor
Dfs60e-S4ea01024 Endlosregler
1211474

23444
C40s-1501da010
5326704 Kup-0810-D
Wt36r230
1037855
1074296 Dbs60e-Thezd0s18 Incremental Encoder
1209147
Wtb4-3p3161
1056428
1037799 Endlosregler (Ident.Nr1037799)
6032669 Ue410-Mu4t5 Controllersicherheit
1059401
LI3-Db01 Glasfaserkabel
1040966 Ime18-08bpszc0induktiver Stellungsgeber
S30a-4011
1051521 Encoder Dfs60e-Thek01024
6 009 868 Kabel Dol-1205-G05m
WI100p4409
6009720
6021175
1044369 Abstandssensor
1081580
1052592
WI250-2p2431
1040764 Ime12-04bpszc0induktive Sensorenproximity
K-SI30-02000-080-1
1036453
1213213 C2c-Ea12030a10000lightcurtain Receiverlicht Schleier Sicherheit
We27-2f430 Dc10

1026049
7900097 Induktiver Sensor Sick Im18-12nps-Zc1
1047396
6037824 Gabelsensoren, Wfm50-60p321
6027538 Dos-2312-G
Olm100-1001
6010785 Dol-0803-G02m Kabel 2 M Mitanschluss 8 Mm 3 Pin
P/N: 1053167
1028487
1040738
1046317
6036385
Bkss20805
1064990
5308074 LI3-Db01 Glasfaseranschlusskabel
Dme4000-121
Pr-Ste-1205-G
1028100 Der Optische Sensor Wtb4-3p2261
1018666
Bef-Khs-K01
VI180-2p42433 Fotosensor
Wt45-P 250
1044075 Fx0-Gpro00000 Controllersicherheit
1022243
Wtv4-3p3441
Dol-1205-W 05m
2096244
We272f450505
1040898

6029831 Sensor	
Lfv310-Daftvxmtx 6041204	
1046012	
Vte180-2n42482 Sensor	
Wt12-2p440 1 016 150 Dc 10..30v	
Pgt-01-S Programmer	
6030928 Ssl-2j04-G10me Starthilfekabel	
6053042	
6029280	
Sks36-Hfa0-S05	previous material number: 6CK-100-200-012 SKS36-HFA0-S05 MOTOR FEEDBACK HIPERFACE 128 sin / cos periods *** RoHS compliant according to EU Directive 2005/95 (from date code 08/36) Country of origin: DE; Stat. Product number: 90314990 EC dual use / export list number: non; US ECCN: non
Bcg05-A1nm0155	
1052684 Distanzsensor DI100-21aa2101	
Wtb4-3p2161	
1041060 3. Ime30-20nnozW2s	
Srs50-Hta0-K21	
2022547 Dol-0612g10m075km0 M26*12	
6025906	
1026538 Kt5w-2p1116d Kontrastsensor	
Wt12-2p440 Sensor	
1092617	
2108625	
M40z-025023tb0	
6063342	
1203240 M40s-63a503aa0 Multiple Beam System Mehrstrahl-Sicherheitssystem	
Dme4000-313	
1200130	
6037662 Sensor Um30-214111	
Wt34-R240	

1040780	
1000382 Reflektor	
1042040	
1047581 Dt50-P1114 Distanz Sensor	
L21s-21ma1a	19/K028940- 1
1058853	
Im04-0b6ps-Zu1	
Wt18-3p410-50-700 Sensor	
Pbs-Rb1x0sgess0bma0z	
6027538 Dos-2312-G P/N 6027538	
6060127	
6009873 Dol-0804-Stecker Mit W05m Kabel 5m	
Wl160p132	
6049456	
1040767	
Atm60-Pah13x13	
1048379	
1082138 Sick Sensor Ktm-Wp11172p	
1059958 Optischer Abstandssensordl100-11ha2101	
2058653 Bef-Ah-Traeger Fuer Dx100dl100	
5306535	
6011050	
5311137	
S30a-6011ca	
2029205 Dol-2312-G30mma1starthilfekabel Mitweiblicher Teil	
1071845 1071845 Iq40-20bpokk0sinduktive Sensorenproximity	
1036750	
Ws27-2d450s05	
6044336 Pressure Sensorpbs-Cb2x5sg1ssnama0z	

1028153 WI4-3f3130 Photovoltaiksensör	
Srs50-Hfa0-K21	previous material number: 6CF-KR0-102-000 Motor feedback systems rotary HIPERFACE® SRS / SRM50, SRS50-HFA0-K21 Type: installation Communication interface: HIPERFACE® Mechanical interface: Spring plate support Spring plate support Connection type: Plug 8-pin radial Safety-related system: no Resolution per revolution: 1 Country of origin: HU; Stat. Product number: 90314990 EC dual use / export list number: non; US ECCN: non
1064706	
Dos1204-G Stecker Female Connector	
DI100-21aa2112	
Ws27-2d450505	
1023890 S30a-7011ba Laser-Scannersicherheit	
1017428 Sensor Im12-02bps-Zck	
1048152 Sensor Al20e-Pm331s01	
6036919 Ultraschallsensoren , Um30-214113	
2045890 Spring Set Terminal	
1040774 Sensor Ime12-04bnszw2s	
Bef-Mu-M08n Sensor	
6020683 Optischer Sensor Mit Spiegel	
1035240	
1059958	
6034484 Ue410-Mdi3 Controllersicherheit	
4069422	
Clv620-0000	
1036664	
Wt45-P200s03	
1041689	
6028958 Sensor	
1056708	
Srm50-Hza0-S25	
1060992	
2095609 Kabel Patch Yf2a14-100ub3xleax	

1036747
Wtb27-3p2411 Sensor
7902925
2023616
2096356
1028153 Sensor
C41s-0301aa300
1211505
1036923 Encoder Dfs60b-Tdpk10000
6026211
4051184
2092035
1028161 Sensor Ws4-3d3130
1053765
1036109
1041404 Wtf12-3p2431 Lichtschränke
6030704
M40s-034000ar0
WI12-P1331
Wt34-B410
7101661
1046396
1218660 Optoelektronische Sensor. Typ: Wla16p-24162100a00
C4mt-12034abb03fe0
Lbst32900
Afm60a-Benb018x12 Encoder
BI16010
P/N: 1059306
6035225 Typ: Imf18-08nppvc0sp/N: 6035225al: N Eccn
WII190t-2n432
7028790

Wtf4s-3p3231s08photoe.Prox.Switch
WI9-2p330s10 Lichtschränke
Imb08-04npovt0k
I110-Ra223
1058230
6010190 10-30
Cable5m
1049042 Sensor Lichtschränke Sick Wtb9-3p1111
Wt100-P3430
6052628
P/N: 1057793, Type: Ttk50-Hxq0k02
2073483
WI34-B430-S03 Sensor
1034094 Skm36-Hfa0-K02 Sensor-Feedback-System (Encoder)al: N Eccn
1058701
1070849
1070814 Sensor Mzt1-03vps-Kp0
M40e-025010rr0
6020112 Induktiver Sensor
Bef-25mmeaku4
Dos-1205-G Cable Connector 6009719
7902138
WII6-P122
1025575 Light-Grid
6011033
1036094
Ste-1204-G Stecker Male Connector
1044120 Wse12-3p2411s36
6036916
Btf13-P1hm0525

1211473	
1018669	
C40e-1501da010	
6011050 Miniatur-Lichtschranken, Wt150-P460	
1026036	
6027538 Stecker (Kabel-Teil) Sick: Typ Dos-2312-G	
7020046	
Vtf18-3f1640	
1028232 Sensor	
5308074	
Wtt12l-B2562	
Wl272p630 (01015108)	
Wf240b410	
C40e-0603da040	
1018045 Kt5w-2n1116 Sensor Kontrast. Tags	
1070852	
6051061	
1040764	
6025067	
1213212 Sicherheits-Lichtschranke2c-Sa12030a10000	
Wlq4s-3p2232 Lichtschranke	
Ds500-P111	Long-range distance sensors Dx500, DS500-P111 Measurement object: natural objects Measuring range: 0.2 m, 0.8 m ... 30 m, 15 m, 90% remission, 6% remission Repeatability: 1 mm Accuracy: ± 3 mm Laser class: 2 (IEC 60825-1: 2014, EN 60825-1: 2014) corresponds to 21 CFR 1040.10 and 1040.11 with Exception of the deviations according to "Laser Notice No. 50 "from June 24, 2007
Fx3-Mpl0000001	
Dol-1205-G05m	
6044760	
Wtb27-3p2413	
6028411	

1081580 Lichtschranketyp:HI18-P4a3aas06
P/N: 7102163, Type: Dol-MS10-G10mma3
1019227
Dme3000-232p
Wt27-2f410
Dol-1205-G10m
2046459
Zt2-P4228 Sensor Lichtschränke
1218698 Klein-Lichtschranken, Wtb16p-24161220a00
1029861
1081580 Lichtschranketyp:VI180-2p42436
6032866 Dol-1208-G02mac1 C
C40s-S113
2029216
6013675
WI 160-F440 9634f
6035225 Induktiver Sensor Imf18-08nppvc0s 6035225 Dc-10-30v, Ia=200ma
1371167
1040748 Ime 12-04npszc-0s Np1029
WI150-N132 1330f Sensor
WI-272f440
1037006
6009383
Clv-650-0000
Fx3-Cpu00000
C4p-Sa04530a001200
Um30-213111 Ultraschallsensor
6013110 Sensor
6020993 Dol-1208-G05mastarthilfekabel Mitweiblicher Teil

6021354
6033186 Wl8g-P2131 (6 033 186 1537h) Mit Anschlusskabel
6025907 Dol-1205-G05mc Mit Steckerkabel 5m0
Wtbs-3p3464v
6025909
1045093 Der Optische Sensor Sick Wtb4s- 3p2235v
Wte280-2n4331
Wtb27-3v2411s02
1053535
6024798
Vtf18-4p1440 Optischer Sensor
Ste-1204-Ge01
Wl280-2r4331 Optischer Endschalter
2030645
Ds500-P511 Codice 1040479
1036112
Dme4000-124
1052108
1018252 Wl12l-2b530 Reflexions-Lichtsch
Wse12-3p2431
7047654
7x03
6053761 Sensor Wfs3-40p01cs01
6041804 Sensor
Wtb4s- 3p2131photoe.Prox.Switchlichtschranke
Bef-W 100-A
6037503
Kt5g-2n111
We272p630

[7074065 Der Optische Sensor Grs18-D2421](#)[6007363](#)[Im08-01b-N-Zw0 Induktiver
Stellungsgeber](#)[???-102-111?-?-0,15/0,15](#)[Vs/Ve18-4p3240](#)[6036918 Sensorum30-213113](#)[7902077 Dos-0803-G-Steckdose \(Ready-
To -Montage\)](#)[Dme3000111](#)[6020757 Hirschmann Cable Socket
M26x22+fe, Gerade](#)[Idec Hs7a Safety Sensor](#)[1037612](#)[6026008](#)[1213202 C2c-Licht
Sa04530a10000schleier Sicherheit](#)[1018651](#)[6039745 Bcg05-K1km01pp Mit
Drehgeberseilzug Trommel](#)[2025268](#)[1040012 Dt20-P214b Verschiebungs-
Sensoren](#)[6022751](#)[6037472 Anschlusskabel Mit Stecker Stl-
1204-W05mc](#)[P250f](#)[Bef-W 4-B](#)[Yg2a14-020vb3xleax](#)[Grte 18s-F234z Optischer Sensor](#)[1025492 Elg3-0930p511 Eco-Lichtgrid](#)[1058175](#)[6051030](#)[Um12-1192261](#)

1052684 Sensor
5308048
Clv632-0000 Scanner
1016911 Sensor
Iq40-40nppkc0k Sensor
Dfs60b-Bzpz0-S01
2045601
6042565 Anschlusskabel
C2c-Ea03030a10000
6052360 Stellungsgeber Sick, WI100- P1439 Retro-Refl. Sens
Reflektor
1023002
Gtb10-P4211 Sensor
1047402
P/N: 1058957, Type: Vfs60b-Beek01024
Im04-0b6ps-Zu1 Sensor
Wt150-P460 Sensor
Im30-15bp0-Zc1
1060544 Endlosregler
2031895
1049061 WI9-3p2462 Lichtschrankensensor
Wtb9l-3p2261
1063175 Rt- B2221multifunktionsoptoelektronische Sensoren
Rt-P3231 Optischer Sensor
1036560
5304812 Reflektor P250
6005698
6 009 872 Kabel Dol-0804-G05m
1062251
1041385 Sensor 10m Conveyor Line WI11- 2p2430

Ime18-05bpszc0k
1034308 Btf13-P1hm2025
1010994
Bracket
5308445
1015741
6025901
Wt24-2v540s10
2096215 Yg2a15- 020vb5xleaxstarthilfekabel
1213213 C2c-Ea12030a10000 Lightcurtain Receiver Licht Schleier Sicherheit
6052386
1017810 Sensor Kt5w-2p1123
1059333 "photo Electric Sensor,Make- Sickmodel-Gtb6-P511
1017815 Sensor Lichtschränke Wt24- 2b420s08
Wll170-2p132 Lwl Lichtschränke
Dt500-P111
Wt27-2f430
Ue403-A0930
1040769
1057064
6058145
Pl80a
Bef-Wg-W 24
1023971
1051521 Dfs60e-Thek01024 Inkrementaler Drehgeber
7902926
1016933 Wt24-2b410
LI3-Tw01-3
Drs60-E4I00500

Iq40-15bpp-Kk1
Dme4000-323
5306531
6033209
1018045
2019659
1211506
6024912 Sicherheitsrelais
6033207 Wtb8-P2131 Stellungsgeberoptoelektronnyj
1007167 Nt6-03025 Kontrast-Sensoren
Im12-04nps-Zc1
P250f Reflektor
Dt35-B15551 Laser Sensor
LI3-Tr02
We9-3p3430
PI80
6037819 Wfm30-40p321 Fork Sensor Position Sensor
1071153 Lichtschränke
1050589
1047578 Lichtschränke
P/N: 1053509
Vfs60a-Bgpz0-S01
Dfs60b-Bdpl10000
5308843 P250f
We27-2f450s05
1017860
Wt160-P460 Proximity/Reflex Sensor
1040966 Ime18-08bpszc0induktive Sensorenproximity
6041819 Stellungsgeber Optoelektronnyj
2033559 Einweg-Lichtschränketyp: We27-3p2430

1033490 Sicherheitsschaltertyp: Eg342-81b001012059
1030009 Atm60-Absolute Aaa12x12multi-Turn-Drehgeber
1072806
1213212 C2c-Sa12030a10000 Lightcurtain Transm.Licht Schleiersicherheit
C4mt-06034abb03fe0
Um18-20012
Ste-1205-Ga
1044124
C20s-045104
1022602
6012829 Sensor Vtf18-4p1212
Tr4-Sdm01c Schalter Notaus 6044638
6026558
Ws100l-D2231 Lasersensor
1040872
1036640
1075436
1076666
1019256
6033948
Dol-1202-W10mc
Ime08-04nnszw2k Induktiver Sensor
P/N: 1070947, Type: Vfs60b-Tgek02048
1059632
6033207 Wtb8-P2131 Stellungsgeberoptoelektrisch
1051547
Im18-12nps-Zc1 Sensor
1051547 Dt20-Sensoren P214bs03bias
2095608

PI30a
1041411 Stellungengeber Optoelektronnyj Wtb12-3p2431
6038697
1200060 Sperre Luminous M40s- 025003aa0
6033225
6011971 Induktiver Sensor
1040839
Dg90-5f1xb0l20g00
6023153
7902127
6039206
6035491
Ws/We260-S270
4051185 Ref-Plus-R50
6008899
Iq40-40nppkc0k
Dt35-B15251
Dol-1204-W02m
Cdd-40p
Dme4000-212
1088335
6026216 Optischer Sensor-Typ: Vt12t- 2p430
1066552
6037323 Connector Dos-0804-G
2096166
1052446 Gse6-P4111 Einweg- Lichtschränke
1047984 Lichtschränke Sicherheit
2027180
1037091 Lampe
2016408

1016031
M40e-062200rr0
1098439
6021127 Induktiver Sensorim18-08n-N-Zw0
Iq12-04bpskt0s Sensor
1041411
6028442 Wf120-60b410 Geschlitztsensoren
1041411 Klein-Lichtschraken, Wtb12-3p2431
Lut8u-11401
6037668
5322547 Kabel Lwl Model LI3-Tv06
Lms111-10100
5304812 Yi2a14- 100ub3xleaxstarthilfekabel
1049042 Wtb9-3p1111lichtschrake
6048405
2065702
1026244 Kt3l-P3216 Kontrast-Sensoren
T4000-Dnac
6021080 Wll170a- V430glasfaserlichtschrake
5311129
7045173
Dme4000-319
6049678
Dfs60b-S4pk10000
1047581
1036101
M12
E34-1-Ar
Wtb12-2p2411-1041422

1036255
Vs18-0d3140
6032636
1071278
2021722 Ws12l-2d430-Sensorposition Optoelektronnyj
6021123
Dt60-P111b
6038991 Dol-0803-G03mc Cab.,Fem.St 3m0 M8-3p
2015069
1018295
1043784 Controller Sicherheit Fx3-Cpu1
6037833
1025910
Clv422-2010s02
6024917-Ue10-3os2d0
1028226 Farbsensor
6025681
DI100-21aa2109 Entfernungsmesser Zur Positionierung
1062523
1054131
1202707
Dme4000-111s05
Pbs-Rb010sg1ssnd5a0z
WII180t-P434
6026216
1078041 Dfs60e-Tjek01024inkrementelles Wegmess
6009720 Anschluss Typ Dos-1205-W, M12, 5-Polig
6033290 Sensor
6020223 Induktiver Sensor

1028123
Dfs60b-S4aa00500 Endlosregler
Wt100-N1432 Lichtschränke
Ime08-02bpszt0s
Dt50-N1113
Vl180-2n41131 Lichtschränke
6049678 Sensor Ufn3-70b413
2056155
1040731
1019247
1028934 Sicherheits-Scanner S30a-4011ba
1033876
Grtb18s-P1112v
Wtb12-3n2431 Lichtschränke
Kt8l-P3656
Ws4-3d2130
M4000 M40z-025000bro
1023547 Einheit Sicherheit
5321089 Pl20chem Reflektor
Wl9g-3n1234s02 Sensor
1019245
6009503
6013458
6041807
1017910 Pl240dg Reflektor
5312984
1017910 Reflektor
6036629
2071329
6043920 Wfs3-40n415
LI3-Db01

Ste-0803-G
S30a-4011ba
Wswe160p132
1036767 Dfs60b- Bdpa10000inkrementelles Wegmess
Wt89-3p211
Iq06-03bpsku3s
6039866
1036924
2071331
Nav350-3232
6011991 Induktiver Sensor
Dol-2321-G03mpa4
Ws/We100-2n3439
1204132
6030709
6027944
Wl12-2p730
1036083
PI560dg
1069073
5308077
6036918 Um30-213113 Ultraschallsensoren
2050205
6009990 Wll160-F420lichtschränke Schalterglasfaser
6027429
1034223
6 007 302 Dos-1204-G Stecker M12 4pin
6044705
6058474 Dol-1204-W02mrn Starthilfekabel

1057656 Ds35-B15821 Abstandssensor
P/N: 1053574
6022758 Sensor
Dol-1205-G05mc
Iq80-60npp-Kk0
1036107
6052626
Bgs-DI10cp
1200122
Wl12-3p243 Sensor
2071330
6026473 Induktiver Sensoriq80-50bpp-Kc0
2095609 Yf2a14- 100ub3xleaxstarthilfekabel
1050912
6020110 Induktiver Sensor
Dfs60b-Tepk 10000 Drehgeber
Dme4000-311
P/N: 1055346
7047620
C45s-0303aa220
Ime18-08bnszw2k Induktiver Sensor
2058653 Traeger
6010189 Optischer Sensor
1054728 Sensor
6010542 Kabel
P/N: 2031071, Type: Dol-2308-G05mjb2
Dol-0612g20m075 Km0 2022549 Stecker Und Kabel
1040982
Wt12lb550
1052967 Pgt-10-S-Programmer
Bef-Khz-Pt1

6035499	
6039095 Wll180t- P434fiberoptikoptoelektronische Sensoren	
202407	
1070871 Rzt7-03zws-Kw0 Magn.Cylinder Sens. Stellungsgeber Magnetische	
6022009	
1045672	
C2c-Sa03030a10000	
1049061 Sensor Lichtschanke Sick WI9- 3p2462	
6025036	
LI3-Tb02	
Dol-0804-G02m Kabel 2m Gerader Stecker M8 4 Pin	
1074817 Dbs60e- Thfn01024inkrementelles Wegmess	
1012720 Pl40a Reflektoren	
Mm12-60aps-Zck Sensor Mit Dos-1204-Wx	
6051101 Ue410-Mu300s01safety-Unit	
Mlgs5-1450i812 Modular Light Grid	
6007303-Dos-1204-W	
2029215	
1059901	
Dfs25a-Azaaz000s10	
Dt35-B15251 Sensor	
Vfs 60 - 1024 - Ttl 4,5- 32v	Encoder VFS 60 - 1024 - TTL 4.5- 32V fully programmed and assembled with plug
1036616 Pgt-08-S-Toolsprogrammierung Undkonfiguration	
Dme3000-111p	
Ag Wtb11-2p2461 1044442	
Elg3-1050p521	
1019229 Wt34-B410 Photoelektrischen Schalter	

2058653
1012719
Range-E50414
6027931 Lichtschränke Vse 18l-4p324 6027931 (Satz Vs187-0d314 + Ve18l-4p324)
6036919 Sensor
C4c-Sa18030a10000 - 1211509
1045093
6033181 Sensor
6032868
1055038 Encoder
1058215 Lichtschränke Grse18s-P2336 Photoelectric Switch
Ue10-3os4d0 Safety Relays Ue10-3ospart Number: 1028303
6027580
1036129
WI27-3p2451
Wt36-R710
18sp1347
4036657
1059510
2066614 Bef-1shabpku4 Befestigungssatzset
1022293
1015798
Wt14-2p432so8 Sensick Sensor
1037808
1049070 Sensor Lichtschränke Sick WI9-2n131
1016934 Wt24-2b440
P/N: 1056742
Btf13-P1hm3025 Endlosregler Mit Seilzug-Mechanismus Komplett

6050248	
6039751 Absolute Wegmessacs/Acm36	
6029282 Type Dsl-1205-G0m6c; Lead Number / Cross Section 5-Polig; Material Polyurethan	
6010754	
1056180	
6036923 Ultraschallsensoren, Um30-213118	
6011050 Optischer Sensor Wt150-P460	
6043440	
1036992	
1019253	
1069503 Grte18s-P1362	
Dos-1208-Ga	
Dx50, Dt50-P1113	1044369 Mid-range distance sensors
1040763 Ime 12-04 Bpszcok	
Ime12-04bnszc0k	
Bef-Ah-Dme Halterung	
Wt34-R210	
1016629 Kt5w-2p1113	
Kt8l-P3656 Sensor-Kontrast	
1045651	
6020976	
Dme Dme5000-211s08 Sensor	
185220	
6036555 Leitungsdosetyp: Dol-1212-G 02 Ma S 01	
1034650	
6052361 Wl100-2p3439	
1036722	
1062253	
Dos-1205-G Stecker Female Connector	

1036907 Dfs60b Tdpa10000
Im12-02bps-Zc1
Wl12-3p2431 Sensor
1062201
1055020
6025814 Induktiver Sensor Iq-15bpp-Kk1
1053007
1061394
6026564 Ws190I-D430 Through-Beams.
Send.
2041834 Kabel. M12/D-Sub, 2 M
1030015
1026031 Sensor
Dme4000-111
E33-1-Ar
Wl170p420
7900013 Induktiver Sensor
1019431 Sicherheits-
Lichtschrankeps125-124
1036084
P/N: 6037417, Type: Mvm-01m-2mc-Mklb
6037668 Um30-215112
Stellungsgeberultraschall
Dol-1208-G20mac1
1037921
7020476
1214002 Mlg05s-0895a10802 Lightgrid
1041323
6037661
1018045 Kt5w-Sensoren 2n1116kontrast
1040766
Dfs60e-Bdea01024
Vt12t-2p430 Sensor

1052952
6042005
Drs60-C4a02048
1028097
7900007
5304819
4040006
Lte090-351
6048391
1052591
6036106
1023546 S30a-6011ba Laserscannersicherheit
1040954
1036749
P/N: 1057250
1017860 WI24-2b430 Optischer Sensor
Dme4000-112
Dfs60b-Bdea00s26
1037013
Wt250-P460
6026558 Reflexions-Lichtschränke Typ: WI 190I-P430
P/N: 6037415, Type: Mvm-0m5-2mc-Mklb
1040763 Sensor
Dme4000-122
DI50-P1123
P41f Reflektor
2068148
1082728
6013551
1037168 Inkrementaler Drehgeber
Rzt7-03zrs-Kw0

M20z02550a121
Dol-0612g7m5075km0
P/N: 1033532, Type: L230-P580c2s00000
1012719 Reflektor PI20a
6009990 Sensor Lichtschränke
C4000 C40s-0704ca010
1200124
Wt34-V220
2073486
6036159
6024915
1063129 Sensor
1058174 Sensor Lichtschränke. Typ: WI9I-3p2232
1036924 Encoder Df60b-Tepk1000
6051509
PI100 5321625 Reflektor
6026528
1040619
6049454
1040755
Wt150p162
1017875 Lichtschränke Ws/We24-2b440
1038000
1023891
6010190 Sensor WI170-P430
Dfs60b-Bhak02048
A3m60b-S4pb013x13 Absolute Encoder 1038826
1047162
7900227 Sensor, Iq80-60npp-Kk0
Wttl2l-B2538 Lichtschränke

6024893 Sicherheitsrelais Ue43-2mfd2
L28s-3d2431
Wt42p431538
6033269 Ste-1208-G Stecker, St.Cab.Sh 8p. Connector
1037384
Lut1u-11331
1038826
6026224 Sensoren Optoelektronische Vs/Ve12-2p430
6048387
P/N: 1057260
P/N: 1054741
6012021 Vt18-204470s01sensor
1025994 Lichtschranke
Dt60-P1115
1050529 Endlosregler
Wlg4s-3 Sensor
Bef-Ah-Dx100 Halterung Zur Positionierung
1057075
Ue402-A0010
1036075
Wtb12-2p410
6009872 Dol-0804-G05m-Kabel M8, 4-X Polig, 5 M
Im12-04nps-Zuk
1051484 Dfs60b-Thpm00s06 Incremental Encoder
1028224 Cs810p1112 Sensoren Farbe
6036833 Sensor
6020993
1036115
1044275

1047984 Lichtschränke
1019254
5320565
Wt27I-2f430
1084501
P/N: 1069457
Dfs60e-Beck01000
DI100-11aa2101
L28e-3p2431
P/N: 6037422, Type: Mvm-3m5-2mc-Mklb
I16-Sa113 Notschalter
1031558 Ars60-Absolute Fla00360wegmess
1036752
1057772
Dol-1205-W02mc (6025909)
1036025
1090909 Dbs60e-B5epd1024
1035384 Dks40-E5I00200inkrementelles Wegmess
P/N: 1054143, Type: Vfs60b-Bhaj01024
1063175 Sensor Sensick WI14-2p431
P/N: 1053525
2103523
2052248
1028232 Optischer Sensor Kt10w-P1115
1030014
Sek37-Hfa0-S01
1067980
WI9-3p2230-1049059
1078888 Dfs60b-S4wa00050 Incremental Encoder
1030001 Absolute Multi-Turn-Drehgeber

6027522
C45e-0103ag220
6052361
1028170 Sensor We4-3f3130
6 009 866 Kabel Dol-1204-G05m
WI27-3p2430
2029246
6034669 Ultraschallsensor Uc4-13341
Dt500-A111
Im18-05bpo-Zc1 Induktiver Sensor
Imf12-04bpcvc0s Induktiver Sensor
WI260-F270
1059760
1040968 Ime18-08bpszw2sinduktive Sensorenproximity
1072798
7900099 Sensor, Im18-12npo-Zc1
1025911 Optischer Sensor WI18-3p430
1045655
W100I-E2141
1098784
1067293 1067293 Csm- Wn11122psensoren Farbe
1048418 DI50-P2225 Distanz Sensoroptoelektronnyj
1213213 Sicherheits-Lichtschranke C2c- Ea12030a10000
Cm30-25npp-Ec1
6025905
6049679
WI9-2p631
1213203 C2c-Licht Ea04530a10000schleier Sicherheit
P/N: 1053485

Dme4000-315s02
6022701 Ws160-G440 Through-Beamsens.
5308076 Linse
Ad-Ssig-Pa
6032637
2029204
7900600
1025380 Rzt1
1034094 Skm36-Hfa0-K02-Sensor-Feedback-System (Encoder)
6037663
1036111
7902124
6036158 Kabel
1034318 Btf13-C1hm0525seilzug-Encoder
1207923
Ufn3-70p415
1036488
1018256 Sensor
1053483
1037456
6025903
6036927 Induktiver Sensor
Strl Xdaf0ac5 Opto Sensor
1041290 Bar Code Scannersclv650-0000
1218660
L230-P580000000001
1092136
6008900
Wt100-2p3439
6043834
1064694

1041390
7102651 Hd32-Do124e0512inkrementaler Drehgeber
5315124
Wtb11-2p2461 Sensor Photoelectric Sensors
1018593
6049579
6027448
6052386 Sensor
1055909 Encoder Dfs60e-Bhek01024
1066557
5325915
Im12-04bps-Zc1
Mht15-P2319
1057324 Adapter-Schnittstelle
1041456
M2000 Standard
1027790
1036767 Dfs60b-Bdpa10000inkrementaler Encoder
Dme4000-113
Mics3-Acaz90pz1p01
Ref-Irf2000r25 Reflektierendes Band
1059631 Sensor Lichtschranke GL6-N4211 (4pin, M8)
1035483
6012643
5319981 Ref-Plus-R50
6058494
6011050 Wt150-P460sensor
1025624
1046537

6030709 Photoelectric Sensor
We4s-3p2430v Sensor
2011435
WI100-N1439
1036616
5315124 P250h Reflektoren
1036105
P/N: 1056153
6035460
1072489
1018586 Kontrastsensoren , Kt5w-2p1216
6058157 Sensor
6027430
1067295
5305850
1026538 Sensor Kontrastierenden Markierungen
1081581
1019250 WI34-R240-Photovoltaiksensoren
Ue403 Ue403-A0930 1026287 Sicherheitsrelais
1025994 Sensor Lichtschranke Sick Wtb27-3p2411
7902077 Steckverbinder Zick Dos-0803-G
1027777
PI240dg Reflektor
Wt18-3p410
6041425
6036645, Lot 1336905018f Sensor Typ Od2-P250w150
1057651
1026287 Ue403-A0930, Ip65,
6020223

6024790
1036723
6036920 Sensor Um30-215113
Mzt8-03vps-Kp0
5306091
1040739
1041411 Wtb12-3p2431 Sensor Die Bestimmungen Optoelektronnyj
1052448
6028357 Dos-1204-Gn Steckdose(Einbaufertige)
Vse1802p42437 Sensor Lichtschränke
Dos-0804-G
6041680
6052625
6041377 Drucksensoren Pbs-Rb016sgess0bma0z
6020219
1019239 Lichtschränke Wt34-R240
1030038
2095895
1037785 Typ: Vfs60a-Tgpz0-S03motorfeedback
1038186
1044508 Sensor Sensick Wl14-2p432so8 Bestell. - Nr. 1 045 104
Vfs60e-Bdez0-S01
Wtf12-3p2431 Sensor
Im30-40nps-Zc1
1049078
1041411 Sensor Wtb12-3p2431
6036384
P/N: 1053719
Wl170-2p430

C4c-Sa04510a10000
1044508
Kt5w-2p1113 Optischer Sensor
6048416 Ultraschallsensortyp: Um18-212161101
Mra-F130-405d2 Encoder Accessory
6029789
6052614 Kabel
1045650
1207236
1018961 Sensor
Ime08-05npszt0ss01 Induktiver Sensor
6007302 Anschluss Typ Dos-1204-G, M12, 4-Polig
4 019 634 Band Reflektierend Ref-Dg-K
6049678 Ufn3-Ultraschall
70b413schlitzsensor
1040722
1030009 Endlosregler
1016131 Lichtschranke Wt12-2p420
1047616 Dt50-P1124 Distancesensor
Abstandssensor
6009382 Steckverbinder Dol-1204-G02m
1029949
6037322
6036830 Wfl15-60b416
1008836
P/N: 1055979
1030013 Atm60-Absolute P4h13x13multi-Turn-Drehgeber
1040748 Ime12-04npszcscos
6042724 Drucksensoren Pbt-Rb010sgtsenama0z
2039248
1064697

1049054 WI9-3p1162
1200127
6029832 Ultraschallsensoren , Uc12-12231
S30a-7011ca
1050615
Wtb27-3p2411
2021463
1040966 Ime18-08bpszc0s Induktiver Stellungsgeber
2033560
WI24-2b230s02 Der Optische Sensor WI24/2r240+pl80a
1036096
2045642
6010186 WI170-P420-Positions-Sensoroptoelektronnyj
1019230
6053253 Sensor
1036746
1028224
6020977
1019291
1022202
T4000-1rba01
1016591
Iq80-50bpp-Kc0 Induktiver Sensor
6013693 Stellungsgeber Vs/Ve18-4p3212 Through-Beam
1061790 Anschlusseinheit
6025908
5310252
C40e 0603cb010
Rtz1-03zrs-Kp0
2048440 Connectoh M23,12-Pin:Typ Dsl-

3d08-G0m5ac2
1041114
Wtb140-P430
1024086
WI140-2p330-10490559
Wtb11-2p2431 Sensor
2050022
1046534
2095838
1047118
2060626
6020320
1037661 Encoder Afm60b-S4aa032768
Wtb27-3s1541
6024910
6029832 Sensor Uc12-12231
Dfs60e-Bdec01250
Dt50 P2113
1059504
6044336
1200115
Im30-20nps-Zc1 Sensor
2029202
1052967
Ime12-04bpszcok 1040763
Iq10-03bpskw2s
4031053
2032127
7902078 Stecker Dol-1612-5m-3
Wf2-40b410
1003865 PI80a Reflektor, 100% Kunststoff

2071327
1041422 Wtb12-3p2411lichtschrankeschalter
Im08-2n5ns-Zc1
1019232
1040734
P/N: 1069902, Type: Vfs60b-Tbaj65536
1025911
1017047 Sensor
Gtb6-N1212
Dfs60b-Bhea08192
1026820 S30b 2011ba
1207250
Gte10-P4211 Sensor
WI150-P122
WII180t-L432
Srm50-Hza0-S50
Mba220zka1n1-A00150-D-XXXXXXX
1008562
1036616 Pgt-08-S-Tools Programmier-Und Konfigurationssoftware
1058882 Sensor
6028440 Gabelsensoren, Wf50-60b410
6012062
6049453
WI8g-P2231s01
6044699
7900085 Sensor
WI9 2p431
1041458
WI45-R260
1019239

VI 18-4p3240
1047616 Distanzsensor Dt50-P1124
1085344 Sicherheitsrelais
P/N: 6037421, Type: Mvm-03m-2mc-Mklb
1200128
1052107
6044892 Ste-1208-Ga01 Coonec.,St. Shield M12-8p Kabel Stecker
1041422
2027171
Sfm60-Hmkt4k02
Fx0-Gent00000
5315172 Reflektor P25
1211470
Dbs36e-S3ek00100 Inkrementelles Wegmess
1043783
1046010 Kt6w-Sensor 2n5116kontrastierenden Markierungen
Ws/We34-B430
Ste-0804-G
106544 1803-0094 Endlosregler Dbs26e- S3ek01000
P/N: 2031072, Type: Dol-2308-G10mjb2
Dos-1612-W
1034893
6013258
1045652
1002314
Wi 130t-P340 Adapter Sensor
Dol-0803-W02mc
2059368
1213209 C2c-Ea09030a10000 Lightcurtain Receiver Licht Schleier Sicherheit

6032326
2039302
2 1045104 Sensor Sensick Wt14-2p432so8
Srm50-Hfz0-S22
1051710
We280-2r4331
Pls109-317
Ch12dob5c
Wl12-2b560s37
1070872 Sensor Rzt7-03zws-Kwb
1027744
6010190
Srs50-Ffa0-S21
Bef-Khs-H01
6058496
1036150
1041030
6012147
5321097
1018256
6044699 Sensor
1028934 Sicherheits-Scanner
6053043
1016629 Sensor
Wfl 80-60b416 Sensor
2073485
1047405
1204146
6024915 Relais Ue48 Sicherheits-2os2d2 / Safety Relay
1036102
Vl180-2p-32436

1018252
Wte11-2p2432
S30a4011da
1052109
1059752
1034650 Dks40-E5j00100inkrementelles Wegmess
1040791
7902077 Rosette Dos-0803-G
6054286
Dfs60b-Teek00100 Inkrementaler Drehgeber
6011038
4019634 Reflektoren
1037632
Wtb4s-3n1361
Kt10w-P1115
Wtb26i-34161120a00 Kompakt-Lichtschranken
1037112
Dme4000-315
6022758 Optischer Sensor
6028627
5312983
6027519
Wt160-F420
1041438 Stellungsgeber Wl12-2p730
1044369
2044417
1018587
6027529 Cable W. Shield . 4*2*0,15 5d8 Leiter Mit Connectors
1036655

2027721	
Wf15-40b410	
Skm36-Hfa0-S05	previous material number: 6CK-100-200-011 SKM36-HFA0-S05 MOTOR FEEDBACK HIPERFACE 128 sin / cos periods RoHS compliant according to EU Directive 2005/95 (from Date-Code 08/32) Country of origin: DE; Stat. Product number: 90318020 EC dual use / export list number: non; US ECCN: non
C40s-0603da040	
1036098	
1019244	
6029514 Sensor Lichtschranke	
M40e-034010rr0	
4043524	
1042059	
6033269 Ste-1208-G	
6029215	
WI 130I-32 Sensor	
1040785 Induktiver Sensor	
2015229	
2024282	
6044728 Optischer Sensor	
6026006	
1036013	
Wtb27-3p2411s18 Sensor	
2038993	
WI24-2v530	
Ds50-P1122	
6011050 Sensor Typ Wt150-P460 (6 011 050)	
1051017 Encoder A3m60b-Bhpb013x13	
1211501	
2071778	
P/N: 7102164, Type: Dol-MS10-G20mma3	

[6037665 Sensorum30-212112](#)[6021156](#)[Wt18-2p610](#)[LI3-Dk63z Sensor](#)[6012828 Vtf18-3f1240lichtschränke](#)[Ws/We140-2p132 \(6024788\)](#)
[Photoelectric Sensor Through-Beam](#)[1029973](#)[6035497 Vli18-4p2240v](#)[1018670](#)[1064578 Wt2s-P031s13](#)[1058164 Sensor](#)[P/N: 1074221, Type: Vfs60e-Tgak02048](#)[6013191 Optischer Sensor](#)[6043919 Wfs3-40p415](#)[1074367](#)[6048390](#)[Bef-W n-Dx35](#)[1059039](#)[WII190t](#)[Dfs60b-S4ca02048](#)[Wt23I-F430](#)[2031086 Dol-0j08-G0m2xb 6,](#)
[Anschlusskabel](#)[1026031](#)[Dme4000-117](#)[Bef-Kp-W45 \(2011435\)](#)[1036020](#)[WI250-P430](#)[Ws45-U260](#)[Gerader Stecker Für WII12](#)[1218237 Licht Schleier MIg10n-](#)
[0590n10501](#)

Mm12-60a-Ps-Zck-Sensor
7900015 Induktiver Sensor
1037685 Sensor
1036078
Wt23lf430
6025908 Stecker Dol-1205-G10mc
1213200 C2c-Licht Sa03030a10000schleier Sicherheit
6022011
Dt50-P1113
1050635
1055503
1051757
2062284
1019246
1058225
1215667
1071843
C2c-Sa06030a10000
Sks36-Hfa0-S01
1064573
Lichtsensor Wt16p112
5318680 P55 Reflector
6033207 Lichtschrankewtb8-P2131
2031079 Bef-Mw-Skx36
1044442 Lichtschrankewtb11-2p2461
Yg2a14-050vb3xleax
WI 12l-2b531
1023546
6041809 Sensor
1018677 C40s-Licht 1804ca010schleier Sicherheit
P/N: 1054498

Dbs36e-S3em00500
Kt5w-2p21160
1042256 Cdb620-001-Kommunikationsmodul
2056306
P/N: 1067934, Type: Ttk50-Hxm0k02
1040886
Vte18-4p4240
We260-F470
6033188 Sensor
6013950 Vs18-0d3640 Through-Beam Sens
S30a-6011da
6028428 Wf2-40b410
Srm50-Hwz0-S01
5311138
6032451 Dol-1208-G20mah1cab.,Fem.St 20m0 M12-8pleiter
1045502 Sensor Lichtschränke ZI1-F2421
1040288
2062909
1042292 C40s-S113 Lightcurtain
1025511
Wt170-P132
Wt2s-P231
5321625 Pl100 Reflektoren
1036097
Wl12g-P510s10
1044163 Der Optische Sensor Sickwtb27-3p2461
P/N: 1053483
Ag661-466111000000
Wt27p6116910
1052684

5308446
6009383 Connector, M12, 4-Pin
C4c-Sa12030a10000
6013263
6049969
2015236 Kabelfiber Optic Lm37-450
6020422
Dme4000-222
7900280
Dme4000-219
6029515 Sensor Lichtschränke
1018044 Sensor Sensick Kt5w-2p 1116
1037419 Dfs60e-Teek01024 Incremental Encoder
Wl273p2451
1204145
Wl160-E440
1018587 Sensor Kt5w-2p1126
Wtb 12-3p2431 Sensor
6007303
2067762
1062460
Wl24-2v530s04
1058126 Sensor
1052596
Rt-P2231
2096235
Dme4000-317
1015798 Der Optische Sensor Typ:Wlg12-P537
1018575
Im12-06bns-Zc1

1062916
6024893
6026568 We190I-P430 Through-Beams. Rcvr
P/N: 1054485
1049045 Sensor Lichtschränke Wtb9- 3p2211
Ad-Atm60-Sr2dn - Bus-Adapter
Dme4000-224
Dt50-P2113
1026245
1040759 Sensor
2046458
1036114
1073212 Kontaktloser Sicherheitsschalter
1047402 Ds50-P1112 Distanz Sensor
1017885 Der Optische Sensor Sick Wt24- 2b420 Dc 10...30v
2029205 Kabel
I12s-B213 Sicherheits-Positionsschalter
1023668
2048370
1072635
6036722
6012831
1022949
6032639
5322723
6036351
6052386 Miniatur-Lichtschränken, WI100- 2p4429
10556550 Endlosregler
2076230 Spz-58z-010-P Spannzangen
1056222 Dfs60e-Teek00100.

Inkrementelles Wegmess
7042400
6044998
Srm50-Hfao-K21
Iq08-04npoktos Proximity Sensor
1038238
207654 DoI-127sg15vt25rv0 Starthilfekabel
1062400 Encoder Dfs60b-Beec01024
2033613
1019243
6026216 Lichtschranketyp:Vt12t-2p430
1 026 822
2096237
?T6w-2p5116 1046013
1066284 Dfs60b-S4em01800 Incremental Encoder
6034482 Ue410-Mm3-Controllersicherheit
6053548 Ultraschallsensor Um12-1192261
6030709 Sensor Lichtschränke. Typ: WI100I-F2131
C40s-0901aa030 - 1022204
1037366
Vt180p142
1029846 Sensor Mz2q-Ftzps-Kp0
6036917 Ultraschallsensorum30-212113
1213208 C2c-Sa09030a10000 Lightcurtain Transm. Licht Schleier Sicherheit
6009720 Dos-1205-W Stecker Des Kabelsm12 5-Poligen
Wt24-2b440
2024489
6037782 Photoelectric Converter Dc10- 30v
Clv630-6120 Barcode-Scanner

Dme4000-324
WI260-R270
Dme4000-217
6036630
2023335 Modular Light Gridmlge5-1450i812
6011032 Ws/We150-P430 Through-Beam Sens. Sensordie Bestimmungen Optoelektronnyi
1036486
1040783
1023009
WII260-F440
1052684 Abstandssensor DI 100-21 Aa2101
1055909 Endlosregler
Wtt12I-B2538
1041030 Sensor
S3000 51280359
S30b-2011ca
L27e-3p2450
7074074 Der Optische Sensor Gre18-P2412
1040966
Kt5w-2p1116 1018044 Sensor Q=pnp
1071021
1072763
P/N: 1055020
1036733
Im18-12nps-Zc1
1036023
1072687
2027649
1036759 Encoder Dfs60b-S1pm10000

(Welle 6 Mm.)
1072560
1044442
Wtb9-3p1161
1072555
1040933
Connector
1030024 Atm60-C4h13x13 Absolute Multi-Turn-Drehgeber
1042084
Um30-214111 Ultraschallsensor
6052373 Lichtschranke Sick Wt100-2p3439
1078098
2095733 Verbindungskabel Mit Stecker
Vte 183f4712 Optoelektronische Sensoren
1028106
1052446 Gse6-P4111
Rt-P3231
Mlg1-0290a412
6032553
1086821
6048416 Ultraschallsensor
1036080
P/N: 1053821
P/N: 1037434, Type: Ttk70-Hxa0-K02
Pm3s11-00330030
1036026
2014458
Dks40-E5I00200 Inkrementaler Drehgeber
7902923
1052593
5308082

1059644 Optischer Sensor
1200150
WI24-2b440
2039002
1061012
1028099 Wtb4-Optische 3p2161sensor
7902077
Hd32-Do124e0512 Encoder
Kd-Lo9n-12111
1054051
Afs60a-S4nb262144 Wandler Ecken Bewegungen
Dfs60e-Teek01000 Dfs60e-Teek01000
1041322
2029227 - Bus-Adapterad-Atm60-Sr2dn
6027537
Optischer Sensor
1036017
6044336 Drucksensor Pbs- Cb2x5g1ssnama0z
6032730 Kabel 5m Sick Dsl-0803-G05nc
I17 S?213
Mm12-90aps-200
1026518 Distanzsensortyp: Dt 500-A 212
6041816
Bef-2smgeaku4 2030510 Befestigungssystem
1059503
6024915 Sicherheitsrelais Sick Ue48- 2os2d2
Wtb27-3r2611
1030013 Absoluter Drehgebertyp: Atm 60-P 4 H 13 X 13
1071850 Induktiver Sensor

6010182
Dol-1204-G05m
1051022
6007302
1037091
Df S60b-S4 Cl01250
Dfs-60b-S4pc10000
1042293
6037661 Sensor Um30-212111
1059522 WI12I-2b530s06
1070871
Rtz1-03zrs-Kpo
Re11-Sa05
P/N: 1070720, Type: Vfs60e-Bdcj01024
Wtv4-3p3441s38
WI24b4301 (01011463)
1019234
Bef-2smmeaku4
Wse9-3p3430 Optischer Sensor
2017038
1213184 C2c-Licht Ea03030a10000schleier Sicherheit
6028357 Connector M12 Sick Dos-1204-Gn
1025887
6025955
2045339
6029514 WI170-2p430fiberoptikoptoelektronische Sensoren
1079384
1027982 Stellungsgeber WI27-3p2431
A3m60-S4pb13x13 Absoluter Drehgeber
Wtb26i-21161120a00

1041457 Wl12g-3o2431
LI3-Tk75
Wtb12-3p2411
1041459
6041751
Wl11g-2b2531
Cq4-08epsku
Tct-1abzz1006mz Temperatursensor
4063333
1003546 Reflektor PI22-1
5310008
6037322 Ste-0803-G Stecker (Ready-To - Montage)
Ue10-2fg
M20s-03140a122 Paar (Links Und Rechts)
1045095
Im30-10bus-Zu0 Induktiver Sensor
Atm90-Axa12x12
6020977 Sensor Lichtschränke
1026052 Optische Sensor Wt14-2p422
1040406 Distanz-Sensor Dt20-P244b (Dt20-Hi) 100-300mm/Dc24v/4-20ma/Pnp
C45s-0103aa220
Bef-Ah-Dx50
1094835
1038032 Incremental Encoder, 0-5v Ttl (Rs 422), 4096 Rrp, Solid Shaft 6mm, Conne
6033950 Sensor
1204162
6052368 Sensor
6048397
1052594

Wtb27-3
Dme4000-215
Ue410-Mu3t5
Wlg4s-3p3432v
6032869
P/N: 1059265, Type: Vfs60b-Bbaj01024
WI27-2f440
1040625
4036250
1036086
6048399
6027522 Im30-40nps-Zc1induktive Sensorenproximity
1052453
6029832 Sensor
1019236
2013942
Um18-217161101 Ultraschallsensoren, Um18-217161101
Atm60-A4n12x12
6053788
1019229 Sensor Wt34-B410,
GI6-P1111
1034892 Abstandssensor
6034941
6036919
Dol-1205-G02m
Bks5208pu05
6009872
L27s-3d2450
6048403
6024908
6022758 Ws/We160-F440

6027422
1054198
1031548+2029222
P/N: 1078859, Type: Vfs60e-Bgek01024
1041050
2096234
Dks40-A5j01024
Wt45-P260s01
1054706 Sensor
6049458
5309981
Ref-Plus-R50 Reflektierendes Band
6006821
Mlg2-0880f511
6013893 Ve18-4p3640
6026625
1036643
1053075
Ime18-08bpoz0s Induktiver Schalter
Wt24-2b210
5321870
Cs81-P1112
Dn400
?4?-??03030?10000
1036787 Sensor Dfs60b-Bhpk10000
Wp12-2p730
Dqs60-Aza0-S03
2071259
Mlg1-0290f521
1018040 Kontrasttastertyp: Kt 5 G-2 P 1411
1063129

1040696
1053016 Sensor
1017885 Foto-Sensor Wt24-2b420
Im08-02bpo-Zt1 Inductive Sensor Sick
1017046 Sensor
6052368 Ws/We100-Sensor 2p4439die Bestimmungen Optoelektronnyj
2046172
Bef-Khz-Rt1-63
5308843 Reflektor
1036748
6035490 Vte18-4n4240v P. Prox. Sens. Energ. Sensorbestimmungen
1018663
Clv620-1000
2029178
1044163
Dol-0612g20m075km0 2022549 Stecker Und Kabel
6041818
7902078 Dos-0803-W Steckdose (Ready- To -Montage)
1040733
1075843
1032665
6029280 Type: Dsl-1205g01mc; Lead Number / Cross Section: 5-Pole; Length: 1 M
1058181 Wse9l-3p2437photoelectric Switchstellungsgeberoptoelektronnyj
6026220 Optischer Sensor
2029213
1028934 Sicherheits-Scanners30a-4011ba
6025900
Wl14p430 1012925 Sensor

Ad-Atm60-Ka3pr
6027519 Sensor Im18-20nps-Zc1
1332 0254 Sensor 1332 0254 2023797
1213212 Licht Schleier Sicherheitc2c-Sa12030a10000
6024917
Rt-P2233 Optischer Sensor
Sks36-Hfa0-K02 Encoder
1041150
In30-E0407k
1015397 Lut3-620 Sensorenfluoreszierende Etiketten
6026146
6052616
Ws4-3p2130
1043916
Drs60-D4a01024 Endlosregler
1028541
Wt34-V210
Ars60-A4a08192 Endlosregler
1041977 Clv630-6120 Barcodecodes
2095836 Stecker Mit Kabel Yi2a14-020ub3xleax
5304549 Reflektor C110a
C2mt-06034bbc03fb0
1028934
6012822 Optischer Sensor
192290625
1018678 C40e-Licht 1804ca010schleier Sicherheit
Mzc1-4v3ps-Kp0
1028232 Kontrastsensoren , Kt10w-2p1115

6 022 009 Kabel DoI 0803-W05m
5313019 SensorII3-Dk06
1058999
Clv450-0010
6051780
1000132 Reflektor
1023546 Sicherheits-Scanner S30a-6011ba
1049063 Sensor Lichtschränke
1059521 Der Optische Sensor. Typ: WI12I-2b530s05
P/N: 1054619
1301068
Wt18-3n430
2051612 Befestigungssystem
6044724
1037419 Encoder Dfs60e-Teek01024
1036459
6027529
2013824
1027769 Optischer Sensor
1000238
Mzt1-03vps-Kra
1058168
6025871
1200131
1036458
6039097
6043208 Um30-213113s07ultraschall-Sensor
6037824
1058211 Sensor
1015852 Lichtschränke Mit Reflektorprk 96m/P-1400-22

1073406 Mzt6-03vps-Kpx
1050618
Vs18l-0d314
5 305 535 Lichtschränke Wiv-V 180-T 400
1075638
1057656
Ds500-P511
1032954
P/N: 1057791, Type: Ttk50-Hxj0k02
6035622
2022545
1036106
Mcs 100 6023093
6027531
104062 Stand
1091393
Wtb26i-1h161120a00 Kompakt-Lichtschränke
Clv610-C1000
1059559 Sensor
1078111
6027538
PI240dg
Dme4000-127
WI23-2p2432s02
1036558
1036016
6030589
1060529
1040072 Sensor Magnetisch Mm18-70aps-Zck
1036755
6063340

6020688 WI150-P420-Photovoltaik Sensor
6025893 Sensor-Kabel Dol-0803-W 10mc
1047782
WI9-2p330s10
P250
1059035 Afm60a-Bdnb018x12absolute Wegmess
1204161
1085742
6036155
We8-P2231v Sensor
2015625
1041429
Wt18-3p420s12
Nt6-03082
4003353
Bef-Slit Mask-G
6036386
Die Induktiven Sensoren Ime 12-04bpsc0s
6026555 WI190I-N132
1028097 Wtb4-3p3161lichtschränke
1040975
6043313
2025241
2029191
Vtf18-4p1340
6029515
1017853
5308071
1047578
6063335

Dos-1208-Ga01
6020977 Wl260-F470 Fotosensor
5304549
1200065 Sperre Luminous M40e-025003rb0
1018045 Optischer Sensor
1047056
6032451 Kabel
Mlg1-0140f521
6052365
1040736 Inductive Sensorime 12-02 Bpozcs
Bef-Dkh-W12
1037555 Dfs60e-Siam01024inkrementelles Wegmess
1053835
1041029
5308050
7901784 Magnet
1012720
6024915 Ue48-Relais 2os2d2sicherheit
Wl12g-3v2572
6034595
2065223
1069009 Incremental Encodertyp: Dfs60b-Bdca00s30
1204936
We160-F132
We272p630 (1007914)
1026244
Sel37-Hfa0-S01
1045089 Lichtschränke Wl14-2p430s07
1026822
Im18-05bds-Zw1

1076095
Mpa-179tthtpo
P/N: 1055021
1040981
6026473 Induktiver Sensor Iq80-50bpp-Kc0
1034892
6028431 Optischer Sensor. Wf30-40b410
Dsl-8d04q02m025km1
1211469
Wtb27-3f2611
6007092
Kt5w-2p1113 Sensor-Kontrast Q=pnp
6033208
6032653
1037077 Endlosregler Srs50-Hgv0-K21
5308843 Reflektor P250f
1046446
1044369 Dt50-P1113sensor
1072254 Pgt-10-Pro Toolsprogrammierung Undkonfiguration
6041823
Zt-1200n
1026287
1071553
1036092
P/N: 1068879, Type: Ttk70-Hxi0-K02
6024909
6039745 Bcg05-K1km01pp Drehgeber Mit Seilzug Trommel
5308078
WI9-2n131

6035225
1064578
6039095
1003865
S30a 7011ea
Dos-1205-Ga
1025911 Optische Sensor Wl18-3p430
Dfs60b-S1aa04096
6043358 Dos-1208-Wa-Steckverbinder M12-8p
Vl180-2p42436 Sensor Lichtschränke
Dt250 P2113
1217875
1028232
??-Sa09030a10000
Im18-20nps-Zc1
Idm161-300s Lcb-Reading-Scanner
1019229
Dos-1205-W
Pe1cne2g
1036022
6025931 Dsl-1205-G02mc Kabelverbindender
602097
DI100-21aa2101 Sensor Distanz
Wtb27-3p2483
Nav300-2232
Gse6-P1212 Single-Pass-Sensor
6013407
6041795
5310028
2019506 Type: Bef-1shabazn4
1038155 Inkremental-Encoder, Dfs60b-

Bhek04096
1066552 Fotosensor Grte18-P246
Wtb27-3p2413s09
2073543 Bef-1shabbku2 Bracket 2verbindungselemente Aus Kunststoff
Dg60-5r4150f00501
Im12-02bcp-Zc1
WI24-2r230
Clv620-0120
I200 Lock
1064706 Sensorgse10-P4211 Photoelectricswitch
Cfs50-Aaz0-S01
6036918 Sensor
Nt6-N112
6032669 Controller Ue410-Mu4t5
6009719
1000132
1040977 Lichtschranketyp:Ime18-08bnozc0k
1025994 Lichtschanke Wtb27-3p2411
6028422
6048391 Sensor
6048395
Lms500-2000
1036767 Encoder Dfs60b-Bdpa10000 (Welle 10 Mm.)
1040764 Die Induktiven Sensoren Ime 12-04bpsc0s
Wt260-F470-6020980
Im18-12npo-Zc1
Lut3-650
6020685 Sensor Lichtschanke F. Sick Type: WI150-N420
1041114 2d-Lidar-Sensoren , Lms111-

10100	
1041376 Wtb11-2p2431lichtschränke	
1025994	
P/N: 6049001, Type: Mvm-1m0-2mc-Mklb	
6041662	
Ime30-20npocz0s Sensoren	
PI40a	
Elg3-0330p511 Elg3-0330p511	
1040870 Ime08-02bpszt0s	
6009719 Dos-1205-G-Steckdose (Ready-To -Montage)	
2017550	
Wt2s-P211	
PI80a Reflektor	
Dol-0804-G02m	
2055515	
1045653	
PI100 Reflektor Kv Optische	
WI280-2p2431 Sensor	
Mht15p2349	
1018254 Sensor	
6020974	
1027785	
1040870 Inductive Sensor Sick Ime08-02bpszto	
1036103	
Dfs60, Dfs60e-S4cl01250	1054136 Incremental Encoder
1041014	
Ars60-F4a01024	
Dme4000-223	
C4mt-04214abb04de0	
Stl-1205-W10mq	

1049062 Sensor Lichtschränke
6037322 Steckverbinder Ste-0803-G
Im30-40nps-Nc1
1037063 Drehgeber
WI9-3n1132
1040887
Vt18-204470s01
Bef-Khs-Kh1
5311136
1071552
1071153
Mzt6-03vps-Kp0
1041390 WI11g-2b2531 Lichtschränke
6012829
6048385
Cdm490-0103 Modul Klassifikation
Wtb4s-3n1162v
Im30-10bds-Zw1
1036095
Vte18-3f4712 Optischer Sensor
2029225 Ad-Atm60-Ka3pr Adapterreifen
P/N: 1053411
6010193
1028935 Scanner Laser Sick S30a-4011ca
5311875
2095898 Kabel Yg2a14-100vb3xleax
1051325
Im08-02bps-Zt1
6020767 WI260-S270-Photovoltaiksensor
6037154
2095962
2031086 Kabel

2095838 Reflektoren P250
Vte18-4n8240 Optischer Sensor
1018044 Sensor Kontrastierenden Markierungen, 1 018 044, Q=pnp
6033221
Wt12l-2b530
2076231 Spz-58z-012-P Spannzangen
4056054 Befestigungssystem
1041262
1074761 Absolut-Encoder, Ahm36a- S4pc014x12
1028081
6033188
6048328
6020410
Clv650-0000
1017860 Schalter
6048389
1071746 Lichtschranketyp:Hte18-P4a1bb
6048062 Wtt280l- 2p2536multifunktionsoptoelektronische Sensoren
6022790 Sensoren Optoelektronische Wt160 Wt160-F420
Wl27-3f2631
6029282?
5309683
P/N: 1056741
6025076
P/N: 1057915
1017910
1200120
Ime18-12npszc0s

1040763
1036113
1040405
I17 Sa213 Schalter
1085344
1027754
Vte 180-2p41187
1064914
Dme4000-123
Ime12-04bnsvcos
1209145
2015624
2045891 Screw Terminal Set Kabel- Anschluss
Wl12-P4381
2046579 Connectoh M12.8 Pin:Typ Dsl- 2d08-G0m5ac3
5308961
1050541
1041381
1036116
6036841
Wtb27-3r2611 Lichtschränke Schalter
6029514
Atm60-P1h13x13
1050271 Sensor Sensick Kw5w-2p 1116 Kat. Nr. 1 018 044
Dfs60e-S4ea02000
P/N: 1053494
1030015 Drehgeber Stegmann Atm60- Pah13x13
53009987
Wt45-D260s01
Ws9d430

Ws45r250
Mainhak Rm 210
6048402 Um18-21812a211 Ultraschall-Sensor
2096236
1063131
2045884
Cable
Ime12-08npozcok 1040783
Dol-1204-W02mrn
1025889
Wtb9-3p2261 Optischer Sensor
1037143
6063342 Sensor Lichtschränke. Typ: GII170t-B333
1019231
5320017
5310158
1049052 Klein-Lichtschränken , Wtb9-3n11614047084191732 4047084191732
7901786 Magnet Mag-3015-B
Clv622-1120
1050271 WI14-2p431 Photovoltaiksensor
6052373
WI11-2p2432 4-008-61-1456/50
1301670
Wt18-3p430
1019245 Sensor WI34-B430.
1037869 Afm60b-S1ac004096absoluter Drehgeber Ssi
Dbs60e-Thek05000
GI10-P4151 Kle. Lichtschränke GI10
Dos-1204-G Stecker

Wt9-2p330
Wf80-60b416 Sensor
6034575 Dsl-8u04g10m025km1 Kabel
1013289
1031495
6053041
Cs81-P3612
Dos-1205-Wq
1070872 Sensor
2095898
1027605
Kt5w-2p1116
1047402 Ds50-P1112
Lqts090-351
1036787
WI260-F470
WI170-P122
1050571
Im18-08bpszc0s Induktiver Sensor
2034999
2066614
6009867 Kabel
Kt5g-2p1211
6012828 Sensor Lichtschränke Sick Vtf18-3f1240
1064594 Sensor
Bcg13-K1km05pp
Rt-P3221
6044738 WI280-2h4331 Retro-Refl. Sens.Stellungsgeberoptoelektronnyj
P/N: 6037418, Type: Mvm-1m5-2mc-Mklb
2076543
6025894

1053536 Optische Sensor
1215668
P/N: 1057772
1059338 Dfs60b-S4va04096 Incremental Encoder
S30b-2011ba
LI3-Dm02
1018044 Sensor
P/N: 1057064
6041823 Fotosensor Pnp24v7m
Wt100-N3419
6011050 Wt150-P460-Photovoltaiksensör
6026548 Photoel.-Proximity-Switch Wtb190I-N430
Im08-04npo-Zw1
1054155
Atm60p4h13x13
Dmt10-2-1211
2071332
5308077 Lichtleiter LI3-Dm02
1027908
Ssl-2j04-G02mz60 Kabel
6020280 Induktiver Sensor
Wtb4s-3p3260s02 Sensor
Wtb27-3p2421
1040878
1046135 2d-Lidar-Sensortyp: Lms511-10100 Pro
1043006
Yf2a85-100ub6m2 A85 2096120 Kabel
Vfs60a-Bhpsz0-S02
1065890
6028428

1019250
2025266
Dfs60b-S1pa10000
P/N: 1055606
2092106
6013227 Optischer Sensor
1024123 Lut1b-41235
1042256
Kt5w-2p1216 Contrast Sensor Sick
Vte180-2p42447 Sensor Lichtschränke
6053050
Fx0-Gpro00000
WI24-B2301
WI150-P430
Dol-1205-W10mq
Wtb4-3p 2261 Sensor Lichtschränke
1041436
Im08-1b5ps-Zc1
Dfs60b-S4eb04000
Bef-FI-Alupbs-Hldr (5322501)
6052627
6037496
1036104
2021269 Deckel
6058910 Sensor Doppelte Blatt Ud18-22cc221 Auf Automatik Tetra Pack
WI9-3p2232 P/N: 1049060
Dme2000000
WI 160-F440 9634f 10/30v Dc
102 3958
6010186
5313035

1030015 Atm60-Absolute Pah13x13wegmess
2022547 Dol-0612g10m075km0 Kabel M26*12
1027787 Wl23-2n2430 Lichtschränke
1036093
1041436 Optische Sensoren Pnp, Reflex (Optoelektronische Sensoren Mit Reflektor).Wl12-3p2431
1003865 Pl80a, Reflektor
1044075 Schnittstellenmodul Fx0-Gpro
C45e-0303ag220
Dme4000-311s01
P/N: 6037420, Type: Mvm-2m5-2mc-Mklb
Pgt-01-S
1059466
1019229 Wt34-B410- Lichtschrankenschalter
Kt5w-2n1116 Optischer Sensor
1036110
6050247
1044125
Dfs60e-S1ak01024
1055909
1010995
2022548
Kt5w-2n1116
6012639
5322778
Dme4000-314
6013695
Wtb8-P1111 Sensor
C40s-0701ca010
1054675

10667183
2017381
1041290
6034582
1036089
1025888
2015623
1062542 Mit Kabel 200mm
6020598 I10-E0453 Safetyswitch Schalter Sicherheit
6013872 Sensor
6028369 Dos-1208-Ga Steckdose (Fertigezur Montage)
Dos-1208-Ga Stecker Pin Geschirmt
Dfs60b-S 4 Rk 10000
P/N: 2031070, Type: Dol-2308-G03mjb2
6049452
Wt45-P260
We12I-2p430
Dme4000-221
Srm50-Hza0-S01
7902077 Leitungsdosem 8, 3-Polig (Dc), Geradety: Dos-0803-Gartikel-Nr.: 7902077
Mzz1-03v-N-Awo
Dme4000-327
Im12-04bns-Zw1
1074411
Uc12-11231
Clv650-0120
Cs81-N3612
1060529 Dbs36e-Bbek00100 Inkrementaler Drehgeber
1066548

Im12-02bpo-Zc1
2020935
7028790 Block
6006685
VI18-3p3840
Wt150-P460
T4000-1rca04 Relais
6010190 Sensor Palletizer WI170-P430
Ime12-04bnozcs Induktiver Sensor
Wtb140-P132
1041381 Wte11-2p2432 Lichtschränke
1019228
1061134
1018594
Wt24-2b410
1029789
6044699 Optischer Sensor Mit Reflektor Bis Zu M 13 WI250-P430 Sick 6010610
1052292
1049062
Bef-Mr10500apg Weiel
VI18-3n3940
1058174
6028459
1059925 Sick GL6g-N1211 Miniatur Optoelektronische Sensoren, Npn
Kt5w-2p1116d Pnp 1026 538
M20z-02550a122 Optoelektronische Schutzeinrichtungen
2058653 Sensor
1026833
1059521
1078884 Ahm36b-Bdcj012x12absolute

Wegmess
1018250 Wt12I- 2b530lichtschrankeschalter
7900157 Induktiver Sensor > Im30- 20nps-Zc1
1037651
1037435 Drehgeber Afm60e-S4aa004096
2096238
P/N: 6037419, Type: Mvm-02m-2mc-Mklb
WI23-2p2430
2050705
1050271
6033188 Miniatur-Lichtschrankenwl8g- P2231
5304812
1054675 Sensor W4s-3 Inox
Dme4000-213
1019233
2032807
Clv610-C0000
6059177 Dol-0803-G02mnistarthilfekabel Mitweiblicher Teil
1045654
1223266
1031427 1031427 Ars60-A4b04096 Absolute Wegmess
C40e-0701ca010
6013407 Encoder
Encoder Sick Dgs66-Azzo-S04, 2000 Impulse/Umdrehung, 4-6 Vdc, Ttl.
Iq40-20bpp-Kc1 Induktiver Sensor
1200125
Atm60-P4h13x13
1067207

6048416_Sensor
6010544
Plg3-210f431
6020784
Lichtschranksick W 11-2wtb11-2p2461
Mlg05s-1195a10501