



Sineax

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Sineax Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Sineax Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Sineax U 553	Sineax U 553 AC voltage Transmitter, rms value With the following configuration: ***** Execution according to NLB: No. 01.Form 4 in housing P13, rail mount. 02.Frequency input voltage 1 nominal frequency: 50/60 Hz 03.Measuring range L measuring range: 0 ... 500 V 04.Output signal 2 output: 4 ... 20 mA 05. auxiliary power 1 auxiliary clock: 85 ... 230 V DC / AC 06.Setting time 1 setting time: 0.3 s 07.Test report 0 without test report
Sineax I 552	
KP26643-SINEAX U553	
ECL-10	EXCITATION CURRENT LIMITER ECL-10
Sineax M 562	Ind.Multi-transmitter Programmable, 2 outputs 20 mA HE: 85-230V AC / DC Country of origin: Switzerland Stat. commodity number: 85437090
158437	Sineax M 562 Ind.Multi-Transmitter Programmable, 2 outputs 20 mA HE: 24-60V AC / DC
143587	Connection cable to PRKAB560, FCC6P / USB for M563 / TV809
147779	PRKAB560 programming cable for M563 / TV809 (without connection cable)
M 563 (146458) 24-60V AC/DC	Sineax M 563 Ind.Multi-Transmitter Programmable, 3 outputs 20 mA HE: 24-60V AC / DC 85437090 Switzerland
Sineax I 538	146979 Current transducer Input 1A, 50Hz, output 4-20 mA HE 24V DC
Sineax I 538	146979 Sineax I 538 current transducer Input 1A, 50Hz, output 4-20 mA HE 24V DC
	Sineax M 562 Ind.Multi-Transmitter Programmable, 2 outputs 20 mA HE: 85-230V AC / DC Total net weight: Approx.

Sineax M 562 HE:85-230V AC/DC	0.450kg Country of origin: Switzerland Stat. commodity number: 85437090
152447	
163189	
172081	
530-Sineax P 530	
973059	
999154	
C604S	
DM5F	
Sineax U 553 0...20 mA 24....60 V DC/AC	Sineax U 553 AC voltage Transmitter, RMS value With the following configuration: Execution according to NLB: No 01.Type 4 in P13 housing, rail mount. 02.Frequency input voltage 1 rated frequency: 50/60 Hz 03. Measuring range C measuring range: 0...100 V 04.Output signal 1 output: 0...20 mA 05.Auxiliary energy 2 auxiliary.Uh: 24....60 V DC/AC 06.Response time 2 Response time: 50ms 07.Test report 0 without test report
143587	Connection cable to PRKAB560, FCC6P/USB for M563/TV809 Country of origin: China Total Net Weight: Approx. 0.050kg Country of origin: P.Rep. of China Statistical goods number: 85444290
147779	PRKAB560 programming cable to M563/TV809 (without connection cable) Total Net Weight: Approx. 0.100kg Country of origin: Switzerland Statistical goods number: 85444290
P530	4-20mA transducer
980179	PC connection cable AT
809- Sineax	Sineax TV 809 Programmable isolation amplifier With the following configuration: ***** NLB version: no NLB 01. Design 3 In housing P12/17, screw terminals 02.Version/power supply 2 standard, Un: 85..230V DC/AC 03. Layout of current input 1 input current max. end value 100 mA 04. Limit value signaling 0 Without limit value signalling 05.Test report Without test report 06.Configuration 1 Programmed to order 07.Input signal Z input [mA]: Entry beginning -20,000 Entry late 20,000 08.Output signal Z output [mA]: Output beginning -20,000 Exit late 20,000 09.Output transfer behavior 0 Linear 10.Output time behavior 0 response time standard, approx. 80 ms 11.Mains hum suppression 0 ambient frequency 50Hz 12. Limit, type and values 0 Limit signaling inactive 13.Limit value, switching delay 0 Limit value signaling inactive 14. Limit value, mode of operation 0 Limit value signaling inactive
146458	Sineax M 563 Ind.Multi measuring transducer Programmable, 3 outputs 20 mA HE:24-60V AC/DC

Sineax V 604 transmitter programmable.	Vg corr. 85-230V
Sineax V604 transmitter programmable.	Vg comp. 24-60V ALTERNATIVELY WITH HE 24 - 60V ACDC
ECL-10	EXCITATION CURRENT LIMITER ECL-10
530-	Sineax P 530 active power transmitter With the following configuration: NLB version: no NLB 01.Type 4 in housing P, rail mount. 02.Application 3 4L three-phase current unequal bel. 03.Input rated frequency 1 rated frequency: 50Hz 04.Input nominal voltage 9 input voltage Un [V]: Nominal voltage [V] 500.00 05.Rated input current 2 input current In: 5A 06. Measuring range 1 measuring range bipolar: Measuring range final value 4,330.000 Measuring range unit W Calibration factor c 0.999000 07.Output signal, start value 3 Live-zero output, start value 20% end value 08.Output signal, end value 1 output end value 20 mA 09. Auxiliary energy 1 hour: 85..230V DC/AC 10.Additional text on type plate 0 without additional text 11.Test report 0 Without test report
534-	Sineax F 534 frequency transducer With the following configuration: ***** NLB version: Not according to NLB 01.Design 4 SINEAX in housing P13, rail mounting 02.Input nominal voltage 1 input voltage. Un: 10...230 V 03.Measuring range 1 measuring range: 45..50..55Hz 04.Output signal 2 output: 4...20 mA 05.Auxiliary energy 1 Uh: 85..230V DC/AC 06.Setting time 1 4 periods of the input freq.
536-	G 536 phase angle/ Power factor transmitter With the following configuration: ***** NLB version: Not according to NLB 01.Design 4 SINEAX in housing P13, rail mounted. 02.Measuring type 2 power factor (prop.cosPhi) 03.Application 2 3-or 4L-revolving str.U:L1-L2/I:L1 04.Input Rated Frequency 1 Rated Frequency: 50Hz 05.Input nominal voltage 1 input voltage. Un: 100V 06.Input Rated Current 1 Input Current In: 1 A 07.Measuring range 2 MB: 0.5..cap..1..ind..0.5 08.Output signal 2 output: 4...20mA 09.Auxiliary energy 1 Uh: 85..230V DC/AC 10.Setting time 1 4 periods of the input freq. 11.Test report E Test report English
538-	Sineax I 538 AC measuring transducer With the following configuration: ***** NLB version: Not according to NLB 01.Design 4 in housing P8, rail mounted. 02.Frequency of input current 1 Rated frequency: 50/60 Hz 03.Measuring range A Measuring range: 0...1 A 04.Output signal 2 output: 4...20 mA 05.Auxiliary energy 5 Uh: 230 V AC 06.Adjustability measuring range 0 MB final value fixed 07.Test report E Test report English
530-	Sineax P 530 active power measuring transducer With the following configuration: ***** NLB version: no NLB 01.Design 4 in housing P, rail mounted. 02.Application 3 4L three-phase current unequally charged. 03.Input Rated Frequency 1 Rated Frequency: 50Hz 04.Input nominal voltage 1 input voltage Un 100..115V[V]: Rated voltage [V] 100.00 05.Input Rated Current 1 Input Current In: 1 A 06.Measuring range 2 Measuring range unipolar: Measuring range final

	value 173.210 Measuring range unit W Calibration factor c 1.000000 07.Output signal, initial value 3 Output live zero, initial value 20% final value 08.Output signal, final value 1 Output final value 20 mA 09.Auxiliary energy 1 Uh: 85..230V DC/AC 10.Additional text on nameplate 0 without additional text 11.Test report E Test report English
531-	Sineax Q 531 reactive power measuring transducer With the following configuration: ***** NLB version: no NLB 01.Design 4 in housing P, rail mounted. 02.Application 3 4L three-phase current unequally charged. 03.Input Rated Frequency 1 Rated Frequency: 50Hz 04.Input nominal voltage 1 input voltage Un 100..115V[V]: Rated voltage [V] 100.00 05.Input Rated Current 1 Input Current In: 1 A 06.Measuring range 1 measuring range bipolar: Measuring range final value 173.210 Measuring range unit var Calibration factor c 1.000000 07.Output signal, initial value 3 Output live zero, initial value 20% final value 08.Output signal, final value 1 Output final value 20 mA 09.Auxiliary energy 1 Uh: 85..230V DC/AC 10.Additional text on nameplate 0 without additional text 11.Test report E Test report English
539-	Sineax U 539 AC voltage measuring transducer With the following configuration: ***** NLB version: Not according to NLB 01.Design 4 in housing P8, rail mounted. 02.Frequency of input voltage 1 Rated frequency: 50/60 Hz 03.Measuring range A Measuring range: 0...100 V 04.Output signal 2 output: 4...20 mA 05.Auxiliary energy 5 Uh: 230 V AC 06.Adjustability measuring range 0 MB final value fixed 07.Test report E Test report English
542-	Sineax I 542 AC measuring transducer With the following configuration: ***** NLB version: Not according to NLB 01.Design 4 in housing P8, rail mounted. 02.Measuring range 1 measuring range: 0...1.0 / 5 A 03.Output signal 3 output: 0...20 mA 04.Adjustability measuring range 0 MB final value fixed 05.Test report 0 without test report
Dm5s-	SINEAX DM5S Multi-Transmitter with Analog Output, MODBUS / RTU (optional), programmable With the following configuration: NLB version: Not according to NLB 01 Type 0 Without display, for DIN rail mounting 02.Application 1 Universal version all applications 3U / 3I 03.Nominal frequency 1 45..50 / 60..65 Hz 04.Auxiliary energy 1 rated voltage 24..230V DC, 100..230V AC 05.Bus connection 1 RS-485 (Modbus / RTU protocol) 06.Outputs 4 4 analogue outputs, bipolar ± 20mA 07.Test protocol without 08. Programming basic programming
Sineax I542	
Sineax U 543	Sineax U 543 AC voltage transmitters With the following configuration: NLB version: Not according to NLB 01.Form 4 In housing P8, rail mounting. 02.Measurement range L Measuring range: 0 ... 250 V 03. Output signal A Output: 0 ... 10 V. 04.Adjustability Measuring range 0 MB end value fixed 05. Test report 0 without test report
Dme440	

Tv809	
154063	Sineax A200 Display Unit for DME4 96x96, 20-265V AC / DC Country of origin: Switzerland stat.warnumber: 85439000 Preference: no
I 538	
V604-112	
137887	
Sineax M 563	Sineax M 563 Ind.Multi-Transmitter Programmable, 3 outputs 20 mA Power supply: 85-230 V AC / DC Country of origin: Switzerland stat.warnumber: 85437090 Preference: no
Usb Rs485,	
129214	Sineax DME 442 multi-measuring transducer Programmable, output: 4 analogue / 2 digit. Auxiliary power: 85-230 V AC/DC
531 4221123110d	
141896 V624	
141416	
V624 Order Code : 141929	Sineax V624 Temperature Transmitter programmable, 4- 20mA, [EEx] HE 85-110 / 230V Country of origin: Switzerland stat.warnumber: 85437090
531-	Sineax Q 531 reactive power transmitters With the following configuration: NLB version: no NLB 01.Form 4 In housing P, rail mounting. 02.Application 2 3L three-phase current unequal bel. 03. Input nominal frequency 1 Rated frequency: 50 Hz 04. Input rated voltage 1 input voltage 100u.1.15V [V]: Rated voltage [V] 100.00 Up (primary) [V] 154,000.00 05. Input rated current 1 Input current In: 1 A Ip (primary) [A] 500.00 06.Measurement range 1 measuring range bipolar: Measuring range final value 120,000 Measuring range unit Mvar Calibration factor c 0.899000 07. Output signal, initial value 3 Live-zero output, initial value 20% final 08. output signal, end value 1 output end value 20 mA 09. auxiliary power 1 Uh: 85..230V DC / AC 10.Additional text on type plate 0 without additional text 11. Test report 0 Without test protocol
U 539	
Dm5s	
Dme 442	
Vc603-122	TRANSMITTER/ALARM SMART SIGNAL
Tv 809	
	Sineax TV 809 Programmable Isolation amplifiers With the following configuration: NLB version: no NLB 01.Form 3 In

809	housing P12 / 17, screw terminals 02.Execution / Power 2 Standard, Un: 85..230V DC / AC 03. design current input 1 input current max. Final value 100 mA 04. Limit value signaling 0 Without limit value signaling 05. Test report Without test protocol 06.Configuration 1 Programmed by order 07.Input signal 9 input [V]: Input beginning 0,000 Entrance end 0.060 08. Output signal 0 Output: 4..20 mA 09.Output Transmission Behavior 0 Linear 10.Output time response 0 Standard setting time, approx. 80 ms 11. Power hum suppression 0 Ambient frequency 50Hz 12. Limit value, type and values 0 Limit signaling inactive 13. Limit value, switching delay 0 Limit signaling inactive 14. Limit value, mode of operation 0 Limit value signaling inactive
537-G	537 Phase angle difference measuring envelope With the following configuration: NLB version: Not according to NLB 01.Form 4 SINEAX in housing P13, rail mounting. 2nd input frequency 2 Rated frequency: 60 Hz 03. Input rated voltage 9 Input sp. Un [V]: Rated voltage [V] 115.00 04.Measurement range 9 Messber. [° el]: Measuring range beginning [° el] - 180,00 Measuring range end [° el] 180.00 05. Output signal 2 Output: 4 ... 20mA 06.Hilfsenergie 4 Uh: from Messeing. 85..230VAC 07.Setting time 1 4 periods of input freq. 08. Test Protocol 0 without test protocol Country of origin: Switzerland stat.warnumber: 85437090
Z242200035	