

Sondermann



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz. **Sondermann** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Sondermann Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Rm-Pp-E-24/340-90-2,2/3	"Replacement for pump: RM-PP-EGKKK-24/340, serial no .: 2011040367" Magnetic centrifugal pump BG 4 Material: polypropylene O-ring: EPDM Impeller ring: Teflon graphite Housing thrust rings: oxide ceramic Plain bearings: oxide ceramics Centering shaft: oxide ceramic Connections: suction side G 2¼ Print page G 2 Delivery rate: max. 350 l / min Delivery head: max. 24 mWS Impeller Ø: 50 Hz Motor: three-phase 230/400 V, 2.2 kW, 2900/3450 min.-1, IP 55, 50/60 Hz Efficiency class: IE2 including connection seals Weight / unit: 27.3000 kg
Rm-Pp-13/240-60s	Magnetic centrifugal pump BG 4 RM-PP-E-18 / 240-60-60S-1,5 / 3 Material: polypropylene - O-ring: EPDM Impeller ring: Teflon graphite Housing thrust rings: oxide ceramic Plain bearings: oxide ceramics Centering shaft: oxide ceramic Connections: suction side G 2 1/4 - Print page G 2 Delivery rate: max. 310 l / min Delivery head: max. 17.5 mWS - Impeller Ø: 50 Hz Motor: three-phase 230/400 V, 1.5 kW 2900 // 3450 min.-1, IP 55, 50 // 60 Hz Efficiency class: IE2 - including connection seals Impeller turned to 60 Hz. - Voltage 254/440 V HS code: 8413 70 51 Origin: CE - Weight / unit: 19.4000 kg
60-130235	Replacement for pump: RM-PP-VGKKK-20 / 300-60, serial number: 2016040156 Magnetic centrifugal pump BG 4 RM-PP-V-20 / 300-60-60S-1,5 / 3 Material: polypropylene O-ring: FKM Impeller thrust ring: Teflon graphite Housing thrust rings: oxide ceramic Plain bearing: oxide ceramic Centering shaft: oxide ceramic Connections: suction side G 2¼ Pressure side G 2 Delivery rate: max. 325 l / min Delivery head: max. 20 mWS Impeller Ø: 50 Hz Motor: three-phase 230/400 V, 1.5 kW 2900 // 3450 min.-1, IP 55, 50 // 60 Hz Efficiency class: IE3 including connection seals HS code: 8413 70 51 Origin: EU Weight / unit: 21.0000 kg

70-000111	Magnetic centrifugal pump MAGSON BG6 MA-PFSK-22 / 400-1.5 / 35 Materials: Pump housing: PP (glass fiber reinforced) Impeller magnet unit: PP (glass fiber reinforced) Magnetic coating: PP (without glass fiber) O-ring: FKM Housing thrust washers: oxide ceramic Thrust washer impeller: PTFE (carbon fiber reinforced) Plain bearing: SiC with ETFE surround Centering axis: oxide ceramic Connections: suction side: thread G 2 3/4 " : Pressure side: thread G 2 1/4 " Delivery head: max. 22 m Delivery rate: max. 400 l / min Motor: three-phase, 230 / 400V, 1.5kW, : 2900 min.-1, 50Hz, : IM B5, IP55 Efficiency class: IE3 FU suitability: yes, PTC thermistor Painting: RAL 5011 ***** *) Thread connection can optionally be used against loose flange DN50 (suction side) and DN 40 (pressure side), please use accessories 70-001395 use.
04012900RF	Disc spring De: 40.00 Di: 20.40 L0: 3.10 t: 2.00 F: 4870.50 s: 0.82 Material: 302 stainless steel Weight gr./stc.:14.616 HS code: 7318210000 Country of origin: DE, UK
60-110586	Containment can PP BG 4/60 mm with thrust ring oxide ceramic HS code: 8413 91 00 Origin: EU Weight / unit: 0.5780 kg + Item 314.3 is already included in the containment shroud!
hydraulic cylinder NPR, HD250 50-25/25-50-MFS-0	
PP-100/50-1000, FKM	10-43040510 Barrel pump F430 PP-100/50-1000, FKM Made of polypropylene (PP) O-rings in the mechanical seal O-rings made of FKM (fluorine rubber) Shaft in the liquid area made of Hastelloy C, Outer Ø: 100 mm Immersion depth: 1000 mm Driven by collector motor, brushless motor or compressed air motor
Type: R1 Pp 20/330-305, 3003040753 Obsolete, Replaced By Rm-Pp-Egkkk-20/300-60(60s)-1,5-Ie2/3	
114572	
Rm-Ts-Pp-Vtttt-30/400-90(90)-3,0d/3-Ie2	
118883	
Rm-Pp-Vkkk-2/20-30(30s)-60/1-G	
Rm-Pp-Egkkk-23/650-90s(90s)-4,0/3-Ie2 (118715)	
60-110571	
Rm-Pp-Vkkk-5/35-30(30s)-60/1-G	
Rm Pp Vgkkk	
119323	
Typ Rm-Pp-12/150-30s Obsolete	

Replacement Rm-Pp-Vgkkk-12/150-30(30s)-0,55/3
Rm Pp Vkkk 5 35 30
Rm-Pp-Vgkkk-12/150-30(30s)-0,55/3
60-110570
118666
Gr01 Rd-VIfm-UI F 5958
Rm-Pp-Egkkk-12/150-30(18)-0,37/3-G
Pump
Rm-Pp-Vgkkk-23/650-90s(90s)-4,0/3-Ie2 (118672)
(119323) Rm-Pvdf-Vgkkk-35/200-90(90s)-3,0-Ie2/3-G
Rmb 3.1 Capacity: 20m3 / H Pressure: 8mss
Gr01 Rd
Pompa
Geräte Nr: 2010012679 Obsolete Replacement Rm-Ppsw-Ekkk-5/45-10(16s)-60w/1-G5/4 G1
60-110573
110119
Rm-Ppsw-Vkkk-10/100-45 Obsolete, Replacement Rm-Pp-V-10/100-45-250/3
2009040066
Rm-Pv-E-30/400-90
118794
60-130235
Rm-Pp-Vgkkk-20/300-60(60s)-1,5/3-Ie2
Rm-Ppegkkk-14/180-30(185)
Rm-Pp-Egkkk-20/300-60(60s)-1,5-Ie2/3
Rm-Pp-Vkkk-5/35-30(30s)-60/3-G
60-110439
Replacement for serial number 2011040620 Magnetic

60-130272	centrifugal pump BG 4 RM-PP-E-20 / 300-60-60S-1,5 / 3 Material: polypropylene O-ring: EPDM Impeller start ring: Teflon graphite Housing start rings: Oxide ceramics Plain bearing: oxide ceramic Centering shaft: oxide ceramic Connections: suction side G 2¼ Pressure side G 2 Delivery rate: max. 325 l / min Delivery height: max. 20 mWS Impeller Ø: 50 Hz Motor: Three-phase 230/400 V, 1.5 kW 2900 // 3450 min-1, IP 55, 50/60 Hz Efficiency class: IE3 including connection seals HS Code: 8413 70 51 Origin: CE
Rm-Ppsw-Ekkk-5/45-10(16s)-60w/1-G5/4 G1	
Rmb 3 1 Capacity 20m3	
60-110583	
Rm-Pp-V-5/35-30-30s-60/1	
(118883) Rm-Pvdf-Vgkkk-24/340-60(60s)-1,5/3-G	
Rm-Pp-V-10/100-45-250/3	
S.126/80-3-2pm1	
Rm-Pp-Egkkk-20/300-60(60s)-1,5/3-1e2	
60-116147 , Type Rm-Pp-V-5/35-30-30-60/1	