



Spirotech

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Spirotech Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Spirotech Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Bronze 1/2"	
SpiroTech AB050	ApiroTop brass large air vent SpiroTop - large air vent with no lockable Permanent vent valve and right-angled drilled Exhaust port for quick release and Ventilate of pipeline networks. Medium water and water / glycol (50/50%) Execution: brass Connection: DN 15 internal thread at the vent valve: DN 15 male thread. Operating pressure: 10 bar max. Max. Temperature: 110 degrees C
Wie bild 180 Grad	
SpiroCross 200 hydraulic distributor	
SpiroCross 250 hydraulic distributor	
SpiroCross 80 hydraulic distributor	
BA050L	5liter
BA125F	
Spirotech	
Spirotech	
Spirotech	
Spirotech	
SpiroTop PN16	
SpiroTop PN25	
IST21.03 DN80	

IST 22.03 DN80	
AB050	SpiroTech AB050 SpiroTop brass large air vent SpiroTop - large air vent with not lockable Permanent- vent valve and drilled at right angles exhaust port for quick unloading and aerate of pipeline networks. Medium water and Water/Glycol (50/50%) Version : brass Connection : DN 15 inner thread at the drain valve: DN 15 outer thread Working pressure : 10 bar Max. Max. temperature : 110 degrees C
Body and Cover: AISI 316L Quality Stainless Steel	Sphere: AISI 316L Quality Stainless Steel Gasket:PTFE Operating Temperature: -20 / + 150 �C Threaded Three Piece Full Bore Ball Valve 1/2" AUTOMATIC AIR EXTRACTION DEVICE
AUTOMATIC AIR EXTRACTION DEVICE	Body and Cover: AISI 316L Quality Stainless Steel Maximum Operating Temperature: -25 / +180 �C Pressure Class:PN16 Threaded Strainer 1/2"
AUTOMATIC AIR EXTRACTION DEVICE	Body and Cover: Ni Plated Brass Globe: Chrome Plated Brass Gasket:PTFE Maximum Operating Temperature: 110 �C Pressure Class:PN16 Threaded Full Bore Ball Valve 1/2"
AUTOMATIC AIR EXTRACTION DEVICE	Body and Cover: Ni Plated Brass Globe: Chrome Plated Brass Gasket:PTFE Maximum Operating Temperature: 110 �C Pressure Class:PN16 Threaded Strainer 1/2"
Automatic Air Release Device 1/2" (DN15)	
2" Spirovent BSP FEMALE	
7738307340	
Ua022w	SPIROVENT RV2 micro bubble separator Connection: 22 mm - clamping ring
Ba100f	SpiroVent Air separator DN 100 flange P max. 10 bar T max. 110 C
Ba150l	
Tab050	optional Prefabricated insulation for SpiroTop - automatic large air vent Max. 110 � C Item No. TAB050
Ab050	SpiroTech AB050 SpiroTop brass large air vent SpiroTop - large air vent with non-lockable Permanent- vent valve and drilled at right angles exhaust port for quick venting and ventilation of pipeline networks. Medium water and Water/Glycol (50/50%) Version : brass Connection : DN 15 inner thread at the drain valve: DN 15 outer thread Operating pressure: 10 bar max. Max. temperature : 110 degrees C
7738323622	
Sanit�re Installation	
Et 01/02	
7747222507	

Aa075/008	
7738323616	
Spirotop Ab050	
Bf100f	SpiroTrap Removable Mud separator DN 100 flange P max. 10 bar T max. 110 C
Et 03	
7738323619	
7726241011	
S-Hc200f-002	
Art.-Nr.: Ab050/007	SPIROTOP - automatic large air vent High temperature Connection: ½ "IG T-Max .: 180 ° C P-max .: 10 bar
Art.-Nr.: Ab050/002	SPIROTOP - automatic large air vent High temperature Connection: ½ "IG T-Max .: 180 ° C P-max .: 10 bar
Bv/00/03-1000 Lt	
Bv 1/2quot;	
Bv/00/04-750 Lt	
Ab050-R007	
Art.-Nr.: Aa075	SPIROVENT MICROBUM BLOWER SEPARATOR CONNECTION: ¾ "IG
Spirtrap Dn 125	
Et 04	
S-Hc200f-002 (Tap)	
Hc150f	
Ae150	
7747204666	
Bv/00/01amp;02-4000 Lt	
Ab050/002	
Ab050/008	
Be100f	SpiroTrap Mud separator DN 100 flange P max. 10 bar T max. 110 C
Sv2-150-Fh	
Ab050/R007	SPIROTOP - automatic large air vent Connection: ½ "IG Max. 10 bar / 180 ° C Housing: stainless steel Float: stainless steel Art.-No .: AB050 / R007

Art.-Nr.: Ab050/030	SPIROTOP - AUTOMATIC BIG DEVICES SPECIAL CONNECTION: ½ "IG MAX. 16 BAR / 110 ° C
Art.-Nr.: Ab050	SPIROTOP - automatic large air vent Connection: ½ "IG Art.- No .: AB050