

Straub

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Straub Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Straub Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Eco Grip Ø88.9 - Stainless Steel A4	
100695	
103519	
103537	
1105	
1110	
1112	
13146	
481-525-300	
G20206	
G20351	
G20450	

G20550	
G20551	
G20558	
G20601	
G20650	
G20900	
G21051	
STRLE48	
WGR560	Item No.: G21107 STRAUB-GRIP FF 133.0 mm NBR/ES W5 Clamping range 131.7 - 134.3 Housing 1.4404 or equivalent Screws A4-80 Bolt 1.4404 or equivalent Sealing sleeve NBR Operating pressure (Ind.) 21.00 Temperature -20°C - +80°C
article_code=6829/0612	name plate=6620M0016 NORMA Grip-E-FP-W5-NBR ø133.0
article_code=6829/0612	name plate=6620M0018 NORMA Grip-E-FP-W5-NBR ø133.0
OPEN-FLEX 1 □ 114.3mm EPDM/ES PN20 W5	35650 Sealing Sleeve :EPDM Clamping Range :112,5. - 116.0 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :20
OPEN-FLEX 1 □ 76.1mm EPDM/ES PN25 W5	35250 Sealing Sleeve :EPDM Clamping Range : 74.5-77.5 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25
OPEN-FLEX 1 □ 88.9mm EPDM/ES PN25 W5	35350 Sealing Sleeve :EPDM Clamping Range :87.5-90.5 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25
OPEN-FLEX 1 □ 48.3mm EPDM/ES PN25 W5	35000 Sealing Sleeve :EPDM Clamping Range :47.0 - 49.5 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25
OPEN-FLEX 1 □ 60.3mm EPDM/ES PN25 W5	35150 Sealing Sleeve :EPDM Clamping Range :59.0-63.0 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :25
GRIP 33.7 mm EPDM/ES W5	ALTERNATIVE (Bu boyuttaki OpenFlex modeli üretimden kaldırılmıştır) G20100 Sealing Sleeve :EPDM Clamping Range :33.2-34.2 Temperature : -20 C to +100C CAsing : 1.4404 o. equivalent Bars : A4-80 Bolts : 1.4404 o.rquivalent Pressure (Ind.) :39
30600	108.0mm EPDM/W5 /PN20 Clamping range 106.5-110.0 Pressure ind. 20 EPDM Casing 1.4404 Bars A4-80
30800	133.0mm EPDM/W5 / PN16 Clamping range 131.0-135 Pressure ind. 16 Sealing sleeve : EPDM Casing 1.4404 Bars A4-80
Grip-L 166,6 - 170,0mm	

Grip-L 166,6-170,0mm	
491-625-300	
41681663	
Grip W5 114,3mm	NBR PN bar 22
42218654	
Grip-L 47,8 - 48,8mm	
41806532	
S30651/1-L-114,3	
381-215-200	
S30251/1-L-76,1	
42216950	
Grip-L 138,3-141,1mm	
Grip-L 33,2 - 34,2mm	
392-420-400	
381-108-200	
Grip-L 59,7 - 60,9mm	
500246716	
Grip W5 168,3mm	NBR PN Bar 16
491-525-300	
Grip-L 113,2-115,4mm	
500246715	
Grip-L 113,2 - 115,4mm	
Rep-Flex Kupplung Reparaturd525mm (525-535) L=300mm Nbr/Es	
Grip-L 26,4 - 27,4mm	
Grip-L 273,0mm	
41625338	
Grip-L 138,3 - 141,1mm	
Grip-L 216,9 - 221,3mm	
Grip-L 59,7-60,9mm	
Grip-L 88,0 - 89,8mm	

Grip-L 33,2-34,2mm
381-269-300
Grip-L 75,3-76,9mm
381-159-200
Grip-L 41,9-42,9mm
Grip-L 48.3 Kupplung
S30151/1-L-60,3