



Tapeswitch

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Tapeswitch Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Tapeswitch Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
PRSU/4	PRSU / 4 evaluation device Supply voltage: 24V AC / DC Mounting: DIN mounting on top hat rail Contacts: 3 NO contacts, 1 NC contact Reset: aut. / Ext. Temperature range: -25 ° C to + 55 ° C Safety category: EN ISO 13849-1 PL "d" Customs tariff number: 85364190 country of origin: Germany Net weight: 0.2kg
121BP/0100/2	
121BP/0250/1	
CKP/C1/0175/0120/1	
CKP/S1/0600/0500/4	
GS140/S/4/15/LED	
M12/5/20	
M12/8/20	
PSSZ/4	

TS26C/0805/3	
TS26C/1270/1	
TS26C/5000/7	
TS28	
TS-46-AL FC - VAL0044325	
PRSU/4	PRSU/4 evaluation device Supply voltage: 24V AC/DC Mounting: DIN mounting on top-hat rail Contact equipment: 3 NO contacts, 1 NC contact Reset: aut. / ext. Temperature range: -25°C to +55°C Safety category: EN ISO 13849-1 PL"d" Customs tariff number: 85364190
Ts28/1060/4 Ts28/1060/F/A/B/Fs/Ee/0500/ 0500/N	
Ts3/0558/1	
Ts26c/0750/9	
Ts-46d - Val0044338	
B1230	SAFETY UNIT
800-234-8273	
B3230	LIGHT CURTAIN
Ckps1sesrs100009003000	
Ts26c/0805/3	
Pssu/2.	
Ts6/2235/1	TS6/2235/F/A/R/FS/EE/5000/ 2000/N/AC Safety Edge Type: TS6 Length: 2,235mm Profile rail: aluminum, flat Profile color: red Material: EPDM / PP Band switch: 107BPE IP67 Wiring: Fail-Safe (4-wire) Cable outlet: two-sided (EE) Cable length: 1 x 5,000mm, 1 x 2,000mm Cable type: Ölflex Robust 210; 2 x 0.5mm² Connection: make contact max. 30V @ 1A loadable End cap version: without Special feature: At the beginning and end has the safety edge is not active Range of max. 50mm. Drawing: ---- Tariff No .: 85365019
B0830r	LIGHT CURTAIN RECEIVER 808MM 18MS 24VDC
0921m	LIGHT CURTAIN
B0830r0905	B SERIES LIGHTCURRENT
0930	LIGHT CURTAIN
Ts-26p	
0906	LIGHT CURTAIN
Ts26/Lca/0620/4w	

E3049-119-004	
B/S/1200/30/15/Cb	LIGHT CURTAIN RECEIVER 12V 24VDC
Prsu/2	
Ts26c/1700/1	
Ts26c/0750/F/A/B/Fs/Oe/2000/ 2000/N	
Pssu/2	
Prsu/4	
B830	RECTIFIER
Ts26/Lca/1000/4w	
121- Val0008760	
Ckp/S1/Se/Srs/1600/1100/3000	
0904	LIGHT CURTAIN 608MM 30MM 24VDC
Ts6/860	
B0630e	LIGHT CURTAIN EMITTER
Sp-1324-1	
Ts-46-AI Fc ? Val0044325	
B0630r	LIGHT CURTAIN RECEIVER
Bs0330r	LIGHT CURTAIN RECEIVER 0.5-15M RANGE 24VDC
Sensing Edge Ts-26p 750 Mm	
Ts-26p 750 Mm In Length	
121bp/0270/1	
920022	
B/S/0800/70/15/Cb	LIGHT CURTAIN
121-Bp	CABLE LENGHT 8m 8m TO OTHER END+LENGHT OF RİBBON SWITCH
Mes0628	LIGHT CURTAIN RANGE .3-6M CAP 28MM P.HEIGHT 630MM
Ckp/S1/2000/1200/7	
Sab Tx 116/Sd Range 6m	
Sp-3291-1	