

Tecsis



Garanti: 12 ay
Bu ürüne ait Türkiye içi
kapı teslim fiyat ve
teslim süresi içeren
teklifimizi almak için
info@yursat.com.tr e-
posta adresine başvuru
yapabilir ya da ayrıntılı
bilgi için +90 224 240 03
04 numaralı
telefonumuzdan bizlere
ulaşabilirsiniz.
Tecsis Markası, tedarik
süresi için lütfen bizimle
iletişime geçiniz.

*Firmamız Tecsis Türkiye
Distribütörü veya temsilcisi
değildir. Firmamız sipariş
durumunda, belirtilen ürünlerde
sadece Orjinal ve yeni ürün teklifi
sunmaktadır. Bu sitede gösterilen
Özel marka adları ve ticari
markalar ilgili sahiplerinin
mülkiyetindedir, talep durumunda
kaldırılmaktadır.*

Ürün	Açıklama
14255043	Digital display for panel mounting BR-specific standard text 1: 5-digit red Series: E1931 LED display for mA or V Signal input: 0 (4) ... 20mA (2L / 3L) or 0 ... 10V Display height: 14 mm Supply voltage: 85 ... 250 VAC Data sheet: DD965 Customs tariff number: 85312020
Typ A-10	Pressure transmitter for general applications Type A-10 Technical data according to data sheet: PE 81.60 Wetted parts: 316L Case: 316L Nonlinearity: 0.5% BFSI Unit: bars Type of pressure: relative Measuring range: 0...10 bar Process connection: G 1/2 A DIN EN ISO 1179-2 (formerly DIN 3852-E) Gasket: NBR permissible medium temperature: -30...+100 °C Output signal: 4 ... 20 mA, 2-wire Auxiliary power: 8...30 V DC Electrical connection: Angular connector DIN EN 175301-803 A Approvals: cULus Customer logo: WIKA standard Customer address: www.wika.com Type designation customer-specific: A-10 Type of packaging: folding box simple Assignment of electrical output: UB=1, 0V=2 Type: A-10 2.0 Import documentation CIS countries: without Customs tariff number: 90262020
PSD-4	-1...+15 bar ; two Switching outputs (PNP/NPN) Electronic pressure switch with Advertisement Output signal: two Switching outputs (PNP/NPN) IO-Link: without Auxiliary power: 15...35 V DC Measuring range: -1...+15 bar Process connection: G 1/4 B Seal: stainless steel Medium temperature: -20 ... 85 °C (-4 ... +185°F) Electrical output: circular connector M12x1 (4-pin) Assignment of electrical output: U+=1, U-=3, SP1=4, SP2=2 Accuracy: ± 0.5% of span Approvals: cULus with test protocol Technical data according to data sheet: PE 81.86 Customs tariff number: 90262020
S2410B084003	
56019219	
P3276 SO 658 12 O 250MBAX	ABS 0 25%, 4 20MA DC 10 30V
S6210C050001	
F2301 tension/compression force transducer	amplifier Publication: FO 51.17 Series: F2301 tension/compression force transducer with integrated amplifier Direction of force: tension Unit: kN Rated load: 30 kN Relative non-linearity: 0.50% From Output signal: 2x4...20mA 2-L, integrated Electrical connection: circular connector, M12 x 1, 4 pin Publication: FO 51.17
S4250B144042	
P2324	Manometer 0...16bar R1/2"
P3297B075040	
S5400 -50..200 C	

MPR6-B1H08-5 Ü C R1/4" 2K-CCB	
TR06-ÖZEL-2K-Ü-M12 1 X PT-100	
3354786/ 2932705	
1106184196	
Tep11x221302	
P3297b084001	
S1100b070007	
P3276b128674	
P3317m063120	
F13041450001	
31143085	Electronic pressure switch "Mag switch" Series: S1100 MagSwitch Setting ranges up to 25 bar Unit: bar Adjustment range: -0.9 ... 0.05 bar Connection thread: G 1/4 B Output: 1 NO (NO), 1 NC (NC) Switching function: P-switching Factory set: no El. Connection: Circular connector M12 x 1, 4-pin, IP65 Wetted materials: brass, Ni / Cu alloy Datasheet: DD740 Label logo: tecsis Customs tariff number: 90262020
1601.016.001	
P3251b074001	
Ts-P3276b087920	
S2410b047003 - Digitaler Druckschüttler	
Te200x12b025	
Epe01x001001	
F53084515011	
S4250b086023	
S4250b084001	
P3297b081001	
S2410b047003 - Electronic Pressure Switch/Sensor With Led Display - 1...10bar,12...30vdc,4...20ma	
2850	
Egs80x002001	
3373.195.813	
Vdo 4-20ma	

41139	
P3276b075001	
P3326b086002	
P3276b078001	
F23011450001	
P3276b072001	
3373.084.001	
P3298b091101	
P3410	
S2400b084403	
P3297s073001 (Ex.P3296s073002)	
P3276b075501	
P3276b084622(Ex.3376.084.922)	
S2410b047003 - Drucktransmitter	
P3297s069021	
P3276b087920 (Ex.3376.087.920)	
P2590b070003 (Ex. 2591.070.001)	
P3298 B 091 001	
P3251b075090	
Art Nr. 12701050	Pressure transmitter for general applications type A-10 Technical data according to data sheet: PE 81.60 Wetted parts: 316L Housing: 316L Non-linearity: 0.5% FSL Unit: bar Printing method: relative Measuring range: 0 ... 10 bar Process connection: G 1/4 B Seal: copper permissible medium temperature: -30 ... + 100 ° C Output signal: 4 ... 20 mA, 2- wire Power supply: 8 ... 30 V DC Electrical connection: Angle connector DIN EN 175301-803 A Approvals: cULus TE Customer logo: Tecsis Customer address: www.tecsis.de Type designation customer specific: tecsis type Packaging: folding carton easy Seal electr. Connection: Neutral (brown)
60121510bar3	SWITCH
F32103410112	