



Thyracont

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Thyracont Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Thyracont Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
B_VSM77	
SLKBT	
SLKUSB	
SLN4	
VD85M	
VSM77D	
VSP63MA4	
W1515010	
XB15SL05	
ZSR2025	
ZZCH025	
ZZR025	
VSP63MV	Pirani vacuum transmitter Absolute pressure 1.0e-4 - 1000 hPa Output signal 1.5 - 8.5 V logarithmic Electrical connection: Hirschmann 6-pin male. Stainless steel flange DN 16 ISO-KF
W0600002	Measuring cable with open ends, 2 m

DCERT	Factory calibration digital
VCP63MV Vacuum transmitter Pirani	absolute pressure 5.0e-4 - 1000 hPa, Corrosive gas version, platinum-rhodium filament Output signal: 2.2-8.5 V (logarithmic) Electrical connection: Hirschmann 6-pin male. Stainless steel flange DN16 KF
XB0600002	Line socket 6-pin. GO 6 WF Mating connector for analog line transmitter 0-10 V
DCERT - Factory calibration digital	four-page calibration certificate as a PDF DOCUMENT for documentation, 4 reference points per printing decade (traceable to national DAKKS standards)
VD85	Compact vacuum gauge Piezo / Pirani Absolute pressure 5.0e-4 - 1200 hPa, combination sensor Data logger function, min/max memory USB interface for battery (9 V) or ext. Power adapter (15V) Stainless steel flange DN 16 ISO-KF
VD8ZUB	Accessory set VD8 consisting of: VD8CASE protective case VD8, with foam insert, 275 x 230 x 83 mm; VD8N4 plug-in power supply 15 V, input plug: AC plug, EURO, US, UK, AUS Output: 15 VDC / 200 mA, DC jack connector: 2.5 x 5.5 x 10 mm; VD8ALK alkaline block battery 9 V (vacuum tested); WUSB0002 Interface cable, 2 m, USB; VGR VacuGraph 11 software, for Windows Vista / 7 / 8 / 10 / 11
VCP63MA4	Vakuumtransmitter Pirani
XB0500004	Angle socket 5-pin, series 713 Mating connector, 5-pin for analog line transmitters 4-20 mA
DCERT	Factory calibration digital
SP363MV	Pirani vacuum transmitter Absolute pressure 1.0e-4 - 1000 hPa Output signal 1.0 - 10 V logarithmic (1.286 V/decade) Electrical connection: FCC68 8-pin female. Stainless steel flange DN 16 ISO-KF
VSP63MV	Pirani vacuum transmitter Absolute pressure 1.0e-4 - 1000 hPa Output signal 1.5 - 8.5 V logarithmic Electrical connection: Hirschmann 6-pin male. Stainless steel flange DN 16 ISO-KF
VD85	Compact vacuum gauge piezo / Pirani Absolute pressure 5.0e-4 - 1200 hPa, combination sensor Data logger function, min/max memory USB interface for battery (9 V) or ext. Power supply (15V) Stainless steel flange DN 16 ISO-KF
VD8ZUB	Accessory set VD8 consisting of: VD8CASE VD8 protective case, with foam insert, 275 x 230 x 83 mm; VD8N4 plug-in power supply 15 V, input plug: AC change-over plug, EURO, US, UK, AUS Output: 15 VDC / 200 mA, DC jack plug: 2.5 x 5.5 x 10 mm; VD8ALK alkaline block battery 9 V (vacuum tested); WUSB0002 interface cable, 2 m, USB; VGR VacuGraph 11 Software, for Windows Vista / 7 / 8 / 10 / 11
VD8ANS	Connection set consisting of: - 1 piece ZTS016 DN 16 ISO-KF T-piece, stainless steel - 2 pieces ZZR016 DN 16 ISO-KF centering sealing ring, stainless steel / Viton - 2 pieces ZSR1016 DN 10/16 ISO-KF clamping ring, aluminum
Vd8alk	
Vsp62mvsw	
Wusb0002	
Vd85	
Vd8case	
Vgr	

Vd8ans
W1500002
Zzr016
Vd81
Vd8n4
Vd84
W0606002
Adjcert
Vsr53d
Zsr1016
Vd81sw1
Vd85m Obsolete/Replacement Vd85
Vd83
Vsp63mv
Vsp52 Ma4
Vcc200ma4
Vsh88d
Vd84/1
Vsm77dl