



TLV

Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

TLV Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız TLV Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Druckreduzierendes Dampfventil Dn50 Pn40 Cs	angeflanscht Flüssigkeit: Wasserdampf; Auslegungsdruck und -temperatur: 26 bar.g @ 230 derC; Arbeitsbedingungen in der Sattedampfphase; Arbeitsdruck: 18-20 bar.g; Ausgangsdrucksollwert: 3-5 bar.g; Kapazität: 13-14 TPH
1/2 "800lb Sw Astm A105 Absperrschieber	
1 "300lb Kondensatableiterflansch	(Beispiel: Modell P46SRN der Marke TLV)
1/2 "thermodynamischer	Kondensatableiteranschluss (z. B. TLV-Marke P46SRN-Modell)
Dn40 Pn40 Vollhub-Sicherheitsventil	(Flüssigkeit: Wasserdampf-Einstelldruck: min. 4,5 bar.g)
JF3X-8 DN25 PN16 GGG40.3	Free float steam trap Material: ductile iron (GGG40.3) Nominal width: DN 25/1 "/ 25 mm Connection type: flange PN 16 Installation position: horizontal PMA (maximum allowable pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C Vent: X element Max. Differential pressure: 8 bar HS code: 84818061 Country of origin: JP Item weight: 19.12 kg
J3X-8 3/4" Rp (BSP) GGG40.3	Free float steam trap Material: ductile iron (GGG40.3) Nominal width: DN 20 / 3/4 "/ 20 mm Connection type: threaded socket BSP Installation position: horizontal PMA (maximum allowable pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C Vent: X element Max. Differential pressure: 8 bar HS code: 84818061 Country of origin: JP Item weight: 6 kg

JF3X-8 DN15 PN16 GGG40.3	Free float steam trap Material: ductile iron (GGG40.3) Nominal width: DN 15 / 1/2 " / 15 mm Connection type: flange PN 16 Installation position: horizontal PMA (maximum allowable pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C Vent: X element Max. Differential pressure: 8 bar HS code: 84818061 Country of origin: JP Item weight: 14.24 kg
LV13N 1/2" Rp (BSP) C3771	Thermal capsule steam trap Material: brass (C3771) Nominal width: DN 15 / 1/2 " / 15 mm Connection type: threaded socket BSP PMO (max. Permissible operating pressure): 13barG TMO (max. Permissible operating temperature): 200 ° C HS code: 84818069 Country of origin: JP Item weight: 0.72 kg
VENKAVA VSR8	
1041525	
1083533	
1285064	
1295927	
1295933	
1295973	
1295990	
1296074	
1338207	
1340466	
1342807	
1343342	
3000356	
3004365	
3050167	
5110182	
COSR-16	
SJ5FNX-5	
PN16-DN20	
J3S-X-10 3/4" Rp (BSP) CF8	Free-float steam trap Material: stainless steel (CF8) Nominal width: DN 20 / 3/4" / 20 mm Type of connection: threaded socket BSP Installation position: horizontal PMA (maximum pressure): 21barG TMO (max. allowable operating temperature): 220°C Vent: X element max. differential

	pressure: 10 bar
J3X-10 1" Rp (BSP) GGG40.3	Free-float steam trap Material: nodular cast iron (GGG40.3) Nominal width: DN 25 / 1" / 25 mm Type of connection: threaded socket BSP Installation position: horizontal PMA (maximum pressure): 13barG TMO (max. allowable operating temperature): 200°C Vent: X element max. differential pressure: 10 bar
P46SRN DN20 PN63 A105 (L=210mm)	Thermodynamic condensate drain Material: carbon steel (A105) Nominal width: DN 20 / 3/4" / 20 mm Type of connection: Flange PN 63 PMO (max. allowable operating pressure): 46barG TMO (max. allowable operating temperature): 400°C
TLV LV21 Repair Kit	
5330103	dirt sieve
5338285	X element
5330149	Tension bracket
JF3X-10 DN25 PN16 GGG40.3	1343303 Free-float steam trap Material: nodular cast iron (EN 5.3103) Nominal width: DN 25 / 1" / 25 mm Connection type: flange PN 16 Installation position: horizontal PMA (maximum permissible pressure): 13barG TMO (max. permitted operating temperature): 200°C Venting: X element
L21S DN25 PN40 A105	1295918 Thermal capsule steam trap Material: carbon steel (A105) Nominal width: DN 25 / 1" / 25 mm Connection type: flange PN 40 PMO (max. permitted operating pressure): 21barG TMO (max. permitted operating temperature): 235°C
Repair kit P65SRN A105	3000145
Repair kit P65SRN A105	3000145
V2P-RB 15mm SW ASME F304	1033481 Base unit for drainage station with 2xASV Material: stainless steel (F304) Nominal width: DN 15 / 1/2" / 15 mm Connection type: S.W. ASME welding socket PMO (max. permissible operating pressure): 50barG TMO (max. permitted operating temperature): 425°C
V2P-LB 15mm SW ASME F304	1033509 Base unit for drainage station with 2xASV Material: stainless steel (F304) Nominal width: DN 15 / 1/2" / 15 mm Connection type: S.W. ASME welding socket PMO (max. permissible operating pressure): 50barG TMO (max. permitted operating temperature): 425°C
L21C	1079855 Thermal capsule steam trap unit Material: stainless steel (CF8) Installation position: universal PMA (maximum permissible pressure): 21barG TMO (max. permitted operating temperature): 235°C
Universal connector:	F46 DN20 PN40 CF8 Universal connector Material: stainless steel (CF8) Nominal width: DN 20 / 3/4" / 20 mm Connection type: flange PN 40 Installation position: universal PMA (maximum permissible pressure): 50barG TMO (max. permitted operating temperature): 400°C

Free-float steam trap unit:	S5-10 316L Free-float steam trap unit Material: Type316L Installation position: universal PMA (maximum permissible pressure): 32barG TMO (max. permitted operating temperature): 400°C max. differential pressure: 10 bar
1295640 / J7x-10 Dn40 Pn16rf	
Ef73 Dn80 Pn40	
J3x-10	
J5x-10	
Jh7rlx-14 Dn50 Pn40	
Sf1 Jis10kff 40a Scs13a 0.5um	
P46srn C22.8	
1338149	
Mc-Cosr-16 Jis10kff 25a Fc250	
Bbf1n Jis10kff 40a Cac407	
P46srn	
901100000000	
Sc-F70-7-N-N-0	
Cosr-16 Jis10kff 25a Fc250	
745000110416	
J3x-8 25a Fcd450	
Bb1n Rc 15a Cac407 Long Handle	
P46srn A105	
29121085	
745050140000	
Y3 25a Sc13a	
Dc3a	
1342561, Jf3x-5 Dn15 Pn16rf	
729000000001	
J7x-10 Dn40 Pn16rf	
Bbfin Jis10kff 40a Cac 407	
Tm5/Trapmanager	
Dc3s	

J8x-10 Dn100 Pn16
J3x-J5x-J7x
1342807, Jf3x-5 Dn20 Pn16rf
J8sn-8-100a- Obsolete, Replaced By J8x-10 Dn100 Pn16
Ja3-16 Bsp 1/2quot;
Ckf3mg-Dn80 Pn40 Cf8
745050080002
Ck3m-A
Bbin Rc 25a C377i
Cos-16 4quot; Jis 20k Rf
1343575 Ja3-16 Bsp R 1/2quot;
Ef73