

Tosaca



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz. **Tosaca** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Tosaca Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
PN-40 / CF3M	
1216-2x2SS-40-P-00000-8,0L20	TOSACA safety relief valve model 1216 2" x 2" PN-40 BSP-M / BSP-F MATERIAL: A351 CF3M Orif. 32 Area: 804 mm2 End connections: DIN 259 BSP-M / BSP-F Accessories Bonnet: Closed Lever: No Test gag: No Bellows: No Materials Body/Bonnet: A351 CF3M Nozzle: A351 CF3M Disc: SS AISI316L, surface PTFE Spring: AISI-302 Fluid: Demineralized water / L Density: 1000 kg/m3; Molecular weight: 18 g/mol; Cp/Cv: N/A Set pressure: 8,0 barg (116,03 psig) @ Temperature: 20,0° C (68,0° F) Back pressure: 1,0 bar a (14,69 psi a) Requerid capacity: No information Max. flow capacity @ selected orif: 58.286,03 Kg/h
	Alternative item 1 (flanges) TOSACA safety relief valve model 1400 50 x 80 PN 16 / PN 16 MATERIAL: SS 1.4409 Orif. 46 Area: 1662 mm2 End connections: EN 1092 Type B PN 16 / PN 16 Accessories Bonnet: Closed Lever: No Test gag: No Bellows: No Materials Body/Bonnet: SS 1.4409 Nozzle: A351

1400-50x80sS-16-P-00000-8,0L20	CF8 Disc: SS AISI316L, surface PTFE Spring: AISI-302 Service conditions Fluid: Demineralized water / L Density: 1000 kg/m3; Molecular weight: 18 g/mol; Cp/Cv: N/A Set pressure: 8,0 barg (116,03 psig) @ Temperature: 20,0° C (68,0° F) Back pressure: 1,0 bar a (14,69 psi a) Requerid capacity: No information Max. flow capacity @ selected orif: 125.507,08 Kg/h
1216S HP-0,5x0,75SNSS-400-M-00000-200,0L20	TOSACA safety relief valve model 1216S HP 1/2" x 3/4" PN-400 NPT-M / NPT-F MATERIAL: AISI316L Orif. 6 Area: 28 mm2 End connections: ANSI B2.1 NPT-M / NPT-F Accessories Bonnet: Closed Lever: No Test gag: No Bellows: No Materials Body/Bonnet: AISI316L Nozzle: SS AISI316L Disc: SS 17-4 PH, surface Metal Spring: Inconel X-750 Fluid: NO INFORMATION Requerid capacity: No information Back pressure: 1,0 bar a (14,69 psi a) Set pressure: 200,0 barg (2.900,76 psig) @ Temperature: 20,0° C (68,0° F) Max. flow capacity @ selected orif: 10.149,31 Kg/h
D2046	
1216-2x2SS-40-P-00000-34,5G20	TOSACA safety relief valve model 1216 2" x 2" PN-40 BSP-M / BSP-F MATERIAL: A351 CF3M Orif. 32 Area: 804 mm2 End connections: DIN 259 BSP-M / BSP-F Accessories Delivery time: 1 Week Body/Bonnet: A351 CF3M Nozzle: A351 CF3M Disc: SS AISI316L, surface PTFE Spring: AISI-302 Bonnet: Closed Lever: No Test gag: No Bellows: No Others: Degreased Fluid: Oxygen / G Density: 1,43 kg/m3; Molecular weight: 32 g/mol; Cp/Cv: 1,4 Requerid capacity: No information Back pressure: 1,0 bar a (14,69 psi a) Set pressure: 34,5 barg (500,38 psig) @ Temperature: 20,0° C (68,0° F) Max. flow capacity @ selected orif: 15.368,49 Kg/h
SAFETY VALVE 4526101002 SP 38 BAR	
Seri 800	min. 9 bar LR Certifikat
1400-50x80sS-63-M-00000-38,0G20	TOSACA safety relief valve model 1400 50 x 80 PN 63 / PN 16 MATERIAL: SS 1.4409 Orif. 32 Area: 804 mm2 End connections: EN 1092 Type B PN 63 / PN 16 Accessories Bonnet: Closed Lever: No Test gag: No Bellows: No Others: Degreased Materials Body/Bonnet: SS 1.4409 Nozzle: A351 CF8+Stellite Disc: SS AISI316L, surface Metal Spring: AISI-302 Service conditions Fluid: Oxygen / G Density: 1,43 kg/m3; Molecular weight: 32 g/mol; Cp/Cv: 1,4 Requerid capacity: 16.849,00 Kg/h Back pressure: 1,0 bar a (14,69 psi a) Set pressure: 38,0 barg (551,14 psig) @ Temperature: 20,0° C (68,0° F) Max. flow capacity @ selected orif: 19.651,00 Kg/h Degreased
1216-0,5x0,75SS-40-M-00000-0,5L20	TOSACA safety relief valve model 1216 1/2" x 3/4" PN-40 BSP-M / BSP-F MATERIAL: A351 CF3M Orif. 13 Area: 133 mm2 End connections: DIN 259 BSP-M / BSP-F Accessories Body/Bonnet: A351 CF3M Nozzle: A351 CF3M Disc: SS AISI316L, surface Metal Spring: AISI-302 Bonnet: Closed Lever: No Test gag: No Bellows: No Service Conditions; Fluid: Liquid / L Density: 1000 kg/m3; Molecular weight: 28 g/mol; Cp/Cv: N/A Requerid capacity: No information Back pressure: 1,0 bar a (14,69 psi a) Set pressure: 0,5 barg

	(7,25 psig) @ Temperature: 20,0° C (68,0° F) Max. flow capacity @ selected orif: 2.410,46 Kg/h
1216-1x2SS-40-M-00000-10,0L20	TOSACA safety relief valve model 1216 1" x 2" PN-40 BSP-M / BSP-F MATERIAL: A351 CF3M Orif. 22 Area: 380 mm2 End connections: DIN 259 BSP-M / BSP-F Accessories Bonnet: Closed Lever: No Test gag: No Bellows: No Body/Bonnet: A351 CF3M Nozzle: A351 CF3M Disc: SS AISI316L, surface Metal Spring: AISI-302 Service conditions Fluid: NO INFORMATION Requierid capacity: No information Back pressure: 1,0 bar a (14,69 psi a) Set pressure: 10,0 barg (145,04 psig) @ Temperature: 20,0° C (68,0° F) Max. flow capacity @ selected orif: 30.799,74 Kg/h
1216 B-25x25BSS-16-P-00000-8,0L40	TOSACA safety relief valve model 1216 B 25 x 25 PN 16 / PN 16 MATERIAL: A351 CF3M Orif. 16 Area: 201 mm2 End connections: EN 1092 Type B PN 16 / PN 16 Accessories Body/Bonnet: A351 CF3M Nozzle: SS AISI316L Disc: SS AISI316L, surface PTFE Spring: AISI-302 Bonnet: Closed Lever: No Test gag: No Bellows: No Fluid: Liquid / L Density: 1000 kg/m3; Molecular weight: 28 g/mol; Cp/Cv: N/A Requierid capacity: No information Back pressure: 1,0 bar a (14,69 psi a) Set pressure: 8,0 barg (116,03 psig) @ Temperature: 40,0° C (104,0° F) Max. flow capacity @ selected orif: 14.571,51 Kg/h
Prv-56566-Oc 1400-25x40cs-40-M-11000-3,5v150	
Prv-5301-Abs	
1216 Hp	
Prv-34567-Oc 1400-50x80cs-40-M-11000-3,5v100	
Prv-34566-Oc 1400-25x40cs-40-M-11000-3,5v150	
Prv-34563-Oc 1400-40x65cs-40-M-11000-3,5v100	
En4216-1	
Prv-34548-Oc 1400-65x100cs-40-M-11000-6,2v120	
Prv-56563-Oc	
Pn16	
Prv-56547-Oc	
Prv-3360-Abs	
Prv-56564-Oc 1400-50x80cs-40-M-00000-6,8v70	
1400-40x65nd-16-M-00000-0,0L20	

Prv-34563-Oc
Prv-34564-Oc 1400-50x80cs-40-M-00000-6,8v70
40473085
Prv-4360-Abs
1216-0,75x1ss-40-M-00000-3,0l20
Prv-56567-Oc
Prv-34547-Oc 1400-40x65cs-40-M-00000-6,0l100
1216 C
Prv-56567-Oc 1400-50x80cs-40-M-11000-3,5v100
Alternative Item 2
Prv-6360-Abs
Prv-56566-Oc
1400
Prv-56547-Oc 1400-40x65cs-40-M-10000-6,0l100
1216 B
1400 Lp
Prv-6301-Abs
Prv-3360-Abs 1400-80x125cs-40-M-00000-0,8v140
1415 Lp
Prv-56564-Oc
1216
Prv-34564-Oc
Prv-56548-Oc 1400-65x100cs-40-M-11000-6,2v120
Prv-34566-Oc
Prv-4301-Abs
1415
Prv-5360-Abs
Prv-3301-Abs

Prv-34567-Oc
Prv-34548-Oc
Prv-56548-Oc
1400 Lp Pn 16
Prv-34547-Oc
Prv-56563-Oc 1400-40x65cs-40-M- 11000-3,5v100