



Tsubaki

Garanti: 12 ay
 Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Tsubaki Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Tsubaki Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Rs 80-2 Super-H (27,45mtr Total)	302RS80-2SUP-H RS 80-2 SUPER-H, TSUBAKI high-performance roller chain, DIN 8188, Reinforced heavy duplex version, bundle of 3.05 m. incl.
Rs 80-2 Super-H	TS split pin link for high-performance roller chain RS 80-2 SUPER-H, reinforced heavy duplex version, DIN 8188
№820637	TH 049 LS 100 LT 380v 50Hz 1430 r/min 2,2 kw 5,40A IP I. c.I. F 40 C C mf V S1- c/h C mf V min voltage (AT50Hz.) 380v IES 34-1
RS10B-1	
TGM200 D40 WS 6.9	Drive Coupling CLUTCH, 1 Set TGM200 D40 WS 6.9 / TSUBAKI], 40IDx178ODx100L, 6.9kgm, 200RPM, FOR STS2 APF PICKLE FILTER PRESS According to the data sheet supplied ***** ***** When an order is placed, a new item number is assigned
KC 0650.133-RS-145-20020	KABELSCHLEPP energy chain - chain without pretension - Order designation KC 0650.133-RS-145-20020 Chain length Lk 20020.0 mm Number of links n 308 Inside width up to 133 mm External width Bk 161 mm Radius of curvature KR 145 mm Bar variant aluminum bar, rotatable Number of bars nst 154 Connection fixed point / driver FU / MU Interior height hi 38.0 mm Chain link height hG 57.5 mm Grade: The unsupported length of the chain has been exceeded.

302RS80-1ML	Roller chain 80-1 ANSI, 1 "x 5/8", Lambda, DIN 8188, maintenance-free, pitch 25.4 mm, inner width 15.88 mm, roller Ø 15.88 mm, TSUBAKI, collar to 3.05 M. incl.
312RS80-1L	Reinforced split pin locking link 80-1 ANSI, 1 "x 5/8", Lambda, DIN 8188, maintenance-free, pitch 25.4 mm, inner width 15.88 mm, roller Ø 15.88 mm, TSUBAKI
4061408139972	EF chain KU TKA38.080, radius of curvature 145 mm, 26 links = length 1001.0mm, pitch 38.1mm, inner width 103mm, outer width 119mm, Inner height 26 mm, link height 36 mm, full web (Alternative to TKC340, since discontinued model) + Connection ZSB to EF chain TKA38 FP, fixed point + Connection ZSB to EF chain TKA38 MN., driver
4061408139972	Connection ZSB to EF chain TKA38 FP, fixed point
4061408006786	TSUBAKI chain clutch CR 6018 H (old designation CR6018J) 37CR6018H
Model: Chain with attachment A-1, Chain no. RS16B	
PL055X085AS-SS	4061408139972
4061408023004	37BB25 Freewheel ball bearing Ø 25 X Ø 52 BB25, TSUBAKI, width 15 mm, Torque 78 Nm
kr 340	
GMTA040-28U40B Gear Motor	4061408139972
Cam Clutch MZ60G-50	4061408139972
ROLLER CHAIN RS08B-SS-1-5M	STAINLESS STEEL 5 METERS ISO606/DIN8187/BS 394 LINKS
RS10B-1K	
RS10B-1	
Rs80-1b19t	
Bb25 - Tsubaki Freilauf	
Tkc470r100w80-22l-laka	
Mz30	
Rs40-1-Jl	
51g-1111-10	
08b 1 Rs	
H45-Tb-T1-C5	
Tkp0680w100r125-26l	
Hmta040-35h160bh	
Rs80-Lmd-1-166l	
12b 1 Rs	
10b-2 206 Winner Verschlussglied	
H15tab1t220c5w1	
64 1 04 294	
H15tab1280c5w1	

Cl-Comb-B-165	TS reinforced spring closure link for high-performance roller chain RS 60-1 lambda, maintenance-free, DIN 8188
Ts Reinforced Spring For Rs 60-1 Lambda	
36p8m15bf	
Tkp0450-W58 R50 50link With Ia Ka	
37cr8018j	
Tkc47h36w80r100ã215;46l+foa+mia	
Ts826pa-128	
50rsd10-510hr-W	
12b-1 Rs	
2240 Up14m 9y16	
Cr 8022 J	
64 1 04 299	
TI500	
0110602004	
48p8m25af	
PI035x060as	
856p8m15	
Bb40-2k-K	
Tsbss05	
H45t	
40 Tifus30 ? 1577 C3	
Hcma020-220u200lbp1	
Mg 500	
Gkw6\"-Trolley	
PI038x065as	
Tkp0450-78b-R75 24	
Rf2040s-1200t-Ss-H25j	
Rf2060r 1054	
PI040x065as	
PI080x120 As	
Erh25er-To-C5	
10b-3 Rs Winner Rollenkette	
?65 X 1155I Shaft	
Tkp58h39-30w75r90	
Rs40-1-0I	
L150-H	

?65 X 1006.5l Shaft	
1970600000	
08b-1 Rs	
0120200003	
Ts1524pa-106	
Tkp0625 St	
66 Bat10 32	
L099-H-35jã215;28j	
Rs40-1-Rp-U	
301rs20b3	
Rs25x111, JI1	
Rs35-1-Rp-38lx1h	
Kr-75, 1i 0650k ? 2i 0650k	
Cr 12018-J	
Gkw6\"-Elo-Interno	
?65 X 856.5l Shaft	
Rf2040s-Lmc-10lep	
Rs25x93l,JI1	
Rs35-1b38t	
PI 045x075	
10b-3 206 Winner Verschlussglied	
Cr5018k	
Rs40-1b18 D=20	
64 1 04 298	
Rs35-1-Rp-139lx1h(JI-JI)	
H20tab1t1	
Rs35-1-Rp-70lx1h	
37cr16018j	
Rf 2080 Vrp - A	
Ed6m-U-L-Y	
H15tab1t0-0220c5w1/F	
Rs50x53l+jl+ol	
0120160000	
Rs20 B-2 Gt4winner	RS20 B-2 GT4Winner, TSUBAKI High Performance Roller Chain, DIN 8187, duplex version, Bund to 5 Mtr. Incl. Vbgl. Art NR. 301RS20B2
0462-1-Pino	

Cr6018-J	
51 G 0927 7 Screw Shaft	
Gmta150-38l25bv1	
322rs40-1ss	
L070 -M-12jx19en	
Bb25-Ku	
Pl140x190 Ad-N	
Pl045x052ef	
66 Bat10 44	
Gkw6\"-Elo-Externo	
04 Bb 40 2k	
Duplex Sprocket 20b-2 With Collar	ALTENATİF Duplex sprocket 20B-2 with collar, 27 teeth Material C45 Bore Ø with H7 fit and groove
Rssuper2	
Mg300	
Rssuper200x2-2-C-26t	
Tkp35h22-30w50r50 32l+fo+mi	
H25tab1t1-C5	
H30er-B2-510-C3-W 1/F	
C2100h Type K1	
Rssuper200-2-C-26t	
Gkw-Fj-X-678-2\"	
Rs35-1b20t	
Rs80-Lmd-1-172l	
Pl090x130ae	
Lptc1000m4x-Tk Stroke:400 Mm	
1225p5m25	
Tkp0680-Stas	
2310 Up14m 8z10	
Ed6m 1-L-Y Ratio : 1:1 Mfg :Be0064-4	
375l100	
Pi080x120ae	
Mz20	
Bseu40-40	
Tkp0625w65r75	
0120100004	

Tkp580w100r90-20l+mia+foa	
Rs 60-1 Lambda.	TSUBAKI high performance roller chain, DIN 8188, maintenance-free, Bund to 3.05 Mtr. Incl. Vbgl.
Rs Super 200-2	
Tkp0320-38b-R50	
H15tab2t1280c5w1	
H30leb	
6205-S Wsa2/121á; 72lá;	
H15tab2t1580c5w1	
40 Tifcs16 ? 813 C5	
Rf 2080 Vr.	
H45-Ta-T1-C5	
Rs120-5-Rp	
Tkp0680w150r125-30l+ia+ka	
Tkp0625 Iu	
Gmta150-38l5b	
Hcma020-220u200rbp1	
PI025x050as	
37cr8018j-Ca	
44p5m25af	
0110600004	
?65 X 1813l Shaft	
Ta370bzfqcce - 3.7kw.-1710	
H15tab1t1280c5w1	
H25er-B2-220-C5w1/F	
Md200	
Stotz4\	
Rsd50?Ã215;45l J12	
Rs40-1	
Tgs8d	
L225-S	
4800056070 Nef18 Huub-35p2	
Cr 6022 H + K	
64 1 04 296	
64 1 04 300	
PI030-055as	

Gkw6\"-Elo.Arrastador
Rs16b-Lm-1 - 186
Mg 300
Rs12b-2
Rs120-4-Rp
22p8m15bf
1971602012
H20 2.500
Hmta370-55h60bzbv2 N + Hrta370-55h60fi
Gmta150-38l25bv
10b-2 Rs Winner Rollenkette
21-N-0294-5
Rs50-Lmd-1-Jl
Gmta-075-42l120bvn
Ed4m 1-Lr-Y Mfg:Z815882710-3 1:1
Pb14-Rh
Tkp68h46-30w125r150
PI035 X 057 Ke
23120/138-03/18
Rs50-Lmd-1-303link
Rs80-1
04-Bb-40-2k
Mg-300
1736p14m60 Belt
Mz-20
?65 X 1106.5l Shaft
Cr8018-J Coupling Body + Cr8018 Casing
Rs40-1b-16 D=20
Tga 65
L190-H
10b-1 Rs
Rs35-20
?65 X 1863l Shaft
Tkp0450ka
Tks095 R145-10

Mz-30
H15tab1t1220c5w1
Rs100-6-Rp
24p8m25bf
Tkp0625_Ka
Rs25-1b25
20l100af
Upx Hc 1736 14m 55
40l100af
Rs100-1 C.P.
H 30 L 1720
Tkp0450ia
15575
6000007170 Nef18
14l100af
45rsd10-415hr-W
0462-1-Elo-Externo
Mk-08
Electric Gear Motor, 3hp 230/460 V, 3 Dia
Gmta150-38l25b
Pi045x075ae
1971600012
Cr 8022 H + K
Tkp0680w100-Ka
Tkp0680w100-Ia
?65 X 1662l Shaft
302rs200-2su
Rs16b-Lm-1 - 183
3500 Up14m 6z15
PI015x031re-Ss
Mz300
Tkp0450 58b R95
Rs35-1-Rp-65l+jl+ol
Rs40-1b18 D=22
X458
(Ek Bilgi Gerekli) Inter:55 Ext:62 Ep:10 PI055 X 062 E

[0462-1-Elo-Interno](#)