

Vivoil

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Vivoil Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Vivoil Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
9RD0229	RV-1D / 4.9x2 p max: 220bar - input 1x1 / 2 "IG 2-way gear flow divider without valves - guidelines for the design and commissioning of flow dividers be sure to note on our homepage! Weight: 3.2800 kg / 3.2800 kg Item number: 84122981 Country of origin: IT
1964.565.X071	H80 11cc Bidirectional Steering
1964.509.X071	H65 11cc Bidirectional Steering
XV2+2P/11+11S-LK30/30-30/30	Z024-00110-9999 9M201ECA4747 2-way aluminum pump - counterclockwise - EL = 197mm 2-way external gear pump with aluminum body Direction of rotation: counterclockwise Sealing material: NBR 1st stage: External gear pump size 2 Delivery volume: 10.8 ccm / rev Mounting flange: Fitting Ø 36.5 mm - 4-hole fastening 96.2 mm x 71.5 mm Drive shaft: conical 1: 8 - woodruff key 4 mm Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 2nd stage: External gear pump size 2 Delivery volume: 10.8 ccm / rev Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 For applications in which multiple pumps are supplied from separate tanks, please

	stop first consultation with our technical department. Weight: 5.1441 kg / 5.1441 kg Item number: 84136031 Country of origin: IT
XV2+2P/11+4S-Ø36,5-CO.001-LK30/30-30/30 Euro	2-way pump - counterclockwise - EL = 182 mm 2-way external gear pump with aluminum body and aluminum flanges Direction of rotation: counterclockwise Sealing material: NBR 1st stage: External gear pump size 2 Delivery volume: 10.8 ccm / rev Mounting flange: Fitting Ø 36.5 mm - 4-hole fastening 96.2 mm x 71.5 mm Drive shaft: conical 1: 8 - woodruff key 4 mm Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 2nd stage: External gear pump size 2 Delivery volume: 4.2 ccm / rev Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1
Z024-00110-99999	9M201ECA4747 XV2 + 2P / 11 + 11S-LK30 / 30-30 / 30 2-way aluminum pump - counterclockwise - EL = 197mm 2-way external gear pump with aluminum body Direction of rotation: counterclockwise Sealing material: NBR 1st stage: External gear pump size 2 Delivery volume: 10.8 ccm / rev Mounting flange: Fitting Ø 36.5 mm - 4-hole fastening 96.2 mm x 71.5 mm Drive shaft: conical 1: 8 - woodruff key 4 mm Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 2nd stage: External gear pump size 2 Delivery volume: 10.8 ccm / rev Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1
022-080-01000	X2F4102QOOA XV2F/4D-Ø36.5-SCF.01-30/30 4.2ccm/rev - clockwise - 260 bar End section external gear pump size 2 with aluminum body and aluminum flanges Delivery volume: 4.2 ccm/rev Direction of rotation: clockwise Mounting flange for the pump installed in front of it, size 2: fitting Ø 36.5 mm - 4 hole fastening 96.2 mm x 71.5mm Drive shaft: splined 9 teeth DIN5482 - 17x14 - Ø 16.5 h11 Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 Installation length: 87.2 mm Seal material: NBR Permissible shaft torque: 86.2 Nm Continuous pressure limited by drive shaft: 260 bar Continuous pressure: 260 bar Peak pressure (max. 0.5 sec): 300 bar Minimum speed: 700 rpm Maximum speed: 3500 rpm
022-060-01000	X2T4102EOOA XV2T/4D-Ø36.5-COP.01-30/30 4.2ccm/rev - clockwise - 260 bar Front section external gear pump size 2 with aluminum body and aluminum flanges Delivery volume: 4.2 ccm/rev Direction of rotation: clockwise Mounting flange: Fitting Ø 36.5 mm - 4 hole mounting 96.2 mm x 71.5 mm Mounting flange for the middle or end section size 2: fitting Ø 36.5 mm - 4 hole fastening 96.2 mm x 71.5mm Drive shaft: conical 1:8 - disc spring 4 mm - through drive geared 9 teeth DIN5482 - 17x14 - Ø 16.5 h11 Suction connection: LK 30 mm - M6 x 1 Pressure connection: LK 30 mm - M6 x 1 Installation length: 83.4 mm Seal material: NBR Permissible shaft torque: 86.2 Nm Continuous pressure limited by drive shaft: 260 bar Continuous pressure: 260 bar Peak pressure (max. 0.5 sec): 300 bar Minimum speed: 700 rpm Maximum speed: 3500 rpm
026-001-1200	8KITR004 Connection kit XV 2+2 without flange - NBR

13 4e2
9rd0427
X2p4702e00a
X2p4702ecba
7p2302001
X2p4502e00n
Rd9m100es
X0p0502abba
Rd15m100es
X1p2902fbba
9s202aga0101
9rv03a34
X0r1321bbbe
Rv-2v/17x2 Eav 70-210bar
9rd0429
X2p6352iqpa-40cc
Xv2p-D-1/2-1/2
7p3402005
7p2502005
Kv-2dfv/40x2
X1p-2502fbba
X2p5702eqpa
9rv04a27
Mtz-2-2-17-G
Rv-1s 9rs 03d36
X1p2302fjja