

Vortex

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Vortex Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Vortex Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
106BSP-8-H	
20025 Inox	
2700000150	
2710127025	
2710200213	
35H	
620-1BSP	
721BSP-25H, 1500BTUH	
BP2612	
BX17X1700 LI	
DVC5X7-MG	
EXAIR 4040 2800BTU	

GS06 -15	
GS08 -15	
GS10 -15	
Laufrad VXC 10/45-N	
PL20C-6AIS	
TOP-YTH1500A2-T216EVD20CF	
Tube 308BSP-35H (BP3240)	
VXC 10/45-N	
AS007 - Vortex Flow Sensor	G3/4A - 1,8...32 l/min - analog 4...20 mA
Mechanical Seal (Belonging to Vortex 9 Stage)	Booster) RT-240 in Marked Dimensions as in the Attached Picture
SOLVAHT 220 VAC 5.0 VA MODEL : VC-B2	
CABINET BP4030 // CABINET COOLER BP4030	
VX150 DRAIN PUMP	
GRA350-F-AP-S4-MG-PET	Vortex Model No. GRA350-F-AP-S4-MG-PET, 350MM Quantum Series Orifice Gate Valve. Aluminum valve body with live loaded, wear compensating seals, a 304 stainless steel blade, main flange and orifice liners. Material contact is 304 stainless steel and polymer. Oversized double acting air cylinder actuator (AP) - Inlet and Outlet Flanges match #125/150 ANSI mounting pattern. Flanges are aluminum to prevent corrosion due to oxidation and have blind tapped steel thread inserts for bolted customer connection. Caution: Using a bolt longer than the specified maximum will result in damage to the gate valve. Consult IOM manual for correct bolt length. (MG) - Air cylinder is equipped with a magnopiston for use with magnetic reed position indication switches. (PET) - Valve is rated for 180F(82C) maximum continuous service. PET pressure plates are backed with a foam void filler and live loaded natural rubber load seals. Valve has boss welded into main body to accept proximity switches. **OPTIONAL ACCESSORIES**
GRFISS-14	14" Special Service Inlet, 304 stainless steel construction, eliminates material packing and reduces wear on seals; should be used when closing on abrasive, potentially sticky, pelletized, or granular materials, (adds 3/16" to OAH of valve). NOTE: RECOMMENDED WHEN VALVE IS INSTALLED IN HORIZONTAL PLANE. NOT RECOMMENDED WHEN VALVE IS TO BE INSTALLED VERTICALLY.
2F375-24ES1-24VDC	Air Control Assembly, single solenoid, 24v DC/1.5 W, IP 65, G 3/8 ports, flow rate 3200 l/min, includes Polyurethane tubing, fittings and mounting brackets.

2CC1A-SPST	Magnetic Reed Switch, SPST, Normally Open, NEMA 6 IP67, CSA Approved, 5-240 Volts VDC/VAC 50/60Hz, 2 wire output, 30 W/1 AMP Max, LED indication light, 9 foot PVC cable. CAUTION: Do not exceed rated wattage/current, permanent damage to sensor may occur.
Air Knife For Archimedes Pat. 2009 097 22	
Pmb-4-Ut	
Gvp_01	
Cold Air Gun 620-1bsp	
83f-Tihs2dtjtje-N	
Exair 4040 2800btu	
60040a-Nema Type 12	
Gc-6sb	
Ef73-Dn50 Pn40	
Archimedes Pat. 2009 097 22	
Vg-T2 400-00	
4m25a-24es1-24vdc	
4cc1a-Spst	
H2o Guardian	
Vv-Vt-Bf-6-300-Hdi	
A-70325-220v	
Dn200	
Tube For Archimedes Pat. 2009 097 22	
Dn16-Dn32	
308mh	
Type 20e-300model .P/N: PI20c-6ais. Size: 2 3/8; 3/4; X 300 Obsolete, No Replacement	
Cold Air Gun 630-1bsp	
Ef73-Dn80 Pn40	
83f-A02s1sstna	
Vm 0070 10 02	
Gc-2ss	

Gc-2ss-M4 260.00	
Vor.760	COOLER SYSTEM MINI 8SCFM
106bsp-8h	
Bw 152 Ot Obsolete,Repleced By Bwo 155 R	
610-1bsp	
610-26+701s-24a	
Sa225tv1-Ws1	
308bsp-35h	
Vg-T2	
Abb Trio-Wirl Vr 42 Order No: 240069595/X019 Qmax Dn: 1900.0 M3/H,Mat: 1.4571/1.4571/1.4571 Gasket:	
Vt-Bf-4-300-M1	
W4000-15g-W-F1 Ckd	
106-2-H	
7725	ENCLOSURE COOLING SYSTEM TYPE 4/4X
Gc-6sb-M4 768.00	
7735	ENCLOSURE COOLING SYSTEM 4/4X 2500BTUH 35SCFM
Dy150-Dbmba1-2d/Ff1	FLOWMETER 24VDC 0.5NPTF 4-20MADC/PULSE OUTPUT
Cabinet Coolers	
72f80-Skoaarhab4aw	
83wa02s1sstna	
Tlv Ef73	
Bx17x1700 Li	
Vg1744504114101060103000000003	
Yf115-Aaua1a-S3s3-E/Fmf/Tbl	FLOWMETER 24VDC 0.5IN NPTF 4-20MADC/PULSE OUTPUT
Model: Mcv 11	
A 50	
Vv-Bv-2-G	
208mh	

[4040 2800btu 706kcal/Hr](#)

[Hose For 60040a-Nema Type 12](#)

[Model: Mcv 11 S/N: 020111122210](#)