

Walvoil

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Walvoil Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Walvoil Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
VMP/B/L 5-38/TS.S	1111021104 230-0030-0210 3/8 "adjustable 50-220bar cap nut Pressure relief valve-directly operated-aluminum housing-max. 210bar-35l / min. Weight: 0.4800 kg / 0.4800 kg Item number: 84812010 Country of origin
VDFR 38-12	230-1410-4625 3/8 "pitch 1: 1 fixed Flow divider Aluminum case-Max. Working pressure210bar-4-12l / min. Weight: 0.8500 kg / 5.1000 kg Item number: 84812010 Country of origin: EU
PBL6/VMP 38/5.TR.S/ac	Z230-00031-99999 1114022100 3/8 "adjustable 180-350bar cap nut Connection block-Cetop 03-with DBV-steel housing-max.350bar-35l / min. Weight: 0.1980 kg / 0.1980 kg Item number: 84812010 Country of origin: IT
VUC 100/Pa0,5	Z230-00178-99999 1 "opening pressure 0.5 bar fixed Check valve-steel housing-max.300bar-150l / min. Product number: 84812010 Country of origin: IT
DPX160 PWM KIT 8EB34LHF3 -24VDC	
DPX160 UL350	

DPC200 PRESSURE RELIEF	
DPX100-DPX160 - INLET COVER SAFETY VALVE (TGW4-250)	
DPX160 - SLICE ORING COMPLETE VITON	
230-0060-5550	1114021102 PBL6 / VMP 38 / 5.TS.S. 3/8 "adjustable 50-220bar cap nut Connection block-Cetop 03-with DBV aluminum housing-Max. Working pressure 210bar-35l / min.
231-800-02100	VEB-12-NC-NOT-24VDC 2/2-way seat valve in the body 1/2 "-24VDC-Alu Screw-in cartridge: EC10M / 20TB - 2/2-way poppet valve "NC", normally closed with emergency manual operation (Screw) - one side tight / open - pilot operated - conical seat - -70l / min - max.380bar Body: 2-way / SAE-10 / G-1/2 "aluminum - 60mmx60mmx35mm - max. 210bar Magnet coil BER: 24VDC - square - L: 38.5mm, W: 36mm, iØ13.2mm Associated cubic connector: black: 730-010-1000 gray: 730-010-1050 transparent with LED: 730-010-1200 ATTENTION, CUBE PLUG NOT INCLUDED IN THE DELIVERY
231-850-02100	VEB-12-NC-NOT-24VDC 2/2-way seat valve in the body 1/2 "-24VDC-Alu Screw-in cartridge: EC10M / 20TB - 2/2-way poppet valve "NC", normally closed with emergency manual operation (Screw) - one side tight / open - pilot operated - conical seat - -70l / min - max.380bar Body: 2-way / SAE-10 / G-1/2 "aluminum - 60mmx60mmx35mm - max. 210bar Magnet coil BER: 24VDC - square - L: 38.5mm, W: 36mm, iØ13.2mm Associated cubic connector: black: 730-010-1000 gray: 730-010-1050 transparent with LED: 730-010-1200 ATTENTION, CUBE PLUG NOT INCLUDED IN THE DELIVERY
231-800-01700	VEB-38-NC-NOT-12VDC 2/2-way seat valve in the body 3/8 "-12VDC-Alu Screw-in cartridge: EC08M / 20TB - 2/2-way poppet valve "NC", normally closed with emergency manual operation (Screw) - one-sided tight / open - pilot operated - conical seat - 40l / min - max.380bar Body: 2-way / SAE-08 / G-3/8 "aluminum - 50mmx50mmx30mm - max. 210bar Magnet coil BER: 12VDC - square - L: 38.5mm, W: 36mm, iØ13.2mm Associated cubic connector: black: 730-010-1000 gray: 730-010-1050 transparent with LED: 730-010-1200 ATTENTION, CUBE PLUG NOT INCLUDED IN THE DELIVERY
231-850-01700	VEB-38-NC-NOT-24VDC 2/2-way seat valve in the body 3/8 "-24VDC-Alu Screw-in cartridge: EC08M / 20TB - 2/2-way poppet valve "NC", normally closed with emergency manual operation (Screw) - one-sided tight / open - pilot operated - conical seat - 40l / min - max.380bar Body: 2-way / SAE-08 / G-3/8 "aluminum - 50mmx50mmx30mm - max. 210bar Magnet coil BER: 24VDC - square - L: 38.5mm, W: 36mm, iØ13.2mm Associated cubic connector: black: 730-010-1000 gray: 730-010-1050 transparent with LED: 730-010-1200 ATTENTION, CUBE PLUG NOT INCLUDED IN THE DELIVERY
11C90016	
Z230-00635-99999 1565041102 Lowering brake valve-double-	

VODL/SC/CC 34/TR.S.p7	acting-aluminum housing-max.210bar-120l / min.-setting range 50-350bar
VOSL/SC/CC 34/TR.S.p7.PG	Z230-00143-99999 1525041102 3/4"-Öff.v. 1:7 Lowering brake valve-single-acting-aluminum housing-max.210bar-120l / min. Can be used for closed centers
1/2" H-P 4-WAY VALVE	
Z258-00660-99999	181540001 SVM510-B / 00001C hydraulic pilot control unit
VUPSL 38/p3	check valve 3/8" Qmax = 35 l/min - Pmax = 400 bar Weight: 0.9210 kg / 0.9210 kg Commodity number: 84812010
4CAV70 3000	
5116	
511604	
51160892	
51161094	
BC16A/302B	
BETCS24VDC	
DFE 10/3B 18ES.Y201-24VDC	
DFE20/3A18ES-Y201	
DH10/4A	
ER08M/10NB	
O1210021101	
OD150618A000000	
SD25/3	
SDS180/4	
VABAL/SF38/TR.SP3	
VDFR-40S	
VE/B/VMP/VUI/SR38/NC/TS.S/EC08M	
VEB12NC + BTCS24VDC	
VODL/SC/CC 34S	
VOSL/SC 12 1/2	
VPR/3/ET/VMP 34/L/03.TR/ac	
VPR3ET12	

VUS 34	
V-VEP34/TS-TV.S-17	
YAR12400	
VDJR 34-90	230-1440-4655 3/4" division 1:1 fixed Current divider aluminum housing-max. 210bar-40-90l/min. Weight: 2.1500 kg / 2.1500 kg Item number: 84812010 Country of origin: EU
Special Proportional Joystick - DPX 160	
181121065	SVM100/1-B/10G3-00001Ax2 Hydraulic - pilot valve element Connections P + T on the side Rest in neutral Commodity number: 84819000 Country of origin: IT
Lower chain case - 1 set - PM 180 rotary table	
Hydraulic handle - 4 nos - 3 and 5 tons vinches	
Upper chain case lower sprocket -	
SD11/5	
SVM100-1	
80 lt/ dk P-T-C 3/4", A-B 1/2"	SDM 140/3 Elektropnomatik 24V DC +CO (AE =180 Bar)
160 lt/ dk A-B-P 3/4" T 1"	SD18/3 Elektropnomatik 24V DC + (AE =180 Bar)
45 lt/ dk A-B-P 3/8" T 1/2"	SD5/2 Mekanik (AE =180 Bar)
230-0090-0591	1116041102 VMP/VE 34/NA/03.TS.S/EC08M zgh. Solenoid BER Weight: 1.2100 kg / 1.2100 kg Item number: 84812010 Country of origin: EU + 230-1780-4050 Solenoid BER - 12 VDC 4SLE001200A
Z251-10888-99999	102211504 SD5/2-P(KG3-120)/1CS8L/1CS8L/AET 2 section monoblock valve 45l/min-315bar 2-section monoblock valve 45l/min-315bar - connections 3/8" - DBV 60 - 200bar - hand lever actuated 1st section: double-acting with fine control slide max. 30 l/min. 4/3-way - middle position: A+B closed+pressureless circulation-spring centered in 0 2nd section: double-acting with fine control slide max. 30 l/min. 4/3-way - middle position: A+B closed+pressureless circulation-spring centered in 0
VDJR 34-90	230-1440-4655 3/4" division 1:1 fixed Current divider aluminum housing-max. 210bar-40-90l/min. Weight: 2.1500 kg / 2.1500 kg Item number: 84812010 Country of origin: EU
SELF LEVEL VALVE(VCFL 12/SE GHISA)	VCFL 12/SE10ASAEGHISA-WITH FLOAT BYPASS P/N:1992033208
3/4" VUS34 0,5 BAR CHECK VALVE	
1/2" VUS12 0,5 BAR CHECK VALVE	
ERGONOMIC JOYSTICKSVM 400	TYPE+DEAD MAN WITH DETENT FOR FLOAT P/N:181420484

JOYSTICK- SLOPED	SERVOCOMANDO SVM400-EMD1/7 1-S/01E 15HMB03G-1R4040-4R3040-5R2040-.....12VDC
PILOT CONTROL VALVE	FEED UNIT 6 VALVE BLOCK FU-NA-NR-A-NV/6-EJ08F/NPM-BSP-12VDC P/N:DFRI15025
TRAVELING JOYSTICK SVM430/23-B/01HA049-0RD040	SVM430/23-B/01HA049-0RD040 P/N:181430056
250A-125-01340	5LEV110000S S10/LSG lever housing Lever housing aluminum for hand lever M10 - SD11+SD14+SDS150+SD16+SDS180+DLS16+DLS180 Weight: 0.2809 kg / 2.8090 kg Item number: 84819000 Country of origin: EU
1720021105	VE/B38/NC/EC08M 3/8" 2/2-way poppet valve-with emergency manual-currentless E to U closed / energized E to U open aluminum housing max. 210bar-40l/min. Solenoid: BT
SVM510-520-521	
250A-130-01200	4SOL412024-C Magnetspule D12C - 24VDC Magnetspule für ISO-Stecker Magnetspule eckig für SD4, SD5, SDE030, SDE060B L: 50mm, B: 35mm, iØ: 19,15mm Spannung: 24 VDC ±10% Einschaltdauer: 100% Schutzklasse: IP65 Leistungsaufnahme: 36 Watt max. Stromaufnahme: 1,5 Ampere Zugehöriger Würfelstecker: Schwarz: 730-010-1000 grau: 730-010-1050 transparent mit LED: 730-010-
VOSL/SC/CC 34/TR.S.p7.PG	Z230-00143-99999 1525041102 3/4" f.f. 1:7 Lowering brake valve-single-acting-aluminum housing-max.210bar-120l/min. Can be used for closed center Goods number: 84812010 Country of origin: IT
Art.183520154 (14308800019) JOYSTICK	
Z257-02106-99999	183540004 Joystick AJW P-Handle - 1x thumbwheel 1x button FNR with deadman button Joystick base AJW for handle P Supply voltage: 8 - 32V Output: 0.5 - 4.5V Line: 35 cm Connector: German DTM06-12S Position W: Thumbwheel Position Z: button FNR Position 0: red deadman button
1814200001	repair kit
SVM510-B/00001C	181540001 Z258-00660-99999
254-030-01161	12Z640025 DFE20/3A18ES-W 200-24VDC-CRZ 3/4"-140l/min.-200bar Galvanized 3/2-way switching valve Connection size P + A + B: 3/4" Max. working pressure: 200bar Actuation: directly electrically operated 24VDC / 60W with ISO4400 contacts - on the side of connection "A" Switch position 1: P + A connected and B blocked Switch position 2: P + B connected and A blocked Switch overlap: negative
230-0320-1420	1210031101 VDA 12/TR.S.VRR 1/2" adjustable 100-250bar cap nut Shut-off valve (accumulator) aluminum housing - max. 250bar-50l/min. non-return valve with steel seat
	1210032101 VDA 12/TR.S.VRR/ac 1/2" adjustable 100-250bar

230-0320-1425	cap nut Shut-off valve (accumulator) steel housing max. 350bar-50l/min. non-return valve with steel seat
VOSL/SC/CC 12/TR.S.p7.PG	Z230-00146-99999 1525031102 1/2"-opening 1:7 - 50-350bar(max.210) - 75l/min. Lowering brake valve-single-acting-suitable for closed centers-aluminum housing Weight: 1.0300 kg / 2.0600 kg Item number: 84812010 Country of origin: IT
VBCD12-SE-A-CC	Lowering brake valve - single-acting - partially relieved - Connection size: 1/2" Max. flow rate: 60l/min Control ratio: 1:4.5 Setting range: 100-350 bar Maximum pressure: 350bar Adjustment lock with counter nut and cap nut Spring space relieved Used when the upstream directional control valve has ports A+B blocked in the neutral position are. Weight: 1.2280 kg / 2.4560 kg Item number: 84812010 Country of origin: IT
230-0500-1885	1230021125 VRPRL 38/TV.S 3/8" adjustable 40-110bar cap nut Pressure reducing valve-with leakage oil connection+with bypass check valve-aluminum housing-max. 210bar-20l/min.
205-045-01250	V0705/C180 VRPRL38/35-180 Pressure reducing valve with leakage oil connection and bypass check valve - directly controlled Connection size: 3/8" Max. flow rate: 30l/min Setting range: 35-180 bar Maximum pressure: 350bar Adjustment lock with lock nut
254-130-01200	122054050 DF5/3AC17CB 3/8"-60l/min.-315bar 3/2-way switching valve Connection size P + A + B: 3/8" Actuation: rollers operated via brass roller Ø 22mm - on the side of connection "B" Positioner: spring return in switching position 1 - on the side of connection "A" Switch position 1: P + B connected and A blocked Switch position 2: P + A connected and B blocked Switch overlap: negative
230-0320-1420	1210031101 VDA 12/TR.S.VRR 1/2" adjustable 100-250bar cap nut Shut-off valve (accumulator) aluminum housing - max. 250bar-50l/min. non-return valve with steel seat
258-041-02000	3CAS105746 DFE052/6B Slider 6 ways DFE052-slider-unswitched A to E + B to F open-positive switch overlap Just the slider
Z257-02281-99999	183334031 CED400X proportional control for 8 coils
SDS150/5 - VALVE, HYDRAULIC,	3 PIECES WITH DETANT- 2 PIECES ABT
CODE : 12G060032	DFE100/6B18ES-W 24DB1-14VDC-CRZ DIVERter VALVE 51592128 -1 Jahresbedarf
Z230-00146-99999	1525031102 VOSL/SC/CC 12/TR.S.p7.PG 1/2"-Öff.v. 1:7 - 50-350bar(max.210) - 75l/min. Lowering brake valve, single-acting, suitable for closed centers, aluminum housing
230-0310-1400	1210021101 VDA 38/TR.S.VRR 3/8" adjustable 100-250bar cap nut Shut-off valve (accumulator) aluminum housing - max. 250bar-25l/min. check valve with steel seat

230-0310-1405	1210022100 VDA 38/TV.S.VRR/ac 3/8" adjustable 5-110bar cap nut Shut-off valve (accumulator) steel housing - max. 350bar-25l/min. check valve with steel seat
Z258-00782-99999	18Z010173 SV01-B
258-040-26250	3CU2410120 SDS150/1 Slider SDS150
Dpc 130/6	
Vpr/3/Et 12-Mg	
Vpr/3/Ep 12/L	
Df10/3a17slp / 254-140-01100	
Od150618a000000 2wv Noe 350[.]bar-40l/Min [h] Nscca-08a-2n [od150618a000000]	
Sd14/1 3/4" 250 Bar 120 Lt	
Vabal/ Sf38 Control Valve	
Veb12nc + Btcs24vdc 2/2 Valve	
Sds/2 Ac Yg4-220 18l*3rc	
Sd25/3 Wegeventilp0723688117300029	
Dn25-4/3 Sd25/1	
250-060-02200 Sdm140/5-P(Yg3-175)	
Vosl/Sc 12 1/2 Ventil Bremse Montage Der Tuben	
Plb6/Wmp38	SD1-2 TANDIS HEIZUNG PRESS.RELIEF.VALVE
Oc5101017	
Mg10a/0s2b	
Sd5/1-D(Kg3)/28l	
5v08130902	
1720042102	
5v08130900-Obsolete	
Vda12	
Vuc100	
252-070-03600	
Vpr/3/Ep 12/Mg/Ac	
Kreuzhebel Mit Hohlstange - Seilzugsteuerung, 179040002,	

Scf031/02v004	
1210041101	VDA 34 / TR.S.VRR 3/4 "setting 100-250bar cap nut Shut-Off Valve (Tank) Aluminum body-max.250bar-100l / min. Check valve with steel seat
Pm1302785	
230-0310-1400 Vda 38/Tr.S.Vrr	
252-070-03300	
Halteventil	
Vosl/Sc 1/2quot;	
Svm510	Z258-00441-99999 5CIN5003 SVM510 Pedal 258 Valve Items W
230-0960-2940	
Bc16a/302b Valve	
252-070-02150	
Vpr3et12 Flow Control Valve 2/2 Valve	
Vpr/3/Ep 12/Mg	
Sd 6/2 Ac(Yg4-215)18l*2/Rc	
1101808	
Voslp 100/Tr.S.P7/Ac	
Vuc114	
Dh10/4a Vierweg Plugkraan	
Sd 11/1-Sv/111 L	
Vuc34	
Vbpd1 34/P4	230-0800-2610 1420041100 VBPD1 34 / p4 3/4 "opening: 4.5 Check Valve Double Acting Unlockable-Aluminum Casing-max.210bar-100l / min. 230-pipe valves O
Sds150/1/Ac(Xg3-125)/P-18l/Rc	
243876 Vda 12/Er.S.Vpp 1210031101	
5cr6a1135rm	Z258-00449-99999 Valve item KIT CURVA A1135R-MM main bearing
230-0500-1880	
1230021102	
Er08m/10nb Walvoil 4/2 Cartridge Er08m/10nb210 Bar20 Liter / Minute	

1992751112	
Dhv080/8In-Sae-Crvn	
Al01/M10x200	
Vep 34/Tr-Tv.S Pressure Block	
Oe150009	
150-S-3/4-Ipm-35-Ap Hydraulic Brake	
VbpdI 38/P4	
Vpr/3/Ep 12/L/Ac	
Sd25-2	
Dhv080/8In-Crvn	
Art.183520154	Joistik--14387700120 -46.30.000980.01 ART.183520154 PX.1400539\001 19\14
Vmp/Ve 12/Na03/Ts.S	
Svm400	
Sds150/2/Ac(Xg3-125)/P-18I/P-18I/Rc	
VodI/MI/10-12	
5lev138700 Dpc38 Pk1110542	
Vdfr-40s Flow Divider Housing (Steel)	
252-070-01000	
Ve/B 34 Na	
Gjs1-B3t4	
5v08140902	
Vpr/3/Ep 12/V	
Dfe 10/3b 18es.Y201-24vdc Ventil Magnetventil	
258-030-01450 170012020	
Sd4/1 Sv 112	
Od410303040000	
256-040-02200	
Sds180/4 Wegeventil P0906272115400036	