

Warom

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Warom Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Warom Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Bny81-36x2x (2x36w) Ex	
Bjd81-Y 220v Ac 50/60hz	Explosion-proof Caution Spotlight Fittings 220V AC1.Ex mark:II 2 G Ex d IIC T6 Gb II 2 D Ex t IIIC T80°C Db IP66 2.Enclosure:copper-free aluminium alloy, powder coated surface, yellow(RAL 1021) 3.Rated voltage:220V AC 50/60Hz; 4.Lamp power:3W 5.Degree of protection:IP66 6.Ambient temperature:-40°C~+55°C 7.Please refer details to WAROM Catalogue 2020
Bjd81-Y 24vdc	1.Ex mark:II 2 G Ex d IIC T6 Gb II 2 D Ex t IIIC T80°C Db IP66 2.Enclosure:copper-free aluminium alloy, powder coated surface, yellow(RAL 1021) 3.Rated voltage:24V DC 4.Lamp power:3W 5.Degree of protection:IP66 6.Ambient temperature:-40°C~+55°C 7.Please refer details to WAROM Catalogue 2020
Bzc 8050-40092ba-96	
Bza8050-A2-40066 / Atex	
BDD81-A100X	
BYA 51-36x2x	
BNY81-LED-2X18 WATT	
BZA8050-A2D1	Explosion-proof Control Unit Systems ATEX 1. Ex-mark: II 2 G Ex d e IIC T6 2. Enclosure: GRP, in black 3. Rated voltage: Max. 415V AC 4. Rated current: 10A 5. Degree of protection: IP65 6. Ambient temperature: -20°C~+55°C 7. Cable entries: 1 x M25 x 1.5 cable gland 8. Details refer

	to catalogue
BAZ8050-A1D1	Explosion-proof Control Unit Systems 1. Ex-mark: II 2 G Ex d e IIC T6 2. Enclosure: GRP, in black 3. Rated voltage: Max. 415V AC 4. Rated current: 10A 5. Degree of protection: IP65 6. Ambient temperature: - 20°C~+55°C 7. Cable entries: 1 x M25 x 1.5 cable gland 8. Details refer to catalogue
15092021681	BZA8050 A2D1 CTP 415 V AC Atex IP65
Model : BAYD-B-F	Ex-Proof Wall Mounted EXIT Luminaire with Aluminum Cast Body, Tempered Glass Resistant to Thermal Shocks and Impacts, Electronic Ballast, 120 Minutes Capacity Battery
BBJ81-R / ATEX	1.Ex-mark:II2 G Ex d ib IIC T6 Gb II2 D Ex t IIIC T80°C Db IP66 2.Enclosure:Copper-free aluminium, powder coated surface,yellow(RAL1021) 3.Rated voltage: 220-240V AC 50/60Hz 4.Lamp power: 5W LED 5.Lamp colour: Red 6.Ambient temperature:-40°C~+ 55°C 7.Cable entry: 3×M25×1.5 plugs 8.Degree of protection:IP66 Please see detail to catalogue 2022. Explosion-proof Audio and Visual Caution spotlight fittings
EXPROOF IICT4 16A 380VAC	
BAK51-50/240B	
30008.	
Bak51-50/240b	
Bay-H21x1	
Bcz8060-16/250/3p/Z	
Bayd-Bf	
Bza8050-A1	
Yk18df-2cs	
Bjd-Z	
Bsx-60 E27 Lamp Holder	
Bcz8060-16/250/3p	
Bat51 - Hie400	
Explosion Proof Portable E-26 220v 100w Obsolete Replacement Bsx-60	
Dqm- Ii/M20x1.5 (708001)	
Bay51-D-236	EX-PROOF ALUMINUM BODY 2X36 W
5136019	
Bdh51-C/M20 X 1.5	
Cdz-Hr160-1560-Qd	
Bat53-400-Hie400	
Bzm-16b	EX-PROOF Switch
Baz51 - Hie400	
S Series	4 INSERT BUGS
Bhd51-A M25x.5	

Bay51-Q36x2x	
Bbj81-R Dc 24v	
Bzc8050-A1q	
Bbj81-R24	
Dqm- Ii/M20x1.5 (709002)	
Bat86-160-120g	100 Watt – 100-300V – IP66, CLASS II
Bxj-Iib-Iv	
¾" Ex-Proof Fittings	
BBJ81-R	Explosion-proof Audio and Visual Caution spotlight fittings ATEX 1.Ex-mark:II 2 G Ex d ib IIC T6 Gb II 2 D Ex t IIIC T80°C Db IP66 2.Enclosure:Copper-free aluminium, powder coated surface,yellow(RAL1021) 3.Rated voltage: 220-240V AC 50/60Hz 4.Lamp power: 5W LED 5.Lamp colour: Red 6.Ambient temperature:-40°C~+55°C 7.Cable entry: 3×M25×1.5 plugs 8.Degree of protection:IP66 Please see detail to catalogue 2022 page2/161.
Bay51-D-258	
Bjd-Gr	
Bhd51-B/M20x1.5	
Bjd-Gy	
Yk36df-2cs	
Bad 85-120-120-D	
Bza8050.....Ex	
Bcz85-16-250-3p	EX-PROOF MONOPHASE Plug-in
Bzx-6	
Bat86-160-120y	
Bbj81-Y	