



Waycon

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz. **Waycon** Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Waycon Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
172805272	
SX80-2500-420A-SA12-IP67	Draw wire displacement transducer, measuring range: 2500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.1%, 4-pin axial M12 connector output Option: increased protection class IP67
SX50-500-420A-SA12-IP67	Draw wire displacement transducer, measuring range: 500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.15%, 4-pin axial M12 connector output Option: increased protection class IP67
SX50-250-420A-SA12	Draw wire displacement transducer, measuring range: 250 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output
SX50-375-420A-SA12	Draw-wire transducer, measuring range: 375 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output
MAB-A-A-900-E	Magnetostriuctive displacement transducer, rectangular profile, IP67, Measuring range: 900 mm, linearity: max. $\pm 0.01\%$, Output: 4...20 mA, 5-pin connector output M12
SX50-150-420A-SA12	Cable displacement transducer, measuring range: 150 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output

SX50-125-420A-SA12	Cable displacement transducer, measuring range: 125 mm, Output: 4...20 mA, supply: 12...30 VDC, IP 65, Linearity: 0.5%, 4-pin axial M12 connector output
LRW-M-275-S	
PMU-10V	
Sx80-2000-420a-Ka02	
Sx50-500-420a-Sa12-Ip67	Pull-wire position transducer, measuring range: 500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.15%, 4-pin axial M12 connector output Option: increased protection class IP67 Tariff No .: 90318020 Origin: DE Weight: 0.30 kg Prefix: YES
Wp -6,8t-420a-Ka02 Lenkwinkelsensor	
Sx80-2500-420a-Sa12-Ip67	Pull-wire position transducer, measuring range: 2500 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, Linearity: 0.1%, 4-pin axial M12 connector output Option: increased protection class IP67 Customs Tariff No .: 90318020 Origin: DE Weight: 0.80 kg Prefix: YES
Sx80-1000-420a-Sa12 Sensor	
Lzw-M-500	
Sm25-Hyd-F18-Ka-0	
Rp-M-180-420?-??02 Lenkwinkelsensor	
Wp-90-420a-Sa12	Angle of rotation sensor, anodised aluminum and stainless steel, ø 60 mm, IP67 (on the housing side), IP60 (on the shaft side), Measuring range: 90 °, spin-through, Supply: 12 ... 30 VDC, output: 4 ... 20 mA, Linearity: 0.3%, 4-pin axial connector output M12
Con006	
Sx80-1500-420a-Sa	
Sx50-125-420a-Sa	
Las-Tx-4-420a	
Sr128-015	
Sm10-T-Sa-1312112	
Las-T5-100-V	
Lrw3-C-25	
???-?-?-800-W	
4p-Gegenst.-2kab-Hyd Ptfe-UI Kabel, 2 M, Orangemit Konfektioniertem Gegenstecker, Typ Lemo Phg.0b	
Sx80-3000-420a-Sa-00	
Rx80-2500-420a-Sa12 Sensor	
Lx-Ep 40	
Lzw-M-150	
Sx120-6000-420a-Sa	
K4p2m-S-M12	Cable socket 4-pin, straight M12 plug incl. 2 m cable, shielded. Cable end stripped 40 mm, screen braid twisted, Stranded ends with

insulated ferrules provided	
Sx80-2000-420a-Sa	
Rx80-1000-Net-Sr12-M4 Profinet,Vers: 10-30vdc,Ip65,L=1000	
Sx50-750-10v-Ka	
Sx50-1000-420a-Sa	
Mss976r-0500I02	
Md20b	
Sm100-Sg-Ka	
Cmss65-002-00-15-10	
Sx200-6-Ssi-Sr23 Seilzug-Wegaufnehmer	
Sx50-375-420a-Sa	
Lrw-M-225-S	
K4p2m-Sw-M12	Cable socket 4-pin, M12 angle plug incl. 2m cable, shielded. Cable end stripped 40 mm, screen braid twisted, Stranded ends with insulated ferrules provided.
Sx50-750-420a-Ka02-Om4	
Sx50-375-420a-Ka02	
Sx50-1250-10v-Sa	
Sx200-6-Ssi-Sr23	
???-?-?-1000-W	
Imca-24v-420a Lvdt-Externelektronik F. Din-Schiene, Versorgung: 9...36 V, Ausgang:4...20 Ma	
Zx-Pa-1,5-A Bewegungserfassungs	
Sensor Lineartechnik Mav-A-A-250-E	
Lam-F-200-Hd Lasersensor	
Ima2-Lvdt3a-24v	SIEHE ANHANG
Las-T5-500-V	
Sx50-500-420a-Sa	
Sm10-T-Sa-1112112	
Lzw-M-300	
Rp-M-90-420a-Ka02 Lenkwinkelsensor	
Sx135-10-420a-Ka	
Rx120-4000-Net-Sr12-M4 Wegaufnehmer Seilzug	
Sx50-1000-1r Sa	
Kab24-420a	

Ps-100-240ac/24dc/1.3
Mg10-P1 Main-Modul Com-, Versorgung: 12-24vdc Rs232c
Rx80-1000-Net-Sr12-M4 Wegaufnehmer Seilzug
Ras-Tx-4-420a Laser-Wegaufnehmer
Sx80-3000-420a-Ka02
Sx80-8000-420a-Ka02
Sx50-1000-420a-Ka
K4p2m-S-M12-Cat Kabel Mit Stecker
Imca-24v-10v
Ha705Ik-905
Sx50-375-10-Sa
Sx50-225-420a-Sa
???-20-26-10-10 Kupplung
Ima-24v-420
Sx80-3000-Srm50
Sx120-4000-420a-Sa
Sm25-Hyd-T-Sa-F18
Sx80-2000-420a-Ka
Sx80-2500-420a-Sa
Sx80-2500-1-G-Sr
D4-W-M12-S Verbinder
Rm15-Wtja-8s
Pmx-24 Sensor
Lzw2-F-50
Sm25-T-Ka-H-Ks
Sm140-Hyd-H-18-Ks
Sm50-Hyd-T-Ka-L20-F18
Rx80-2000-Net-Sr12-M4 Wegaufnehmer Seilzug
Sx50-500-420a-Sa-0
Sx50-1000-420a-Ka02-Om4
Con011
Sx80-3000-420a-Sa-O Imal S00128
Sm25-T-Sr

Wp-320-10v-Ka02 Analoger Drehwinkelsensor	
Sx80-1500-420a	
Rx80-2000-10v-Sa12 Bewegungserfassungs	
Rp-15t-420a-Sa12 Lenkwinkelsensor	
Imca-24-420a	
K5p2m-S-M12 Kabel Mit Stecker	
Rm15-Wtpa-8p	
Sx50-50-420a-Sa	
Sx50-375-420a-Sa12	Pull-wire position transducer, measuring range: 375 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, IP 65, Linearity: 0.15%, 4-pin axial M12 connector output Tariff No .: 90318020 Origin: DE Weight: 0.30 kg Pref .: Yes
110294	
Sx80-3000-420a-Sa-O	
Sx50-125-420a-Sa12	Pull-wire position transducer, measuring range: 125 mm, Output: 4 ... 20 mA, supply: 12 ... 30 VDC, IP 65, Linearity: 0.5%, 4-pin axial M12 connector output Tariff No .: 90318020 Origin: DE Weight: 0.30 kg Prefix: YES
Mss976r-0400I03	
Zx-Hm-1,5-A Bewegungserfassungs	
Sx50-300-420a-Ka	
Sx50-125-420a-Ka02	
Sx80-2000-420a-Sa Kabeltrommel Sensor	
Lzw1-F-75	
Sx80-1000-Pro-K1	
Imca-24v-420a	
Sx80-1500	
Sx120-6000-Pro-M12-O-S1-K1	
Sx50-225-10v-Ka02	
Con012-S	
Sx50-750-420a-Ka02	