

Zeca

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Zeca Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Zeca Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
805/10	
4325RNF	
4325	
Trainline roller type 1730	Equipment: 29 m cable H05 VV-F 4 x 4 qmm plus 2 m freely hanging Power: rolled up - 11 kW - 400 V unrolled - 15 kW - 400 V Dimensions: H x W x D = 530 x 440 x 365 mm Protection class: IP 65 Execution: - Direct mounting on the wall - special spring drive with high Resilience
6186/PRC/IP65	Art-Nr.: 2.402.009 Automatic cable reel PR-C IP65 (cast aluminum housing) with 26m cable 3x1.5 mm ² H05VV-F, max. 500 V, 1.1/1.8KW, IP65, slip ring 10A, wall bracket pivotable
2.250.006	Automatic cable reel X 4000 (plastic housing) with 10m cable H05VV-F 3x2.5 mm ² , 220V (test load: 500V), max. 1.9/2.5KW, IP42, 2m connection cable with Rubber Schuko

	connections, thermal fuse, Locking device, swiveling wall bracket
2.580.703	Fix mounting bracket for cable reel IE 1700
2.580.704	Roller guide reversible (width 160mm)
2.582.782	1782 Automatic cable reel IE 1700 (steel, aluminum housing) with 8m cable H05VV-F 16x2.5 mm ² , max. 7.5A, slip ring 32A, protection class IP65, 2m connection cable, Detent, side mounting flange, type 1
6628	Balancer from the PR series with steel cable. Further information is on the data sheet. Attention: Special order, no returns possible not a listed item.
2.582.773	Automatic cable reel IE 1700 (steel, aluminum housing) with 53m cable H05VV-F 10x1.5 mm ² , max. 4.5A, Slip ring 16A, protection class IP65, 2m connection cable, without locking, side mounting flange, type 2
2.300.005	Automatic cable reel MAGNUM 7000 (plastic housing) with 27m cable H05VV-F 4x1.5mm ² , 500V, max. 1.1/1.8KW, IP 42, locking, wall mount pivotable
2.300.003	Automatic cable reel MAGNUM 7000 (plastic housing) with 27m cable H05VV-F 3x1.5mm ² , max. 220V (test load: 500V), 1.1/1.8KW, IP42, 2m cable with Schuko connections, Locking, wall bracket swiveling
Am58/Am8	
6619prc	
370/10	
1.000.821 Automatik Schlauchaufröller Aml 200	
4315	
2.408.009 Automatik Kabelaufröller Pr-L	
6175 Prc	
Art328/10 230v	
5000 Series - Am8	
1.000.821 Automatik Schlauchaufröller	
1735	
040630-03x1,5(Ex. 6186)	
Balancer With Anti-Fall Device 634	
804/8	
6069/Prc	

[Cv2501x4grmt](#)

[107a1 9003](#)

[117a1 9003](#)

[208 Detektor, Prüfgerät Für Batterien](#)

[5908/360](#)

[207 Battery Tester](#)

[945](#)