

Ziehl



Garanti: 12 ay

Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.

Ziehl Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Ziehl Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
TR1200IP,	Temperature measurement Pt 100 art nr T224078 12 sensors, TCP/IP, IEC 61850 (GOOSE) 1 alarm relay Interface TCP/IP IEC 61850 GOOSE no limits, no alarms Us AC/DC 24-240V cURus UL-E337414 replaces T224081 (without GOOSE)
T224361	TR600, temperature relay for Pt 100 6 sensors, 6 alarms, RS 485 (Modbus RTU) 6 sensors, -199...800 °C 6 alarms/relays digital display Interface RS 485, Modbus RTU Us AC/DC 24-240V USB interface for programming cURus UL-E337414 replaces T224153 + T224154
T224370 (alternative)	TR660IP, temperature relay for Pt 100/1000, PTC 6 sensors, 7 limits, TCP/IP, 4 analogue outputs 6 sensors, 7 limit values 4 analog outputs 2x 0/4-20 mA, 2x 0/2-10 V, individually configurable LCD display and joystick for easy operation IP interface Us AC/DC 24-240V cURus UL-E337414 Experience the product live (username=password="test"):
TR600 (T224361)	Temperature relay for Pt 100 6 sensors, 6 alarms, RS 485 (Modbus RTU) 6 sensors, -199...800 °C 6 alarms/relays digital display Interface RS 485, Modbus RTU Us AC/DC 24-240V USB interface for programming cURus UL-E337414 replaces T224153 + T224154
TR600 (T224360)	Temperature relay for Pt 100 6 sensors, 6 alarms, 2 analogue outputs 6 sensors, -199...800 °C 6 alarms/relays digital display 2 analogue outputs 0/4-20 mA / 0-10 V Us AC/DC 24-240V USB interface for programming cURus UL-E337414 replaces T224150 + T224151
TR1200IP, T224078	
MSF220K	PTC thermistor relay for dry transformers Warning - Shutdown, AC/DC 24-240V no trigger pulse when switching ON and OFF Short-circuit and interruption monitoring can be switched on cURus replaces T221715 Changes (March 2017): - cURus approval - switchable sensor monitoring - improved test function
	Frequency input 110-880V frequency and speed relay, transmitter Frequency 10-500 Hz, speed 5-99,999 rpm 2

FRMU1000	output relays min/max/window Frequency inputs 110-300 V / 210-830 V Speed input 2-/3-wire, npn + pnp Analogue output 0-10 V, 0/4-20 mA, scalable Us AC/DC 24-240V
FRMU1000 40-440 V	Frequency and speed relay transmitter Frequency 10-500 Hz, speed 5-99,999 rpm 2 output relays min/max/window Frequency inputs 20-200 V / 80-440 V Speed input 2-/3-wire, npn + pnp Analogue output 0-10 V, 0/4-20 mA, scalable Us AC/DC 24-240V Replaces U226132
UFR1001E NA-Schutz VDE-AR-N 4105 +	S222296 voltage - frequency - vector surge - ROCOF Undervoltage and/or overvoltage Monitoring 10-minute average Under- and/or over-frequency control voltage AC/DC 24-270 V Single-fault safe VDE-AR-N 4105
MSF220SE, PTC thermistor relay for dry type	transformers Warning - Shutdown, AC/DC 24-240V no trigger pulse at To switch on and off replaces T 221690 (DC 24-220 V)
MSF220SE, PTC thermistor relay for dry type	transformers Advance warning - shutdown, AC/DC 90-240 V no trigger pulse when switching ON and OFF replaces T 221691 (AC 220-240V)
T224071	TR210, limit relay, 2 inputs, Transducer Pt 100/1000, KTY, thermocouples, 0/4-20 mA, 0-10V Pt 100, Pt 1000, KTY 83/84 Thermocouples B, E, J, K, L, N, R, S, T 0/4-20mA, 0-10V - 270...+1820 °C, 4-digit digital display 2 alarms / 2 changers Analogue outputs 0/4-20mA / 0-10V Us AC/DC 24-240V, V4 housing cURus UL-E337414
STWA4MH	STWA4MH electronic current transformer Measuring transducer AC 0-60 A ... RS 485 Modbus RTU Control voltage DC 24 V Housing design H
T224190	TR250, Temperaturrelais Pt 100/1000, KTY, PTC KTY, PTC, 3 sensors, 3 alarms 3 sensors Pt 100, Pt 1000, KTY 83/84, PTC 3 limits Us AC/DC 24-240V Pluggable connection terminals cURus UL-E337414
Stw200 Current-Relay For Obstacle Lights	
Qk08a-2dm.35.Cf	
Current Transformer Stwa3d35 For Use With Rcm1000v	
108307	
208617k	
210991	
Drr10 Phase-Sequence Relay	
Current Transformer Stwa3d125 For Use With Rcm1000v	
K401045 Single Thermistor Minika K120	

Rh22m-2dk-1b-1r	
Tf 510 Pt 100 1x2	
T224184 Pt100-Temperature-Relay Type Tr440	
Fe080 Sda 6n 2	
Stwa2ah Ac-Electronic Current Transducer	
Rh35m-4ek.2f.1r	
Stw20k Current-Relay	
Ks90 90 Å177; 5 Green - Green K302015 G2 (M4)	
Ptc Resistor Relay Ziehl Msd22vu	MSF220VU, PTC thermistor relay for dry transformers Fan pre-warning - shutdown, AC / DC 24-240 V Test button, fan control no trigger pulse when switching ON and OFF in a V4 housing cURus
Tf101zg2 -50;C...+200;C	
Tf101g3 -50;C...+200;C Mit Gewinde	
207548	
103604	
Ds6 Twilight Switch	
K150 150 Å177; 5 Black - Black K401075	
12090 1203 00 S N 152	
T221697 / Msf220se (Ac/Dc 90-240 V)	
T221696 (Msf220se) (C/Dc 24-240 V)	
Rf22p-2dk3f5r(124623)	
As500/5 A Class 1, 2.5 A Measuring-Transducer For Ac-Current	
613-7473	
Tf101 Pt100-Temperature-Sensors	
112167	
Kd110 110 Å177; 5 Brown - Yellow - Yellow - Brown K401335	
K140 140 Å177; 5 White - Blue K401065	
C106009eqk8502	

P/N: T223060 Type: Tf101r
K 180 180 Å177; 5 White - Red K401090
Current Transformer Stwa3d70 For Use With Rcm1000v
Ks80 80 Å177; 5 White - White K302109 G3 (M6)
Kd120 120 Å177; 5 Grey - Yellow - Yellow - Grey K401345
K120 120 Å177; 5 Grey - Grey K401045
124153
00279519
Drr10 Phase Sequence-Change
Stwa1s Ac-Electronic Current Transformer
Stwa1lh, Ac 2-20a, Switching Output Ac 230 V / 0.5 A (S22559)
120621(00088113)
Rh50m-4-Dk-6f-1r
Stwa1seh Ac-Electronic Current Transformer
107232
109768
303599
As100/5 A Class 1, 2.5 A Measuring-Transducer For Ac-Current
Stwa1sh
K100 100 Å177; 5 Red - Red K401025
Qk10a-2dm.38.Fe 210911 (Ex 203470)
Stw20v Current-Relay
K401055
As200/5 A Class 1, 2.5 A Measuring-Transducer For Ac-Current
As200/1 A Class 1, 2.5 A Measuring-Transducer For Ac-Current
Tf101k -50;C...+200;C

Qk08a-2em.50.M.Ch	
Cosfi100v Load And Current-Monitor	
210991-Qk10a2dm68fk	
As100/1 A Class 1, 2.5 A Measuring- Transducer For Ac-Current	
Frmu1000 Frequency- And Speed-Relay	
K 80 80 Ã177; 5 White - White K401005	
Dker35/2sp	
T221775 Msr220k 2 U, Ac 220-240 V	
613-7502	
Kd100 100 Ã177; 5 Red - Yellow - Yellow - Red K401325	
Tf 101u2 -30;C...+105;C	
384020	
K170 170 Ã177; 5 White - Green K401095	
Stwa1 Current Transformer	
T224361 / Tr600	
12090-1203-00 S/N 152	
380058	
104725 (Ex.106144)	
137376	
Sw31k Voltage Monitor For 3-Phase Networks	
K 90 90 Ã177; 5 Green - Green K401015	
As60/5 A Class 1, 2.5 A Measuring- Transducer For Ac-Current	
Tr600 (T224360)	Temperature relay for Pt 100 6 sensors, 6 alarms, 2 analog outputs 6 sensors, -199 ... 800 ° C 6 alarms / relays Digital display 2 analog outputs 0 / 4-20 mA / 0-10 V Us AC / DC 24-240 V USB interface for programming HS code: 85364900 Weight / pc: 0.4300 kg Country of origin: Germany
110179	
K60 60 Ã177; 5 White - Grey K401000	
Ks90 90 Ã177; 5 Green - Green K302119	

G3 (M6)
As60/1 A Class 1, 2.5 A Measuring- Transducer For Ac-Current
109487
K70 70 Å177; 5 White - Brown K401010
Ds6v Twilight Switch
Sw31v Voltage Relay For Three-Phase Current
K160 160 Å177; 5 Blue - Red K401085
Gr45m-2dk-6k-2r
T224360 Tr600 / Analog
As500/1 A Class 1, 2.5 A Measuring- Transducer For Ac-Current
T221771 Msr220k 2 U, Ac/Dc 24 V
K401025 Single Thermistor K100 Minika Single Ptc
Current Transformer Stwa3d20 For Use With Rcm1000v
Order No. T223154, Type: Tf101k
K110 110 Å177; 5 Brown - Brown K401035
Fe071-Sda6k2-122060
T221775
Tf101n -70;C...+500;C
308140
Sw32v Universal Voltage Monitor
Stwa1ah Ac-Electronic Current Transducer