



Ziehl Abegg

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapılabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Ziehl Abegg Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Ziehl Abegg Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün	Açıklama
Artikelnummer: 167240	Axial fan with sickled blades and square wall ring plate. Type: FN063-4DQ.6N.V7P6 3 ~ 230 / 400V ± 10% D / Y 50Hz P1 1.75kW 6.4 / 3.7A DI = 5% 1400 / MIN COZY 0.68 70 ° C 3 ~ 230 / 400V ± 10% D / Y 60Hz P1 2.80kW 8.4 / 4.8A DI = 5% 1580 / MIN COZY 0.84 60 ° C 3 ~ 265 / 460V ± 10% D / Y 60Hz P1 2.90kW 8.0 / 4.6A DI = 10% 1640 / MIN COZY 0.80 60 ° C IP54 THCL 155 ErP compliant 2015 N = 42.5 statA = 37.5% Terminal box K62 firmly built on stator. Circuit diagram: 1360-106XA Rating plate: 1x fixed. Installation position H / Vu / Vo. Motor protection: thermostat switch Operating mode: continuous operation with occasional Startups (S1) according to DIN EN 60034-1: 2011-02 Occasional start-up between -40 ° C and -25 ° C is permitted. Permanent operation below -25 ° C only with special Storage for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term lubrication .. Aluminum wing. Stator paint: unpainted Painting rotor: unpainted Painting wing: unpainted Engine suspension, powder-coated, resistance class 2 (504 h NSS, KK) RAL 9005 (deep black). Wall ring, powder-coated, resistance class 2 (504 h NSS, KK) RAL 9005
Et2r-1024/38/30v	Encoder shaft: 38.0 mm Resolution: 1024 pulses Voltage: 10-30 VDC Cable length: 10.00 m
DX fan FN045-4EK.2F.V7P2	motor
Fan [RF22P-2DK.3F.5R	OR[RF22P-2DK.3F.5R/MVI],2320Nm3/min,470PA/620PA,0.49kW,400V,STEEL,2320rpm,FOR SIEMENS MOTOR Q4371019
FN050-VDK.4I.V7P1	
RF28P-4DN.C5.4L	
RH31M-2DK.31.1R	
112305	Single-flow centrifugal fan with spiral casing. Type: RG28P-4EK.4I.1R UL Recognized Component E111399 ZA-155 1~ 230V ±15% 50Hz P1 0.69kW 3.0A 1360/MIN 14uF/400V PsF min.250PA 1~ 230V ±15% 60Hz P1 1.05kW 4.5A 1440/MIN 14uF/400V PsF min.450PA IP10 THCL 155 MK106-4EK.14.U ErP compliant 2015 N=44.0 statA=36.0% Capacitor attached to case. Connection cable on the side, 25cm. Wiring Diagram: 1360-151XA Rating plate: 1x fixed. Direction of rotation arrow: 1x fixed. Installation position H Motor protection: thermostat switch Conveyor temperature min - 20 degrees Celsius Humidity/tropical protection. Balancing quality G 2.5 Motor 1-layer paintwork RAL 7032 (pebble grey) in resistance class 1 (L-TI-0596) Impeller made of sheet steel, galvanized, unpainted Housing unpainted. Fan wheel assembly on the stator side on the K flange. Inlet nozzle without measuring device for volume flow measurement Inlet nozzle made of galvanized steel, unpainted Without mounting bracket. Discharge flange fixed to the volute casing Ball bearings with long-term greasing.
	Axial fan with sickled blades and short nozzle wire support grid (cold). Type:FN050-VDK.4I.V7P1 3~ 400V ±10% D/Y 50Hz P1 0.77/0.49kW 1.7/0.84A DI=0% 1300/1025/MIN COZY 0.64 70°C 3~ 400V ±10% D/Y 60Hz P1 1.10/0.60kW 1.9/1.0A DI=0% 1400/980/MIN COZY 0.81 70°C 3~ 460V ±10%

156916	D/Y 60Hz P1 1.20/0.70kW 2.0/1.05A DI=0% 1480/1100/MIN COZY 0.76 70�C IP54 THCL 155 ErP compliant 2015 N=40.7 statA=33.4% Terminal box K62 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 �C and -25 �C is permissible. Continuous operation below -25 �C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing.. Aluminum wings. Fan 1-layer paint finish RAL 9005 (jet black) in resistance class 1 (L-TI-0596) ring grid
S-DT2ST	Switching device for 3�motors Artikelnummer: 301024 Switching device for 3�motors Type: S-DT2ST ZIEHL-ABEGG standard design Mains voltage: 3N�400 V 50/60 Hz Rated current: 10 A Degree of protection: IP54 Motor protection through connection option for thermostat switch
FN050-VDK.4I.V7P1	156916 Axial fan with sickled blades and short nozzle wire support grid (cold). Type:FN050-VDK.4I.V7P1 3� 400V �10% D/Y 50Hz P1 0.77/0.49kW 1.7/0.84A DI=0% 1300/1025/MIN COZY 0.64 70�C 3� 400V �10% D/Y 60Hz P1 1.10/0.60kW 3� 460V �10% D/Y 60Hz P1 1.20/0.70kW 2.0/1.05A DI=0% 1480/1100/MIN COZY 0.76 70�C IP54 THCL 155 ErP compliant 2015 N=40.7 statA=33.4% Terminal box K62 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 �C and -25 �C is permissible. Continuous operation below -25 �C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing.. Aluminum wings. Fan 1-layer paint finish RAL 9005 (jet black) in resistance class 1 (L-TI-0596) ring grid
FN080ZII.GL.V7P3 154942	
RH35B.2EK.6N.2R 4,1 kw, 3300 d/min	
751102	PNOZ safety relays PNOZ s2 C 24VDC 3 n/o 1 n/c PNOZsigma safety switching device (standalone), inputs: 1-channel wiring, without cross-circuit detection, manual/automatic start, Outputs: 3 NO, 1 NC, 1 HL, UB = 24 V DC, width: 17.5 mm, pluggable Spring-loaded terminals, emergency stop monitoring, protective doors.
751167	PNOZ s7.1 C 24VDC 3 n/o cascade PNOZ safety relays PNOZsigma contact expansion, outputs: 3 NO, UB = 24 V DC, width: 17.5 mm, pluggable spring terminal block, contact block for Contact expansion in connection with safety-related Control parts, additional voltage connection for the supply of further contact blocks
751177	PNOZ s7.2 C 24VDC 4 n/o 1 n/c expand PNOZsigma contact expansion, outputs: 4 NO, 1 NC, UB = 24 V DC, width: 17.5 mm, pluggable spring terminals, contact block for Contact expansion in connection with safety-related Control parts, additional contact blocks can be attached on the right.
FN063-SDQ.4I.A7P1 art. 141382	
RD28S-4DW.4R.AL Apr. 209880	
RH50C-ZID.GG.CR Apr. 114624	
ZN091-ZIQ.GL.V5P1	180696 ZAplus axial fan with sickled blades and square wall ring plate. ZAplus Ontop ECblue Type:ZN091-ZIQ.GL.V5P1 MK152-0008 UL Listed Product E213826 ZB-155 3� 380-480V 50/60Hz P1 3.20kW 5.2-4.2A 1100 RPM 55�C IP55, THCL 155 IE5 ECblue BASIC MODBUS ErP compliant 2015 N=65.3 statA=62.0% VSD integrated integrated controller Connection plan: AP00001C ECblue BASIC-MODBUS Rating plate: 2x fixed. Data matrix code 1x loose in the controller Information sign 1x fixed. Installation position H/Vu/Vo. Motor protection: integrated active temperature management Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -35 �C and -25 �C is

	permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing.. Aluminum impeller. Stator unpainted Rotor 1-layer paint RAL 5002 (ultramarine blue) in resistance class 1 (L-TI-0596) Wings unpainted Wall ring unpainted black Protective grille powder-coated RAL 9005 (jet black) in resistance class 2 (L-TI-0585). ring grid Protective grille on the outlet side supplied loose Fastening parts supplied loose in the accessory bag Replacement for Item 165016! 2nd generation ! Net weight per unit: 48.6000 Commodity number: 8414 59 25
111215E	Double flow centrifugal fan with spiral housing. Type: RD28S-4EW.4R.AL 1~ 230V ±10% 50Hz P1 1.50kW 6.7A 1150/MIN 25uF/400V PsF min.170PA Capacitor wired with cable ties flying on the cable IP54 thermal class 155 ErP compliant 2013 N=38.4 statA=32.1% Connection cable axial. 110 cm from the axle end. Wiring Diagram: 1360-104XB. Rating plate 1x fixed, 1x loose in a plastic bag Installation position H Condensation water holes open Motor protection: thermostat switch Conveyor temperature min - 20 degrees Celsius Moisture-proof motor. Motor 1-layer paintwork in resistance class 1 (L-TI-0596) RAL 7032 (pebble grey) Impeller material: Impeller made of galvanized sheet metal Housing unpainted Inlet nozzle made of unpainted aluminium cast with integrated engine mount Ball bearings with long-term greasing. Balancing quality G 6.3 Fixed suction-side protective grille. Protective grille made of blue-chromated steel Discharge flange mounted on the volute housing Galvanized steel, unpainted Mounting brackets supplied loose.
THCL 155, IP54	1P, 230V, 50Hz, P1, 680W, 3.1A, DI=%5, 870rpm, 12Uf/400V
RH50M-4DK.6F.1R	Single-flow motor fan wheel with backward-curved blades Art. Nr. 203558 3.6/2.1A DI=10% 1340/MIN COZY 0.78 70°C IP54 THCL 155 ErP compliant 2015 N=62.0 statA=52.2% Terminal box K08 permanently mounted on the motor. Wiring Diagram: 1360-106XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Humidity/tropical protection. Balancing quality G 6.3 Motor 1-layer paintwork RAL 7032 (pebble grey) in resistance class 1 (L-TI-0596) Aluminum impeller, unpainted Ball bearings with long-term greasing.
S120 (230 V 1P) RG28P-4EK.4I.1R	
QR06A-2EM.38.AB	Artikelnummer: 111955 Single phase AC motor. 1~ 230V ±10% 50Hz P1 40W 0.17A 2450/MIN 1UF/400V 1~ 230V ±10% 60Hz P1 50W 0.22A 2500/MIN 1UF/400V IP10 thermal class 105 Fixed capacitor QR06A-2EM.38.AB Connection via Europe terminal strip, operating capacitor set up and connected Rating plate: 1x fixed Signs: 1x each fixed Installation position H Thermostat switch connected in the winding, clockwise rotation Humidity/tropical protection. Protective grille on the suction side, supplied loose Front grille and filter supplied loose Filters supplied loose Motor bearing with standard greasing Counter bearing with cold greasing Aluminum impeller Motor mounting side A (clockwise rotation) www.ziehl-abegg.com/erp-ab.pdf (E)
RH28L-2EP.WD.1R 113045	1~ 230V 50Hz P1 290W 1.24A DI=0% 2250/MIN 8uF/400V 45°C THCL 155 IP44 depending on installation and position according to EN 60034-5 ErP compliant no Capacitor not included Connection cable variable 45cm. Without schematic sandwich label Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Balancing quality G 6.3 Condensation drain holes in the stator and rotor are open Stator unpainted Rotor painted RAL 5002 (ultramarine blue) Impeller made of sheet steel, galvanized, unpainted Impeller pressed onto rotor Ball bearings with long-term greasing.
FN091-SDS.7Q.V5P1	VT01419 Fan 3~ 400V ±10% D/Y 50Hz P1 2.20/1.70kW (1.75/1.2kW 2HP) 4.8/3.0A DI=10% 940/820/MIN COZY 0.65 80°C 3~ 400V ±10% D/Y 60Hz P1 3.30/2.2kW (2.70/1.35kW 4HP) 6.00/3.90A DI=15% 1060/820/MIN COZY 0.80

	60°C 3~ 460V ±10%D/Y 60HzP1 3.5/2.50kW (2.9/1.75kW 4HP) 5.8/3.8A DI=15% 1100/900/MIN COZY 0.76 60°C Air direction: Inlet IP54 THCL F
THCL 155,P1 0.78kw.1230rpm.RE25P	
131018	Single-flow motor fan wheel with backward-curved blades Type: RH45M-4DK.4Y.1R ATEX fan motor unit Ex II 2G Ex h IIB T3 Gb 3~ 230/400V D/Y 50Hz P1 0.77kW 2.4/1.4A DI=6% 1350/MIN COZY 0.79 IP44 THCL 155 Ex II 2G Ex eb IIC T3 Gb 3~ 290/500V D/Y 50Hz P1 0.92kW -20°C<Ta<+40°C 2.6/1.49A 1370RPM COZY 0.71 max. current 2.75/1.58A at partial voltage D/Y MK106-4DK.14.Y IA/IN 4.1tA 50s PTB 08 ATEX 3061/03 N=58.0 statA=46.3% Connection cable axial, 105cm. Wiring Diagram: 1360-130XA rating plate: Fan - rating plate: 1x fixed. Fan rating plate: 1x in BAL. Direction of rotation arrow: 1x fixed. Installation position H/Vu/Vo. Motor protection: PTC thermistor Conveyor temperature min - 20 degrees Celsius Humidity/tropical protection. Balancing quality G 6.3 Motor 2-layer paintwork RAL 9005 (jet black) in resistance class 3 (L-TI-0596) Aluminum impeller, galvanized cover plate, powder-coated RAL 9005 (jet black) in resistance class 1 (L-TI-0585). Ball bearings with long-term greasing. Note: ATEX fan with the above ATEX classification: In particular, check whether the fan those in the explosion protection document/risk assessment specified end use requirements. On this point, we contradict the possibly in mentioned in your inquiry or order deviating information on Ex category, Ex temperature class, etc.
FN 045-4DK.4I.V7P1	N2 AIR DRYER UNIT CONDENSER COOLING FAN DETAILS: AXIAL FAN WITH SICKLE BLADES MAKER: ZIEHL-ABEGG MODEL: FN 045-4DK.4I.V7P1 RATED VALUES: 3 PHASE 265/460 V, 60 Hz, 0,82 KW, 1520 rpm DETAILED INFORMATION PAGE WAS ATTACHED IN ATTACHMENT SECTION
FC091-SDS.7Q.V7 (209589)	Axial fan with die-cast blades and protective cage. Type:FC091-SDS.7Q.V7 3~ 400V ±10% D/Y 50Hz P1 3.60/2.50kW 7.2/4.3A DI=5% 890/700/MIN COZY 0.72 60°C IP54 THCL 155 ErP compliant 2015 N=41.2 statA=38.3% Terminal box K07 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing.. Aluminum wings. Fan 1-layer paint finish RAL 9005 (jet black) in resistance class 1 (L-TI-0596)
RH28C-2DD.3I.CR 163827	Single-flow motor fan wheel with backward-curved blades Cpro UL Recognized Component E111399 ZA-155 3~ 400V ±10% D 50Hz P1 0.66kW 1.25A 2800RPM COZY 0.77 70°C 3~ 400V ±10% D 60Hz P1 1.00kW 1.65A 3170/MIN COZY 0.90 60°C 3~ 460V ±10% D 60Hz P1 1.10kW 1.55A 3270/MIN COZY 0.86 60°C 3~ 500V ±20% Y 50Hz P1 0.58kW 0.72A 2640/MIN COZY 0.89 70°C IP54 THCL 155 MK092-2DK.14.U ErP compliant 2015 N=63.1 statA=50.6% Connection cable on the side, 65cm. Wiring Diagram: 1360-106XA Sandwich Label Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Conveyor temperature min - 20 degrees Celsius Special impregnation HV. Balancing quality G 2.5 Motor 1-layer paintwork RAL 7032 (pebble grey) in resistance class 1 (L-TI-0596) Impeller made of ZAMid, unpainted similar to RAL 5002 (ultramarine blue) Fan wheel construction on the D flange. Ball bearings with long-term greasing.
FN080-SDS.6N.V7	Artikelnummer: 138756 Axial fan with sickled blades and protective basket. Type:FN080-SDS.6N.V7 3~ 400V D/Y 50Hz P1 1.80/1.15kW 3.9/2.2A DI=5% 900/700/MIN COZY 0.68 65°C IP54 THCL 155 ErP compliant 2015 N=41.5 statA=36.8% Terminal box K62 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing.. Aluminum wings. Stator unpainted Rotor unpainted Wings unpainted Motor mount powder-coated RAL 9005 (jet black) in resistance class 2 (L-TI-0585). mesh grid All fasteners made of stainless steel.

131510	
FAN FN050-VDK.4I.V7P1 400V	
FAN RE28P-4DK.6F.1R 210192	
RH28M-ZIK.DC.1R	Artikelnummer: 116444 Single-flow motor fan wheel with backward-curved blades ECblue Type: RH28M-ZIK.DC.1R MK116-0009 UL Listed Product E213826 ZB-155 3~ 380-480V 50/60Hz P1 0.96kW 1.65-1.3A 3400/MIN 60°C IP55 THCL 155 IE5 ErP compliant 2015 N=65.8 statA=55.1% VSD integrated Integrated controller ECblue BASIC MODBUS Connection plan: AP00001C ECblue BASIC-MODBUS Rating plate: 1x fixed. Data matrix code 1x loose in the controller Notice sign : 1x fixed Installation position H/Vu/Vo. Motor protection: integrated active temperature management Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -35 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Humidity/tropical protection. Balancing quality G 6.3 Stator unpainted Rotor 1-layer painting RAL 5002 (ultramarine blue) in resistance class 1 (L-TI-0596). Aluminum impeller, unpainted Stainless steel fasteners. Ball bearings with long-term greasing.
FN050-VDS.4I.V7P1	Axial fan with sickled blades and protective basket. 140471 3~ 400V ±10% D/Y 50Hz P1 0,84/0,54kW 1,45/0,96A DI=15% 1340/940/MIN COSY 0,80 70°C IP54 THCL 155 ErP compliant 2015 N=41.3 statA=34.2% Terminal box K62 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing.. Aluminum wings. Stator unpainted Rotor unpainted Wings unpainted Motor mount powder-coated RAL 9005 (jet black) in resistance class 2 (L-TI-0585). ring grid
GR31M-6ID.BF.2R	
FC091-SDS.7Q.V7	axial fan 400V 50Hz 3Ph 890/700 rpm 2.79/1.36kW 3hp . (3.6/2.5kW el.) 7.2/4.3A LR suction IP54 THCL F This fan meets the efficiency requirements of the 2009/125/EG directive (ErP regulation).
Type:VR080-4DI.6N.V5L	177695 Axial fan with variable blade connection for pipe sockets. 3~ 230/400V ±10% D/Y 50Hz P1 2.30kW 7.3/4.2A DI=10% 1340/MIN COZY 0.78 60°C IP54 THCL 155 ErP compliant 2015 N=49.1 statA=44.8% Terminal box K62 permanently mounted on the stator. Wiring Diagram: 1360-106XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Conveyor temperature min - 40 degrees Celsius Moisture and tropical protection. Ball bearing with cold grease.. With ball bearing 2RS. Aluminum wings. Stator unpainted Rotor unpainted Wings unpainted Motor mount powder-coated RAL 9005 (jet black) in resistance class 2 (L-TI-0585). ring grid All fasteners made of stainless steel
RH28M-2EK.3F.1R	UL Recognized Component E111399 ZA-155 1~ 230V ±15% 50-3Hz P1 0.59kW 2.6A DI=0% 2680/MIN 12uF/400V 70°C 1~ 230V ±15% 60+3Hz P1 0.70kW 3.3A DI=0% 2550/MIN 12uF/400V 70°C IP10 THCL 155 MK092-2EK.10.U ErP compliant no Capacitor not included Connection cable on the side, 55cm. Wiring Diagram: 1360-117XA Sandwich Label Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Conveyor temperature min - 25 degrees Celsius Humidity/tropical protection. Balancing quality G 6.3 Motor 1-layer paintwork RAL 7032 (pebble grey) in resistance class 1 (L-TI-0596) Aluminum impeller, unpainted Ball bearings with long-term greasing. With Nilo ring. www.ziehl-abegg.com/erp-ab.pdf (G)
XGZA9999W	Fan S0300 CR46 MG030W04 230V 50HZ 500102954
	Article number: 180681 ZAplus axial fan with sickled blades and round wall ring plate. ZAplus Ontop ECblue Type:ZN091-ZIL.GL.V5P1 MK152-0008 UL Listed Product E213826 ZB-155 3~ 380-480V 50/60Hz P1 3.20kW 5.2-4.2A

ZN091-ZIL.GL.V5P1	1100 RPM 55°C IP55, THCL 155 IE5 ECblue BASIC MODBUS ErP compliant 2015 N=65.3 statA=62.0% VSD integrated integrated controller Connection plan: AP00001C ECblue BASIC-MODBUS Rating plate: 2x fixed. Data matrix code 1x loose in the controller Information sign 1x fixed. Installation position H/Vu/Vo. Motor protection: integrated active temperature management Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -35 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing.. Aluminum impeller. Stator unpainted Rotor 1-layer paint RAL 5002 (ultramarine blue) in resistance class 1 (L-TI-0596) Wings unpainted Wall ring unpainted black Protective grille powder-coated RAL 9005 (jet black) in resistance class 2 (L-TI-0585). ring grid Protective grille on the outlet side supplied loose Fastening parts supplied loose in the accessory bag. Replacement for Item 165010! 2nd generation !
RH31M-2DK.31.1R	
VT011	FC091-SDS.7Q.V7 axial fan 400V 50Hz 3Ph 890/700 rpm 2.79/1.36kW 3hp . (3.6/2.5kW el.) 7.2/4.3A L.R. suction IP54 THCL F This fan meets the efficiency requirements of Directive 2009/125/EG (ErP regulation).
Type:ZC091-SDQ.7Q.V5 / 179572	ZAplus axial fan with die-cast blades and square wall ring plate. ZAplus Ontop Type:ZC091-SDQ.7Q.V5 3~ 400V ±10% D/Y 50Hz P1 2.80/1.70kW 5.4/2.9A 840/650/MIN COZY 0.73 70°C 3~ 400V ±10% D/Y 60Hz P1 3.80/1.95kW 6.6/3.4A 890/620/MIN COZY 0.83 60°C 3~ 460V ±10% D/Y 60Hz P1 4.30/2.40kW 6.6/3.6A 950/690/MIN COZY 0.80 60°C IP54 THCL 155 ErP compliant 2015 N=49.2 statA=45.6% Terminal box K07 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing.. Aluminum wings. Stator unpainted Rotor unpainted Wings unpainted Wall ring unpainted black Protective grille powder-coated RAL 9005 (jet black) in resistance class 2 (L-TI-0585). ring grid Protective grille on the outlet side supplied loose Fastening parts supplied loose in the accessory bag.
FB063-VDK.4M.V4L	135711 Axial fan with sheet metal blades and short nozzle wire support grid (cold). Type:FB063-VDK.4M.V4L 3~ 400V ±10% D/Y 50Hz P1 1,10/0,65kW 2,2/1,25A DI=0% 1300/910/MIN COSY 0,72 60°C IP54 THCL 155 **ONLY IN SHORT NOZZLE ErP compliant 2015 N=44.7 statA=38.5% Terminal box K62 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing.. Aluminum wings. Stator unpainted Rotor unpainted Wings unpainted Motor mount powder-coated RAL 9005 (jet black) in resistance class 2 (L-TI-0585). All fasteners made of stainless steel.
RD28S-4DW.4R.2L	209773 Double flow centrifugal fan with spiral housing. Type: RD28S-4DW.4R.2L 3~ 230/400V ±10% D/Y 50Hz P1 1.75kW 5.4/3.1A DI=0% 1130/MIN COZY 0.82PsF min.0PA 3~ 230/400V ±10% D/Y 60Hz P1 2.10kW 5.7/3.3A DI=0% 1330/MIN COZY 0.87PsF min.380PA 40°C 3~ 265/460V ±10% D/Y 60Hz P1 2.20kW 5.7/3.3A DI=0% 1420/MIN COZY 0.84PsF min.410PA 40°C IP54 thermal class 155 ErP compliant 2015 N=45.7 statA=39.2% Connection cable axial. 100 cm from the axle end. Wiring Diagram: 1360-106XB. Rating plate 1x fixed Installation position H Condensation water holes open Motor protection: thermostat switch Conveyor temperature min - 20 degrees Celsius Moisture-proof motor. Motor 1-layer paintwork in resistance class 1 (L-TI-0596) RAL 7032 (pebble grey) Impeller material: Impeller made of galvanized sheet metal Aluminum housing, unpainted Inlet nozzle made of unpainted aluminium cast with integrated engine mount Ball bearings with long-term greasing. Balancing quality G 6.3 Without mounting bracket.

QK08-2EM.25.CF	
RH25M-2DK-3B-1R	E340734
32447262	
FN050-VDK.4I.V7P1	Article number: 140056 Axial fan with sickled blades and short nozzle wire support grid (cold). 3~ 400V ±10% D/Y 50Hz P1 0.84/0.54kW 1.45/0.96A DI=15% 1340/940/MIN COZY 0.80 70°C IP54 THCL 155 ErP compliant 2015 N=41.3 statA=34.2% Terminal box K62 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing. Aluminum wings. Stator unpainted Rotor unpainted Wings unpainted Motor mount powder-coated RAL 9005 (jet black) in resistance class 2 (L-TI-0585). ring grid Balance quality G 4.0
138292	Axial fan with sickled blades and square wall ring plate. Type:FN080-SDQ.6N.V7 3~ 400V D/Y 50Hz P1 1.80/1.15kW 3.9/2.2A DI=5% 900/700/MIN COZY 0.68 65°C IP54 THCL 155 ErP compliant 2015 N=41.5 statA=36.8% Terminal box K62 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special
179572	ZAplus axial fan with die-cast blades and square wall ring plate. ZAplus Ontop Type:ZC091-SDQ.7Q.V5 3~ 400V ±10% D/Y 50Hz P1 2.80/1.70kW 5.4/2.9A 840/650/MIN COZY 0.73 70°C 3~ 400V ±10% D/Y 60Hz P1 3.80/1.95kW 6.6/3.4A 890/620/MIN COZY 0.83 60°C 3~ 460V ±10% D/Y 60Hz P1 4.30/2.40kW 6.6/3.6A 950/690/MIN COZY 0.80 60°C IP54 THCL 155 ErP compliant 2015 N=49.2 statA=45.6% Terminal box K07 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing. Aluminum wings. Stator unpainted Rotor unpainted Wings unpainted Wall ring unpainted black Protective grille powder-coated RAL 9005 (jet black) in resistance class 2 (L-TI-0585). ring grid Protective grille on the outlet side supplied loose Fastening parts supplied loose in the accessory bag.
XGZA9999W	Motor TX140L06 400V/56Hz ZIEHL ABEGG 5001023509
DGZA0605A	Ziehl Abegg fan blades 23559 A09004PA27 Wing
210540	
FN080-SDS.6N.V7	138757 - Axial fan with sickled blades and protective basket 3~ 400V D/Y 50Hz P1 1.80/1.15kW 3.9/2.2A DI=5% 900/700/MIN COZY 0.68 65°C IP54 THCL 155 ErP compliant 2015 N=41.5 statA=36.8% Terminal box K62 permanently mounted on the stator. Wiring Diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is Continuous operation below -25 °C only possible with special bearings for cold applications on request. Moisture and tropical protection. Ball bearings with long-term greasing. Aluminum wings. Stator unpainted Rotor unpainted Wings unpainted Motor mount powder-coated RAL 9005 (jet black) in resistance class 2 (L-TI-0585). ring grid All fasteners made of stainless steel.
32447262	

130043E	ZAondemand Single-flow motor fan wheel with backward-curved blades Type: RH35M-4EK.2F.1R UL Recognized Component E111399 ZA-155 1~ 230V ±10% 50Hz P1 0.30kW 1.4A 1340/MIN 6uF/400V 1~ 230V ±10% 60Hz P1 0.42kW 1.9A 1450/MIN 6uF/400V IP10 THCL 155 -NOT VOLTAGE ADJUSTABLE ARMK085- 4EK.10.U ErP compliant no Capacitor not included Connection cable on the side, 75cm. Plug wired to the cable, flying Without a circuit diagram Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Conveyor temperature min - 25 degrees Celsius Humidity/tropical protection. Balancing quality G 6.3 Stator unpainted Rotor 1-layer paintwork RAL 7032 (pebble grey) in resistance class 1 (L-TI-0596). Aluminum impeller, unpainted Ball bearings with long-term greasing.
Type:FC056-4DQ.6F.A7	Axial fan with die-cast blades and square wall ring plate 3~ 230/400V ±10% D/Y 50Hz P1 1.25kW 3.8/2.2A DI=10% 1300/MIN COZY 0.82 60°C IP54 THCL 155 ErP compliant 2015 N=40.4 statA=34.6% Terminal box K62 permanently mounted on the stator. Wiring Diagram: 1360-106XB Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing. Aluminum wings. Fan 1-layer paint finish RAL 9005 (jet black) in resistance class 1 (L-TI-0596)
RH25M-2DK.1E.2R	
RF22P-2DK.3F.5R	2320Nm3/min,0.49kW,400V,STEEL,2320rpm,470PA/620PA
VT01396	FC091-SDI.7Q.V7 Axialventilator 400V 50Hz 3Ph 890/700 1/min 2,79/1,36kW 3hp . (3,6/2,5kW el.) 7,2/4,3A L.R. saugend IP54 THCL F Version for flange ring nozzle
FN065-SDK.6N.V7P1	CONDENSER WITH FANS FN065- SDK.6N.V7P1, Axial condenser - Part No. 1000084242 with Fans 7037596
RH22V-6IP.0E.1R	
153975	Axial fan with sickle blades and square wall ring plate. Type:FN080-SDQ.6N.V7 3~ 400V D/Y 50Hz P1 1.80/1.15kW 3.9/2.2A DI=5% 900/700/MIN COZY 0.68 65°C IP54 THCL 155 ErP compliant 2015 N=41.5 statA=36.8% Terminal box K62 firmly built on the stator. Circuit diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Operating mode: continuous operation with occasional Starts (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permitted. Continuous operation below -25 °C only with special ones Storage for cold applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing. Aluminum wings. Fan 1-layer paint RAL 9005 (deep black) in resistance class 1 (L-TI-0596) Ring grid
155858	Axial fan with sickle blades and protective basket. Type:FN100-SDS.7Q.V5P1 3~ 400V ±10% D/Y 50Hz P1 3.10/1.95kW 5.6/3.4A DI=5% 870/660/MIN COZY 0.80 65°C IP54 THCL 155 ErP compliant 2015 N=42.1 statA=38.7% Terminal box K07 firmly built on the stator. Circuit diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Operating mode: continuous operation with occasional Starts (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permitted. Continuous operation below -25 °C only with special ones Storage for cold applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing. Aluminum impeller. Stator unpainted Rotor unpainted Wings unpainted Engine suspension powder-coated RAL 9005 (jet black)
	Axial fan with sickle blades and square wall ring plate. Type: FN080-SDQ.6N.V7 3~ 400V D/Y 50Hz P1 1.80/1.15kW 3.9/2.2A DI=5% 900/700/MIN COZY 0.68 65°C IP54 THCL 155 ErP compliant 2015 N=41.5 statA=36.8% Terminal box K62 firmly built on the stator. Circuit diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection:

153975	thermostat switch Operating mode: continuous operation with occasional Starts (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permitted. Continuous operation below -25 °C only with special ones Moisture and tropical protection. Ball bearings with long-term greasing. Aluminum wings. Fan 1-layer paint RAL 9005 (deep black) in resistance class 1 (L-TI-0596) Ring grid
134300	axial fan with sheet metal blades and wire support grid (heat). Type: FB056-SDW.4F.A4L 3~ 400V ±10% D/Y 50Hz P1 280/180W 0.68/0.39A DI=0% 910/660/MIN COZY 0.60 70°C 3~ 460V ±10% D/Y 60Hz P1 440/210W 0.83/0.44A DI=5% 1060/600/MIN COZY 0.66 70°C IP54 THCL 155 ErP compliant 2015 N=44.2 statA=34.0% Connection cable side-slanted, cable length 95 cm Wiring Diagram: 1360-108XB Sandwich Label. Rating plate: 1x fixed, 1x loose. Installation position H/Vu/Vo. Motor protection: thermostat switch Operating mode: continuous operation with occasional Starts (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permitted. Continuous operation below -25 °C only with special ones Storage for cold applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing. Aluminum wings. Stator unpainted Rotor unpainted Wings unpainted Engine suspension powder-coated RAL 9005 (jet black) in resistance class 1 (L-TI-0585).
Type: RH40M-VDK.4C.1R	3~ 400V ±10% D/Y 50Hz P1 0.38/0.24kW 0.62/0.39A 1230/870/MIN COZY 0.88 IP54 THCL 155 ErP compliant 2015 with FU N=62.8 statA=48.2% VSD required Terminal box K02/N permanently installed on the motor. Circuit diagram: 1360-108XA Rating plate: 1x fixed, 1x loose. Installation position H/Vu/Vo. Motor protection: thermostat switch Operating mode: continuous operation with occasional Starts (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permitted. Continuous operation below -25 °C only with special ones Storage for cold applications possible on request. Moisture/tropical protection. Balancing quality G 6.3 Motor 1-layer paint RAL 7032 (pebble gray) in resistance class 1 (L-TI-0596) Impeller made of aluminum, unpainted Ball bearings with long-term greasing.
125797E	ZAondemand Single-flow motor fan wheel with backward-curved blades Type: RH28M-2EK.3F.1R UL Recognized Component E111399 ZA-155 1~ 230V ±15% 50-3Hz P1 0.59kW 2.6A DI=0% 2680/MIN 12uF/400V 70°C 1~ 230V ±15% 60+3Hz P1 0.70kW 3.3A DI=0% 2550/MIN 12uF/400V 70°C IP10 THCL 155 MK092-2EK.10.U ErP compliant no Capacitor not included Connection cable on the side, 55cm. Wiring Diagram: 1360-117XA Sandwich Label Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Medium temperature min - 25 degrees Celsius Moisture/tropical protection. Balancing quality G 6.3 Motor 1-layer paint RAL 7032 (pebble gray) in resistance class 1 (L-TI-0596) Impeller made of aluminum, unpainted Ball bearings with long-term greasing. With Nilos ring.
Fan [RF22P-2DK.3F.5R	
102304	Single-flow motor fan wheel with forward-curved blades. Type: RE28P-4DK.6F.1R 3~ 230/400V ±10% D/Y 50Hz P1 1.50kW 4.4/2.6A 1310/MIN COZY 0.83 PsF min.30PA 40°C 3~ 230/400V ±10% D/Y 60Hz P1 1.65kW 4.7/2.7A DI=0% 1530/MIN COZY 0.88 PsF min.370PA 40°C 3~ 265/460V ±10% D/Y 60Hz P1 1.85kW 4.7/2.7A 1600/MIN COZY 0.86 PsF min.370PA 40°C IP54 THCL 155 ErP compliant 2015 N=47.1 statA=39.2% Terminal box K08 permanently installed on the motor. Circuit diagram: 1360-106XA Rating plate: 1x fixed, 1x loose. Installation position H/Vu/Vo. Motor protection: thermostat switch Medium temperature min - 20 degrees Celsius Moisture/tropical protection. Balancing quality G 6.3 Engine 1-layer paint RAL 7032 (pebble gray) in resistance class 1 (L-TI-0596) Impeller made of sheet steel, galvanized, unpainted Ball bearings with long-term greasing.
FN063-6EK.4I.V7P1	141725
ZC091-SDQ.7Q.V5	
	Single-flow centrifugal fan with spiral housing. Type: RG28P-4DK.4I.1L 3~ 400V ±10% Y 50Hz P1 1.25kW 2.2A 1290/MIN COZY 0.82 PsF min.150PA 55°C 3~ 400V ±10% Y 60Hz P1 1.35kW 2.3A 1490/MIN COZY 0.85 PsF min.440PA 55°C 3~ 460V ±10% Y 60Hz P1 1.50kW 2.3A 1520/MIN COZY 0.82 PsF

160760	min.450PA 55°C IP10THCL 155 ErP conformal 2015 N=47.7 statA=39.4% Connection cable on the side, 105cm. Wiring Diagram: 1360-159XB Sandwich Label Rating plate: 1x fixed. Direction of rotation arrow: 1x fixed. Installation position H. Motor protection: thermostat switch Medium temperature min - 20 degrees Celsius Special impregnation HV. Balancing quality G 2.5 Motor 1-layer paint RAL 7032 (pebble gray) in resistance class 1 (L-TI-0596) Impeller made of sheet steel, galvanized, unpainted Housing unpainted. Fan wheel structure on stator side on K-flange. Inlet nozzle without measuring device for volume flow measurement Inlet nozzle made of galvanized steel, unpainted Protective grille on the suction side is firmly installed. no contact protection according to DIN EN ISO 13857 Without mounting brackets. Blow-out flange firmly attached to the spiral casing Ball bearings with long-term greasing.
FC063-VDQ.6K.V7	Axial fan with die-cast blades and square wall ring plate 3~ 400V ±10% D/Y 50Hz P1 1.90/1.35kW 3.2/2.2A DI=15% 1340/1070/MIN COZY 0.86 60°C IP54 THCL 155 ErP compliant 2015 N=41.8 statA=37.2% Terminal box K62 firmly built on the stator. Circuit diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Operating mode: continuous operation with occasional Starts (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permitted. Continuous operation below -25 °C only with special ones Storage for cold applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing. Aluminum wings. Fan 1-layer paint RAL 9005 (deep black) in resistance class 1 (L-TI-0596) Replacement for engine no. 32447768!
QK10A-2DM.48.FK	
179572	ZAplus axial fan with die-cast blades and square wall ring plate. ZAplus Ontop Type: ZC091-SDQ.7Q.V5 3~ 400V ±10% D/Y 50Hz P1 2.80/1.70kW 5.4/2.9A 840/650/MIN COZY 0.73 70°C 3~ 400V ±10% D/Y 60Hz P1 3.80/1.95kW 6.6/3.4A 890/620/MIN COZY 0.83 60°C 3~ 460V ±10% D/Y 60Hz P1 4.30/2.40kW 6.6/3.6A 950/690/MIN COZY 0.80 60°C IP54 THCL 155 ErP compliant 2015 N=49.2 statA=45.6% Terminal box K07 firmly built on the stator. Circuit diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Operating mode: continuous operation with occasional Starts (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permitted. Continuous operation below -25 °C only with special ones Storage for cold applications possible on request. Moisture and tropical protection. Ball bearings with long-term greasing. Aluminum wings. Stator unpainted Rotor unpainted Wings unpainted Wall ring unpainted black Protective grille powder-coated RAL 9005 (deep black) in resistance class 2 (L-TI-0585). Ring grid Protective grille on the outlet side supplied loose Fastening parts supplied loose in the accessories bag.
RH56M-VDK.6N.1R	124379E Single-flow motor fan wheel with backward-curved blades 3~ 400V ±10% D/Y 50Hz P1 2.20/1.55kW 4.0/2.6A DI=15% 1350/1090/MIN COZY 0.80 60°C IP54 THCL 155 ErP compliant 2013 N=58.1 statA=50.9% Terminal box K08 permanently installed on the motor. Wiring diagram: 1360-108XA Rating plate: 1x fixed. Installation position H/Vu/Vo. Motor protection: thermostat switch Operating mode: continuous operation with occasional Starts (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permitted. Continuous operation below -25 °C only with special ones Storage for cold applications possible on request. Moisture/tropical protection. Balancing quality G 6.3 Motor 1-layer paint RAL 7032 (pebble gray) in resistance class 1 (L-TI-0596) Impeller made of aluminum, unpainted Ball bearings with long-term greasing.
ZC091-SDQ-7Q-V5	Ø910- WITH ADAPTER
104873	
RF22P 2DK 3F 5R	
TR600-T224361	RELAY TEMPERATURE TR600-T224261 24-240VAC\DC
131510 RF22P-2DK.3F.5R	
Gr31m61dbf2r	

112266var	
130552/Z01	
130531/Z01	
Rh45m-4ek.6c.1r	
164434	FAN
138757, Fn080-Sds.6n.V7	
130580/Z01	
S0450 Vd46 Tg060w04 400v50hz	
Fe080-Adq 6n.V7 - , - Type: Fn080-Adq.6n.V7	
130610/Z01	
Mpr300	
Fe050-Sdq.4f.V7 - , - Type:Fn050-Sdq.4f.V7p1	
130572/Z01	
106795	
130592/Z01	
112464/Z01	
Rf22p-2dk.3f.1r	
130544/Z01	
130043e	
130605/Z01	
R4e280-Ad08-13	
Rh31m-4ek.2c.1r	IMPELLER/FAN 2AMP 115V 50/60HZ 1340RPM
132990	
130601/Z01	
130581/Z01	
130540/Z01	
112269var	
041-42-703	
Motor Tx033p04 230/400v 50hz	
S0420 Vd46 Tg060w04	
126387	FAN
02006452	
Type: Rg28p-4ek.4i.1r	
50110026	

130587/Z01	
Fc040-4dq.2f.3	
130590/Z01	
Fe045-4dk.4i.V7 50	
Mk165-Bdk.24.N	
130547/Z01	
130557/Z01	
Fn040-6el.0f.A7p1 Artikelnummer: 152911	
Er90c-4dy.N7.1r	
Rg28p-4ek.4i.1r	FAN AXIAL 1PH 0.69KW 230V 50HZ
101604	
S0300 Vd41 Tg030w04	
130556/Z01	
106872	FAN
130578/Z01	
S0300 Vd46 Tg030w04	
112265var	
Rh63n-4dk.7q.Ar Artikelnummer: 129266e	
Qr06a-2em.37.Ab	Horizontal Blower 19" Mount
Fb063-6eq.4i.V4l	
134795	MOTOR
130561/Z01	
Fn030-4el.Wc.A7 Artikelnummer: 139721	
112470var	
130593/Z01	
L-Erp Pauschale (Flat Rate)	
04190172/0019 , No	
S457-Vd46 Old Code, New Code S0450 Vd46	
Fn063-Ziw.Dg.A7p2	
112305	
110842	FAN
112283var	
112277var	
130546/Z01	
112290var	
Imb3	siehe Bild

Rd35p-4dw.7t.1l	
Fb050-Vdk.41.6l Obsolete, Alternative Fb050-Vdk.4i.V4l	
Type:Fc071-Vdq.6n.V7	
112288var	
130611/Z01	
A762-4pr35	
Ziehl-Abegg-Gr25v-6ikbf1r-114182-30748923-Oem-For-Siemens-In-N3;Rnberg-Istanbul-Turkiye	
Fn080-Sds.6n.V7	
130586/Z01	
130600/Z01	
130539/Z01	
130535/Z01	
Fn063-6da.4i.V7p1	
88922a (Qr06a-Gkm.43.Bp) By Type:Qr06a-Gim.43.11 (110400x)	
130538/Z01	
Mk165-4dk.24.N	
112268var	
05067745 , 154500 (Type Fn050-Vds.4i.V7p1)	
113045e	Single-flow motor fan with backward curved blades Type: RH28L-2EP.WD.1R 1 ~ 230V 50Hz P1 290W 1.24A DI = 0% 2250 / MIN 8uF / 400V 45 ° C THCL 155 IP44 depending on installation and position according to EN 60034-5 ErP compliant no Capacitor not included Connection cable variable 45cm. Schematic: 1360-177X sandwich label Rating plate: 1x fixed. Installation position H / Vu / Vo. Motor protection: thermostat switch Balancing weight G 6.3 Condensate holes in the stator and rotor open Stator unpainted Rotor with 1-coat finish RAL 5002 (ultramarine blue).
130615/Z01	
130573/Z01	
130613/Z01	
130609/Z01	
Fc056-4df 4i.3 Obsolete!! Replaced By Fc056-4df.4i.A7	
205165	Crossflow fan with capillary chord and Single-phase AC motor. Type: QK08B-2EM.50.CH 1 ~ 230V ± 10% 50Hz P1 0,27kW 1,2A 2470 / MIN 6UF / 400V 1 ~ 230V ± 10% 60Hz P1 0,28kW 1.2A 2600 / MIN 6UF / 400V PsF min.50PA Operating capacitor firmly established IP10 thermal class 130 ErP compliant 2015 N = 23.7 TOTB = 19.1% Connection via European terminal block, operating capacitor built and connected Rating plate: 1x fixed Installation position H Engine storage with standard lubrication Counter bearing with cold grease Without 180 degree guide plate (standard) Impeller made of aluminum

Motor mounting side B (anti-clockwise)	
130569/Z01	
141690	
Type: Fn080-Adq.6n.V7	
112273var	
112289var	
130565/Z01	
112274var	
114182	COOLING FAN GR25V-6IK.BF.1R
S355 Vd43 Mg30w4	
112467/Z01	
130529/Z01	
130607/Z01	
112278var	
Ta 33 P4	
130598/Z01	
130602/Z01	
Gr31m-61d.Br.2r	
130563/Z01	
130595/Z01	
S0355 Vd46 Mg030 W04	
124018	
205407	IMPELLER
130585/Z01	
Gr35c-Zid.Dc.Cr	BLOWER 220V 10POLE
130571/Z01	
Rf22p2dk3f5r	FAN
154500 (Type Fn050-Vds.4i.V7p1)	
109016	
130606/Z01	
Rh31m-2dk.3i.1r	
112466/Z01	
105553	FAN
130553/Z01	
142502380v	
Fn050-Vdk.4i.V7p1 Ziehl Abegg Fan	

130544/Ex01	
130604/Z01	
Fe080-Sds.6n.6 , By Fn080-Sds.6n.V7	
130560/Z01	
130564/Z01	
130603/Z01	
S0450 Vd46 (230v 50hz)	
130558/Z01	
Ip55 Thcl 155	
Ziehl-Abegg Zadyn4cs/ 62 A	
128888	FAN
A0900	
112285var	
130559/Z01	
130566/Z01	
130541/Z01	
142603	FAN-RF22P-2DK.3F.5R
Mg030w04 (Ä 5001018741)	
Type:Fn050-Sdq.4f.V7p1	
130588/Z01	
Gr31m-6id.Bf.2r - Oem For Siemens, Order Code - 1ph8912-1bc80-0aa0	
Artikelnummer: 125195 , Type Fc056- 4df.4i. A7	
2cf023s4	DRIVE 23AMP
115278	
Fn080-Ada.6n.V7	
Msr220k2, Us Ac 230 V T221945	
Qk08a-2em.25.Cf	
164084	
130548/Z01	
112279var	
RH28M-2Dk.3F.1R	Article number: 109342 ZAondemand Single-flow motor fan wheel with backward-curved blades Type: RH28M-2Dk.3F.1R 3~ 230/400V ±10% D/Y 50Hz P1 0.53kW 1.65/0.95A 2750/MIN COZY 0.81 3~ 265/460V ±10% D/Y 60Hz P1 0.86kW 2.2/1.25A 3220/MIN COZY 0.87 IP10 THCL 155 ErP compliant 2015 N=62.0 statA=48.7% Operation on frequency converters under defined operating conditions permitted. Notice that Paragraph "Operating conditions" in the assembly instructions. Terminal box K03 fixed to the motor. Wiring Diagram: 1360-106XA Rating plate: 1x fixed. Installation position H/Vu/Vo.

	Motor protection: thermostat switch Mode of operation: continuous operation with occasional Start-up (S1) according to DIN EN 60034-1:2011-02 Occasional start-up between -40 °C and -25 °C is permissible. Continuous operation below -25 °C only with special Bearings for refrigeration applications possible on request. Special impregnation HV. Balancing quality G 6.3 Motor 1-layer paintwork RAL 7032 (pebble grey) in resistance class 1 (L-TI-0596) Aluminum impeller, unpainted Ball bearings with long-term greasing. With hybrid ball bearing.
130562/Z01	
123118	
130594/Z01	
Mk1064dk14u	MOTOR
130597/Z01	
133995	
Qk10b-4em.98.Ch	
130533/Z01	
112463/Z01	
1240018	
Capacitor 15mf For 510-29-203	
Fx 045-4dk.4i.V7p1	
Fb063-6eq.4i.V4p (101780e)	
Mkp 3,0uf/400v UI Artikelnummer: 02006932	
5001023509	
Rh31m-4ek.2f.1r	IMPELLER/FAN 2.0AMP 115V 50/60HZ 1380/1520RPM
880/660 Cosy 0,74 Thcl F Ip 54 Obsolete, Replaced By 138757, Fn080-Sds.6n.V7	
112264var	
130550/Z01	
FI050vdk4iv5s	FAN
S0350 4pr35	
Type:Qk10a-4em.B8.Ch	
110400x Qr06a-Gim.43.11	
130567/Z01	
130591/Z01	
130545/Z01	
130608/Z01	
21087 Fa035-Vdl 2c V6	
112276var	
131399/Z01	

112281var Tr600 / Rs 485	
Type: Mk106-4dk.14.U (Art. Nr.: 125775)	
111151	FAN
165575	
Type: Fn071-Ziq.Gg.V7p4 (Art. Nr. 159832)	
308138	FXDM5AM Frequency Inverter FXDM5AM
124379e	
00406435	
107743	MOTOR
130584/Z01	
Tx033p04	
103676e	
112469var	
130582/Z01	
120926h	MOTOR
130568/Z01	
130554/Z01	
112270var	
Fn063-6dk.4i.V7p1	
1ph8912-1ab64-0aa0	
173052	
Rh35b-2ek.6n.2r	FAN RADIAL 3300RPM 230V 47-63HZ
S0600 3pr25 Obsolete, No Replacement	
130551/Z01	
Rh35m-4ek.4f.1r	IMPELLER/FAN MOTORIZED 1520RPM SINGLE INLET 230V
130614/Z01	
Rh35m-4ek.2f.1r	FAN W/MOTOR 1-230V +-10% 50HZ 0.30KW P1
130576/Z01	
106794	
Type: Rh22m-2dk.1b.1r	Artikelnummer: 121860E Single-flow motor fan with backward curved blades 3 ~ 400V ± 10% Y 50Hz P1 0.19kW 0.34A 2700 / MIN COZY 0.81 70 ° C 3 ~ 400V ± 10% Y 60Hz P1 0.31kW 0.47A DI = 5% 2840 / MIN COZY 0.94 40 ° C 3 ~ 460V ± 10% Y 60Hz P1 0.34kW 0.46A DI = 5% 3010 / MIN COZY 0.94 40 ° C IP44 THCL 155 ErP compliant no Connection cable laterally, 105cm. Schematic: 1360-159XA sandwich label Rating plate: 1x fixed. Installation position H / Vu / Vo. Motor protection: thermostat switch Operating mode: continuous operation with occasional Start-ups (S1) according to DIN EN 60034-1: 2011-02 Occasional starting between -40 ° C and -25 ° C is permissible. Permanent operation below -25 ° C only with special Storage for

refrigeration applications available on request. Wet / tropical protection. Balancing weight G 6.3	
112271var	
130612/Z01	
112280var	
109544 00214073 , 164084	
130589/Z01	
Ia300 5p28	
114826	
A0762 4pb35 Tx140I06	
112272var	
130575/Z01	
130532/Z01	
112275var	
130530/Z01	
130542/Z01	
112465/Z01	
Rh50m-Vdk-6k-5r Old Code, New Code - Rh50m-Vdt.6k.5r	
112282var	
210823	FAN
114878	
Fa0404da2ca6	FAN
132144	
112284var	
130543/Z01	
125999	
Fh065-4iu.4i3 Obsolete, Alternative Fn063-Ziw.Dg.A7p2	
Fe080-Ada.6n.V7., , By Fn080-Ada.6n.V7	
134454	FAN
112468/Z01	
130555/Z01	
130583/Z01	
130574/Z01	
130596/Z01	
Fb050-Vdk.4i.V4I	

112286var	
130528/Z01	
130599/Z01	
137874	FAN
130577/Z01	
130534/Z01	
A0762 4pb35	
Rh40m4dk4f1r	UNIT
130579/Z01	
00275850	
Fxdm32am	F CONTROL FREQUENCY INVERTER
130537/Z01	
130549/Z01	
130570/Z01	