

Zimm

Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için **info@yursat.com.tr** e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Zimm Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Zimm Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.



Ürün

Açıklama

[199C0018](#)

=== ZE-25-RN TR30x6-RH-H846-DM(FG)+SIFA-GLP Our DESIGN BASIS for the following ZIMM screw jacks are yours the following, known to us requirement parameters: Max. Lifting load: no information provided by the customer Max. Stroke: 846 mm (useful stroke) Installation position: vertical, spindle upwards Duty cycle: no information provided by the customer Lifting speed: 1 mm per drive shaft revolution Ambient temperature: 20 ° C Environmental conditions: calm, dry, Lifetime calculation: none Project-related assumptions: guided lifting movement, no side forces We ask you to check this data again and to inform us if there are any changes required are. ZIMM screw jacks for rotating spindles, ZE-25-RN, max.25kN static, i = 6: 1 Housing: aluminum, anodized, black, Seals: NBR Lubrication: standard grease (also suitable for the food industry) Optileb GR UF 00 Trapezoidal thread spindle for screw jacks with rotating spindle, ZE-25-R-TR, TR 30x 6, made of steel, Pitch accuracy 0.2 mm / 300 mm Total spindle length Lb = 1080 mm, for stroke 846 mm Installation dimension Y: 1090 mm (gear side F up to and including GLP) End machining 1 (spindle side): Ø 20j6 / 25 mm End machining 2 (gear side): Standard EB for R gear Lubrication: without Duplex nut, ZE-25-DM, for TR 30x 6 RH including

	SIFA mounted: flange on the gearbox side, SIFA on the gearbox side LOOSELY DELIVERED: Counter bearing plate, ZE-25-GLP Customs tariff number: 84834029, country of origin: AUSTRIA Net weight of the item in kg: 11.1 / piece => 22.2 kg
ZE-25-SN-TR	ZIMM screw jack for stationary spindle, 199C0021 ZE-25-SN-TR, max.25kN static, i = 6: 1, for spindle TR 30x 6 Housing: aluminum, anodized, black, Seals: NBR Lubrication: standard grease (also suitable for the food industry) Optileb GR UF 00 with grease nipple on housing, side C
Z-10-SL	
Z-25-SL	
Z-35-SL	
L-Z02-0066747	
S485000-9099	ZE-25-R-TR
S485000-9104	KUZ-19-16N_16N
S485000-9103	ZE-25-SN-TR
S485000-9102	KSZ-H-25-L
GSZ-50-SN mit Klappe	STROK:531mm L:908mm + VS + SRO + FB600
25 kN-30x6-R-Trapezoidal screw	Screw Jack Screw size standard: 30x6 Size: 25 kN Nominal speed: 1500 rpm Nominal speed: 1500 rpm
199C0021	ZIMM screw jack for standing spindle, ZE-25-SN-TR, max. 25kN static, i= 6:1, for spindle TR 30x 6 Housing: aluminum, anodized, black, Seals: NBR Lubrication: standard grease (also suitable for the food industry) Optileb GR UF 00 with grease nipple on housing, side C
Z-25-RN	2 NL PRESS CAR REDUCER
10018930	KSZ-H-25-T-1:1, spiral bevel gearbox, primed, standard BS1 RAL 7021 (black-gray), NDFT 40µm, size 25, T-design = 3 shaft ends, ratio 1:1, Oil filling: Mobilgear 600 XP 100, shaft ø 2x d2j6 = 16 mm / 1x d1j6 = 16 mm
199C0006	Pillow block bearing, STL-30 version, gray cast iron blue
10073914	ZE-25-SL TR30x6-RH-H100-SRO173-VS-BF-FB300 ZIMM screw jack for standing spindle, ZE-25-SL-TR, max. 25kN static, i= 24:1, for spindle TR 30x 6 Housing: aluminum, anodized, black, Seals: NBR Lubrication: standard grease (also suitable for the food industry) Optileb GR UF 00 with grease nipple on housing, side C Trapezoidal thread spindle for lifting gear with standing spindle, ZE-25-S-TR, TR 30x 6, made of steel, Pitch accuracy 0.2mm/300mm Total spindle length Lb = 344 mm, for stroke 100 mm End processing 1 (spindle side): M 20 x 2.5 / 38 mm End processing 2 (SRO side): for AS/VS Lubrication: Standard grease - Tribol GR 4020/460-2 PD including lock nut including anti-twist device (ZE-25-VS)

	protective tube, ZE-25-SRO, 50x50 / 2 mm, steel, powder-coated, matt black (iron mica) Length from gear edge = 178 mm (with cover), tube length = 173 mm, Version with: 1x lubricating strip, SL1: Position C / X3 = 86.5 mm Safety against blocking: 10 mm (gear side) / 10 mm (pipe end) mounting flange, ZE-25-BF round bellows, ZE-25-FB-300, max. stroke 300 mm, inner / outer Ø = D1 / D2 = 50 / 86 mm, ZD / AZ = 70 / 370 mm, cuff: S1 = S2 = Ø46x15 mm, Material: plastic thermoplastic TP60, for use: vertical Including INOX hose ties
10073916	Connecting shaft VWZ-30-SO for radial installation and removal, VWZ-30-460-16N/16N-SO Material: aluminum Length LA = 460 mm, for shaft speed: 1500 rpm including star: plastic elastomer, 64 Shore D 1st side: Ø 16 mm H7 with groove DIN 6885-1 for feather key 5x5 2nd side: Ø 16 mm H7 with groove DIN 6885-1 for feather key 5x5
10073915	Connecting shaft VWZ-30-SO for radial installation and removal, VWZ-30-350-16N/16N-SO Material: aluminum Length LA = 350 mm, for shaft speed: 1500 rpm including star: plastic elastomer, 64 Shore D 1st side: Ø 16 mm H7 with groove DIN 6885-1 for feather key 5x5 2nd side: Ø 16 mm H7 with groove DIN 6885-1 for feather key 5x5
10073914	ZE-25-SL TR30x6-RH-H100-SRO173-VS-BF-FB300 ZIMM screw jack for standing spindle, ZE-25-SL-TR, max. 25kN static, i= 24:1, for spindle TR 30x 6 Housing: aluminum, anodized, black, Seals: NBR Lubrication: standard grease (also suitable for the food industry) Optileb GR UF 00 with grease nipple on housing, side C Trapezoidal thread spindle for lifting gear with standing spindle, ZE-25-S-TR, TR 30x 6, made of steel, Pitch accuracy 0.2mm/300mm Total spindle length Lb = 344 mm, for stroke 100 mm End processing 1 (spindle side): M 20 x 2.5 / 38 mm End processing 2 (SRO side): for AS/VS Lubrication: Standard grease - Tribol GR 4020/460-2 PD including lock nut including anti-twist device (ZE-25-VS) protective tube, ZE-25-SRO, 50x50 / 2 mm, steel, powder-coated, matt black (iron mica) Length from gear edge = 178 mm (with cover), tube length = 173 mm, Version with: 1x lubricating strip, SL1: Position C / X3 = 86.5 mm Safety against blocking: 10 mm (gear side) / 10 mm (pipe end) mounting flange, ZE-25-BF round bellows, ZE-25-FB-300, max. stroke 300 mm, inner / outer Ø = D1 / D2 = 50 / 86 mm, ZD / AZ = 70 / 370 mm, cuff: S1 = S2 = Ø46x15 mm, Material: plastic thermoplastic TP60, for use: vertical Including INOX hose ties
10018930	KSZ-H-25-T-1:1, spiral bevel gearbox, primed, standard BS1 RAL 7021 (black-gray), NDFT 40µm, size 25, T-design = 3 shaft ends, ratio 1:1, Oil filling: Mobilgear 600 XP 100, shaft Ø 2x d2j6 = 16 mm / 1x d1j6 = 16 mm
10073916	Connecting shaft VWZ-30-SO for radial installation and removal, VWZ-30-460-16N/16N-SO Material: aluminum Length LA = 460 mm, for shaft speed: 1500 rpm including star: plastic elastomer, 64 Shore D 1st side: Ø 16 mm H7 with groove DIN 6885-1 for feather key 5x5 2nd side: Ø 16

10073917	mm H7 with groove DIN 6885-1 for feather key 5x5 Connecting shaft VW Z-30-SO for radial installation and removal, VW Z-30-550-16N/16N-SO Material: aluminum Length LA = 550 mm, for shaft speed: 1500 rpm including star: plastic elastomer, 64 Shore D 1st side: Ø 16 mm H7 with groove DIN 6885-1 2nd side: Ø 16 mm H7 with groove DIN 6885-1
199C0006	Pillow block bearing, STL-30 version, gray cast iron blue
10073915	Connecting shaft VW Z-30-SO for radial installation and removal, VW Z-30-350-16N/16N-SO Material: aluminum Length LA = 350 mm, for shaft speed: 1500 rpm including star: plastic elastomer, 64 Shore D 1st side: Ø 16 mm H7 with groove DIN 6885-1 for feather key 5x5 2nd side: Ø 16 mm H7 with groove DIN 6885-1 for feather key 5x5
VWZ-30-350-16N 16N	Ø30-350mm
ZIMM WZ-30 130	Ø30 L:130 mm
ZIMM STL-30-G	STL-30-G
ZIMM VWZ-30-550-16N 16N	Ø30-550mm
ZIMM VWZ-30-460-16N 16N	Ø30-460mm
ZIMM KSZ-H-25-T-1:1	
ZIMM ZE-25-SL-TR H100	
ZIMM VWZ-30-350-16N 16N	
KUZ KK-24 Q20-Q19	
199C0004	Connecting shaft VW Z-30-SO for radial installation and removal, VW Z-30-130-16N/16N-SO Material: aluminum Length LA = 130 mm, for shaft speed: 1500 rpm including star: plastic elastomer, 64 Shore D 1st side: Ø 16 mm H7 with groove DIN 6885-1 2nd side: Ø 16 mm H7 with groove DIN 6885-1
Kuz 55	
Sh60000 906 100-P4-3,0-B14b	
Sh10002093	
Sh30001483	
Msz- 5-A-Sn	
Vwz-30-La 1035 14/14	
Frek7exx	
Vwz-40-1s-La 1251 20/16	
Vwz-60-La 840 30/30	

Sh20001600	
Sh70000168	
Sh10002095	
Wz-15-74-0p	
Vwz-40-1s-La 582-20/14	
Vwz-40-La 1250 16/14	
Sh30001195	
10011075	
KgZ-5-L/T-1	
Kgw-32-La-590-16/16 Min. Length:480mm Max. Length:680mm	
Vwz-30-La 425-14/14	
Sh10000240 L=1377mm	
Vwz-80-La 730 35/30	
Wz-20/76-0p	
Vwz-40-2s-La 1249-20/20	
Ksz-50-T	
Sh10000240 L=1069mm	
Msz-10-Vs	
Tire For Kuz-Kk32 Coupling	
Shz-05-5s	
Vwz-30-1s-La 998-14/15	
Kuz-Kk45 For Coupling	
Msz Z 5 Fm	
Sh30000086	
Msz-50-Mf-200-130	
Msz-100-Rn-Tr60x12 R	
Msz-10-A-Sn	SCREW JACK TRANSLATING VERSION 10KN 1MM PDSR
10022212	
Sh30001481	
Stl-20-G	

Kuz-Kk16 14/14 H7
Trapezoidale Tr50*16 Double Filet A Gauche L : 900 Mm (Pas Apparent 8 Mm)
Z-5 Sn
Sh20001602
Artikel-Nr - L532500
Trapezoidale Tr50*16 Double Filet A Droite L : 900 Mm (Pas Apparent 8 Mm)
Sh45003818
Msz-50-Bfl
Msz-5-Sn
Ksz-50-L