

Zimmer Group



Garanti: 12 ay
Bu ürüne ait Türkiye içi kapı teslim fiyat ve teslim süresi içeren teklifimizi almak için info@yursat.com.tr e-posta adresine başvuru yapabilir ya da ayrıntılı bilgi için +90 224 240 03 04 numaralı telefonumuzdan bizlere ulaşabilirsiniz.
Zimmer Group Markası, tedarik süresi için lütfen bizimle iletişime geçiniz.

Firmamız Zimmer Group Türkiye Distribütörü veya temsilcisi değildir. Firmamız sipariş durumunda, belirtilen ürünlerde sadece Orjinal ve yeni ürün teklifi sunmaktadır. Bu sitede gösterilen Özel marka adları ve ticari markalar ilgili sahiplerinin mülkiyetindedir, talep durumunda kaldırılmaktadır.

Ürün	Açıklama
Rbps2000-A	Serie 101240
Lcp-2505ak-08	
ZIMM TYP-MSZ-50-S İ=28-1 1800 MİN MSZ-50-S-2E NR=	837114
MKS2501A	
MKS2005AK	Clamping element pneumatic Holding force: 600.0 N Holding force PLUS: 1300.0 N theoretical holding force PLUS: 1600.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 5.5 bar State: passive (NC) RoHS Compliant: Yes CE marking: Yes
MK3502K-03	Pneumatic clamping element Holding force: 2000.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 2.0 bar State: active (NO) Scraper: No. Other: clearance height RoHS Compliant: Yes
MK3502K	JD157AJ
M14X1.5S-104	

M20X1.5M-110	
MKS3505AK	Clamping element pneumatic Holding force: 1250.0 N Holding force PLUS: 2200.0 N Theoretical holding force PLUS: 2750.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 5.5 bar State: passive (NC) RoHS Compliant: Yes CE marking: Yes
MBPS 2001 GS1A Zimmer	Clamp
MKS2505AR	Clamping element pneumatic
MK 3001 A	Clamp MK 3001 A Linear
MK 2501 A	Clamp MK 2501 A Linear
M14x1.5S 401	
M20X1.5M 110	
Klemme MKS 4501 A M5 Zimmer	Linear
ROTASCLEEN TG13	seri: 5773m1 ELERO JUNIOR 1S FİLE AKTUATÖR MOTOR
GPP5008N-AL-A	2-jaw parallel gripper pneumatic Nominal operating pressure: 6 bar Stroke per jaw: 8.0 mm Gripping force when opening: 560.0 N Gripping force when closing: 520.0 N
MKS2505KB	Clamping element pneumatic RoHS Compliant: Yes Holding force: 750 N Holding force PLUS connection: 1950 N Nominal operating pressure: 6.0 bar Operating pressure min .: 5.5 bar State: passive (NC)
RBPS2000-A	Pneumatic clamping and braking element RoHS Compliant: Yes Holding force: 10000 N Operating pressure min .: 4.0 bar State: passive (NC) Shaft Ø: 20.00 mm Scraper: Yes Sensor connection: query groove
HM1030NC	
mk3505ak AB00204218AG	
GK 20 N-B	Gripper GK 20 N-B Zimmer handling element
MK2502K	
M14X1.5S-104	
M20X1.5m-110	
MKS2001A	BJ-00414805
MGH8375	
MK5501A	
HK1501A	
SF74-180N-C	

DB314586AH	
MKR2500A	
BH777	
GP406N-C	handling element 2-jaw parallel gripper pneumatic Nominal working pressure: 6 bar Stroke per jaw: 6.0 mm Gripping force when opening: 325.0 N Gripping force when closing: 300.0 N Nominal gripping force: 300.0 N
MK3502K-03	
TKPWS 5505 AS1DA	JH/102700
GPP5035NC-00-A	handling element 2-jaw parallel gripper pneumatic Nominal working pressure: 6 bar Stroke per jaw: 35.0 mm Gripping force when closing: 8000.0 N Min. spring secured gripping force: 1900 N Nominal gripping force: 8000.0 N
SF155-180N-C	handling element flat swivel unit pneumatic Nominal working pressure: 6 bar Pan Angle: 180° Torque: 62.0 Nm
GK35N-B	
Gripper GP 406NC-C Zimmer	Your item no. GP406NC-C Nominal operating pressure: 6 bar, Stroke per jaw: 6.0 mm, Gripping force when closing: 400 N, Gripping force secured by spring min.: 100 N, Gripping force: 300N - 950N
MK1501A	
M20x1,5M-110	
M14x1.5S-104	
MBPS2004BS1	
EB5025ST	
GPP5025N-24-A	
Mk3502k-03	Jh00192046 ag
1943293	
M27X3S-109	Damper
4482832 - PP WINDER	SCHNEIDER MAGNETIC SWITCH MFS204 SKHC 211044
MK3505AK	
Brake element RBPS2500A	Clamping elements RoHS Compliant: Yes REACH compliant: Yes PLUS connection possible: No Min. operating pressure: 4.0 bar Min. operating pressure: 4.0 bar Holding torque: 140 Nm Scraper: Yes Cylinder volume per cycle: 280 cm³ Shaft Ø: 25.00 mm Sensor connection: query groove Holding torque: 140 Nm Scraper: Yes Cylinder volume per cycle: 280 cm³ Sensor connection: query groove Positioning accuracy +/-: 0.020 mm Operating temperature min.: -10 °C Operating

temperature max.: 70 °C	
MGP806N	
MKS2502K	
E050-08-147	Self-closing Silento Doppio RoHS Compliant: Yes REACH compliant: Yes Stroke: 50.0 mm, medium: fluid Type: self-closing Mass to be braked: 50.0 kg Direction of action: closing on both sides, without freewheel Freewheel length: 0.0 mm SEZ color housing: gray RAL7035 SEZ locking lever color: natural Total length max.: 237.0 mm SEZ hole spacing: 224.0 mm SEZ Ø holes: 4.2 mm SEZ width: 12.2mm SEZ height: 17.8mm SEZ locking lever design: Type S SEZ connection drilling: Cross drilling with countersink SEZ spring force F1: 17.0 N SEZ spring force F2: 28.0 N
S000-00-024	Aktivator Universal
LS16-25	
PHE16X15LMDD-A	PowerStop Industrial shock absorbers RoHS Compliant: Yes REACH compliant: Yes Series: High Energy Head: without head, short piston rod Protection: without protection Fixed stop: Yes Number of lock nuts: 1 Stroke max.: 20 mm Adjustability: No
GPD5013N-00-A	3-jaw centric gripper pneumatic RoHS Compliant: Yes REACH compliant: Yes Nominal operating pressure: 6 bar Stroke per jaw: 13.0 mm Gripping force when opening: 3910.0 N Gripping force when closing: 3770.0 N
TPC-AS59X58M	Structural damper BasicStop
GS65-B	O-ring assembly gripper pneumatic RoHS Compliant: Yes REACH compliant: Yes Spreading stroke per jaw adjustable min.: 3.0 mm Spreading stroke per jaw adjustable max.: 6.0 mm Wiping stroke: 5.0 mm
GD308NC-C	
GPP5025N-24-A	
KWH3512ES1A-A	
HK2001G	
UBPS 5503 AS1L/02	
HK2001A	
MK2001A	
MK3505AK	
MGP803N	
MGP803NC	
HK4501A	

MKR3000A	
Mk2502k	Clamping element pneumatic Holding force: 1200.0 N Nominal operating pressure: 6.0 bar Operating pressure min .: 2.0 bar State: active (NO) RoHS Compliant: Yes
Mk3505ak	clamping element pneumatic Holding force: 2000.0 N Nominal operating pressure: 6.0 bar Min. Operating pressure: 2.0 bar State: active (NO) RoHS Compliant: Yes Reach compliant: Yes
Mks2505kb	clamping element Pneumatic DE 84 79 90 70 Holding force: 750.0 N Holding force PLUS: 1950,0 N theoretical holding force PLUS: 2400.0 N Nominal operating pressure: 6,0bar operating pressure: 5.5 bar RoHs; yes CE: Yes